



TO: Planning Board
FROM: Gregory Gordos, AICP, Town Planner
DATE: December 18, 2024
SUBJECT: Application by Toll Brothers requesting Conditional Zoning approval for a 62-Lot Conventional Subdivision located on Weddington Road

APPLICATION INFORMATION:

SUBMITTAL DATE: December 11, 2023
APPLICANT: McKim&Creed
PROPERTY LOCATION: 610 Weddington Road
PARCEL ID#: 06129109, 06126001, 06126017, 06126017B, 06126017C
ACREAGE: +/- 167.48 acres
EXISTING LAND USE: Agriculture
EXISTING ZONING: R-CD, Conservation District

PROPOSAL:

The applicant, Toll Brothers, is proposing the development of a new residential subdivision of 62 homes on approximately one acre lots. It is located on two sides of Weddington Road (NC-84) with the majority of homes located to the south of the street. Aero Plantation subdivision is located to the south (zoned R-80). Stratford on Providence and Lochaven is west and Weddington Hills is east of the subject property.

Four entrances onto Weddington Road are provided: all right-in, right-out as reflected in an approved TIA.

The subdivision was previously proposed as a conservation subdivision with greater than 50% open space. This was abandoned for the current proposal with larger lots and fewer homes. The southwest corner of the site is adjacent to a lake and is environmentally sensitive with a noted eagle's nest located there. From application, there have been three significant revisions with lot count reduced from 93 to 82 to 70, and with a 4th and final revision down to 62. This last change lies outside the 660' buffer around the eagles.

Of note is the private septic system proposed for the entire site. Once previously shown on plans as a treatment plant, septic is provided via a panel block system. However nearly half of the lots do not contain a septic field on their parcel. Fields are grouped in common open space including across stream buffers.

Development Standards.

The development proposal does not include any changes to the Development Standards already set forth in the Unified Development Ordinance (UDO). Lots are compliant with R-CD standards. The development shall be governed by this Plan and all applicable requirements of the UDO.

RELATION TO THE UNIFIED DEVELOPMENT ORDINANCE:

UDO Section D-607(C), Conditional Rezoning.

As required by UDO Section D-607(C)(5), the applicant held their site walk/charette on November 28th, 2023, a Community Meeting virtually on December 22nd, an in-person Community Meeting on May 2nd and a second Community Meeting on July 16th.

The Conditional Zoning process allows the developer and the town to ask for conditions which could include special exceptions to rules or additional improvements. The town and the developer must agree on a condition for it to become a part of an approval.

UDO Section D-703(D), Permitted Uses (by zoning district).

Pursuant to Table 1, Permitted Uses, as contained within UDO Section D-703(D), Traditional Residential Development (> 6 Lots) is specifically listed as a permissible use within the R-CD, subject to Conditional Zoning approval.

UDO Section D-703(E), Lot and Building Standards Table.

Pursuant to Table 2, Lot and Building Standards, as contained within UDO Section D-703(E), all development within the R-CD is required to meet certain standards. The following table identifies those standards, as well as how the subject development proposal complies:

Lot and Building Standards		Standard	Proposed
Minimum Lot Size		40,000 sq. ft.	40,000 – 56,797 sq. ft.
Minimum Lot Width		120'	120' (min)
Minimum Setbacks	Front	50'	50'
	Side	15'	15'
	Rear	40'	40'
Maximum Height		35'	35'
Maximum Floor Area Ratio		N/A	N/A

UDO Section D-917A, Specific Requirements for All Residential Development.

UDO Section D-917A, establishes numerous rules for how residential development is intended to occur within the Town. These rules include, but are not limited to, the location of house sites, easements, the requirement of lots to abut public roads, street design and layout, cul-de-sacs, open space, buffering, and

tree requirements. While not all these rules are appropriate to be included at this stage of the development process, there are many that must be considered.

- UDO Section D-917A(A) Side lot lines shall be substantially at right angles or radial to street lines, and double frontage lots are to be avoided wherever possible.*
- The lots proposed with the subdivision are generally consistent with this provision. Several lots are abnormal in shape (11, 48) due to stream buffers. However, positive findings of compliance can be made.
- UDO Section D-917A(D) Lots partially subject to flooding. No proposed residential building lot that is partially subject to flooding as defined herein shall be approved unless there is established on the lot plan a contour line representing an elevation no lower than two feet above the base flood line as defined in Appendix 7. Floodplain Regulations.*
- Lot 39 lies closest to the floodplain on the far western portion; previous site plans designated this area as a Stormwater Control Measure (SCM).
- No new lots contain floodplain but many are adjacent to streams and steep slopes that may be subject to flooding.
- UDO Section D-917(F)(1) All subdivision lots shall abut public roads.*
- All lots within the subdivision shall abut a public road without need of an access easement. As such, positive findings of compliance can be made.
- UDO Section D-917(J)(1) Permanent dead-end streets shall not provide sole access to more than 16 dwelling units or 1,200 linear feet, whichever is less.*
- One of the proposed cul-de-sacs is long (>1000') with fourteen lots fronting it for access. This has been a design criticism since the first site plan. However it does not exceed the current standard for unit count or length. As such, positive findings of code compliance can be made.
- UDO Section D-917(J)(2) When cul-de-sacs end in the vicinity of an adjacent undeveloped property capable of being developed in the future, a right-of-way or easement shall be shown on the final plan to enable the street to be extended when the adjoining property is developed.*
- A stub out is provided to property to the north (WEDDINGTON 270 LLC). It is bound by completed residential subdivisions on other sides. Positive findings of compliance can be made.
- UDO Section D-917(K)(2) The proposed street layout shall be coordinated with the street system of the surrounding area. Where possible, existing principal streets shall be extended. Street connections shall be designed so as to minimize the number of new cul-de-sacs and to facilitate easy access to and from homes in different part of the tract (and on adjoining parcels).*
- The proposed street layout is limited by the topography as it slopes down towards the lake and Mundy's Run creek basin. Four new cul-de-sacs would be created for internal use (two on each side) with four connections to Weddington Road. Each site design has improved with regard to cul-de-sac use; previous site plans extended over streams or were longer in length.

UDO Section D-917(K)(5) Two points of ingress and egress onto an adjoining public road from subdivision containing more than 15 lots is required.

As the subdivision consists of 62 lots, there will be four points of ingress/egress along one main thoroughfare. Findings of compliance made.

UDO Section D-917(K)(7) Streets shall be designed, wherever practicable, with green "terminal vistas," for example by situating some conservation areas and other open space along the outside edges of street curves (for greater visibility). In addition, other visible open space shall be provided, such as in neighborhood greens that are bordered by streets on several sides, or along non-curving sections of the street system, wherever practicable.

Two cul de sac streets on the south half of the site terminate at the wetlands and the 660' radius from the eagle's nest, respectively. Roads do not traverse the steep slopes or creeks except for ROAD A on the north side, generally matching topography. No neighborhood greens or useable open spaces are within the development. Open space exceeds the 10% required.

UDO Section D-917(K)(8) Whenever a tract of land to be subdivided includes any part of a thoroughfare shown on the comprehensive transportation plan or LARTP adopted by the Town, and whenever such right-of way has been further defined by acceptable locational procedures sufficient to identify properties to be affected, a right-of-way for the major or minor thoroughfare must be platted in the location and to the width specified in the plan. The subdivider is responsible for the reservation of the right-of-way. All measurements involving minimum lot standards under this UDO will be made at the edge of the full/future right-of-way.

The Rea Road Extension is reflected in the R/W provided and in the TIA.

UDO Section D-917(O)(1)(b) Where the side or rear yards of lots may be oriented toward existing thoroughfare roads, a buffer at least 100 feet wide of existing woodland providing adequate visual screening throughout the year is required. The buffer width may be reduced to 50 feet if plantings are installed to include year-round screening.

The development includes a 100' roadside buffer both north and south. Previous iterations contained only the 50' supplemented buffer. Like many 2024 projects this proposal is located along a major thoroughfare. (NC-84) and there are no existing trees where the buffer is required. In this case an earthen berm would be recommended and the landscape plan for the thoroughfare buffer shall be provided as a condition of approval.

UDO Section D-917(P) Any major subdivision shall be required to provide that a minimum of ten percent of the gross area of the subdivision, exclusive of any required minimum buffers along thoroughfares, consists of common open space.

Positive findings of compliance can be made as the site well exceeds the 10% requirement. The site plan indicates that 50% of open space was provided. This open space shall include the thoroughfare buffer.

UDO Section D-917(Q)(2)(e) In association with the approval of any permit herein required or any site plan or subdivision plat, the Zoning Administrator and/or Town Council may require additional tree preservation measures above and beyond those listed herein that are deemed to support the tree preservation objectives of this UDO.

Staff recommends a tree survey be provided prior to any clearing or grading commences on site, as tree removal is not permitted within areas that have naturally occurring trees located outside the buildable area of a lot or development. Numerous heritage trees have been lost this year due in a similar subdivision: these above and beyond measures are suggested as a condition of approval.

UDO Section D-917(Q)(7) All applications for development and construction activities that are subject to the landscape and screening regulations of this article must be accompanied by a landscape plan. No building permit or similar authorization may be issued until the administrator determines that the landscaping and screening regulations of this article have been met.

Landscape Plan must include verification of compliance with Tree Save and Tree Replenish Requirements (“buildable area” subsection).

UDO Section D-917D, Supplemental Requirements for Certain Uses.

UDO Section D-917D, establishes supplements requirements for certain uses; however, no uses other than conventional residential apply to this case. As such, this Section is not applicable.

UDO Section D-918, General Requirements.

The various provisions set forth in UDO Section D-918, including, but not limited to visibility at intersections, lighting, screening, and landscaping, fences and walls, signs, and off-street parking and loading, as applicable, shall be reviewed for compliance with the submittal of plans for a Construction Permit. It is noted, however, that there do not appear to be any immediate concerns regarding compliance with these provisions. Landscaping shall not affect the vision triangle when entering or existing NC-84.

Subdivision entry and perimeter walls and entry monuments are not required to be of any specific height or style but are subject to review and approval of the planning board prior to the start of construction.

RELATION TO THE CODE OF ORDINANCES:

Appendix C, Traffic Impact Analysis.

Pursuant to Sec. II (A) (1), a Traffic Impact Analysis (TIA) is required for any CZ which is expected to create 50 or more peak hour vehicle trips or 500 or more daily vehicle trips. The proposal met the threshold of requiring a TIA to be completed and approved by the Town. This document was reviewed and found satisfactory by LaBella Engineering on September 13th, 2024 after several revisions and confirmed with the latest revision in a letter dated 11/18/2024. As stated previously all entrances are right-in, right-out.

LAND USE PLAN CONSISTENCY:

On June 3rd 2024 the Weddington Town Council adopted the new Comprehensive Land Use Plan, which established new goals and policies from those previously used by the Planning Board. This project is among the first to submit under these new guiding principles and the first non-residential proposal.

Land Use Goals:

Goal 1: New development and redevelopment activities shall be consistent with the Future Land Use Map and categories.

Policy: LU 1.1: The following Future Land Use categories, along with their intended uses, densities, and intensities, are hereby established (floor area ratio (FAR) only applies to non-residential uses): Agriculture: This category is intended to accommodate very low-density residential development to retain rural character and agricultural activity. Maximum density: 1 dwelling unit per 1.5 acres.

The subject property is identified as *Agriculture* in the 2024 Future Land Use Map (Map 4). At 0.4 dwelling units per acre, this meets the intended low density residential development standards and exceeds it, having 1 dwelling unit per every two acres.

Policy: LU 1.4: Ensure that land uses abutting residential development are compatible with the scale, intensity and overall character of existing and planned neighborhoods.

Lots are smaller than those found to the south within Aero Plantation. However, Aero Plantation is zoned R-80 and is the only neighborhood with 80,000 sq.ft. lot requirements. Weddington Hills is a conventional subdivision (40,000 sq.ft. minimum) while Lake Forest Preserve is a conservation-type development (12,000 sq.ft. minimum at the time).

Transportation Goals:

Goal 1: Encourage the development of well-designed streets that are safe, connected, and welcoming for all users.

Policy: T 1.1: Major thoroughfares and key entryways shall be given the highest priority for beautification efforts and corridor design.

Weddington Road (NC-84) is the main east-west thoroughfare in Weddington. Attempts to utilize the 50' buffer with supplemental plantings as permitted by code was not supported and thus a 100' roadside buffer was added to the entire thoroughfare and meets width requirements.

Policy: T 1.3: Encourage roads be designed and constructed to provide a high level of safety and comfort for all users (pedestrians, bicyclists and motorists), in a manner consistent with the character of the neighborhood through which the road travels.

Sidewalks are not provided as submitted. Access to-from Weddington Road is a safety concern for both residents and commuters and has resulted in the right-turn only recommendations of the Traffic Impact Analysis. Road widening as a result of the Rea Road Extension by NCDOT heightens this safety concern. Exact dimensions of the Weddington Road connections are not shown on the plans, including an island to be installed on the DOT road to prevent left turns.

Housing Goals:

Goal 2: Maintain the Town's strong single-family residential character.

Policy: H 1.1: Retain the residential character of the community by ensuring that new residential development consists of single-family homes with a maximum density of one (1) dwelling unit per 40,000 sq feet.

Toll Brothers original application for a conservation subdivision (lots smaller than 40,000 square feet) was amended to the current proposal, which only includes lots 40,000 square feet or larger. Findings of compliance can be made.

Conservation Goals:

Goal 1: Ensure that all new development takes place in a manner that conserves open space and scenic views.

Policy: C 1.1: Preserve open space and scenic views through zoning regulations that require open space preservation in both conventional and conservation subdivisions, as well as commercial developments. and minimize the visual impact of development from surrounding properties and roadways.

In this third major revision no private lots directly border another subdivision or private yard. Previous designs were directly adjacent to Aero Plantation via a creek crossing. A floodplain separates the proposal from Lochaven. Units near the lake and eagle's nest have been removed. The site is primarily used as a agricultural field and no significant natural buffer would be removed with redevelopment; additional plantings will be necessary to meet the 100' buffer requirement as found in the UDO. No lots contain stream buffers, spatially separating the lots.

Goal: Limit development activities on environmentally sensitive land.

Policy: C 3.3: Limit development in designated 100-year floodplains, wetlands and along natural waterways to reduce the risk of significant damage and injury to life and property, as well as preserving the natural areas and habitats.

The project site is located within Mundy's Run, a largely undeveloped riparian area from Providence Road down to the lakes within Aero Plantation. All natural waterways shall be contained to the Common Open Space. Seven Stormwater Control Measures (SCMs) are shown and must meet the 100-year requirements of the Town of Weddington ordinances including approval of construction/grading plans should it be recommended for approval. There is a large number of SCM's with several adjacent to the eagle's nest buffer. Creeks are protected using the required stream buffers and easements. No homes are within the 660'.

Infrastructure Goals:

Goal 1: Ensure that all existing and future developments in Weddington are served by adequate water, wastewater, drainage and emergency services.

Policy: I 1.1: Require water, wastewater, and drainage system improvements to be constructed concurrent with new development and that they provide adequate capacity to meet demands from existing and new users.

A McKim and Creed exhibit located in the agenda packet details the proposed septic field locations. It makes site assumptions located in the right hand table and demarcates CONVENTIONAL areas using a diagonal red line. Numerous lots do not have septic fields on their lot, locating them instead on deeded portions of the common open space. More detail into these systems requires clarification from the applicant. Note: the reduction of lots due to septic feasibility is considered a Minor Change under zoning regulations. If the Town has concerns regarding these private systems, it is outside the scope of the Unified Development Ordinance.

Based upon the above, staff provides the following Land Use Plan Consistency Statement for consideration:

While the development proposal can be found to be generally consistent with the adopted Land Use Plan, there are Goals and Policies for which compliance cannot be determined at the present time based upon the level of plans required to be submitted for this phase of development. In addition, while there may also be Goals and Policies for which there may be reason for concern, positive findings can nonetheless be made in support of this development proposal.

The site plan as submitted meets all requirements for cul-de-sac length, lot size, thoroughfare buffer, open space requirements, and maximum density. Wastewater systems are under the jurisdiction of N.C. Department of Environmental Quality and Union County, but that does preclude ensuring they are approved by all regulating agencies as demonstration of due diligence and as a condition for approval.

RECOMMENDATION:

It is the recommendation of staff that the request for Conditional Zoning to allow for the development of a 62-Lot Conventional Subdivision located on Weddington Road, known as Deal Lake, be recommended for **approval with conditions**.


- Union County Environmental Health approval of the proposed lots for septic tanks and wells.

ATTACHMENTS:



Application
Sketch Plan
Land Use Map
Zoning Map
Community Meeting Report
Traffic Impact Analysis

VICINITY MAP

N.T.S.





Sheet List Table				
Sheet Number	Sheet Title	ORIGINAL ISSUE DATE	REVISION DATE	REVISION NUMBER
1	COVER	12/11/2023	11/22/2024	A
2	SITE PLAN	12/11/2023	11/22/2024	A
3	EXISTING CONDITIONS	12/11/2023	11/22/2024	A



REV NO.	DESCRIPTIONS	DATE
A	REVISED PER SEPTIC	11/22/2024

DEAL LAKE

WEDDINGTON, NORTH CAROLINA



SITE DATA:

PROJECT NAME:	DEAL LAKE
PROJECT ADDRESS:	610 WEDDINGTON ROAD & OTHER PARCELS, WEDDINGTON, NC
PID'S:	06129109, 06126001, 06126017, 06126017B, 06126017C
JURISDICTION:	WEDDINGTON
ACREAGE:	+/- 167.48 AC TOTAL
EAST SIDE:	+/- 41.1 AC
WEST SIDE:	+/- 126.38 AC
ZONING:	
EXISTING:	R-CD
PROPOSED:	R-CD
FLOOD PLAIN:	+/- 13.6 AC
WETLANDS:	+/- .52 AC
STREAM BUFFERS:	
EAST SIDE:	+/- 3.0 AC
WEST SIDE:	+/- 14.3 AC
OPEN SPACE:	
REQUIRED MINIMUM:	16.75 AC (10% OF GROSS ACREAGE)
PROVIDED:	+/- 78.1 AC (+/- 47% OF GROSS ACREAGE)
	EAST SIDE: +/- 17.6 AC
	WEST SIDE: +/- 60.5 AC
LOTS:	
MAXIMUM DENSITY:	1 DU / 40,000 SF
TOTAL LOTS SHOWN:	62 (.37 DUA / 1 LOT PER 2.7 AC)
MINIMUM LOT SIZE:	40,000 SF REQUIRED / 40,000+ SF PROVIDED
MINIMUM LOT WIDTH:	120' REQUIRED / 120' MINIMUM PROPOSED
SETBACKS:	50' FRONT 40' REAR 15' SIDE 25' SIDE CORNER
STREETS:	7,118 LF PROPOSED

SITE ASSUMPTIONS:

- CONCEPT ASSUMES CONVENTIONAL SEPTIC. SOIL TESTING AND FEASIBILITY STUDY REQUIRED & PROVIDED SEPARATELY.
- CONCEPT ASSUMES 100' BUFFER WITH LANDSCAPING ALONG BOTH SIDES OF NC ROUTE 84 WEDDINGTON MATTHEWS ROAD.
- SITE PLAN REFLECTS ROW, CENTERLINE, AND SIDEWALK FROM NCDOT PROPOSED IMPROVEMENTS TO NC ROUTE 84 / WEDDINGTON ROAD (NCDOT PROJECT #U-3467).

ADJACENT PROPERTY OWNERS

NO.	Name	PID	PARCEL ADDY	DEED (BOOK/PAGE)
1	WEDDINGTON 278 LLC	06126002	2827 BREKONRIDGE CENTRE DR	06337788
2	HAMILTON GARY R	06153195	6887 OXFORDSHIRE RD	09877741
3	FRENETTE GARY P	06153196	6965 OXFORDSHIRE RD	33695942
4	FRENETTE GARY P	06153197	6965 OXFORDSHIRE RD	33203389
5	FRENETTE GARY P	06153198	6968 OXFORDSHIRE RD	33203389
6	BARAJAS CHRISTOPHER M	06153199	6973 OXFORDSHIRE RD	0851631
7	HEUSTESS LAUREN	06153246	8 LOCHAVEN RD	06200180
8	HORENSTEN LAWRENCE	06128111	617 LOCHAVEN ROAD	06618661
9	LEE JONATHAN STEPHEN TRUSTEE	06128154	629 LOCHAVEN RD	06160179
10	MOFFAT DEBORAH	06128116	8 LOCHAVEN RD	76260204
11	MOFFAT JAMES DONALDSON V	06128089	938 BARON RD	76271929
12	QUEEN DAN H JR	06128019	669 BRANDY COURT	08870680
13	BONDURANT CHARLES W	06128010	646 BRANDY COURT	0886767
14	PERRY SCOTT W	06128017	628 BRANDY COURT	01671471
15	SNYDER MARK WAYNE	06128016	610 BRANDY CT	0463468
16	WYBY BRIAN W	06128015	646 BARON RD	01410689
17	TAKE ALBERT G II	06128014	634 BARON RD	73390155
18	BALLETTA PETER J	06128013	620 BARON RD	0076579
19	WISE MANAGEMENT & REALTY LLC	06128012	609 BARON RD	0946074
20	DEPARTMENT OF TRANSPORTATION	06099114	1201 WEDDINGTON HILLS DR	4993323
21	SCHMIDT ROBERT	06099115	1209 WEDDINGTON HILLS DR	6467375
22	ZHANG JI	06099116	1217 WEDDINGTON HILLS DR	02230310
23	FOX CHARLES IVAN	06099117	1221 WEDDINGTON HILLS DR	4681001
24	HUTAFF RICHARD R	06099118	1227 WEDDINGTON HILLS DR	10320772
25	CHUMAMANO DAVID PASQUALE	06099142	1431 WEDDINGTON HILLS DR	01339468
26	WILLIAMS ROBERT DEAN TRUSTEE	06099141	1440 WEDDINGTON HILLS DR	09630542
27	LAKE FOREST PRESERVE HOMEOWNERS ASSOCIATION INC	06099004A	1004 LAKE FOREST DR	02618892
28	PROPOST JANICE G	06126017A	231 WEDDINGTON RD	1464807

OWNERS

PIN 06126001	NAME:	THE DEAL FARM, LLC
ADDRESS:	3610 ETHAN CT.	CHARLOTTE, NC 28226
PIN 06129109	NAME:	DEAL LAKE PROPERTY, LLC
ADDRESS:	601 WEDDINGTON RD	3610 ETHAN CT.
		CHARLOTTE, NC 28226
PIN 06126017	NAME:	RICHARD G & ELIZABETH D PROPOST
ADDRESS:	601 WEDDINGTON RD	MATTHEWS, NC 28104
PIN 06126017B	NAME:	ELIZABETH & RICHARD PROPOST FLP
ADDRESS:	601 WEDDINGTON RD	MATTHEWS, NC 28104
PIN 06126017C	NAME:	ELIZABETH & RICHARD PROPOST FLP
ADDRESS:	601 WEDDINGTON RD	MATTHEWS, NC 28104

DEVELOPER

NAME: TOLL BROTHERS
ADDRESS: 9130 KINGS PARADE BLVD.
CHARLOTTE, NC
CONTACT: ROBERT PRICE
PHONE #: (704) 849-2625
EMAIL: rprice1@tollbrothers.com

ENGINEER

NAME: McKIM & CREED
ADDRESS: 8020 TOWER POINT DRIVE
CHARLOTTE, NC 28227
CONTACT: BETH B. JOHNSTON, PLA
PHONE #: (704) 841-2588
EMAIL: bbailey@mckimcreed.com

BASE DATA:

- PLAN IS CONCEPTUAL IN NATURE AND IS SUBJECT TO CHANGE DURING FINAL CIVIL DESIGN.
- BOUNDARY FROM SURVEY PROVIDED BY CLIENT DATED 03/07/2024.
- APPROVED WETLANDS/STREAM PRELIMINARY JURISDICTIONAL DETERMINATION (PJD) PROVIDED BY WETLANDS & WATERS DATED 11/05/2024. VERIFICATION OF CONCURRENCE BY USCOE 11/07/2024.
- EAGLE'S NEST LOCATION GPS COORDINATES PROVIDED BY WETLANDS & WATERS, DATED 02/27/2024.
- FUTURE NCDOT ROW FOR PROJECT REF. NO. U-3467 NC ROUTE 84 FROM "U3467_Rdy_RPC_psh_10-12," SHEETS 10 & 11, BY NVS ENGINEERS & CONSULTANTS, INC, DATED 10/30/2023.
- BASE DATA (TOPOGRAPHY, EXISTING BUILDINGS, ETC.) FROM UNION COUNTY GIS, NC ONEMAP, NCDOT, AND OTHER PUBLICLY AVAILABLE SOURCES. BASE DATA IS CONSIDERED PRELIMINARY AND SUBJECT TO FIELD VERIFICATION AND FIELD SURVEY. SITE PLAN MAY CHANGE PENDING FINAL FIELD SURVEY AND CIVIL DESIGN.

DEAL LAKE
WEDDINGTON
UNION COUNTY, NORTH CAROLINA

COVER

DATE:	JUNE 2024
MCE PROJ. #	02741-0011
DRAWN:	BBJ
DESIGNED:	BBJ
CHECKED:	TMM
PROJ. MGR.	BBJ

SCALE:	
HORIZONTAL:	1" = 400'
VERTICAL:	N/A

1
DRAWING NUMBER
A
REVISION



STATUS: PRELIMINARY DRAWING
NOT FOR CONSTRUCTION

MCKIM & CREED
8020 Tower Point Drive
Charlotte, North Carolina 28227
Phone: (704) 841-2588, Fax: (704) 841-2567
NC License# F-1222
www.mckimcreed.com

Toll Brothers
AMERICA'S LUXURY HOME BUILDER®

This electronic document is the property of
McKim & Creed, Inc.
and is not to be used for any purpose without the written consent of the engineer whose seal appears on the original certified document.
DO NOT REMOVE FROM ELECTRONIC FILE

N.T.S.



PROJECT NAME:	DEAL LAKE	
PROJECT ADDRESS:	610 WEDDINGTON ROAD & OTHER PARCELS, WEDDINGTON, NC	
PID'S:	06129109, 06126001, 06126017, 06126017B, 06126017C	
JURISDICTION:	WEDDINGTON	
ACREAGE:	+/- 167.48 AC TOTAL	
EAST SIDE:	+/- 41.1 AC	
WEST SIDE:	+/- 126.38 AC	
ZONING:		
EXISTING:	R-CD	
PROPOSED:	R-CD	
FLOOD PLAIN:	+/- 13.3 AC	
WETLANDS:	+/- .52 AC	
STREAM BUFFERS:		
EAST SIDE:	+/- 5.3 AC	
WEST SIDE:	+/- 4.12 AC	
OPEN SPACE:		
REQUIRED MINIMUM:	16.75 AC (10% OF GROSS ACREAGE)	
PROVIDED:	+/- 78.1 AC (+/- 47% OF GROSS ACREAGE)	
	EAST SIDE: +/- 17.6 AC (+/- 10.5% OF GROSS AC, +/- 43% OF EAST SIDE AC)	
	WEST SIDE: +/- 60.5 AC (+/- 36.1% OF GROSS AC, +/- 48% OF WEST SIDE AC)	
LOTS:		
MAXIMUM DENSITY:	1 DU / 40,000 SF	
TOTAL LOTS SHOWN:	62 (.4 DUA)	
MINIMUM LOT SIZE:	40,000 SF	
MINIMUM LOT WIDTH:	120'	
SETBACKS:	50' FRONT 40' REAR 15' SIDE 25' SIDE CORNER	
STREET LENGTHS:	STREET A = +/- 633 LF STREET B = +/- 959 LF EAST SIDE / +/- 3,143 LF WEST SIDE STREET C = +/- 1,237 LF STREET D = +/- 524 LF STREET E = +/- 622 LF	

1. CONCEPT ASSUMES CONVENTIONAL SEPTIC. SOIL TESTING AND FEASIBILITY STUDY REQUIRED & PROVIDED SEPARATELY.
2. CONCEPT ASSUMES 100' BUFFER WITH LANDSCAPING ALONG BOTH SIDES OF WEDDINGTON ROAD.
3. SITE PLAN REFLECTS ROW, CENTERLINE, AND SIDEWALK FROM NCDOT PROPOSED IMPROVEMENTS TO NC ROUTE 84 / WEDDINGTON ROAD (NCDOT PROJECT #U-3467).

LOT AREA TABLE					
LOT NUMBER	AREA (SF)				
1	54841.5	19	40629.8	41	40019.9
2	44027.5	20	43270.1	42	40021.0
3	40415.2	21	51302.0	43	40505.0
4	43886.2	22	40638.2	44	40406.2
5	40018.5	23	40154.5	45	40446.4
6	41903.3	24	45083.1	46	42321.0
7	40255.7	25	46611.4	47	46184.6
8	40049.4	26	45444.0	48	41692.2
9	40734.0	27	53521.5	49	51016.0
10	40748.2	28	40182.5	50	40280.1
11	44973.1	29	40028.2	51	40077.1
12	47653.4	30	40028.3	52	40733.6
13	40793.4	31	40028.2	53	40245.8
14	44646.0	32	40208.3	54	40181.7
15	40154.4	33	40094.0	55	40032.1
16	40901.0	34	42026.2	56	40107.9
17	67285.2	35	45568.8	57	40309.3
18	44666.3	36	44253.0	58	44264.2
		37	40170.8	59	40052.4
		38	40122.8	60	40856.3
		39	40503.6	61	40245.1
		40	40200.0	62	40149.0

SMALLEST LOT: +/- 40,019.9 SF

LARGEST LOT: +/- 67,285.2 SF

AVE. LOT SIZE: +/- 42,712 SF

1. PLAN IS CONCEPTUAL IN NATURE AND IS SUBJECT TO CHANGE DURING FINAL CIVIL DESIGN.
2. BOUNDARY FROM SURVEY PROVIDED BY CLIENT DATED 03/07/2024.
3. APPROVED WETLANDS/STREAM PRELIMINARY JURISDICTIONAL DETERMINATION (PJD) PROVIDED BY WETLANDS & WATERS DATED 11/05/2024. VERIFICATION OF CONCURRENCE BY USFWS 11/07/2024.
4. UTM ZONE 18N DATUM NAD 83 GRID COORDINATES PROVIDED BY WETLANDS & WATERS, DATED 02/27/2024.
5. FUTURE NCDOT ROW FOR PROJECT REF. NO. U-3467 NC ROUTE 84 FROM "U3467_Rdy_RPC_psh_10-12," SHEETS 10 & 11, BY NVS ENGINEERS & CONSULTANTS, INC. DATED 10/30/2023.
6. BASE DATA (TOPOGRAPHY, EXISTING BUILDINGS, ETC.) FROM UNION COUNTY GIS. NO INFORMATION FROM ANY OTHER PUBLICLY AVAILABLE SOURCES. BASE DATA IS CONSIDERED PRELIMINARY AND SUBJECT TO FIELD VERIFICATION AND FIELD SURVEY. SITE PLAN MAY CHANGE PENDING FINAL FIELD SURVEY AND CIVIL DESIGN.

NAME: TOLL BROTHERS
ADDRESS: 9130 KINGS PARADE BLVD.
CHARLOTTE, NC
CONTACT: ROBERT PRICE
PHONE #: (704) 849-2625
EMAIL: rprice1@tollbrothers.com

ENGINEER

NAME: McKim & CREED
ADDRESS: 8020 TOWER POINT DRIVE
CHARLOTTE, NC 28227
CONTACT: BETH B. JOHNSTON, PLA
PHONE #: (704) 841-2588
EMAIL: bbailey@mckimcreed.com

[illegible]

This electronic document is the property of
McKim & Creed, Inc.
and is not to be used for any purpose without the written consent of the engineer whose seal appears on the original certified document.

**DO NOT REMOVE FROM
ELECTRONIC FILE**





**DEAL LAKE
WEDDINGTON
UNION COUNTY, NORTH CAROLINA**

SKETCH PLAN

DATE: JUNE 2024	SCALE	2
MCE PROJ. # 02741-0011	HORIZONTAL:	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">DRAWING NUMBER</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">A</div> <div style="border: 1px solid black; padding: 5px;">REVISION</div>
DRAWN BBJ	VERTICAL:	
DESIGNED BBJ	1" = 20'	
CHECKED TMM	N/A	
PROJ. MGR. BBJ		

STATUS: PRELIMINARY DRAWING
NOT FOR CONSTRUCTION

N.T.S.



PROJECT NAME:


PROJECT NAME:	DEAL LAKE
PROJECT ADDRESS:	610 WEDDINGTON ROAD & OTHER PARCELS, WEDDINGTON, NC
PID'S:	06129109, 06126001, 06126017, 06126017B, 06126017C
JURISDICTION:	WEDDINGTON
ACREAGE:	+/- 167.48 AC TOTAL
EAST SIDE:	+/- 41.1 AC
WEST SIDE:	+/- 126.38 AC
ZONING:	
EXISTING:	R-CD
PROPOSED:	R-CD
FLOOD PLAIN:	+/- 13.3 AC
WETLANDS:	+/- .52 AC
STREAM BUFFERS:	
EAST SIDE:	+/- 5.3 AC
WEST SIDE:	+/- 4.12 AC

NO.	Name	PID	PARCEL ADDY	DEED (BOOK/PAGE)
1	WEDGINGTON 370 LLC	09130602	3627 BRESKIDGEOLE CENTRE DR	66337169
2	HAMILTON GARY R	09153195	6057 OXFORDSHIRE RD	89577741
3	FRENETTE GARY P	09153196	6066 OXFORDSHIRE RD	35681842
4	FRENETTE GARY P	09153197	6066 OXFORDSHIRE RD	30203389
5	FRENETTE GARY P	09153198	6066 OXFORDSHIRE RD	30203389
6	BARAJAS CHRISTOPHER M	09153199	6072 OXFORDSHIRE RD	50011831
7	HUSTESS LAUREN	09153046	9 LOCAVEN RD	82820190
8	HOENSTEIN LAWRENCE	09129111	417 LOCAVEN ROAD	68611661
9	LEE JONATHAN STEPHEN TRUSTEE	09129115A	629 LOCAVEN RD	86190179
10	MOFFAT DEBORAH	09129118	0 LOCAVEN RD	76281024
11	MOFFAT JAMES DONALDSON V	09129889	936 BARON RD	76278929
12	QUEEN DAN H JR	09129819	666 BRANDY COURT	68879699
13	BONDURANT CHARLES W	09129810	646 BRANDY COURT	68067667
14	PERRY SCOTT M	09129817	628 BRANDY COURT	61074741
15	SWYDER MARK WAYNE	09129816	610 BRANDY CT	6452460
16	NYBY BRIAN M	09129815	646 BARON RD	61410509
17	TASE ALBERT G II	09129814	624 BARON RD	73301915
18	BALLETTA PETER J	09129813	620 BARON RD	69791679
19	WISE MANAGEMENT & REALTY LLC	09129812	600 BARON RD	69644764
20	DEPARTMENT OF TRANSPORTATION	09091514	1201 WEDGINGTON HILLS DR	69032233
21	SCHMIDT ROBERT	09091515	1208 WEDGINGTON HILLS DR	64673915
22	ZHANG JJ	09091516	1217 WEDGINGTON HILLS DR	82230310
23	FOX CHARLES IVAN	09091517	1221 WEDGINGTON HILLS DR	6601061
24	HUTAFF RICHARD R	09091518	1227 WEDGINGTON HILLS DR	10232772
25	CUSUMANO DAVID PASQUALE	0909142	1541 WEDGINGTON HILLS DR	61333648
26	WILLIAMS ROBERT DEAN TRUSTEE	09091741	1448 WEDGINGTON HILLS DR	69639542
27	LAKE FOREST PRESERVE HOMEOWNERS ASSOCIATION INC	0909064A	1004 LAKE FOREST DR	32611892
28	PROSPIT JANICE G	09129817A	551 WEDGINGTON RD	16404087

1. PLAN IS CONCEPTUAL IN NATURE AND IS SUBJECT TO CHANGE DURING FINAL CIVIL DESIGN.
2. BOUNDARY FROM SURVEY PROVIDED BY CLIENT DATED 03/07/2024.
3. APPROVED WETLANDS/STREAM PRELIMINARY JURISDICTIONAL DETERMINATION (PJD) PROVIDED BY WETLANDS & WATERS DATED 11/05/2024. VERIFICATION OF CONCURRENCE BY USCOE 11/07/2024.
4. BASE DATA NEXT LOCATION IS COORDINATES PROVIDED BY WETLANDS & WATERS, DATED 02/27/2024.
5. FUTURE NCDOT ROW FOR PROJECT REF. NO. U-3467 NC ROUTE 84 FROM "U3467_Rdy_RPC_psh_10-12", SHEETS 10 & 11, BY NV5 ENGINEERS & CONSULTANTS, INC., DATED 10/30/2023.
6. BASE DATA (TOPOGRAPHY, EXISTING BUILDINGS, ETC.) FROM UNION COUNTY GIS, NC ONMAP, NCDOT, AND OTHER PUBLICLY AVAILABLE SOURCES. BASE DATA IS SUBJECT TO PRELIMINARY AND SUBJECT TO FIELD VERIFICATION AND FIELD SURVEY. SITE PLAN MAY CHANGE PENDING FINAL FIELD SURVEY AND CIVIL DESIGN.

NAME: TOLL BROTHERS
ADDRESS: 9130 KINGS PARADE BLVD.
CHARLOTTE, NC
CONTACT: ROBERT PRICE
PHONE #: (704) 849-2625
EMAIL: rprice1@tollbrothers.com

NAME: MCKIM & CREED
ADDRESS: 8020 TOWER POINT DRIVE
CHARLOTTE, NC 28227
CONTACT: BETH B. JOHNSTON, PLA
PHONE #: (704) 841-2588
EMAIL: bbaily@mckimcreed.com



811
Know what's below.
Call before you dig.

[illegible]

This electronic document is the property of
McKim & Creed, Inc.
and is not to be used for any purpose without the written consent of the engineer whose seal appears on the original certified document.

**DO NOT REMOVE FROM
ELECTRONIC FILE**



**DEAL LAKE
WEDDINGTON
UNION COUNTY, NORTH CAROLINA**

EXISTING CONDITIONS

DATE:	JUNE 2024	SCALE	3
MCE PROJ. #	02741-0011	HORIZONTAL:	
DRAWN	BBJ	VERTICAL:	
DESIGNED	BBJ	1" = 200'	
CHECKED	TMM		
PROJ. MGR.	BBJ	N/A	
			DRAWING NUMBER
			A
			REVISION

STATUS:

**PRELIMINARY DRAWING
NOT FOR CONSTRUCTION**



ENGINEERS

SURVEYORS

PLANNERS

November 22, 2024

Robert Price
Vice President of Land Development, Charlotte
Toll Brothers
9130 Kings Parade Blvd
Charlotte, NC 28273

RE: Deal Lake Septic Layout and Permitting

Dear Mr. Price:


This letter is to discuss the wastewater solutions for the proposed subdivision Deal Lake in Weddington, North Carolina. This subdivision will be served through septic systems that will be mixed with onsite systems and offsite systems as depicted on the attached Septic Exhibit and Soils Report.

Conventional systems are proposed with a panel block system that will enable for reduced area required for the disposal area to the extent possible. These systems will be permitted through the Engineers Option Permit (EOP) or Authorized On-Site Wastewater Evaluator (AOWE) in adherence with the Subchapter 18E – Wastewater Treatment and Dispersal Systems.

Please feel free to contact me to discuss in greater detail, either via email at jholland@mckimcreed.com or via phone at (910) 409-8717.

Sincerely,

McKIM & CREED, INC.



James W. Holland, P.E.
Process Group Leader

8020 Tower Point D



Charlotte, NC 28

704.841.2588

Fax 704.841.2567

www.mckimcreed.com

N.T.S.



PROJECT NAME: **DEAL LAKE**

PROJECT ADDRESS: **610 WEDDINGTON ROAD & OTHER PARCELS,
WEDDINGTON, NC**

PID'S: **06129109, 06126001, 06126017, 06126017B, 06126017C**


JURISDICTION: **WEDDINGTON**

ACREAGE: **+/- 167.48 AC TOTAL**
EAST SIDE: +/- 41.1 AC
WEST SIDE: +/- 126.38 AC

ZONING: **R-CD**
EXISTING: R-CD
PROPOSED:

FLOOD PLAIN: **+/- 13.6 AC**

STREAM BUFFERS: **+/- 5.3 AC**
EAST SIDE: +/- 15.62 AC
WEST SIDE:

OPEN SPACE: **16.75 AC (10% OF GROSS ACREAGE)**  **OPEN SPACE**
REQUIRED MINIMUM: +/- 78.45 AC (+/- 47% OF GROSS ACREAGE)
PROVIDED: EAST SIDE: +/- 18.77 AC (+/- 11% OF GROSS AC, +/- 46% OF EAST SIDE AC)
WEST SIDE: +/- 59.68 AC (+/- 36% OF GROSS AC, +/- 47% OF WEST SIDE AC)

LOTS: **1 DU / 40,000 SF**
MAXIMUM DENSITY: 62 (4 DU/A)
TOTAL LOTS SHOWN:

MINIMUM LOT SIZE: 40,000 SF
MINIMUM LOT WIDTH: 100'


SETBACKS: 50' FRONT
40' REAR
15' SIDE
25' SIDE CORNER

1. CONCEPT ASSUMES ON-LOT SEPTIC ON WEST SIDE OF WEDDINGTON ROAD. SOIL TESTING AND FEASIBILITY STUDY REQUIRED & TO BE PROVIDED SEPARATELY.
2. WETLANDS SHOWN ARE PRELIMINARY AND MAY CHANGE WHEN SURVEYED.
3. NO MORE THAN 15 LOTS MAY SHARE SEPTIC FIELDS. IN NO INSTANCE SHALL MORE THAN THREE (3) LOTS SHARE ONE (1) COMMON SEPTIC FIELD.

LOT AREA		20	44648.1	42	40487.8	64	40496.4
LOT NUMBER	AREA (SF)	21	40401.3	43	40042.7	65	47135.4
		22	50998.7	44	40461.1	66	40173.6
1	56797.6	23	41493.3	45	40200.0	67	41088.4
2	49303.9	24	44126.3	46	41465.9	68	41242.9
3	41335.8	25	52938.9	47	40057.6	69	41438.1
4	44455.7	26	52924.7	48	40185.3	70	41020.2
5	40000.0	27	42733.6	49	42235.0		
6	40197.2	28	45444.0	50	51230.1		
7	41213.6	29	53253.2	51	46826.1		
8	40174.3	30	40080.0	52	44615.1		
9	40208.3	31	43285.9	53	50259.8		
10	40049.4	32	40238.9	54	44829.4		
11	40049.3	33	40800.0	55	40213.6		
12	40622.9	34	40800.0	56	40188.7		
13	40110.2	35	40800.0	57	40391.6		
14	51592.2	36	40800.0	58	40056.2		
15	58136.8	37	40185.0	59	40189.5		
16	44168.3	38	43216.4	60	40279.6		
17	40079.7	39	46056.6	61	40030.8		
18	47880.1	40	41015.7	62	41898.1		
19	48817.1	41	40813.8	63	41901.1		

SMALLEST LOT: +/- 40,000 SF
LARGEST LOT: +/- 67343 SF
AVE. LOT SIZE: +/- 44,345 SF

SMALLEST LOT: +/- 40,000 SF
LARGEST LOT: +/- 67343 SF
AVE. LOT SIZE: +/- 44,345 SF



CONVENTIONAL
(+/- 1,999,469 SF)

DRIP
(+/- 63,278 SF)

LPC
(+/- 94,753 SF)

NAME: TOLL BROTHERS
ADDRESS: 9130 KINGS PARADE BLVD.
CHARLOTTE, NC
CONTACT: ROBERT PRICE
PHONE #: (704) 849-2625
EMAIL: rprice1@tollbrothers.com

NAME: MCKIM & CREED
ADDRESS: 8020 TOWER POINT DRIVE
CHARLOTTE, NC 28227
CONTACT: BETH B. JOHNSTON, PLA
PHONE #: (704) 841-2588
EMAIL: bbailey@mckimcreed.com

1. PLAN IS CONCEPTUAL IN NATURE AND IS SUBJECT TO CHANGE.
2. BOUNDARY SURVEY PROVIDED BY CLIENT, RECEIVED 02/20/2024.
3. PRELIMINARY WETLANDS/STREAM DELINEATION PROVIDED BY WETLANDS & WATERS. DATA HAS NOT BEEN SURVEYED OR VERIFIED.
4. EAGLE'S NEST APPROXIMATE LOCATION PROVIDED BY WETLANDS & WATERS. LOCATION HAS NOT BEEN SURVEYED.
5. FUTURE NCDOT ROW FROM "U3467_Rdy_RPC_psh_10-12," SHEETS 10 & 11, BY NV5 ENGINEERS & CONSULTANTS, INC., DATED 10/30/2023.
6. BASE DATA (TOPOGRAPHY, ELEVATION LINES, ROAD CENTER LINES, EXISTING BUILDINGS, ETC.) FROM UNCOUNTED, A UNCOUNTED, ONMAP, NCDOT, AND OTHER PUBLICLY AVAILABLE SOURCES. BASE DATA IS CONSIDERED PRELIMINARY AND SUBJECT TO FIELD VERIFICATION AND SURVEY. SITE PLAN MAY CHANGE PENDING FIELD SURVEY.

[illegible]

This electronic document is the property of
McKim & Creed, Inc.
and is not to be used for any purpose without the written consent of the engineer whose seal appears on the original certified document.

**DO NOT REMOVE FROM
ELECTRONIC FILE**




**DEAL LAKE
WEDDINGTON
UNION COUNTY, NORTH CAROLINA**


R-CD CONVENTIONAL SKETCH
REVISED FOR EAGLE BOUNDARY & SEPTIC

DATE:	MAY 2024	SCALE	1
MCE PROJ. #	02741-0011	HORIZONTAL:	
DRAWN	BBJ	1" = 200'	DRAWING NUMBER
DESIGNED	BBJ	VERTICAL:	
CHECKED		N/A	A
PROJ. MGR.	TMM		REVISION

STATUS: PRELIMINARY DRAWING NOT FOR CONSTRUCTION

Map 4 Future Land Use Map





LEGEND

- Conditional Zoning
- Downtown Overlay
- B1 (CD)
- B2 (CD)
- ED
- MX
- R-40
- R-40D
- R-60
- R-80
- R-CD
- RE

Deal Lake

Traffic Impact Analysis UPDATE

Weddington, North Carolina

Prepared for:

Toll Brothers, Inc.

October 2024

© Kimley-Horn and Associates, Inc., 2024

Kimley»Horn

**Traffic Impact Analysis UPDATE for
Deal Lake
Weddington, North Carolina**

Prepared for:

**Toll Brothers, Inc.
Charlotte, North Carolina**

Prepared by:

**Kimley-Horn and Associates, Inc.
NC License #F - 0102
200 South Tryon Street, Suite 200
Charlotte, North Carolina 28202
(704) 333-5131**

**October 2024
012826089**



Laura N. Reid
10/16/24

TABLE OF CONTENTS

	<u>Page No.</u>
1.0 EXECUTIVE SUMMARY	1
2.0 INTRODUCTION	6
3.0 EXISTING TRAFFIC CONDITIONS	7
3.1 STUDY AREA	7
3.2 EXISTING TRAFFIC VOLUME DEVELOPMENT	8
4.0 BACKGROUND TRAFFIC VOLUME DEVELOPMENT	13
4.1 HISTORICAL BACKGROUND GROWTH TRAFFIC	13
4.2 FORECAST TRAFFIC VOLUMES	13
4.3 APPROVED DEVELOPMENTS	13
4.4 PLANNED TRANSPORTATION PROJECTS	14
5.0 SITE TRAFFIC VOLUME DEVELOPMENT	23
5.1 SITE ACCESS	23
5.2 TRAFFIC GENERATION	23
5.3 SITE TRAFFIC DISTRIBUTION AND ASSIGNMENT	24
5.4 BUILD-OUT TRAFFIC VOLUMES	24
6.0 CAPACITY ANALYSIS	33
6.1 S PROVIDENCE ROAD (NC 16) AND REA ROAD/U-3467	36
6.2 WEDDINGTON ROAD (NC 84) AND COX ROAD	42
6.3 WEDDINGTON ROAD (NC 84) AND TWELVE MILE CREEK ROAD	44
6.4 WEDDINGTON ROAD (NC 84) AND U-3467	47
6.5 WEDDINGTON ROAD (NC 84) AND ACCESS A (RIRO)	49
6.6 WEDDINGTON ROAD (NC 84) AND ACCESS B (RIRO)	51
7.0 AUXILIARY TURN LANE WARRANTS	53
8.0 IDENTIFIED MITIGATION IMPROVEMENTS	54
APPENDIX	58

List of Figures

	<u>Page No.</u>
FIGURE 1.1A – IDENTIFIED MITIGATION IMPROVEMENTS W/ STIPs	4
FIGURE 1.1B – IDENTIFIED MITIGATION IMPROVEMENTS W/O STIPs	5
FIGURE 3.1 – STUDY AREA/SITE LOCATION	9
FIGURE 3.2 – PROPOSED SITE PLAN	10
FIGURE 3.3 – EXISTING ROADWAY LANEAGE	11
FIGURE 3.4 – 2024 EXISTING TRAFFIC VOLUMES	12
FIGURE 4.1 – 2029 BACKGROUND AM PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	17
FIGURE 4.2 – 2029 BACKGROUND MID PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	18
FIGURE 4.3 – 2029 BACKGROUND PM PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	19
FIGURE 4.4 – 2029 BACKGROUND AM PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	20
FIGURE 4.5 – 2029 BACKGROUND MID PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	21
FIGURE 4.6 – 2029 BACKGROUND PM PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	22
FIGURE 5.1 – SITE TRAFFIC DISTRIBUTION AND ASSIGNMENT W/ STIPs	25
FIGURE 5.2 – SITE TRAFFIC DISTRIBUTION AND ASSIGNMENT W/O STIPs	26
FIGURE 5.3 – 2029 BUILD-OUT AM PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	27
FIGURE 5.4 – 2029 BUILD-OUT MID PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	28
FIGURE 5.5 – 2029 BUILD-OUT PM PEAK-HOUR TRAFFIC VOLUMES W/ STIPs	29
FIGURE 5.6 – 2029 BUILD-OUT AM PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	30
FIGURE 5.7 – 2029 BUILD-OUT MID PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	31
FIGURE 5.8 – 2029 BUILD-OUT PM PEAK-HOUR TRAFFIC VOLUMES W/O STIPs	32
FIGURE 8.1A – IDENTIFIED MITIGATION IMPROVEMENTS W/ STIPs	55
FIGURE 8.1B – IDENTIFIED MITIGATION IMPROVEMENTS W/O STIPs	56

List of Tables

	<u>Page No.</u>
TABLE 4.1 – APPROVED DEVELOPMENTS	14
TABLE 5.1 – TRIP GENERATION	23
TABLE 6.0-A VEHICULAR LOS CONTROL DELAY THRESHOLDS FOR <u>UNSIGNALIZED</u> INTERSECTIONS	34
TABLE 6.0-B VEHICULAR LOS CONTROL DELAY THRESHOLDS FOR <u>SIGNALIZED</u> INTERSECTIONS	34
TABLE 6.1A – S PROVIDENCE ROAD (NC 16) AND REA ROAD/U3467	36
TABLE 6.1B –S PROVIDENCE ROAD (NC 16) AND NORTHERN U-TURN BULB	37
TABLE 6.1C – S PROVIDENCE ROAD (NC 16) AND SOUTHERN U-TURN BULB	38
TABLE 6.1D –REA ROAD AND WESTERN U-TURN BULB	39
TABLE 6.1E – READ ROAD EXTENSION AND EASTERN U-TURN BULB	40
TABLE 6.1F – S PROVIDENCE ROAD AND REA ROAD	41
TABLE 6.2A – WEDDINGTON ROAD (NC 84) AND COX ROAD	42
TABLE 6.2B – WEDDINGTON ROAD (NC 84) AND COX ROAD	43
TABLE 6.3A – WEDDINGTON ROAD (NC 84) AND TWELVE MILE CREEK ROAD	44
TABLE 6.3B – WEDDINGTON ROAD (NC 84) AND TWELVE MILE CREEK ROAD	45
TABLE 6.4 – WEDDINGTON ROAD (NC 84) AND U-3467 (FUTURE)	47
TABLE 6.5A – WEDDINGTON ROAD (NC 84) AND ACCESS A (RIRO)	49
TABLE 6.5B – WEDDINGTON ROAD (NC 84) AND ACCESS A	49
TABLE 6.6A – WEDDINGTON ROAD (NC 84) AND ACCESS B (RIRO)	51
TABLE 6.6B – WEDDINGTON ROAD (NC 84) AND ACCESS B	51

1.0 Executive Summary

The purpose of this Traffic Impact Analysis (TIA) is to evaluate the vehicular traffic impacts on the surrounding transportation infrastructure as a result of the proposed Deal Lake development. The primary objectives of the study are:

- To estimate trip generation and distribution for the proposed development.
- To perform intersection capacity analyses for the identified study area.
- To determine the potential traffic impacts of the proposed development.
- To identify improvements to mitigate the proposed development's traffic impacts.

The proposed Deal Lake development is located along both sides of Weddington Road (NC 84) between Lake Forest Drive and Baron Road in Weddington, North Carolina. Based on the site plan, the proposed development is currently envisioned to consist of 17 single-family detached homes on the north side of Weddington Road and 65 single-family detached homes on the south side of Weddington Road (82 single-family detached homes total).

For the purposes of this TIA, a build-out year of 2029 was considered. Based on the site plan, the proposed development will be accessed via two external access points along Weddington Road (NC 84):

- Access A – an unsignalized, right-in/right-out (RIRO) connection to Weddington Road (NC 84) approximately 940 feet east of Lake Forest Drive; this access serves both sides of the development.
- Access B – an unsignalized, RIRO connection to Weddington Road approximately 560 feet east of Access A; this access serves both sides of the development.

North Carolina Department of Transportation (NCDOT) TIA Scoping Checklist was prepared based on the provided site plan that documented all scoping parameters to be used for the TIA and was reviewed and agreed upon by NCDOT and Town of Weddington staff. The approved TIA Scoping Checklist, along with NCDOT and Town scoping comments, are included in the **Appendix**. The analysis in this TIA is based on the development plan described above and as shown in the approved NCDOT TIA Scoping Checklist (included in the **Appendix**). However, the development plan was revised after approval of the TIA Scoping Checklist to reduce density from 93 units (31 north and 62 south) to 82 units (17 north and 65 south). Furthermore, the addition of the southbound approach at the Weddington Road (NC 84) and Access A intersection has now been included.

Per coordination with Town of Weddington Staff, an additional interim scenario was analyzed without any of the NCDOT Statewide Transportation Improvement Program (STIP) Projects in place. This interim scenario was utilized to determine the impacts and recommend mitigation at the proposed study intersections should the proposed development be completed before the STIP projects. It was assumed that in this interim scenario, the proposed access points would operate as full movement until the STIP project widens and installs a median along Weddington Road (NC 84). Upon further coordination with NCDOT Staff, the proposed access points will operate under RIRO conditions in this scenario without the STIP project along Weddington Road (NC 84).

NCDOT and Town of Weddington TIA comments on the April 2024 TIA, along with Kimley Horn's comment response letter, can be found in the **Appendix**.

The following AM, Midday (MID), and PM peak-hour scenarios were analyzed to determine the proposed development's transportation impacts on the surrounding network:

- 2024 Existing Conditions
- 2029 Background Conditions (with STIP projects)
- 2029 Background Conditions (without STIP projects)
- 2029 Build-out Conditions (with STIP projects)
- 2029 Build-out Conditions (without STIP projects)

Based on coordination with the Town and NCDOT, this TIA evaluated operations under each of the AM, MID, and PM peak-hour scenarios above for the following study area intersections:

1. S Providence Road (NC 16) and Rea Road/U-3467
2. Weddington Road (NC 84) and Cox Road
3. Weddington Road (NC 84) and Twelve Mile Creek Road
4. Weddington Road (NC 84) and U-3467 (Future) (with STIP projects scenario only)
5. Weddington Road (NC 84) and Access A
6. Weddington Road (NC 84) and Access B

Kimley-Horn was retained to determine the potential traffic impacts of this development (in accordance with the traffic study guidelines in the [*NCDOT Policy on Street and Driveway Access to North Carolina Highways*](#) and set forth by the [*Town of Weddington Traffic Impact Analysis \(TIA\) Process and Procedures Manual*](#), and to identify transportation improvements that may be required to mitigate these impacts.

Based on the capacity analyses performed at each of the identified study intersections, along with review of the auxiliary turn-lane warrants contained herein, no improvements are required to mitigate the impact of the proposed development on the adjacent street network under either scenario. The following site and mitigation improvements needed for the proposed Deal Lake development are as follows:

With STIP Projects

Weddington Road (NC 84) and Access A

- Construction of the northbound and southbound approaches of Access A under RIRO operations with one ingress lane, one egress lane, stop-control, and an internal protected stem (IPS) of 100 feet.
- Construction of an eastbound right-turn lane along Weddington Road (NC 84) with maximized storage.

Weddington Road (NC 84) and Access B

- Construction of the northbound and southbound approaches of Access B under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.

Without STIP Projects


Weddington Road (NC 84) and Access A

- Construction of the northbound and southbound approaches of Access A under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.
- Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Weddington Road (NC 84) and Access B

- Construction of the northbound and southbound approaches of Access B under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.
- Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

The site and mitigation improvements identified within the study area are shown in **Figures 1.1A and 1.1B**. The improvements shown on these figures are subject to approval by NCDOT and the Town of Weddington. All additions and attachments to the State and Town roadway system shall be properly permitted, designed, and constructed in conformance to standards maintained by the agencies.



2.0 Introduction

The proposed Deal Lake development is located along both sides of Weddington Road (NC 84) between Lake Forest Drive and Baron Road in Weddington, North Carolina. Based on the site plan, the proposed development is currently envisioned to consist of 17 single-family detached homes on the north side of Weddington Road and 65 single-family detached homes on the south side of Weddington Road (82 single-family detached homes total).

For the purposes of this TIA, a build-out year of 2029 was considered. Based on the site plan, the proposed development will be accessed via two external access points along Weddington Road (NC 84):

- Access A – an unsignalized, right-in/right-out (RIRO) connection to Weddington Road (NC 84) approximately 940 feet east of Lake Forest Drive; this access serves both sides of the development.
- Access B – an unsignalized, RIRO connection to Weddington Road approximately 560 feet east of Access A; this access serves both sides of the development.

North Carolina Department of Transportation (NCDOT) TIA Scoping Checklist was prepared based on the provided site plan that documented all scoping parameters to be used for the TIA and was reviewed and agreed upon by NCDOT and Town of Weddington staff. The approved TIA Scoping Checklist, along with NCDOT and Town scoping comments, are included in the **Appendix**. The analysis in this TIA is based on the development plan described above and as shown in the approved NCDOT TIA Scoping Checklist (included in the **Appendix**). However, the development plan was revised after approval of the TIA Scoping Checklist to reduce density from 93 units (31 north and 62 south) to 82 units (17 north and 65 south). Furthermore, the addition of the southbound approach at the Weddington Road (NC 84) and Access A intersection has now been included.

Per coordination with Town of Weddington Staff, an additional interim scenario was analyzed without any of the NCDOT Statewide Transportation Improvement Program (STIP) Projects in place. This interim scenario was utilized to determine the impacts and recommend mitigation at the proposed study intersections should the proposed development be completed before the STIP projects. It was assumed that in this interim scenario, the proposed access points would operate as full movement until the STIP project widens and installs a median along Weddington Road (NC 84). Upon further coordination with NCDOT Staff, the proposed access points will operate under RIRO conditions in this scenario without the STIP project along Weddington Road (NC 84).

Kimley-Horn was retained to determine the potential traffic impacts of this development (in accordance with the traffic study guidelines in the [NCDOT Policy on Street and Driveway Access to North Carolina Highways](#) and set forth by the [Town of Weddington Traffic Impact Analysis \(TIA\) Process and Procedures Manual](#), and to identify transportation improvements that may be required to mitigate these impacts.

3.0 Existing Traffic Conditions

Existing traffic conditions were coordinated with Town of Weddington and NCDOT staff and collected through field observations and turning-movement counts to establish the existing conditions baseline analysis.

3.1 STUDY AREA

Based on coordination with the Town and NCDOT, the study area for this TIA includes the following existing intersections:

1. S Providence Road (NC 16) and Rea Road
2. Weddington Road (NC 84) and Cox Road
3. Weddington Road (NC 84) and Twelve Mile Creek Road

Figure 3.1 shows the study area intersections and the site location, **Figure 3.2** shows the proposed site plan for the development, and **Figure 3.3** shows the existing roadway geometry at the study intersections.

The primary roadways in the vicinity of the site are S Providence Road (NC 16), Weddington Road (NC 84), Rea Road, Cox Road, and Twelve Mile Creek Road.

S Providence Road (NC 16) is currently a four-lane, divided minor arterial with a posted speed limit of 45 miles per hour (mph) in the vicinity of the proposed development that transitions to a two-lane, undivided road just south of Rea Road. S Providence Road (NC 16) carries an annual average daily traffic (AADT) volume of 29,200 vehicles per day (vpd) north of Rea Road and 19,700 vpd south of Rea Road based on 2023 and 2022 NCDOT AADT data, respectively.

Weddington Road (NC 84) is a two-lane, undivided minor arterial with a posted speed limit of 45 mph in the vicinity of the proposed development. Weddington Road (NC 84) carries an AADT volume of 15,700 vpd west of Cox Road and 15,400 vpd east of Twelve Mile Creek Road based on 2023 NCDOT AADT data.

Rea Road is currently a four-lane, divided minor arterial road with a posted speed limit of 45 mph in the vicinity of the proposed development. Rea Road carries an AADT volume of 14,800 west of S Providence Road (NC 16) based on 2022 NCDOT AADT data.

Cox Road is currently a two-lane, undivided local road with a posted speed limit of 45 mph in the vicinity of the proposed development. Cox Road carries an AADT volume of 1,000 vpd north of Weddington Road (NC 84) based on 2022 NCDOT AADT data.

Twelve Mile Creek Road is a two-lane, undivided local road with a posted speed limit of 45 mph in the vicinity of the proposed development. Twelve Mile Creek Road carries an AADT volume of 3,500 vpd north of Weddington Road (NC 84) and 5,800 vpd south of Weddington Road (NC 84) based on 2023 and 2022 NCDOT AADT data, respectively.

3.2 EXISTING TRAFFIC VOLUME DEVELOPMENT


AM (7:00-9:00 AM), MID (2:00-4:00 PM), and PM (4:00-6:00 PM) intersection turning-movement, heavy-vehicle, pedestrian, and bicycle counts were collected by Quality Counts on Thursday, March 7, 2024, at the following intersections:

- S Providence Road (NC 16) and Rea Road
- Weddington Road (NC 84) and Cox Road
- Weddington Road (NC 84) and Twelve Mile Creek Road



The turning-movement counts collected by Quality Counts were utilized for the existing volumes at the existing study area intersections for both build-out scenarios. As documented in the approved NCDOT TIA Scoping Checklist, a growth rate of two percent (2%) was applied to the 2024 counts to determine future year traffic volumes under the scenarios without STIP projects. The NCDOT traffic forecast was used in lieu of the traffic counts to determine future year traffic volumes under the scenarios with STIP projects, as outlined in **Section 4.2**.

Volumes were not balanced between the study area intersections due to the presence of public streets and other residential and commercial driveways. Peak-hour intersection turning-movement count data is provided in the **Appendix**.

Figure 3.4 illustrates the 2024 existing AM, MID, and PM peak-hour traffic volumes.



N.T.S.



LOT AREA		20	21	42	64
LOT NUMBER	AREA (SF)	20	21	42	64
1	56787.6	23	41493.3	45	40040.0
2	43033.9	24	46716.6	46	41746.8
3	41335.8	25	50929.2	47	41052.7
4	44455.7	26	47356.1	48	42532.0
5	60000.0	27	40900.0	49	50605.7
6	46197.2	28	42733.8	50	48623.2
7	55915.6	29	45433.9	51	40231.4
8	40117.8	30	53523.2	52	41674.4
9	43249.2	31	40800.0	53	41483.5
10	43392.3	32	43285.9	54	41731.6
11	40800.0	33	40239.9	55	41321.1
12	40800.0	34	40800.0	56	41384.2
13	40070.0	35	40800.0	57	40273.8
14	42356.5	36	40900.0	58	45274.6
15	52699.4	37	40900.0	59	40441.2
16	51676.2	38	40185.0	60	40990.1
17	58116.8	39	42371.4	61	45118.8
18	44460.3	40	43466.2	62	55290.7
19	40070.0	41	46055.6	63	60503.5

SMALLEST LOT: 41, 40,000 SF
 AVE. LOT #: 41, 46,568 SF

DEVELOPER

NAME: TOLL BROTHERS
ADDRESS: 9130 KINGS PARADE BLV
CHARLOTTE, NC
CONTACT: ROBERT PRICE
PHONE #: (704) 849-2625
EMAIL: rprice1@tollbrothers.com

ENGINEER

NAME: McKIM & CREED
ADDRESS: 8020 TOWER POINT DRIVE
CHARLOTTE, NC 28227
CONTACT: BETH B. JOHNSTON, PLA
PHONE #: (704) 841-2588
EMAIL: bbailey@mckimcreed.com

BASE DATA:

1. PLAN IS CONCEPTUAL, IN NATURE AND IS SUBJECT TO CHANGE.
2. BOUNDARY FROM SURVEY PROVIDED BY CLIENT, RECEIVED 02/02/2024.
3. PRELIMINARY WETLANDS/STREAM DELINEATION PROVIDED BY WETLANDS & WATERS. DATA HAS NOT BEEN SURVEYED OR VERIFIED.
4. EAGLE'S NEST APPROXIMATE LOCATION PROVIDED BY WETLANDS & WATERS.
5. FUTURE NCDOT ROW FROM "U3467_Rdy_RPC_psh, 10-12" SHEETS 10 & 11, BY NVS ENGINEERS & CONSULTANTS, INC, DATED 10/30/2023.
6. USE DATA (TOPOGRAPHY, PARCEL LINES, ROAD CENTERLINES, EXISTING BUILDINGS, ETC) FROM AERIAL PHOTOGRAPHY, NCDOT, AND OTHER PUBLICLY AVAILABLE SOURCES. BASE DATA IS CONSIDERED PRELIMINARY AND SUBJECT TO FIELD VERIFICATION AND

[illegible]

This electronic document is the property of
McKim & Creed, Inc.
and is not to be used for any
purpose without the written consent
of the engineer whose seal appears
on the original certified document.

**DO NOT REMOVE FROM
ELECTRONIC FILE**




DEAL LAKE
WEDDINGTON
UNION COUNTY, NORTH CAROLINA

SITE PLAN - ENLARGED

DATE: JUNE 2024	SCALE	2
MCE PROJ. # 02741-0911	HORIZONTAL:	
DRAWN BIL	1" = 200'	
DESIGNED BIL	VERTICAL:	
CHECKED TMB	N/A	
PROJ. MGR. BIL		REVISION

STATUS: PRELIMINARY DRAWING NOT FOR CONSTRUCTION



4.0 Background Traffic Volume Development

Projected background (non-project) traffic is defined as the expected growth or change in traffic volumes on the surrounding roadway network between the year the existing counts were collected (2024) and the expected build-out year (2029) absent the construction and opening of the proposed project. This includes both non-specific general growth based on historical increase in local traffic volumes (historical background growth), along with specific growth and/or change in traffic volumes caused by either approved, but not yet fully-constructed, off-site developments and/or planned transportation projects specifically identified within the vicinity of the proposed development.

4.1 HISTORICAL BACKGROUND GROWTH TRAFFIC

Historical background growth is the increase in existing traffic volumes due to usage increases and non-specific growth throughout the area, and accounts for growth that is independent of specific off-site developments or planned transportation projects. Historical background growth traffic is calculated using an annual growth rate, which is applied to the existing traffic volumes up to the future horizon years. As shown in the approved NCDOT scoping checklist, an annual growth rate of two percent (2%) was applied to the 2024 existing peak-hour traffic volumes to calculate base 2029 background traffic volumes under the future year scenarios without STIP projects. This growth rate was determined based on review of historical NCDOT AADT maps in coordination with NCDOT and Town of Weddington, along with consideration of the additional specific traffic being added by the two (2) approved developments discussed below.

4.2 FORECAST TRAFFIC VOLUMES

The 2029 background volumes used for the future analyses with STIP projects, were calculated based on the forecast volumes on the latest roadway plan set provided by NCDOT for Statewide Transportation Improvement Program (STIP) Project U-3467. The NCDOT Intersection Analysis Utility (IAU) spreadsheet was used to calculate/convert the AADT volumes from the roadway plans into peak-hour intersection turning-movement volumes. The *FS-1810D Project Level Traffic Forecast Report* (RK&K, September 2018) and U-3467 Environmental Assessment (Mulkey Engineers & Consultants, May 2015) were also utilized in order to determine the directional splits for all study area intersections. This methodology was determined based on coordination with Town of Weddington and NCDOT staff. IAU worksheets and MID peak-hour traffic volume calculations are included in the **Appendix**.

4.3 APPROVED DEVELOPMENTS

At the direction of the Town of Weddington and NCDOT staff, no approved developments were identified for inclusion in this TIA at the time of the original Scoping Process. However, per coordination with Town of Weddington Staff, two approved developments have been added to this TIA UPDATE, as outlined in **Table 4.1**.

Table 4.1 – Approved Developments		
Development	Land Use/Intensity	Required Improvements
Providence & Rea <u>(NW of NC 16 & Rea Rd)</u>	Single-Family (Detached) – 56 DUs	No required improvements at study intersections.
Weddington Office Park <u>(N of NC 84)</u>	General Office – 10,000 SF Medical Office- 10,000 SF	No required improvements at study intersections.

Site trips for both developments were obtained from their respective TIAs:

- Providence & Rea (Design Resource Group, June 2024)
- Weddington Office Road (Design Resource Group, May 2024)

Approved development volumes for the midday peak hour were not included in these TIAs. These volumes were calculated utilizing the hourly breakdowns provided in ITE Trip Generation and applied to the PM peak hour approved development volumes to determine the midday approved development volumes.

Calculations for approved development traffic are included in the **Appendix**.

4.4 PLANNED TRANSPORTATION PROJECTS

Two (2) future transportation projects have been identified within the study area based on review of the following adopted transportation plans for the area:

- NCDOT [2024-2033 State Transportation Improvement Program](#) (STIP)
- Charlotte Regional Transportation Planning Organization (CRTPO) [2050 Metropolitan Transportation Plan](#) (MTP)
- CRTPO [Comprehensive Transportation Plan](#) (CTP)

Below is a summary of the two (2) future transportation projects identified:

- 1. Weddington Road (NC 84) (U-3467)**
 - Construct four-lane road from NC 16 to Waxhaw-Indian Trail Rd (see below for more detail)
 - Funded for Utilities FY 2024-2025
 - Funded for ROW FY 2024-2028
 - Funded for Construction FY 2027-2030
- 2. S Providence Road (NC 16) (U-5769A)**
 - NC 16 Widening from Rea Rd to Bonds Grove Church Rd (see below for more detail)
 - Funded for Utilities FY 2025-2026
 - Funded for ROW FY 2025-2029
 - Funded for Construction FY 2029-2032


Based on input during the TIA Scoping Process and given the current schedule, both TIP projects were included in 2029 analyses. However, based on subsequent coordination with Town of Weddington Staff, an additional scenario was added to reflect operations in the study area should the proposed development be complete before these TIP projects.

U-3467 will extend Rea Road 1.7 miles east from S Providence Road (NC 16) to Weddington Road (NC 84) near Twelve Mile Creek Road. Proposed work also involves widening 2.7 miles of the existing Weddington Road (NC 84) from two to four lanes from Twelve Mile Creek Road to Waxhaw-Indian Trail Road in Wesley Chapel. Based on the [current NCDOT STIP](#) as of April 2024, this project is scheduled to begin construction in FY 2027 and was included in the 2029 background and build-out analysis scenarios. Final intersection configurations for U-3467 may differ from the improvements assumed in this TIA.

Based on the latest roadway plan set provided by NCDOT included in the **Appendix** and confirmed in the latest public hearing map intersection concepts shown below, this project intends to improve the following study area intersections:


3. **Weddington Rd (NC 84) and Twelve Mile Creek Rd** – this signalized intersection is planned to remain full-movement with the following approach laneage:

- Northbound – One through lane, one left-turn lane, and one right-turn lane along Twelve Mile Creek Road.
- Southbound – One through lane, one left-turn lane, and one right-turn lane along Twelve Mile Creek Road.
- Eastbound – Two through lanes, one left-turn lane, and one right-turn lane along Weddington Road (NC 84).
- Westbound – Two through lanes, one left-turn lane, and one right-turn lane along Weddington Road (NC 84).



4. **Weddington Rd (NC 84) and Rea Rd Extension** – this proposed intersection is planned to be full-movement with the following approach laneage:

- Southbound – Two left-turn lanes and one right-turn lane along Weddington Road (NC 84).
- Eastbound – Two through lanes and one left-turn lane along Rea Road Extension.
- Westbound – Two through lanes, one U-turn lane, and one right-turn lane along Weddington Road (NC 84).




The latest ROW design plans for NCDOT TIP Project No. U-3467, funded to improve Weddington Road (NC 84) between S Providence Road (NC 16) and Waxhaw Indian Trail Road, are also included in the **Appendix**.

U-5769A will widen S Providence Road (NC 16) between Rea Road Extension and Bonds Grove Church Road from a two (2)-lane facility to a median-divided, four (4)-lane facility. This project intends to improve S Providence Road (NC 16) through a combination of conventional and reduced conflict intersections (RCIs). Based on the [current NCDOT STIP](#) as of April 2024, this project is scheduled to begin construction in FY 2029 and was included in the 2029 background and build-out analysis scenarios. Final intersection configurations for U-5769A may differ from the improvements assumed in this TIA.

Based on the latest roadway plan set provided by NCDOT included in the **Appendix** and as shown below, this project intends to improve the following study area intersection:

1. **S Providence Rd (NC 16) and Rea Rd/Rea Rd Extension** - this intersection is planned to be converted from the existing standard full-movement configuration to a RCI where left-turns are not allowed at the main intersection. Instead, all left-turn movements will be redirected to U-turn bulbs on each leg of the S Providence Rd (NC 16) and Rea Road/Rea Road Extension intersection. U-turn bulbs on S Providence Rd (NC 16) will be signalized and U-turn bulbs on Rea Rd/Rea Rd Extension will be unsignalized. U-3467 will construct the fourth leg of this intersection and then will be modified to a RCI as part of U-5769A.




Based on these plans, the following approach laneage was assumed:


- Northbound – Two through lanes and two right-turn lanes along S Providence Rd (NC 16)
- Southbound – Two through lanes and two right-turn lanes along S Providence Rd (NC 16)
- Eastbound – Two through lanes and two right-turn lanes along Rea Rd
- Westbound – Two through lanes and two right-turn lanes along Rea Rd Extension


The projected 2029 background peak-hour traffic volumes are shown in the following figures:

- **Figure 4.1** – 2029 Background AM Peak-Hour Traffic Volumes w/ STIPs
- **Figure 4.2** – 2029 Background MID Peak-Hour Traffic Volumes w/ STIPs
- **Figure 4.3** – 2029 Background PM Peak-Hour Traffic Volumes w/ STIPs
- **Figure 4.4** – 2029 Background AM Peak-Hour Traffic Volumes w/o STIPs
- **Figure 4.5** – 2029 Background MID Peak-Hour Traffic Volumes w/o STIPs
- **Figure 4.6** – 2029 Background PM Peak-Hour Traffic Volumes w/o STIPs

Redistribution calculations are provided in the **Appendix**.







5.0 Site Traffic Volume Development

Site traffic developed for this TIA is defined as the vehicle trips expected to be generated and added to the study area by construction of the proposed development, and the distribution and assignment of that traffic throughout the surrounding network.

5.1 SITE ACCESS

For the purposes of this TIA, a build-out year of 2029 was considered. Based on the site plan, the proposed development will be accessed via two external access points along Weddington Road (NC 84):

- Access A – an unsignalized, right-in/right-out (RIRO) connection to Weddington Road (NC 84) approximately 940 feet east of Lake Forest Drive; this access serves both sides of the development.
- Access B – an unsignalized, RIRO connection to Weddington Road approximately 560 feet east of Access A; this access serves both sides of the development.

5.2 TRAFFIC GENERATION

The traffic generation potential of the proposed development was determined using the trip generation rates published in *Trip Generation* (Institute of Transportation Engineers, Eleventh Edition, 2021). Based on the site plan, the proposed development is currently envisioned to consist of 17 single-family detached homes on the north side of Weddington Road and 65 single-family detached homes on the south side of Weddington Road (82 single-family detached homes).

Table 5.1 summarizes the projected trip generation for the proposed development. During a typical weekday, it has the potential to generate 65, 72, and 85 net new external trips during the AM, MID, and PM peak hours, respectively.

ITE LUC	Land Use	Intensity		Daily	AM Peak Hour			Midday Peak Hour*			PM Peak Hour		
					Total	In	Out	Total	In	Out	Total	In	Out
210	Single-Family Detached Housing (North Parcel)	17	DU	198	15	4	11	16	10	6	19	12	7
210	Single-Family Detached Housing (South Parcel)	65	DU	679	50	13	37	56	35	21	66	42	24
Net New External Trips				877	65	17	48	72	45	27	85	54	31

*ITE does not provide weekday, midday peak-hour traffic generation rates. The hourly breakdowns provided in ITE Trip Generation were applied to the PM peak-hour trip generation to determine midday peak-hour trip generation. It was assumed that midday trips would operate with the same in/out percentages as the PM peak-hour.

5.3 SITE TRAFFIC DISTRIBUTION AND ASSIGNMENT

The proposed development's trips were assigned to the surrounding network based on existing peak-hour turning movements, surrounding land uses, locations of similar land use and population densities in the area. The following site traffic distribution was reviewed and approved as part of the TIA Scoping Checklist by the Town of Weddington and NCDOT:

- 20% to/from the east along Weddington Road (NC 84)
- 20% to/from the west along Rea Road
- 30% to/from the north along S Providence Road (NC 16)
- 10% to/from the south along S Providence Road (NC 16)
- 5% to/from the north along Cox Road
- 5% to/from the north along Twelve Mile Creek Road
- 10% to/from the south along Twelve Mile Creek Road

The overall site traffic distribution and assignment can be seen in the following figures:


- **Figure 5.1** – Sight Traffic Distribution and Assignment w/ STIPs
- **Figure 5.2** – Sight Traffic Distribution and Assignment w/o STIPs


5.4 BUILD-OUT TRAFFIC VOLUMES


The build-out traffic volumes include the assignment of the projected site traffic generation added to the appropriate background traffic volumes. Build-out traffic volumes are shown in the following figures:


- **Figure 5.3** – 2029 Build-out AM Peak-Hour Traffic Volumes w/ STIPs
- **Figure 5.4** – 2029 Build-out MID Peak-Hour Traffic Volumes w/ STIPs
- **Figure 5.5** – 2029 Build-out PM Peak-Hour Traffic Volumes w/ STIPs
- **Figure 5.6** – 2029 Build-out AM Peak-Hour Traffic Volumes w/o STIPs
- **Figure 5.7** – 2029 Build-out MID Peak-Hour Traffic Volumes w/o STIPs
- **Figure 5.8** – 2029 Build-out PM Peak-Hour Traffic Volumes w/o STIPs


Intersection volume development worksheets for all intersections within the study network are provided in the **Appendix**.














6.0 Capacity Analysis

Based on the requirements set forth by the [Town of Weddington Traffic Impact Analysis \(TIA\) Process and Procedures Manual](#) and in accordance with the traffic study guidelines in the [NCDOT Policy on Street and Driveway Access to North Carolina Highways](#), capacity analyses were performed at the study area intersections for each of the following AM, MID, and PM peak-hour scenarios:

- 2024 Existing Conditions
- 2029 Background Conditions (with STIP projects)
- 2029 Background Conditions (without STIP projects)
- 2029 Build-out Conditions (with STIP projects)
- 2029 Build-out Conditions (without STIP projects)

Capacity analyses were performed for the AM, MID, and PM peak hours using Synchro Version 11 software to determine the operating characteristics at the study area intersections of the adjacent street network and to evaluate the impacts of the proposed development. Capacity is defined as the maximum number of vehicles that can pass over a particular road segment, or through a particular intersection, within a specified period of time under prevailing operational, geometric and controlling conditions within a set time duration. This software program uses methodologies contained in the *Highway Capacity Manual* (HCM) to determine the operating characteristics of an intersection.

The HCM defines LOS as a “quantitative stratification of a performance measure or measures representing quality of service” and is used to “translate complex numerical performance results into a simple A-F system representative of travelers’ perceptions of the quality of service provided by a facility or service”. The HCM defines six levels of service, LOS A through LOS F, with A having the best operating conditions from the traveler’s perspective and F having the worst. However, it must be understood that “the LOS letter result hides much of the complexity of facility performance”, and that “the appropriate LOS for a given system element in the community is a decision for local policy makers”. According to the HCM, “for cost, environmental impact, and other reasons, roadways are typically designed not to provide LOS A conditions during peak periods but instead to provide some lower LOS that balances individual travelers’ desires against society’s desires and financial resources. Nevertheless, during low-volume periods of the day, a system element may operate at LOS A.”

LOS for a two-way stop-controlled (TWSC) intersection is determined by the control delay at the side-street approaches, typically during the highest volume periods of the day, the AM and PM peak periods. Control delay includes initial deceleration delay, queue move-up time, stopped delay, and final acceleration delay. With respect to field measurements, control delay is defined as the total elapsed time from the time a vehicle stops at the end of the queue to the time the vehicle departs from the stop line. It is typical for stop sign-controlled side streets and driveways intersecting major streets to experience long delays during peak hours, particularly for left-turn movements. The majority of the traffic moving through the intersection on the major street experiences little or no delay.

LOS for signalized intersections is reported for the intersection as a whole, and typically during the highest volume periods of the day, the AM and PM peak periods. Once or more movements at an intersection may experience a low level-of-service, while the intersection as a whole may operate acceptably,

Table 6.0-A and **Table 6.0-B** list the LOS control delay thresholds published in the HCM for unsignalized and signalized intersections, respectively, as well as the unsignalized operational descriptions assumed herein.

Table 6.0-A Vehicular LOS Control Delay Thresholds for Unsignalized Intersections		
Level-of-Service	Average Control Delay per Vehicle [sec/veh]	
A	≤ 10	Short Delays
B	> 10 – 15	
C	> 15 – 25	
D	> 25 – 35	Moderate Delays
E	> 35 – 50	
F	> 50	Long Delays

Table 6.0-B Vehicular LOS Control Delay Thresholds for Signalized Intersections	
Level-of-Service	Average Control Delay per Vehicle [sec/veh]
A	≤ 10
B	> 10 – 20
C	> 20 – 35
D	> 35 – 55
E	> 55 – 80
F	> 80

The signal geometric plans for each of the following signalized intersections were obtained from NCDOT's signal plan database and were used in the development of the existing conditions Synchro network:

1. S Providence Road (NC 16) and Rea Road
3. Weddington Road (NC 84) and Twelve Mile Creek Road

Based on the provided signal plans, the intersection of S Providence Road (NC 16)/Rea Road is part of the NC 16 (Providence Road) Closed Loop System and the intersection of Weddington Road (NC 84)/Twelve Mile Creek Road is isolated and not part of a coordinated signal system. Using the signal timing plans provided by NCDOT, cycle lengths and splits were optimized separately. The signal geometrics plans are included in the **Appendix**.

As discussed in **Section 4.3**, due to the significant reconfiguration of the study area signalized intersections as part of U-3467 and U-5769A, the cycle lengths and splits were optimized under background and build-out conditions. It was assumed that signals along/adjacent to S Providence Road (NC 16) would be part of a coordinated signal system, while signals along NC 84 between Cox Road and Twelve Mile Creek Road would be part of a separate coordinated signal system.

For the scenario without the STIP projects, the S Providence Road (NC 16) and Rea Road and Weddington Road (NC 84) and Twelve Mile Creek intersections were optimized separately under background and build-out conditions.

The following modifications from the background data collected were applied to the capacity analyses to meet NCDOT Congestion Management Capacity Analysis Guidelines:

- Right-turn-on-red (RTOR) operations were not allowed.
- Protected-only left-turn phasing was used for analysis of future operations where protected/permitted left-turn phasing exists in the field.
- Lost time adjust was added to the yellow and all-red times provided in the existing signal and time-of-day plans to maintain a total lost time of 5 seconds for each movement.
- A minimum of 4 vehicles per hour were used for permissible movements, excluding movements into and out of the proposed site.

In the existing condition, the observed peak hour factor (PHF) was used in the analysis, whereas a 0.9 PHF was used for all future conditions with the exception of the Weddington Road (NC 84) and Twelve Mile Creek Road intersection. A weighted PHF was used in the AM and MID peaks hours to account for the impacts of existing school traffic.

In the existing and future conditions, the observed heavy vehicle percentage was used in the analysis, subject to a 2% minimum.

Capacity analysis reports generated by Synchro Version 11 software and queuing and blocking reports generated by the SimTraffic microsimulation model are included in the **Appendix**.

6.1 S PROVIDENCE ROAD (NC 16) AND REA ROAD/U-3467


Table 6.1A summarizes the LOS, control delay and 95th percentile queue lengths at the signalized intersection of S Providence Road (NC 16) and Rea Road/U-3467

Table 6.1A - S Providence Road (NC 16) and Rea Road/U-3467													
Condition	Measure	EB			WB		NB			SB			Intersection LOS (Delay)
		EBL	EBT	EBR	WBT	WBR	NBL	NBT	NBR	SBLU	SBT	SBR	
AM Peak Hour													
2024 Existing	LOS (Delay)	D (38.7)			-		C (21.2)			C (21.4)			C (25.0)
	Synchro 95th Q	#338'	-	115'	-	-	#184'	202'	-	8'	326'	90'	
2029 Background w/ STIPs	LOS (Delay)	C (34.5)			C (32.3)		B (19.8)			B (11.7)			C (20.7)
	Synchro 95th Q	-	214'	196'	134'	184'	-	#800'	m31'	-	316'	445'	
2029 Build-out w/ STIPs	LOS (Delay)	C (34.4)			C (32.4)		B (20.0)			B (11.8)			C (20.8)
	Synchro 95th Q	-	215'	198'	139'	187'	-	#800'	m32'	-	317'	446'	
MD Peak Hour													
2024 Existing	LOS (Delay)	D (48.8)			-		C (25.2)			D (37.2)			D (36.9)
	Synchro 95th Q	#509'	-	241'	-	-	#132'	151'	-	8'	#652'	70'	
2029 Background w/ STIPs	LOS (Delay)	C (21.7)			B (18.8)		B (19.1)			B (13.5)			B (18.0)
	Synchro 95th Q	-	245'	181'	94'	167'	-	#240'	46'	-	200'	121'	
2029 Build-out w/ STIPs	LOS (Delay)	C (21.6)			B (18.7)		B (19.3)			B (13.6)			B (18.1)
	Synchro 95th Q	-	248'	182'	97'	168'	-	#243'	47'	-	193'	123'	
PM Peak Hour													
2024 Existing	LOS (Delay)	D (46.5)			-		C (22.4)			C (32.1)			C (33.5)
	Synchro 95th Q	#567'	-	230'	-	-	#108'	183'	-	8'	#608'	136'	
2029 Background w/ STIPs	LOS (Delay)	C (28.7)			C (26.0)		C (26.9)			B (13.6)			C (22.9)
	Synchro 95th Q	-	316'	266'	82'	259'	-	#637'	17'	-	257'	146'	
2029 Build-out w/ STIPs	LOS (Delay)	C (28.8)			C (26.0)		C (26.7)			B (13.8)			C (23.0)
	Synchro 95th Q	-	323'	268'	84'	260'	-	#623'	34'	-	269'	152'	
Background Storage				750'		425'			375'			500'	
# 95th percentile volume exceeds capacity, queue may be longer													
m Volume for 95th percentile queue is metered by upstream signal													

95th percentile volume exceeds capacity, queue may be longer
m Volume for 95th percentile queue is metered by upstream signal

As shown in **Table 6.1**, under 2024 existing conditions, the overall intersection is expected to operate at LOS C during the AM and PM peak hours and LOS D during the MID peak hour.

As discussed in **Section 4.3**, U-5769A was included in the 2029 w/ STIPs analyses. Based on the roadway plan set provided by NCDOT and shown in the image to the right, this intersection is planned to be converted from the existing standard full-movement configuration to a RCI where left-turns are not allowed at the main intersection. Instead, all left-turn movements will be redirected to U-turn bulbs on each leg of the S Providence Rd (NC 16) and Rea Road/Rea Road Extension intersection. U-3467 will construct the fourth leg of this intersection and then will be modified to a RCI as part of U-5769A. Based on these plans, the following approach laneage was assumed in 2029:



- Northbound – Two through lanes and two right-turn lanes along S Providence Rd (NC 16)
- Southbound – Two through lanes and two right-turn lanes along S Providence Rd (NC 16)
- Eastbound – Two through lanes and two right-turn lanes along Rea Rd
- Westbound – Two through lanes and two right-turn lanes along Rea Rd Extension

Table 6.1A shows that with these planned improvements in place, the overall intersection is expected to operate at LOS C or better for all peak hours under 2029 background conditions. With

the addition of the site traffic, the overall intersection is expected to continue to operate at LOS C or better for all peak hours. Therefore, no improvements are identified for capacity purposes.

6.1B – S Providence Road (NC 16) and Northern U-turn Bulb

Table 6.1B summarizes the LOS, control delay and 95th percentile queue lengths at the signalized U-5769A northbound U-turn bulb planned to be located along S Providence Road (NC 16) approximately 675 feet north of Rea Road.

Table 6.1B - S Providence Road (NC 16) and Northern U-turn Bulb				
Condition	Measure	NB	SB	Intersection
		NBU	SBT	LOS (Delay)
AM Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	C (34.9)	B (16.7)	C (21.2)
	Synchro 95th Q	m215'	572'	
2029 Build-out w/ STIPs	LOS (Delay)	C (34.9)	B (16.8)	C (21.2)
	Synchro 95th Q	m215'	573'	
MD Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	C (25.5)	A (7.9)	B (11.2)
	Synchro 95th Q	m89'	243'	
2029 Build-out w/ STIPs	LOS (Delay)	C (26.0)	A (8.0)	B (11.3)
	Synchro 95th Q	m91'	243'	
PM Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	C (29.0)	B (10.3)	B (13.8)
	Synchro 95th Q	m114'	365'	
2029 Build-out w/ STIPs	LOS (Delay)	C (29.8)	A (10.0)	B (13.7)
	Synchro 95th Q	m118'	352'	
Background Storage		450'		
m Volume for 95th percentile queue is metered by upstream signal				

Table 6.1B shows that with the planned improvements in place, the overall intersection is expected to operate at LOS C or better for all peak hours under 2029 background conditions. With the addition of the site traffic, the overall intersection is expected to continue to operate at LOS C or better for all peak hours. Therefore, no improvements are identified for capacity purposes.

6.1C – S Providence Road (NC 16) and Southern U-turn Bulb

Table 6.1C summarizes the LOS, control delay and 95th percentile queue lengths at the signalized U-5769A southbound U-turn bulb planned to be located along S Providence Road (NC 16) approximately 600 feet south of Rea Road.

Table 6.1C - S Providence Road (NC 16) and Southern U-turn Bulb				
Condition	Measure	SB	NB	Intersection
		SBU	NBT	LOS (Delay)
AM Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	D (44.4)	A (4.0)	A (4.9)
	Synchro 95th Q	m44'	274'	
2029 Build-out w/ STIPs	LOS (Delay)	D (45.3)	A (4.1)	A (5.0)
	Synchro 95th Q	m47'	275'	
MD Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	C (32.3)	A (4.8)	A (5.9)
	Synchro 95th Q	m49'	185'	
2029 Build-out w/ STIPs	LOS (Delay)	C (32.6)	A (4.8)	A (6.0)
	Synchro 95th Q	m53'	186'	
PM Peak Hour				
2029 Background w/ STIPs	LOS (Delay)	C (34.9)	A (4.1)	A (4.8)
	Synchro 95th Q	m29'	242'	
2029 Build-out w/ STIPs	LOS (Delay)	D (39.0)	A (4.2)	A (5.1)
	Synchro 95th Q	m35'	245'	
Background Storage		425'		
m Volume for 95th percentile queue is metered by upstream signal				

Table 6.1C shows that with the planned improvements in place, the overall intersection is expected to operate at LOS A or better for all peak hours under 2029 background conditions. With the addition of the site traffic, the overall intersection is expected to continue to operate at LOS A or better for all peak hours. Therefore, no improvements are identified for capacity purposes.

6.1D – Read Road and Western U-turn Bulb

Table 6.1D summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized U-3467 westbound U-turn bulb planned to be located along Rea Road approximately 1,000 feet west of S Providence Road (NC 16).

Table 6.1D - Rea Road and Western U-turn Bulb			
Condition	Measure	EB	WB
		EBT	WBU
AM Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	B (13.8)
	Synchro 95th Q	0'	15'
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	B (14.0)
	Synchro 95th Q	0'	18'
MD Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	C (19.1)
	Synchro 95th Q	0'	30'
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	C (19.4)
	Synchro 95th Q	0'	30'
PM Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	C (20.4)
	Synchro 95th Q	0'	28'
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	C (20.9)
	Synchro 95th Q	0'	28'
Background Storage			525'

Table 6.1D shows that with these planned improvements in place, the eastbound and westbound approaches are expected to operate at LOS C or better for all peak hours under 2029 background conditions. With the addition of the site traffic, the approaches are expected to continue to operate at LOS C or better for all peak hours. Therefore, no improvements are identified for capacity purposes.

6.1E – Rea Road Extension and Eastern U-turn Bulb

Table 6.1E summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized U-3467 eastbound U-turn bulb planned to be located along Rea Road Extension approximately 850 feet east of S Providence Road (NC 16).

Table 6.1E - Rea Road Extension and Eastern U-turn Bulb			
Condition	Measure	WB	EB
		WBT	EBU
AM Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	C (15.7)
	Synchro 95th Q	0'	90'
2029 Build-out w STIP	LOS (Delay)	A (0.0)	C (16.1)
	Synchro 95th Q	0'	93'
MD Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	C (21.1)
	Synchro 95th Q	0'	155'
2029 Build-out w STIP	LOS (Delay)	A (0.0)	C (21.5)
	Synchro 95th Q	0'	158'
PM Peak Hour			
2029 Background w/ STIPs	LOS (Delay)	A (0.0)	D (26.3)
	Synchro 95th Q	0'	233'
2029 Build-out w STIP	LOS (Delay)	A (0.0)	D (27.1)
	Synchro 95th Q	0'	238'
Background Storage			500'

Table 6.1E shows that with the planned improvements in place, the westbound and eastbound approaches are expected to operate at LOS D or better for all peak hours under 2029 background conditions. With the addition of the site traffic, the approaches are expected to continue to operate at LOS D or better for all peak hours with minimal increases in delay and queuing. Therefore, no improvements are identified for capacity purposes.

6.1F – S Providence Road (NC 16) and Rea Road

Table 6.1F summarizes the LOS, control delay and 95th percentile queue lengths at the signalized intersection of S Providence Road (NC 16) and Rea Road without STIP projects.

Table 6.1F - S Providence Road (NC 16) and Rea Road									
Condition	Measure	EB		NB		SB			Intersection
		EBUL	EBR	NBL	NBT	SBU	SBT	SBR	LOS (Delay)
AM Peak Hour									
2024 Existing	LOS (Delay)	D (38.7)		C (21.2)		C (21.4)			C (25.0)
	Synchro 95th Q	#338'	115'	#184'	202'	8'	326'	90'	
2029 Background w/o STIPs	LOS (Delay)	D (38.4)		C (23.0)		C (22.2)			C (26.0)
	Synchro 95th Q	#392'	126'	#209'	256'	9'	#457'	57'	
2029 Build-out w/o STIPs	LOS (Delay)	D (38.6)		C (23.1)		C (22.5)			C (26.2)
	Synchro 95th Q	#395'	126'	#209'	257'	9'	#464'	58'	
MD Peak Hour									
2024 Existing	LOS (Delay)	D (48.8)		C (25.2)		D (37.2)			D (36.9)
	Synchro 95th Q	#509'	241'	#132'	151'	8'	#652'	70'	
2029 Background w/o STIPs	LOS (Delay)	E (71.3)		C (34.9)		D (54.0)			D (52.9)
	Synchro 95th Q	#751'	377'	#205'	226'	8'	#999'	144'	
2029 Build-out w/o STIPs	LOS (Delay)	E (74.9)		C (34.8)		D (54.6)			D (54.2)
	Synchro 95th Q	#769'	377'	#205'	228'	8'	#1004'	148'	
PM Peak Hour									
2024 Existing	LOS (Delay)	D (46.5)		C (22.4)		C (32.1)			C (33.5)
	Synchro 95th Q	#567'	230'	#108'	183'	8'	#608'	136'	
2029 Background w/o STIPs	LOS (Delay)	E (67.2)		C (34.3)		D (50.4)			D (50.5)
	Synchro 95th Q	#852'	348'	#181'	300'	9'	#917'	285'	
2029 Build-out w/o STIPs	LOS (Delay)	E (71.1)		C (34.3)		D (51.3)			D (52.0)
	Synchro 95th Q	#873'	348'	#181'	301'	9'	#925'	291'	
Background Storage				425'		325'			
# 95th percentile volume exceeds capacity, queue may be longer									

Based on coordination with the Town, an additional interim scenario was run without either of the NCDOT TIP Projects in place.

Table 6.1F shows that without the planned improvements in place, the overall intersection is expected to operate at LOS D or better for all peak hours through 2029 background conditions. With the addition of the site traffic, the overall intersection is expected to continue to operate at LOS D or better for all peak hours with minimal increases in delay and queues. Therefore, no improvements are identified for capacity purposes.

6.2 WEDDINGTON ROAD (NC 84) AND COX ROAD

Table 6.2A summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized, stop-controlled intersection of Weddington Road (NC 84) and Cox Road.

Table 6.2A - Weddington Road (NC 84) and Cox Road					
Condition	Measure	EB		WB	SB
		*EBL	EBT	WBTR	SBLR
AM Peak Hour					
2024 Existing	LOS (Delay)	B (10.7)	A (0.0)	A (0.0)	E (38.0)
	Synchro 95th Q	3'	0'	0'	95'
2029 Background w/ STIPs	LOS (Delay)	B (10.1)	A (0.0)	A (0.0)	D (26.5)
	Synchro 95th Q	0'	0'	0'	43'
2029 Build-out w/ STIPs	LOS (Delay)	B (10.1)	A (0.0)	A (0.0)	D (27.0)
	Synchro 95th Q	0'	0'	0'	45'
MD Peak Hour					
2024 Existing	LOS (Delay)	A (9.6)	A (0.0)	A (0.0)	C (24.9)
	Synchro 95th Q	3'	0'	0'	33'
2029 Background w/ STIPs	LOS (Delay)	A (9.1)	A (0.0)	A (0.0)	C (22.7)
	Synchro 95th Q	3'	0'	0'	28'
2029 Build-out w/ STIPs	LOS (Delay)	A (9.2)	A (0.0)	A (0.0)	C (23.4)
	Synchro 95th Q	3'	0'	0'	30'
PM Peak Hour					
2024 Existing	LOS (Delay)	A (9.1)	A (0.0)	A (0.0)	D (25.6)
	Synchro 95th Q	3'	0'	0'	40'
2029 Background w/ STIPs	LOS (Delay)	A (9.3)	A (0.0)	A (0.0)	C (20.8)
	Synchro 95th Q	3'	0'	0'	15'
2029 Build-out w/ STIPs	LOS (Delay)	A (9.4)	A (0.0)	A (0.0)	C (21.3)
	Synchro 95th Q	3'	0'	0'	18'
Background Storage		125'			
*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions					

As shown in **Table 6.2A**, under 2024 existing conditions, the stop-controlled southbound approach of Cox Road is expected to operate with moderate delays during the AM and PM peak hours and short delays during the MID peak hour.

Under 2029 background conditions, the stop-controlled southbound approach is expected to operate with moderate delay during the AM peak hour and short delays during the MID and PM peak hours. The decrease in delay shown in **Table 6.2A** between existing and background conditions reflects the change in PHFs to meet [NCDOT Congestion Management Capacity Analysis Guidelines](#) as discussed in **Section 6.0**. This is due to the existing PHF being less than 0.9 for multiple movements during each peak hour. An increase in PHF to 0.9 causes the traffic volume to be more evenly distributed throughout the peak hour results in reduction in the average delay.

With the addition of site traffic, the stop-controlled southbound approach is expected to continue to operate with moderate delays during the AM peak hour and short delays during the MID and PM

peak hours with minimal increases in delay and queueing. Therefore, no improvements are identified for capacity purposes at this intersection.

6.2B – Weddington Road (NC 84) and Cox Road

Table 6.2B summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized, stop-controlled intersection of S Providence Road (NC 16) and Rea Road without STIP projects.

Table 6.2B - Weddington Road (NC 84) and Cox Road					
Condition	Measure	EB		WB	SB
		*EBL	EBT	WBTR	SBLR
AM Peak Hour					
2024 Existing	LOS (Delay)	B (10.7)	A (0.0)	A (0.0)	E (38.0)
	Synchro 95th Q	3'	0'	0'	95'
2029 Background w/o STIPs	LOS (Delay)	B (10.7)	A (0.0)	A (0.0)	E (36.5)
	Synchro 95th Q	0'	0'	0'	88'
2029 Build-out w/o STIPs	LOS (Delay)	B (10.9)	A (0.0)	A (0.0)	E (39.6)
	Synchro 95th Q	0'	0'	0'	93'
MD Peak Hour					
2024 Existing	LOS (Delay)	A (9.6)	A (0.0)	A (0.0)	C (24.9)
	Synchro 95th Q	3'	0'	0'	33'
2029 Background w/o STIPs	LOS (Delay)	A (9.4)	A (0.0)	A (0.0)	D (25.8)
	Synchro 95th Q	3'	0'	0'	25'
2029 Build-out w/o STIPs	LOS (Delay)	A (9.5)	A (0.0)	A (0.0)	D (26.9)
	Synchro 95th Q	3'	0'	0'	28'
PM Peak Hour					
2024 Existing	LOS (Delay)	A (9.1)	A (0.0)	A (0.0)	D (25.6)
	Synchro 95th Q	3'	0'	0'	40'
2029 Background w/o STIPs	LOS (Delay)	A (9.3)	A (0.0)	A (0.0)	D (29.5)
	Synchro 95th Q	3'	0'	0'	40'
2029 Build-out w/o STIPs	LOS (Delay)	A (9.4)	A (0.0)	A (0.0)	D (31.8)
	Synchro 95th Q	3'	0'	0'	45'
Background Storage		125'			
*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions					

Based on coordination with the Town, an additional interim scenario was run without either of the NCDOT TIP Projects in place.

Table 6.2B shows that without the planned improvements in place, under 2024 existing conditions, the stop-controlled southbound approach of Cox Road is expected to operate with moderate delays during the AM and PM peak hours and short delays during the MID peak hour.

Under 2029 background conditions, the stop-controlled southbound approach is expected to operate with moderate delay during all peak hours.

With the addition of the site traffic, the stop-controlled southbound approach is expected to continue to operate with moderate delay for all peak hours with minimal increases in delay and queues. Therefore, no improvements are identified for capacity purposes.

6.3 WEDDINGTON ROAD (NC 84) AND TWELVE MILE CREEK ROAD

Table 6.3A summarizes the LOS, control delay and 95th percentile queue lengths at the signalized, intersection of Weddington Road (NC 84) and Twelve Mile Creek Road.

Table 6.3A - Weddington Road (NC 84) and Twelve Mile Creek Road														
Condition	Measure	EB			WB			NB			SB			Intersection
		EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	LOS (Delay)
AM Peak Hour														
2024 Existing	LOS (Delay)	F (124.3)			F (265.5)			F (409.8)			F (212.6)			F (246.0)
	Synchro 95th Q	70'	#623'	-	44'	#931'	-	-	#473'	-	-	#611'	-	
2029 Background w/ STIPs	LOS (Delay)	D (38.7)			D (48.9)			E (71.1)			E (75.7)			D (50.7)
	Synchro 95th Q	138'	354'	131'	165'	605'	63'	#258'	37'	97'	124'	66'	202'	
2029 Build-out w/ STIPs	LOS (Delay)	D (39.6)			D (54.6)			E (72.6)			E (75.8)			D (53.2)
	Synchro 95th Q	164'	343'	128'	#177'	624'	64'	#265'	37'	97'	124'	66'	203'	
MD Peak Hour														
2024 Existing	LOS (Delay)	E (69.5)			D (45.8)			F (123.6)			D (47.3)			E (66.3)
	Synchro 95th Q	62'	#1012'	-	#78'	658'	-	-	#354'	-	-	195'	-	
2029 Background w/ STIPs	LOS (Delay)	C (30.1)			C (33.1)			E (57.6)			E (58.0)			D (39.7)
	Synchro 95th Q	113'	276'	87'	131'	256'	184'	#161'	169'	90'	#182'	135'	56'	
2029 Build-out w/ STIPs	LOS (Delay)	C (30.6)			C (34.3)			E (58.3)			E (58.0)			D (40.3)
	Synchro 95th Q	131'	273'	88'	131'	267'	188'	#173'	169'	90'	#182'	135'	58'	
PM Peak Hour														
2024 Existing	LOS (Delay)	E (77.3)			D (40.2)			F (145.4)			E (74.1)			E (74.8)
	Synchro 95th Q	30'	#1355'	-	#151'	563'	-	-	#570'	-	-	348'	-	
2029 Background w/ STIPs	LOS (Delay)	C (25.3)			C (33.2)			E (75.9)			E (58.2)			D (35.3)
	Synchro 95th Q	204'	393'	115'	113'	430'	88'	#258'	69'	135'	89'	44'	125'	
2029 Build-out w/ STIPs	LOS (Delay)	C (25.8)			D (36.3)			E (70.7)			E (58.1)			D (36.1)
	Synchro 95th Q	226'	399'	121'	113'	#468'	93'	#258'	68'	133'	89'	44'	128'	
Background Storage		450'		400'	300'		375'	225'		225'	175'		125'	
Exceeds storage														
# 95th percentile volume exceeds capacity, queue may be longer														

As shown in **Table 6.3A**, under 2024 existing conditions, the overall intersection is expected to operate at LOS F during the AM peak hour and LOS E during the MID and PM peak hours.

As discussed in **Section 4.3**, U-3467 was included in the 2029 analyses. Based on the latest roadway plan set provided by NCDOT and shown in the image to the right, this intersection is planned to remain full-movement with the following approach laneage:

- Northbound – One through lane, one left-turn lane, and one right-turn lane along Twelve Mile Creek Road.
- Southbound – One through lane, one left-turn lane, and one right-turn lane along Twelve Mile Creek Road.
- Eastbound – Two through lanes, one left-turn lane, and one right-turn lane along Weddington Road (NC 84).
- Westbound – Two through lanes, one left-turn lane, and one right-turn lane along Weddington Road (NC 84).




Table 6.3A shows that with these planned improvements in place, the overall intersection is expected to operate at LOS D or better for all peak hours under 2029 background conditions.

With the addition of site traffic, the overall intersection is expected to operate at LOS D during all peak hours. Therefore, no improvements are identified for capacity purposes.

Based on review of the Synchro 95th percentile queues, the following queues are expected to exceed the planned storage under build-out conditions:

- Northbound left-turn queue along Twelve Mile Creek Road during the AM and PM peak hours
- Southbound left-turn queue along Twelve Mile Creek Road during the MID peak hour
- Southbound right-turn queue along Twelve Mile Creek Road during the AM and PM peak hours

Since the storage is exceeded under both background and build-out conditions and the proposed site is not expected to significantly extend the projected queue lengths, extension of these turn lanes is not recommended as mitigation for the proposed Deal Lake development.

6.3B – Weddington Road (NC 84) and Twelve Mile Creek Road

Table 6.3B summarizes the LOS, control delay and 95th percentile queue lengths at the signalized intersection of Weddington Road (NC 84) and Twelve Mile Creek Road without STIP projects.

Table 6.3B - Weddington Road (NC 84) and Twelve Mile Creek Road								
Condition	Measure	EB		WB		NB	SB	Intersection
		EBL	EBTR	WBL	WBTR	NBLTR	SBLTR	LOS (Delay)
AM Peak Hour								
2024 Existing	LOS (Delay)	F (124.3)		F (265.5)		F (409.8)	F (212.6)	F (246.0)
	Synchro 95th Q	70'	#623'	44'	#931'	#473'	#611'	
2029 Background w/o STIPs	LOS (Delay)	F (189.4)		F (324.7)		F (549.9)	F (290.5)	F (328.9)
	Synchro 95th Q	#152'	#717'	74'	#1058'	#561'	#789'	
2029 Build-out w/o STIPs	LOS (Delay)	F (192.2)		F (306.7)		F (548.1)	F (306.8)	F (327.9)
	Synchro 95th Q	#155'	#733'	74'	#1052'	#563'	#800'	
MD Peak Hour								
2024 Existing	LOS (Delay)	E (69.5)		D (45.8)		F (123.6)	D (47.3)	E (66.3)
	Synchro 95th Q	62'	#1012'	#78'	658'	#354'	195'	
2029 Background w/o STIPs	LOS (Delay)	F (120.6)		F (80.3)		F (177.6)	E (66.1)	F (108.1)
	Synchro 95th Q	#217'	#1493'	#221'	#1017'	#508'	271'	
2029 Build-out w/o STIPs	LOS (Delay)	F (123.2)		F (81.6)		F (185.8)	E (64.2)	F (110.5)
	Synchro 95th Q	#217'	#1447'	#215'	#993'	#498'	258'	
PM Peak Hour								
2024 Existing	LOS (Delay)	E (77.3)		D (40.2)		F (145.4)	E (74.1)	E (74.8)
	Synchro 95th Q	30'	#1355'	#151'	563'	#570'	348'	
2029 Background w/o STIPs	LOS (Delay)	F (88.8)		D (47.3)		F (169.2)	E (71.5)	F (84.4)
	Synchro 95th Q	78'	#1415'	#229'	531'	#540'	#441'	
2029 Build-out w/o STIPs	LOS (Delay)	F (97.7)		D (48.0)		F (163.8)	E (68.3)	F (87.6)
	Synchro 95th Q	81'	#1448'	#229'	555'	#546'	#434'	
Background Storage		100'		100'				
Exceeds storage								
# 95th percentile volume exceeds capacity, queue may be longer								

Based on coordination with the Town, an additional interim scenario was run without either of the NCDOT TIP Projects in place.

As shown in **Table 6.3B**, under 2024 existing conditions, the overall intersection is expected to operate at LOS F during the AM peak hour and LOS E during the MID and PM peak hours.

The overall intersection is projected to operate at LOS F during all peak hours under 2029 background conditions. With the addition of the site traffic, the overall intersection is expected to operate with similar operations as compared to 2029 background conditions with no overall or approach LOS degradations. Delay on the eastbound approach during the PM peak hour is shown to increase, however this is a result of the optimization of the traffic signal where additional green time is provided to the side street movements – resulting in an increase in delay to the mainlines and reduction in delay for the side street movements.

Based on review of the Synchro 95th percentile queues, the following queues are expected to exceed the planned storage under build-out conditions:

- Eastbound left-turn queue along Weddington Road (NC 84) during the AM and MID peak hours
- Westbound left-turn queue along Weddington Road (NC 84) during the MID and PM peak hours

Since the storage is exceeded under both background and build-out conditions and the proposed site is not expected to significantly extend the projected queue lengths, extension of these turn lanes is not recommended as mitigation for the proposed Deal Lake development.

6.4 WEDDINGTON ROAD (NC 84) AND U-3467

As discussed in **Section 4.3**, a new signalized, tee-intersection is planned as part of U-3467 in which existing Weddington Road (NC 84) will be realigned to tie into the new Rea Road Extension approximately 1,050 feet south of Lake Forest Drive. **Table 6.4** summarizes the LOS, control delay and 95th percentile queue lengths at the future, signalized tee-intersection of Weddington Road (NC 84) and U-3467. The new eastbound approach (Rea Road Extension) is referred to as U-3467, with the existing realigned Weddington Road (NC 84) as the southbound and westbound approaches for the purposes of this analysis.

Table 6.4 - Weddington Road (NC 84) and U-3467									
Condition	Measure	EB		WB			SB		Intersection
		EBL	EBT	WBU	WBT	WBR	SBL	SBR	LOS (Delay)
AM Peak Hour									
2029 Background w/ STIPs	LOS (Delay)	B (12.5)		A (5.8)			D (52.7)		B (17.1)
	Synchro 95th Q	52'	219'	m4'	m130'	m59'	280'	33'	
2029 Build-out w/ STIPs	LOS (Delay)	B (12.7)		A (5.4)			D (52.7)		B (16.8)
	Synchro 95th Q	52'	226'	m10'	m109'	m15'	282'	33'	
MD Peak Hour									
2029 Background w/ STIPs	LOS (Delay)	B (10.6)		A (6.9)			D (47.0)		B (19.1)
	Synchro 95th Q	45'	161'	m8'	120'	40'	222'	28'	
2029 Build-out w/ STIPs	LOS (Delay)	B (12.5)		A (6.2)			D (46.9)		B (19.2)
	Synchro 95th Q	45'	173'	m27'	70'	6'	227'	28'	
PM Peak Hour									
2029 Background w/ STIPs	LOS (Delay)	B (15.2)		B (11.0)			D (42.3)		C (20.3)
	Synchro 95th Q	52'	286'	m6'	m209'	m37'	289'	29'	
2029 Build-out w/ STIPs	LOS (Delay)	B (17.8)		A (7.9)			D (42.2)		B (19.7)
	Synchro 95th Q	52'	307'	m24'	m115'	m7'	294'	29'	
Background Storage		425'		425'		400'	325'	125'	
m Volume for 95th percentile queue is metered by upstream signal									

m Volume for 95th percentile queue is metered by upstream signal

Based on the latest roadway plan set provided by NCDOT and shown in the image to the right, this new intersection is planned to operate as full-movement with the following approach laneage:

- Southbound – Two left-turn lanes and one right-turn lane along Weddington Road (NC 84).
- Eastbound – Two through lanes and one left-turn lane along Rea Road Extension.
- Westbound – Two through lanes, one U-turn lane, and one right-turn lane along Weddington Road (NC 84).




Table 6.4 shows the overall intersection is expected to operate at LOS C or better during all peak hours under 2029 background conditions.

With the addition of the site traffic, the overall intersection is expected to operate at LOS B during all peak hours. The decrease in delay and queue shown in **Table 6.4** between background and

build-out conditions is in part due to the optimization of the splits and offsets for the coordinated traffic signals along Weddington Road (NC 84). Therefore, no improvements are identified for capacity purposes.

6.5 WEDDINGTON ROAD (NC 84) AND ACCESS A

Table 6.5A summarizes the LOS, control delay and 95th percentile queue lengths at the proposed unsignalized, stop-controlled intersection of Weddington Road (NC 84) and Access A (RIRO).

Table 6.5A - Weddington Road (NC 84) and Access A					
Condition	Measure	EB	WB	NB	SB
		EBTR	WBTR	NBR	SBR
AM Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (11.0)	B (12.2)
	Synchro 95th Q	0'	0'	5'	3'
MD Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (10.3)	A (9.5)
	Synchro 95th Q	0'	0'	3'	0'
PM Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (12.3)	B (10.9)
	Synchro 95th Q	0'	0'	3'	0'

As shown in **Table 6.5A**, the stop-controlled northbound and southbound approaches of Access A are expected to operate with short delays during all peak hours under build-out conditions.

Based on the anticipated SimTraffic maximum queues (reports included in the **Appendix**), the northbound and southbound approaches of Access A should be constructed under RIRO operations with one ingress lane, one egress lane, stop-control, and the NCDOT minimum IPS of 100 feet.

Review of auxiliary turn-lane warrants at this intersection are included in **Section 7.0**.

6.5B – Weddington Road (NC 84) and Access A

Table 6.5B summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized, stop-controlled intersection of Weddington Road (NC 84) and Access A without TIP projects. This access was assumed to operate as full movement under this scenario.

Table 6.5B - Weddington Road (NC 84) and Access A							
Condition	Measure	EB		WB		NB	SB
		*EBL	EBTR	*WBL	WBTR	NBLTR	SBLTR
AM Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	B (10.5)	A (0.0)	A (9.0)	A (0.0)	F (72.4)	D (25.4)
	Synchro 95th Q	0'	0'	0'	0'	43'	3'
MD Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	A (9.3)	A (0.0)	B (10.7)	A (0.0)	F (70.8)	D (29.7)
	Synchro 95th Q	0'	0'	3'	0'	25'	3'
PM Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	A (9.1)	A (0.0)	B (10.9)	A (0.0)	F (96.6)	F (58.8)
	Synchro 95th Q	0'	0'	3'	0'	43'	15'
*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions							

*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions

Based on coordination with the Town, an additional interim scenario was run without either of the NCDOT TIP Projects in place.

Table 6.5B shows that without the NCDOT TIP projects in place, under 2024 build-out conditions, the stop-controlled northbound approach of Access A is projected to operate at LOS F during all peak hours. The stop-controlled southbound approach is projected to operate at LOS D during the AM and MID peak hours and LOS F during the PM peak hour.

As discussed in **Section 6.0**, it is typical for stop sign-controlled side streets and driveways intersecting major streets to experience long delays during peak hours, particularly for left-turn movements. The majority of the traffic moving through the intersection on the major experiences little to no delay. Additionally, given minimal major street- or right-turning traffic, additional turn lane improvements yield little improvement to side-street approach delay. Therefore, no additional improvements are identified for capacity purposes.

Based on the anticipated SimTraffic maximum queues (reports included in the **Appendix**), the northbound and southbound approaches of Access A should be constructed with one ingress lane, one egress lane, stop-control, and the NCDOT minimum IPS of 100 feet.

Upon further coordination with NCDOT staff, Access A will operate under RIRO conditions in the scenario without TIP projects.

Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Review of auxiliary turn-lane warrants at this intersection are included in **Section 7.0**.

6.6 WEDDINGTON ROAD (NC 84) AND ACCESS B

Table 6.6A summarizes the LOS, control delay and 95th percentile queue lengths at the proposed unsignalized, stop-controlled intersection of Weddington Road (NC 84) and Access B (RIRO).

Table 6.6A - Weddington Road (NC 84) and Access B					
Condition	Measure	EB	WB	NB	SB
		EBTR	WBTR	NBR	SBR
AM Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (10.9)	B (12.1)
	Synchro 95th Q	0'	0'	0'	0'
MD Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (10.2)	A (9.5)
	Synchro 95th Q	0'	0'	0'	0'
PM Peak Hour					
2029 Build-out w/ STIPs	LOS (Delay)	A (0.0)	A (0.0)	B (12.0)	B (10.8)
	Synchro 95th Q	0'	0'	0'	0'

As shown in **Table 6.6A**, the stop-controlled northbound and southbound approaches of Access B are expected to operate with short delays during all peak hours through build-out conditions.

Based on the anticipated SimTraffic maximum queues (reports included in the **Appendix**), the northbound and southbound approaches of Access B should be constructed under RIRO operations with one ingress lane, one egress lane, stop-control, and the NCDOT minimum IPS of 100 feet.

Review of auxiliary turn-lane warrants at this intersection are included in **Section 7.0**.

6.6B – Weddington Road (NC 84) and Access B

Table 6.6B summarizes the LOS, control delay and 95th percentile queue lengths at the unsignalized, stop-controlled intersection of Weddington Road (NC 84) and Access B without TIP projects. This access was assumed to operate as full movement under this scenario.

Table 6.6B - Weddington Road (NC 84) and Access B							
Condition	Measure	EB		WB		NB	SB
		*EBL	EBTR	*WBL	WBTR	NBLTR	SBLTR
AM Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	B (10.5)	A (0.0)	A (9.0)	A (0.0)	E (38.2)	F (52.6)
	Synchro 95th Q	0'	0'	0'	0'	3'	5'
MD Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	A (9.3)	A (0.0)	B (10.5)	A (0.0)	E (35.9)	E (41.8)
	Synchro 95th Q	0'	0'	0'	0'	3'	3'
PM Peak Hour							
2029 Build-out w/o STIPs	LOS (Delay)	A (9.2)	A (0.0)	B (10.7)	A (0.0)	F (57.2)	F (55.8)
	Synchro 95th Q	0'	0'	0'	0'	13'	13'
*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions							

*Conflicting left-turn movements are broken out per NCDOT guidelines under unsignalized conditions

Based on coordination with the Town, an additional interim scenario was run without either of the NCDOT TIP Projects in place.

Table 6.6B shows that without the NCDOT TIP projects in place, under 2024 build-out conditions, the stop-controlled northbound approach of Access A is projected to operate at LOS E during the AM and MID peak hours and LOS F during the PM peak hour. The stop-controlled southbound approach is projected to operate at LOS F during the AM and PM peak hours and LOS E during the MID peak hour.

As discussed in **Section 6.0**, it is typical for stop sign-controlled side streets and driveways intersecting major streets to experience long delays during peak hours, particularly for left-turn movements. The majority of the traffic moving through the intersection on the major experiences little to no delay. Additionally, given minimal major street- or right-turning traffic, additional turn lane improvements yield little improvement to side-street approach delay. Therefore, no additional improvements are identified for capacity purposes.

Based on the anticipated SimTraffic maximum queues (reports included in the **Appendix**), the northbound approach of Access A should be constructed with one ingress lane, one egress lane, stop-control, and the NCDOT minimum IPS of 100 feet.

Upon further coordination with NCDOT staff, Access B will operate under RIRO conditions in the scenario without TIP projects.

Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Review of auxiliary turn-lane warrants at this intersection are included in **Section 7.0**.

7.0 Auxiliary Turn Lane Warrants

Warrants for additional turn-lane improvements for unsignalized intersection beyond those necessary for capacity were determined based on a review of the figure titled 'Warrant for Left and Right-Turn Lanes' found on page 80 in the [NCDOT Policy On Street And Driveway Access to North Carolina Highways](#). The results of the warrants for left and right-turn lanes under the 2029 build-out conditions indicate that turn lanes are not warranted at the proposed site accesses along Weddington Road (NC 84) under either scenario. The turn-lane warrant figures are included in the **Appendix**.

However, based on review of the April 2024 version of this TIA, the following turn-lane will be required by NCDOT for the scenario with TIP projects:

Weddington Road (NC 84) and Access A

- Eastbound right-turn lane with maximized storage based on proximity to the u-turn bulb

If the proposed development is completed prior to the widening of Weddington Road (NC 84), ongoing coordination with NCDOT will be needed to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

8.0 Identified Mitigation Improvements

Based on the capacity analyses performed at each of the identified study intersections, along with review of the auxiliary turn-lane warrants contained herein, no improvements are required to mitigate the impact of the proposed development on the adjacent street network under either scenario. The following site and mitigation improvements needed for the proposed Deal Lake development are as follows:

With STIP Projects

Weddington Road (NC 84) and Access A

- Construction of the northbound and southbound approaches of Access A under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.
- Construction of an eastbound right-turn lane along Weddington Road (NC 84) with maximized storage.

Weddington Road (NC 84) and Access B

- Construction of the northbound and southbound approaches of Access B under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.

Without STIP Projects


Weddington Road (NC 84) and Access A


- Construction of the northbound and southbound approaches of Access A under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.
- Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Weddington Road (NC 84) and Access B

- Construction of the northbound and southbound approaches of Access B under RIRO operations with one ingress lane, one egress lane, stop-control, and an IPS of 100 feet.
- Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

The site and mitigation improvements identified within the study area are shown in **Figures 8.1A and 8.1B**. The improvements shown on these figures are subject to approval by NCDOT and the Town of Weddington. All additions and attachments to the State and Town roadway system shall be properly permitted, designed, and constructed in conformance to standards maintained by the agencies.





Appendix

NCDOT Scoping Checklist



NCDOT Traffic Impact Analysis Need Screening / Scoping Request



TIA Need
Screening



TIA
Scoping



TIA
Submittal

A Traffic Impact Analysis (TIA) may be required for developments based on the site trip generation estimates, site context, or at the discretion of the NCDOT District Engineer. The Applicant or the TIA Consultant shall submit this form along with the site plan to the District Engineer to determine the TIA need and, if a TIA is required, initiate the TIA scoping process. Without an approved scope, the TIA is incomplete and will be rejected until the study is revised to conform to NCDOT's TIA requirements.

Project Name: Deal Lake **Previous Name:** If Applicable _____
Location: 610 Weddington Road **County:** Union **Municipality:** Weddington
Project Description: 31 single-family detached homes on the north side of Weddington Road and 62 single-family detached homes on the south side of Weddington Road (93 single-family detached homes total)

Project Contact:	Applicant	TIA Consultant
Company Name	Toll Brothers	Kimley-Horn and Associates
Contact Person	Robert Price	Laura Reid, PE
Phone Number	(704) 849-2625	(704) 319-7696
Email	rprice1@tollbrothers.com	laura.reid@kimley-horn.com
Mailing Address	9130 Kings Parade Boulevard	200 South Tryon Street, Suite 200
	Charlotte, NC 28273	Charlotte, NC 28202

Site Plan Prepared By: McKim & Creed **Site Plan Date:** February 2024
 See site plan/vicinity map requirements on page 2.
Parcel Size: 167.48 Acre(s) **Anticipated Build-Out Year:** 2029

Weekday Site Trip Generation - Do NOT adjust for mode split, pass-by, internal capture, or diverted trips.

ITE LUC	Proposed Land Use	Size	Unit	Daily Trips	Peak Hour Type	AM Peak Hour Trips			PM Peak Hour Trips			Data Source
						Enter	Exit	Total	Enter	Exit	Total	
210	SF Det. (North)	62	DU	650	Adj. Street	12	36	48	40	23	63	ITE Equation
210	SF Det. (South)	31	DU	344	Adj. Street	7	19	26	21	12	33	ITE Equation
Total		93	DU	994		19	55	74	61	35	96	

Refer to the current [NCDOT Congestion Management Capacity Analysis Guidelines](#) for acceptable trip calculation methods and data sources.

**Explain local or other data sources, if used: _____

- ☐ The estimated site trips meet NCDOT's TIA trip threshold of 3,000 daily trips.
- ☒ The estimated site trips meet the municipal TIA trip threshold of >500 daily and/or > 50 peak hour
- ☒ This project is located in a known [STIP](#) and/ or local CIP project # U-3467, U-5769A
- ☐ This project includes a rezoning request.
- ☐ The proposed site access is located within 1,000 feet of an interchange.
- ☐ The Applicant requests for a new or modified control-of-access break.
- ☐ The Applicant requests for a new or modified median break.

Applicant's Signature	Print Name	Date
Effective Date: 10/01/2017 (Version 17-721)		Page 1 of 2



NCDOT Traffic Impact Analysis Need Screening / Scoping Request

TIA Need
Screening



TIA
Scoping



TIA
Submittal



Site Plan/Vicinity Map Requirement for TIA Need Screening: While the site plan may not be finalized during the TIA scoping stage, the graphic representation of the proposed development shall provide adequate details on the development scope and context. More specifically, the site plan/map shall clearly show the location and type of each access point, spacing to adjacent and opposing driveways or intersections, internal street network, proposed buildings/parcels with their anticipated uses and sizes at full build-out and, if applicable, any nearby interstate, US, NC or Secondary Roads (SR).

Project Name: Deal Lake **Project Reference Number:** _____

☒ **A TIA is Required by the Local Government.** In addition, the study area is expected to include NCDOT maintained transportation facilities.

☐ **A TIA is Required by NCDOT,** per the [Policy on Street and Driveway Access to North Carolina Highways](#).

If either or both of the boxes above are checked, the Applicant/TIA Consultant is hereby requested to fill out as much as possible of the following TIA scoping checklist, and return it along with the supporting documents to NCDOT prior to the scoping meeting.

☐ **A TIA is NOT required.** This decision is based on the development information presented above. Changes in the development plan will require re-evaluation of the TIA need, and may necessitate a TIA. The Applicant should inform the District Engineer of any significant changes in a timely fashion to avoid delays or rejections of the driveway permit / encroachment agreement applications.

Additional Comments:

The TIA need decision is made by the NCDOT Division _____ District _____ on _____.

NCDOT District Representative's Signature
Email concurrence may be used in lieu of the signature.

Print Name



NCDOT TIA Scoping Checklist



Project Name: Deal Lake

TIA Scoping Date: _____

☒ **TIA Need Screening Forms are Attached.** Project Reference #: _____ Decision Date: _____

☒ **Site Plan and Access**

☒ Provide a site plan illustrating site access, internal and external roadways, buildings and land uses.

Refer to NCDOT's [Policy on Street and Driveway Access to North Carolina Highways](#) pages 14 and 15 for site plan requirements.

☒ Identify site access.

New Access	On Road	Access Type		Driveway Spacing		
	Road Name	Permitted Movements	Traffic Control	Distance (ft)	Direction	Nearest Intersection / Access
Access A	Weddington Road	RIRO	2-Way Stop	940	South	Lake Forest Drive
Access B	Weddington Road	RIRO	2-Way Stop	560	South	Access A
Access C						
Access D						
Access E						
Access F						
Access G						
Access H						

Existing Access	Existing Intersection of		Access Modification	Proposed Interconnectivity (If Applicable)		
	Road A	Road B		Connector #	Road Connected	Adjacent Development
Access 1				Connector 1		
Access 2				Connector 2		
Access 3				Connector 3		
Access 4				Connector 4		

☒ Additional access clarifications and provisions (e.g., proposed control-of-access or median breaks, modifications of existing access, loading/unloading area access, bike/pedestrian accommodation).

NCDOT STIP No. U-3467 Public Meeting Maps show a median across the site frontage. Per NCDOT, full-movement access will not be allowed.

☒ **Proposed K-12 School Site**

☐ NCDOT [MSTA School Traffic Calculator](#) for _____ shall be used.

☐ Peak Hour Factors (PHFs) shall be adjusted/weighted for new school trips (0.5 PHF by default).

☐ Internal school circulation analysis is required, and should be submitted in advance or concurrent with the TIA submittal.

☐ Clarify traffic operation plans (e.g. traffic circulation pattern, pedestrian access, drop-off/pick-up zone location and configuration, queue storage area and, if applicable, staggered start times).



NCDOT TIA Scoping Checklist

TIA Need
Screening



TIA
Scoping



TIA
Submittal



☒ Trip Generation

The TIA Consultant shall prepare trip generation estimates following the current [NCDOT Congestion Management Capacity Analysis Guidelines](#), and submit the calculation sheets and supporting information to the District Engineer for approval prior to capacity analysis.

ITE LUC	Proposed Land Use	Size	Unit	Daily Trips	Peak Hour Type	AM Peak Hour Trips			PM Peak Hour Trips			Data Source
						Enter	Exit	Total	Enter	Exit	Total	
210	SF Det. (North)	62	DU	650	Adj. Street	12	36	48	40	23	63	ITE Equation
210	SF Det. (South)	31	DU	344	Adj. Street	7	19	26	21	12	33	ITE Equation
Unadjusted Site Trips				994		19	55	74	61	35	96	
Internal Capture Trips (Attach Calculation Sheets)												
Internal Capture % of Unadjusted Site Trips				%		%			%			
LUC	Proposed Land Use	Any Internal Trips?		Pass-By % of External Trips								
				%		%			%			
				%		%			%			
				%		%			%			
				%		%			%			
				%		%			%			
Pass-By Trips (Attach Calculation Sheets)												
Adjacent Street Volumes												
Non-Pass-By Primary Trips				994		19	55	74	61	35	96	
Diverted Trips, if Applicable and Justifiable												

**Explain local or other data sources, if used:

☐ Existing Site Trip Information for Redevelopment Projects (Attach separate sheets as needed)

ITE LUC	Existing Land Use	Size	Unit	Daily Trips	Peak Hour Type	AM Peak Hour Trips			PM Peak Hour Trips			Data Source
						Enter	Exit	Total	Enter	Exit	Total	
Total Existing Site Trips												



NCDOT TIA Scoping Checklist



☒ Trip Distribution

- ☒ Trip distribution diagrams are submitted concurrently with this document (attach separate sheets).
- ☐ Trip distribution diagrams will be submitted separately, along with supporting information, to the District Engineer for review and approval prior to capacity analysis. The trip distribution shall be based on the current and anticipated traffic patterns, as well as instructions noted below.

If required by the District Engineer, the following additional diagrams shall also be submitted:

- ☐ Mixed-Use Developments (separate diagrams for residential, commercial, and office trips)
- ☐ Inter-Development Trips (if 'internal' trips cross public streets)
- ☐ Pass-By Trips
- ☐ Diverted Trips
- ☐ Each Analysis Period

☐ Mode Split

- ☐ Provide Data Source and Justification

Mode Period	Auto		
AM Peak	%	%	%
PM Peak	%	%	%
Daily	%	%	%
	%	%	%

- ☐ Identify proper infrastructure and accommodation for other modes of travel.

☒ Analysis Peak Periods:

- ☒ Weekday AM Peak 7:00-9:00 AM
- ☒ Weekday PM Peak 4:00-6:00 PM
- ☐ Weekday Midday Peak _____
- ☒ Weekday PM School Peak 2:00-4:00 PM
- ☐ Weekend _____ Peak _____
- ☐ Other _____



NCDOT TIA Scoping Checklist



☒ Study Area Intersections and Data Collection

The study area shall include the site access intersections (both new and existing) identified under “Site Plan and Access” on page 1, as well as the following external and, if applicable, internal intersections.

External Intersection	Intersection of		Traffic Control	Intersection Turning Movement Counts			Notes
	Road A	Road B		New / Existing	Date of Counts	Growth Adjustment	
#1	NC 16	Rea Road	Signal	Require New Counts			
#2	Weddington Road	Cox Road	2-Way Stop	Require New Counts			
#3	Weddington Road	12 Mile Creek Rd	Signal	Require New Counts			
#4	Weddington Road	U-3467	Signal				Future
#5	Weddington Road	Access A	2-Way Stop				Build
#6	Weddington Road	Access B	2-Way Stop				Build
#7							
#8							
#9							
#10							
#11							
#12							

Internal Intersection	Intersection of		Access Type		Intersection Spacing		
	Road A	Road B	Traffic Control	Permitted Movements	Distance (ft)	Direction	Nearest Intersection
#101							
#102							
#103							
#104							
#105							

The following data will be collected:

- ☒ New traffic turning movement counts in ☒ 15-min intervals ☐ 5-min intervals (near schools)
 Unless otherwise noted above, new traffic counts shall be collected at the existing study intersections during the analysis periods. Weekday counts shall avoid Mondays, Fridays, holidays, school breaks, road closures, and major weather events.

- ☒ To account for the impact of existing and/or proposed school traffic, PHFs will be adjusted for:

intersections numbered: #3 - AM and school peak hours

and access points numbered: _____

- ☒ Traffic Forecast Data for TIP: U-3467 for intersections along Rea Road

- ☒ Roadway/Intersection Configuration & Traffic Control

- ☒ Traffic Signal Phasing & Timing Data

☐ Crash Data: _____ Period: _____

- ☒ Other:

NCDOT STIP No. U-5769A U-turn bulbs along NC 16 will be included for modeling purposes but not evaluated for mitigation.



NCDOT TIA Scoping Checklist



☒ Future Year Conditions

☒ Project Build-Out Year: 2029

☒ Future Analysis Year(s): 2029

☒ Identify below any funded/committed future transportation improvements, as well as any approved but incomplete developments near the site.

Funded STIP / Local CIP Project	Project Description		Year Complete
U-3467	Construct four-lane road from NC 16 to Waxhaw Indian Trail		2030
U-5769A	NC 16 widening from Rea Rd to Bonds Grove Church Rd		2031
Nearby Approved Development	Location	Future Land Use (exclude any completed phases)	Committed Improvements
None			

☒ Annual Growth Factor: 2 %

Justification/Data Source: NCDOT AADT data

☒ Local Comprehensive Transportation Plan Compliance

☒ Identify Applicable Local Transportation Planning Documents

CRTPO MTP/CTP

☒ Identify Applicable Roadways inside the Study Area

Road Name	Classification	Speed Limit	Proposed Cross-Section	Proposed Right-of-Way	Compliance Requirements	Affect Study Intersection #
NC 16	Minor Arterial	45				
Weddington Road	Minor Arterial	45				
Rea Road	Minor Arterial	45				
Cox Road	Local	45				
Twelve Mile Creek Road	Local	45				



NCDOT TIA Scoping Checklist



☒ Study Method

The traffic analysis shall follow the current [*NCDOT Congestion Management Capacity Analysis Guidelines*](#), [*Policy on Street and Driveway Access to North Carolina Highways*](#), and use the current approved version of analysis software (e.g. Synchro/SimTraffic, HCS, Sidra Intersection, TransModeler).

The study shall include the following analysis scenarios for each analysis period.

1. Existing Conditions
2. Future No-Build Conditions (existing + background growth + approved developments + committed or funded improvements)
3. Future Build Conditions (future no-build + site trips)
4. Future Build with Improvements Conditions (future build traffic with improvements to mitigate the proposed development's impacts) and, if applicable:
- ☐ 5. TIP Design Year Analysis _____
- ☐ 6. Alternative Access Scenario (without proposed control-of-access or median break / modification)

The following additional analysis/outputs should be provided as warranted:

- ☐ Signal Warrant Analysis for accesses/intersections _____
- ☐ Multi-Modal Level of Service Analysis
- ☐ School Loading Zone Traffic Simulation
- ☐ Phasing Analysis (scope separately as needed)
- ☐ Safety/Crash Analysis
- ☐ Control-of-Access Modification Justification
- ☐ Median Break / Modification Justification
- ☐ Other _____

☒ Submittals

In addition to the hardcopies required below, the TIA Consultant shall provide the District Engineer and, if required, the local government an electronic copy of the study documents, including the latest site plan, figures and appendices, in searchable PDF files and the original traffic analysis files (e.g., Synchro, HCS). To expedite review, the NCDOT electronic submittals shall also be delivered concurrently to:

- ☐ Div. Traffic Engr ☐ Regional Traffic Engr ☐ Congestion Management ☐ Other _____

Submittals	NCDOT		Local Government	
	Electronic	Hardcopy	Electronic	Hardcopy
Trip Generation & Distribution	Required			
Draft TIA Report	Required			
Final Sealed TIA Report	Required			

- ☐ **Additional Comments** (municipal TIA requirements, approved variations from NCDOT guidelines)



NCDOT TIA Scoping Checklist



Agreement by All Parties

The undersigned agree to the contents and methodology described above for completing the required traffic impact analysis for the proposed development identified herein. Any changes to the above methodology contemplated by the Applicant or the TIA Consultant must be submitted to the District Engineer in writing. If approved by NCDOT, then such changes may be accepted for the TIA report. Subsequent revisions to the development plan (e.g. land use, density, site access, or schedule) may require additional scoping and analysis, and may modify the TIA requirements.

This agreement shall become effective on the date approved by NCDOT, and shall expire ____ months after the effective date or upon significant changes to the roadway network and/or development assumptions, whichever occurs first. Once expired, renewal or re-scoping will be required for subsequent TIA submittals.

APPLICANT

_____ Signature	_____ Print Name	_____ Date
--------------------	---------------------	---------------

TIA CONSULTANT

_____ Signature	Laura Reid, PE _____ Print Name	_____ Date
--------------------	---------------------------------------	---------------

LOCAL GOVERNMENT REPRESENTATIVE (If Applicable)

_____ Signature	_____ Print Name	_____ Date
--------------------	---------------------	---------------


Email concurrence may be used in lieu of the signature.


NCDOT DISTRICT REPRESENTATIVE

Reviewed and approved by the NCDOT Division ____ District ____ on _____.

_____ Signature	_____ Print Name
--------------------	---------------------

Email concurrence may be used in lieu of the signature.





[illegible]

January 23, 2024

Mr. Robert G. Tefft
Town Planner
Town of Weddington
1924 Weddington Road
Weddington, NC 28104

RE: Review of Scoping for Traffic Impact Analysis (TIA)
Deal Lake
Town of Weddington

Mr. Tefft:

In accordance with your request, the following is our review of the Scoping document prepared for Toll Brothers, by Laura Reid, PE, Kimley Horn & Associates, dated, October 24, 2023.

The Applicant is proposing to develop 93 single-family residential units on two parcels of approximately 168 acres of vacant land located on Weddington Road between Cox Road and Twelve Mile Creek Road. The north Parcel is proposed to contain 31 single-family units and the south parcel is proposed to contain 62 single-family dwelling units. The applicant proposes to study six (6) intersections consisting of: S. Providence Road (NC 16) and Rea Road; Weddington Road and Cox Road; Weddington Road and Twelve Mile Creek Road; Weddington Road and U-3467; Weddington Road and Access A; and, Weddington Road and Access "B."

A. Intersections to be Studied.

From an overall transportation perspective, the intersections to be studied appear to be appropriate to determine the traffic impacts of the proposed development.

B. Trip Generation.

The Scoping document identifies the single-family housing as Land-use 210 which is considered appropriate for this application. However, because the two parcels are on opposite sides of Weddington Road, each with a different arrival/departure pattern, and which generates a few more trips than as a combined Site, and to perform a more conservative analysis, it is suggested that the two Sites be treated separately for analysis purposes.



C. Trip Distribution and Assignment

The Scoping document contains an exhibit showing the distribution and assignment of the new trips. However, the assignments consider the roadway interconnect (U-3467) between Weddington Road and S. Providence Road (NC 16) to be completed. Further, the Scoping Document indicates that this STIP will not be completed until 2026-2030. Accordingly, it is assumed that the Traffic Impact Analysis (TIA) will be based on that time frame and that the Horizon Year of the completion of the STIP will be that time when occupancy of the single-family homes will be allowed. Alternatively, should the proposed development be phased and occupancy be proposed to begin before the roadway interconnect is completed, an interim TIA is to be performed with a shorter time frame for the Horizon Year as well with a different (appropriate) Site distribution.

D. Analysis Peak Periods

The Scoping Document indicates that the time periods when data is to be collected is between 7:00 and 9:00a.m. and between 4:00 and 6:00 p.m. While these time frames generally reflect the Peak Highway Hours and are consistent with ITE Trip Generation characteristics of single-family homes, the Scoping Document also indicates that the "MSTA School Traffic Calculator" is to be used. Further, there appears to be a number of schools in the vicinity. Accordingly, it is suggested that the afternoon timeframe for data collection also include the school dismissal period, typically between 2:00 and 3:00 p.m. Should the data indicate peaks of significant volumes during the school departure period, additional traffic impacts analyses should be performed during that time frame.

E. Conclusion

We trust the information herein is sufficient for your immediate needs. Please do not hesitate to contact me at 914-269-5610 or Ms. Fisher at 704-941-2132 should you have any questions.

Respectfully submitted,

Bernard Adler, P.E.
Senior Transportation Consultant

LaBella Associates

One North Broadway, Suite 803
White Plains, NY 10601

Bonnie A. Fisher, P.E.
Senior Civil Engineer
Project Manager

Ortiz-Hernandez, Julian

From: Helms, Amelia C <achelms@ncdot.gov>
Sent: Friday, February 2, 2024 1:46 PM
To: Reid, Laura; Robert Tefft; Dewey, Karen; Gardner, Zachary L
Cc: Richard, Elizabeth; Robert Price
Subject: RE: [External] Deal Lake - TIA Scoping Document
Attachments: 2024-01-03_Deal Lake_SCOPING.pdf

Categories: External

Laura,

The site plan should clearly show each access point and all NC and SR routes need to be labeled. Also, please provide the STIP project overlaid on the site plan.

U-3467 will be converting NC 84 to a divided facility with reduced conflict intersections, therefore full movement access will not be allowed on NC 84.

Thank you,

Amelia Helms, P.E.
District Engineer
Division 10 - District 3
North Carolina Department of Transportation

704 218 5100 office
704 292 1800 fax
achelms@ncdot.gov

130 South Sutherland Avenue
Monroe, NC 28112



Email correspondence to and from this address is subject to the North Carolina Public Records Law and may be disclosed to third parties.

From: Reid, Laura <laura.reid@kimley-horn.com>
Sent: Wednesday, January 3, 2024 5:26 PM
To: Robert Tefft <rtefft@townofweddington.com>; Dewey, Karen <kdewey@townofweddington.com>; Helms, Amelia C <achelms@ncdot.gov>; Gardner, Zachary L <zlgardner@ncdot.gov>
Cc: Richard, Elizabeth <Elizabeth.Richard@kimley-horn.com>; Robert Price <rprice1@tollbrothers.com>
Subject: [External] Deal Lake - TIA Scoping Document

CAUTION: External email. Do not click links or open attachments unless verified. Report suspicious emails with the Report Message button located on your Outlook menu bar on the Home tab.

Hi all,

Please see attached for the TIA scoping document for the Deal Lake development in Weddington. We understand we'll need to have a scoping meeting with the Town for this site, so please let us know if there is any additional information you need from us to get that scheduled.

This site is below the NCDOT TIA threshold, but we've included them on this email given the connection to NC 84 and the TIP projects in the vicinity.

Thanks,

Laura Reid, PE (NC & SC)

Kimley-Horn | 200 South Tryon Street, Suite 200, Charlotte, NC 28202

Direct: 704 319 7696 | Mobile: 443 804 7984 | www.kimley-horn.com

Connect with us: [Twitter](#) | [LinkedIn](#) | [Facebook](#) | [Instagram](#)

Celebrating 16 years as one of FORTUNE's 100 Best Companies to Work For

Email correspondence to and from this sender is subject to the N.C. Public Records Law and may be disclosed to third parties.

Deal Lake

TIA SCOPING REVIEW

BULLET LIST OF CONGESTION MGMT. COMMENTS AND CONCERNS (SC-2024-036)

March 4, 2024

The Congestion Management Section (CMS) has performed a review of the scoping document for the proposed Deal Lake development prepared by Kimley-Horn and Associates (received February 20, 2024). According to the document, the proposed development is to be located on both sides of NC 84 (Weddington Rd) 1,300' west of SR 1341 (Twelve Mile Creek Rd) in Weddington, NC. The scoping document states that the full build-out of the development is to be constructed by 2029 and is to consist of residential land use consisting of 93 dwelling units of single-family detached housing (LUC 210) generating 994 unadjusted daily trips. Based on our review, we have the following comments at this time:

Trip Generation

- The Trip Generation appears reasonable.

Trip Distribution and Growth Rate

- Trip distribution appears reasonable.
- Growth rate of 2% appears reasonable.

Study Intersections

- Study Intersections appear reasonable.

Site Plan and Proposed Driveways

- Site plan appears reasonable and appears to match with the trip generation.
- TIP Projects U-3467 and U-5769A are in the immediate area of this project. The scoping documents indicate that TIP Design Year Analyses will not be provided and that a rezoning request will be not be made for this project. (Observation)
- Prior to seeking driveway permit, overlay development project plans on TIP project plans to demonstrate compatibility. Final plans are subject to review by the NCDOT District, Division, and Roadway Design Offices.
- Please ensure that the proposed driveway(s) are in accordance with the NCDOT Driveway Manual and Internal Protected Stem lengths are provided with the TIA.

NOTE: This list should not be considered all-inclusive. Further review may identify additional areas of concern.

NCDOT TIA Comments



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

ROY COOPER
GOVERNOR

J.R. "JOEY" HOPKINS
SECRETARY

May 21, 2024

**Deal Lake
Weddington, NC**

**Traffic Impact Analysis (TIA) Review Report
Congestion Management Section**

TIA Project: SC-2024-036
Division: 10
County: Union
Description: Located on both sides of NC 84 (Weddington Rd) west of SR 1341 (Twelve Mile Creek Rd) in Weddington, Union County.



Michael P. Reese, PE, CPM
Congestion Management Regional Engineer

Jonathan W. Haire
Congestion Management Design Engineer

Michael Reese

21 MAY 2024

Mailing Address:
NC DEPARTMENT OF TRANSPORTATION
TRANSPORTATION MOBILITY & SAFETY DIVISION
TRAFFIC MANAGEMENT UNIT
1561 MAIL SERVICE CENTER
RALEIGH, NC 27699-1561

TELEPHONE: 919-814-5000
FAX: 919-771-2745

WEBSITE: WWW.NCDOT.ORG

LOCATION:
750 NORTH GREENFIELD PARKWAY
GARNER NC 27529



Deal Lake TIA

SC-2024-036

Union County

Per your request, the Congestion Management Section (CMS) of the Transportation Mobility and Safety Division has completed a review of the subject site. The comments and recommendations contained in this review are based on data for background conditions presented in the sealed Traffic Impact Analysis (TIA) and are subject to the approval of the local District Engineer's Office and appropriate local authorities.

Key Dates	
Initially Received by CMS	4/30/2024
Date of Latest Information Received by CMS	4/30/2024
Date of Preliminary Review Accepting TIA for Review	5/21/2024
Sealed TIA Prepared by Kimley-Horn and Associates, Inc.	4/26/2024
Site Plan Prepared by McKim & Creed	2/10/2024

Proposed Development

According to the TIA, the proposed Deal Lake development is to be located on both sides of NC 84 (Weddington Rd) west of SR 1341 (Twelve Mile Creek Rd) in Weddington, Union County. The TIA states the development is to be constructed by 2029 and is to consist of the following:

Land Use	Land Use Code	Size
Single-Family Detached Housing (South of NC 84)	210	62 DU
Single-Family Detached Housing (North of NC 84)	210	31 DU

Trip Generation - Unadjusted Volumes During a Typical Weekday

Based on appropriate methodology outlined in the *ITE Trip Generation Manual, 11th Ed.*

	IN	OUT	TOTAL
AM Peak Hour	19	55	74
Mid-Day Peak Hour	52	30	82
PM Peak Hour	61	35	96
Daily Trips			994

Requested Access Points

Driveway	Public Roadway	Access Type
Access A	South side of NC 84 (Weddington Rd) 400' east of Proposed NC 84/Rea Rd Extension Intersection	Right-In/Right-Out
Access B	Both sides of NC 84 (Weddington Rd) 1250' east of Proposed NC 84/Rea Rd Extension Intersection	Right-In/Right-Out



Study Area

Study Area and Proposed Site Location - ↑ N



Photo Credit: Google Maps

TIP Projects in Study Area

Project	Description	Let Date
U-3467	SR 1316 (Rea Road Extension) and NC 84 (Weddington Road) from NC 16 to SR 1008 (Waxhaw-Indian Trail Rd) in Wesley Chapel. Construct four lane roadway part on new location.	July 2027
U-5769A	NC 16 (Providence Road South) from SR 1316 (Rea Road Extension) to SR 1321 (Cuthbertson Road) in Weddington. Widen to multilanes.	June 2029



CRTPO Comprehensive Transportation Plan	
Route	Facility Vision
NC 84 (Weddington Rd)	Boulevard – Needs Improvement
Rea Rd Extension	Boulevard – Recommended
NC 16 (Providence Rd)	Boulevard – Needs Improvement
SR 1341 (Twelve Mile Creek)	Minor Thoroughfare – Needs Improvement
SR 1343 (Cox Rd)	Minor Thoroughfare – Needs Improvement

TIA Comments

The following items vary from our recommended practices (cumulative of all TIA submittals):

- The locations/distances of the proposed driveway accesses varied in Synchro from what is shown on the site plan.
- The distribution of trip generation traffic to/from the north parcel and to/from the south parcel differ from the data shown in the trip generation table
- The U-5769 roadway plans indicate a single southbound U-turn lane is proposed on Providence Road, not dual U-turn lanes as represented in the TIA.
- Internal Protected Stem lengths for each proposed driveway should be provided in the TIA in conformance with requirements in the Driveway Manual.



General Reference

For reference to various documents applicable to this review please reference the following links: <https://connect.ncdot.gov/resources/safety/Pages/Congestion-Management.aspx> and https://connect.ncdot.gov/resources/safety/Teppl/Pages/Teppl-Topic.aspx?Topic_List=C37.

It should be noted that poor LOS and excessive queuing may persist throughout network after recommended developer and outside mitigation.

Analysis of all lanes with finite storage should include an appropriate default taper of 100 feet or more in the analysis. Our storage distances in our reports are minimums that do not include deceleration or taper distances.

Any signing and pavement marking revisions/modifications or improvements necessitated by the development should be the responsibility of the developer unless otherwise noted.

It should be noted that the comments and recommendations contained in this review are subject to the approval of the local District Engineer's Office.

Once the driveway permit has been approved and issued, a copy of the final driveway permit requirements should be forwarded to this office. If we can provide further assistance, please contact the Congestion Management Section at (919) 814-5000.


Recommendations

Refer to attached diagram(s).

Network Analysis

Based upon opening year 2029 with TIP U-5769 and TIP U-3467 improvements in place.

□



*If these improvements by others are not in place by the build-out year, the developer should be responsible for them or a new TIA may be required.

The District Office recommends a Right Turn Lane with maximized storage based on proximity to the U-turn bulb.

Deal Lake
SC-2024-036

Existing Laneage

Recommended Laneage

Laneage Built By Others*

NCDOT Recommendation

Existing Signal

Signal Proposed By Others

Developer Proposed Signal

XXX

Storage

XXX

NCDOT Recommended Storage

<XXX>

Distance Between Intersections

IPS

Internal Protected Stem

All Distances in Feet

Drawing Not to Scale

RE: [External] Deal Lake - TIA Submittal

From Reid, Laura <laura.reid@kimley-horn.com>

Date Mon 10/14/2024 2:57 PM

To Weltner, Robert C <rcweltner@ncdot.gov>; Gardner, Zachary L <zlgardner@ncdot.gov>; Helms, Amelia C <achelms@ncdot.gov>; Robert Price <rprice1@tollbrothers.com>; Foster, Alexander J <ajfoster@ncdot.gov>; Dewey, Karen <kdewey@townofweddington.com>; Gregory Gordos <ggordos@townofweddington.com>

Cc Richard, Elizabeth <Elizabeth.Richard@kimley-horn.com>; Key, Bryan C <bckey@ncdot.gov>; Attaluri, Radha <rattaluri@ncdot.gov>; Ortiz-Hernandez, Julian <Julian.Ortiz@kimley-horn.com>; Haire, Jonathan W <jwhaire@ncdot.gov>; Sikes, Zachary D <zdsikes@ncdot.gov>; Adler, Bernie <badler@LaBellaPC.com>; Thiruvengadam, Vaishali <vaishali@LaBellaPC.com>

Hi all,

The development team discussed the comments below with NCDOT this afternoon. Per NCDOT, no additional scoping is needed for this site. Our team will issue an updated version of the TIA with the following text edits to the scenario without the TIP projects:

- The driveways will operate as right-in/right-out (RIRO) only.
- Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Amelia – Can you confirm that this is consistent with what we discussed or if NCDOT would like to see any changes? Thanks!

Laura Reid, PE (NC & SC)

Kimley-Horn | 200 South Tryon Street, Suite 200, Charlotte, NC 28202

Direct: 704 319 7696 | Mobile: 443 804 7984 | www.kimley-horn.com

Connect with us: [Twitter](#) | [LinkedIn](#) | [Facebook](#) | [Instagram](#)

Celebrating 17 years as one of FORTUNE's 100 Best Companies to Work For

From: Reid, Laura

Sent: Monday, October 7, 2024 3:15 PM

To: Weltner, Robert C <rcweltner@ncdot.gov>; Gardner, Zachary L <zlgardner@ncdot.gov>; Helms, Amelia C <achelms@ncdot.gov>; Robert Price <rprice1@tollbrothers.com>; Foster, Alexander J <ajfoster@ncdot.gov>; Dewey, Karen <kdewey@townofweddington.com>; Gregory Gordos <ggordos@townofweddington.com>

Cc: Richard, Elizabeth <Elizabeth.Richard@kimley-horn.com>; Key, Bryan C <bckey@ncdot.gov>; Attaluri, Radha <rattaluri@ncdot.gov>; Ortiz-Hernandez, Julian <Julian.Ortiz@kimley-horn.com>; Haire, Jonathan W <jwhaire@ncdot.gov>; Sikes, Zachary D <zdsikes@ncdot.gov>; Fisher, Bonnie

<BFisher@LaBellaPC.com>; Adler, Bernie <badler@LaBellaPC.com>; Thiruvengadam, Vaishali <vaishali@LaBellaPC.com>

Subject: RE: [External] Deal Lake - TIA Submittal

Hi Bob,

Just tried to give you a call, so know you're out of the office this afternoon, but wanted to follow-up on your email from last week.

We were under the impression from NCDOT's July 1 email that an updated scoping document and updated analysis was not needed for the change in unit count or the additional access point. We assumed that with the additions to the scope from the Town being above and beyond the initial scope approval, that we would still be covered by the original scope since these items make the analysis more conservative than the first submittal.

Please let me know when you're available to discuss so we can get this resolved.

Thanks!

Laura Reid, PE (NC & SC)

Kimley-Horn | 200 South Tryon Street, Suite 200, Charlotte, NC 28202

Direct: 704 319 7696 | Mobile: 443 804 7984 | www.kimley-horn.com

Connect with us: [Twitter](#) | [LinkedIn](#) | [Facebook](#) | [Instagram](#)

Celebrating 17 years as one of FORTUNE's 100 Best Companies to Work For

From: Weltner, Robert C <rcweltner@ncdot.gov>

Sent: Thursday, October 3, 2024 8:15 AM

To: Reid, Laura <laura.reid@kimley-horn.com>; Gardner, Zachary L <zlgardner@ncdot.gov>; Helms, Amelia C <achelms@ncdot.gov>; Robert Price <rprice1@tollbrothers.com>; Foster, Alexander J <ajfoster@ncdot.gov>; Dewey, Karen <kdewey@townofweddington.com>; Gregory Gordos <ggordos@townofweddington.com>

Cc: Richard, Elizabeth <Elizabeth.Richard@kimley-horn.com>; Key, Bryan C <bckey@ncdot.gov>; Attaluri, Radha <rattaluri@ncdot.gov>; Ortiz-Hernandez, Julian <Julian.Ortiz@kimley-horn.com>; Haire, Jonathan W <jwhaire@ncdot.gov>; Sikes, Zachary D <zdsikes@ncdot.gov>; Fisher, Bonnie <BFisher@LaBellaPC.com>; Adler, Bernie <badler@LaBellaPC.com>; Thiruvengadam, Vaishali <vaishali@LaBellaPC.com>

Subject: RE: [External] Deal Lake - TIA Submittal

Laura,

The new TIA is rejected by NCDOT as a new scope was not completed for the proposed changes.

Thank You,

Robert Weltner

Engineer 1

Division 10 - District 3

North Carolina Dept of Transportation

704-218-5100 – Office
704-292-1800 fax
rcweltner@ncdot.gov

From: Reid, Laura <laura.reid@kimley-horn.com>

Sent: Friday, August 30, 2024 3:10 PM

To: Gardner, Zachary L <zlgardner@ncdot.gov>; Helms, Amelia C <achelms@ncdot.gov>; Robert Price <rprice1@tollbrothers.com>; Foster, Alexander J <ajfoster@ncdot.gov>; Dewey, Karen <kdewey@townofweddington.com>; Gregory Gordos <ggordos@townofweddington.com>

Cc: Richard, Elizabeth <Elizabeth.Richard@kimley-horn.com>; Key, Bryan C <bckey@ncdot.gov>; Attaluri, Radha <rattaluri@ncdot.gov>; Ortiz-Hernandez, Julian <Julian.Ortiz@kimley-horn.com>; Haire, Jonathan W <jwhaire@ncdot.gov>; Weltner, Robert C <rcweltner@ncdot.gov>; Sikes, Zachary D <zdsikes@ncdot.gov>; Fisher, Bonnie <BFisher@LaBellaPC.com>; Adler, Bernie <badler@LaBellaPC.com>; Thiruvengadam, Vaishali <vaishali@LaBellaPC.com>

Subject: RE: [External] Deal Lake - TIA Submittal

CAUTION: External email. Do not click links or open attachments unless verified. Report suspicious emails with the Report Message button located on your Outlook menu bar on the Home tab.

Hi all,

See link below for the updated TIA for this site. Note that contrary to our previous emails, we have gone back and updated the report to the current unit counts and driveway configuration. Also, per coordination with Town staff & their consultant, we've also added:

- Two approved developments
- Build scenario without the TIP projects
- Additional results for the u-turn bulbs in the scenario with the TIP projects

These changes are outlined in detail in the report. Please let us know if you have any questions as you review. We're happy to jump on a call to discuss as needed!

Sharefile Link: <https://kimley-horn.securevdr.com/d-s3046a91997c94a71b16376604982bc96>

Thanks,

Laura Reid, PE (NC & SC)

Kimley-Horn | 200 South Tryon Street, Suite 200, Charlotte, NC 28202

Direct: 704 319 7696 | Mobile: 443 804 7984 | www.kimley-horn.com

Connect with us: [Twitter](#) | [LinkedIn](#) | [Facebook](#) | [Instagram](#)

Celebrating 17 years as one of FORTUNE's 100 Best Companies to Work For

Town of Weddington TIA Comments

July 19, 2024

Mr. Greg Gordos
Town Planner
Town of Weddington
1924 Weddington Road
Weddington, NC 28104

RE: Review of Traffic Impact Analysis (TIA)
Deal Lake
Town of Weddington, NC

Mr. Gordos:

Pursuant to your request, LaBella Associates has reviewed the Traffic Impact Analysis (TIA) for the proposed subject development, prepared for Toll Brothers, by Laura Reid, PE, Kimley Horn & Associates, dated, April 2024.

The Applicant is proposing to develop 93 single-family residential units on two parcels of approximately 168 acres of vacant land located on Weddington Road between Cox Road and Twelve Mile Creek Road. The north Parcel is proposed to contain 31 single-family units and the south parcel is proposed to contain 62 single-family dwelling units. The applicant proposes to study six (6) intersections consisting of: S. Providence Road (NC 16) and Rea Road; Weddington Road and Cox Road; Weddington Road and Twelve Mile Creek Road; Weddington Road and U-3467; Weddington Road and Access A; and, Weddington Road and Access "B."

A. Traffic Volume Turning-Movement Counts

The TIA states that turning-movement count were conducted by Quality Counts on March 7, 2024. Yet, later in the TIA, there is a statement that the NCDOT Intersection Analysis Utility (IAU) spreadsheet was used to convert the AADT volumes from the roadway plans into peak-hour intersection turning-movement volumes. These are inconsistent statements.

B. Intersections Studied.

From an overall transportation perspective, the intersections to be studied are appropriate to determine the traffic impacts of the proposed development. However, The TIA notes that left turns will be prohibited at the intersection of South Providence Road and Rea Road. It is, therefore, incumbent that the U-turn bulbs on Rea Road east and west of S Providence Road be analyzed.

C. Vicinity Developments

The TIA notes that the Town of Weddington has advised Kimley Horn that there are no approved developments in the area that are to be included in the instant study. However, there are two concurrent applications in the study area which could possibly impact the analyses. These projects are: Weddington Office Park and Providence and Rea. Without



including these proposed developments, the instant TIA would not be considered comprehensive.

D. Trip Distribution and Assignment

For the No-Build and Build conditions, the TIA considers the roadway interconnect (U-3467) between Weddington Road and S. Providence Road (NC 16) to be completed. It is further stated that implementation of this project will not begin until FY 2029. It is, therefore, assumed that the construction will not be completed until at least 2030. However, the Horizon Year (full development and occupancy) of the proposed development is still 2029. There appears to be an inconsistency in using the new roadway while still undeveloped as part of the background and Build conditions.

E. Identified Mitigation Improvements

The TIA identifies the access to the development as mitigation measures. However, since these are a part of the access to the development, they are not considered mitigation but necessary components of the development.

We trust the information herein is sufficient for your immediate needs. Please do not hesitate to contact me at 914-269-5610 or Ms. Fisher at 704-941-2132 should you have any questions

Respectfully submitted,

Bernard Adler, P.E.
Senior Transportation Consultant
LaBella Associates
One North Broadway, Suite 803
White Plains, NY 10601

Bonnie A. Fisher, P.E.
Senior Civil Engineer
Project Manager

Kimley-Horn
Comments Response Letter



COMMENT RESPONSE LETTER

To: Bernard Adler, P.E.
LaBella Associates, Senior Transportation Consultant

Bonnie A. Fisher, P.E.
LaBella Associates, Senior Civil Engineer/Project Manager

From: Laura Reid, PE
Kimley-Horn and Associates, Inc.

Date: July 23, 2024

Subject: Deal Lake Traffic Impact Analysis – Comment Response Letter

The purpose of this Comment Response Letter is to incorporate the Town of Weddington's review comments (dated July 19, 2024) and provide responses regarding the Traffic Impact Analysis (TIA) prepared by Kimley-Horn and Associates, Inc. (dated April 26, 2024) for the proposed Deal Lake development.

North Carolina Department of Transportation (NCDOT) Congestion Management and Division staff have also provided comment on the Deal Lake TIA, but these comments are not discussed in detail in this letter.

The Town and NCDOT comments are attached. The responses to Town comments are provided in *italics* below.

TOWN COMMENTS

Traffic Volume Turning-Movement Counts

- The TIA states that turning-movement counts were conducted by Quality Counts on March 7, 2024. Yet, later in the TIA, there is a statement that the NCDOT intersection Analysis Utility (IAU) spreadsheet was used to convert the AADT volumes from the roadway plans into peak-hour intersection turning-movement volumes. These are inconsistent statements.

*The turning-movement counts collected by Quality Counts were utilized for the existing volumes at the existing study area intersections. The NCDOT Intersection Analysis Utility (IAU) spreadsheet was used to calculate the 2029 background volumes used for future analyses for the intersections part of the NCDOT TIP Project No. U-3467. This methodology was defined in the approved NCDOT TIA Scoping checklist (page 4 of 7) and is explained in Sections 3.2 and 4.1 of the TIA. The approved NCDOT TIA Scoping checklist is **attached**.*

Intersections Studied

- From an overall transportation perspective, the intersections to be studied are appropriate to determine the traffic impacts of the proposed development. However, the TIA notes that left

turns will be prohibited at the intersection of South Providence Road and Rea Road. It is, therefore, incumbent that the U-turn bulbs on Rea Road east and west of S Providence Road be analyzed.

The U-3467 eastern and western U-turn bulbs along Rea Road/Rea Road Extension were modeled in Synchro for future year conditions. As these were not study area intersections, LOS and delays at these intersections were not reported in the TIA. However, the reported results do reflect the impacts of these bulbs as adjacent intersections. The Synchro Capacity Analysis reports included in the TIA Appendix reported these as nodes 103 and 104.

Vicinity Developments

- The TIA notes that the Town of Weddington has advised Kimley-Horn that there are no approved developments in the area that are to be included in the instant study. However, there are two concurrent applications in the study area which could possibly impact the analyses. These projects are: Weddington Office Park and Providence and Rea. Without including these proposed developments, the instant TIA would not be considered comprehensive.

*At the time of the TIA Scoping, NCDOT and the Town agreed that there were not any approved developments within the study area that should be included in the analysis. The provided analysis is therefore consistent with the approved NCDOT TIA Scoping checklist. The approved NCDOT TIA Scoping checklist is **attached**.*

Additionally, if these developments are still in the application stage and not yet approved, then they would typically not be included in future year analysis; the Town TIA Procedures Manual does specify that developments should be approved to be included in the analysis.

Trip Distribution and Assignment

- For the No-Build and Build conditions, the TIA considers the roadway interconnect (U-3467) between Weddington Road and S. Providence Road (NC 16) to be completed. It is further stated that implementation of this project will not begin until FY 2029. It is, therefore, assumed that the construction will not be completed until at least 2030. However, the Horizon Year (full development and occupancy) of the proposed development is still 2029. There appears to be an inconsistency in using the new roadway while still undeveloped as part of the background and build conditions.

*Based on preliminary TIA scoping discussions, it was assumed that the project timeline coincided closely enough with the TIP project timeline to assume one build-out year of 2029. This assumption was outlined in the approved NCDOT TIA Scoping checklist which is **attached**.*

Per the LaBella Associates TIA scoping comments, "should the proposed development be phased and occupancy be proposed to begin before the roadway interconnect if completed, an interim TIA is to be performed".

Identified Mitigation Improvements

- The TIA identifies the access to the development as mitigation measures. However, since these are a part of the access to the development, they are not considered mitigation but necessary components of the development.

The accesses are shown as mitigation since they are new laneage and NCDOT requires that internal protected stem lengths for each driveway be identified as part of TIA mitigation. These new lanes can be shown differently if the Town prefers.

Please reach out to our team should you want to discuss further.

Cc:

- Greg Gordos, Town of Weddington
- Robert Price, Toll Brothers
- Elizabeth Richard, Kimley-Horn and Associates, Inc.
- Julian Ortiz-Hernandez, Kimley-Horn and Associates, Inc.


Attachments:

- Town TIA comments
- NCDOT TIA Congestion Management Comments
- NCDOT TIA Division Comments
- Approved NCDOT TIA Scoping Checklist

Turning Movement Counts

LOCATION: S Providence Rd -- Rea Rd/Marvin School Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497107
DATE: Thu, Mar 7 2024



15-Min Count Period Beginning At	S Providence Rd (Northbound)				S Providence Rd (Southbound)				Rea Rd/Marvin School Rd (Eastbound)				Rea Rd/Marvin School Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
7:00 AM	102	245	0	0	0	78	71	0	86	0	43	0	0	0	0	0	625	
7:15 AM	80	259	0	0	0	98	94	0	100	0	67	0	0	0	0	0	698	
7:30 AM	100	217	0	0	0	123	78	0	97	0	41	0	0	0	0	0	656	
7:45 AM	93	226	0	0	0	148	79	0	61	0	48	0	0	0	0	0	655	2634
8:00 AM	60	199	0	0	0	149	85	0	75	0	41	0	0	0	0	0	609	2618
8:15 AM	70	213	0	0	0	147	97	0	82	0	23	0	0	0	0	0	632	2552
8:30 AM	64	227	0	0	0	129	83	0	86	0	37	0	0	0	0	0	626	2522
8:45 AM	68	225	0	0	0	153	112	0	106	0	48	0	0	0	0	0	712	2579
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	320	1036	0	0	0	392	376	0	400	0	268	0	0	0	0	0	2792	
Heavy Trucks	4	8	0	0	0	16	12	0	4	0	4	0	0	0	0	0	48	
Buses																		
Pedestrians		0				0				0				0			0	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	0		0	
Scooters																		


Comments:

Report generated on 3/11/2024 1:14 PM

SOURCE: Quality Counts, LLC (<http://www.qualitycounts.net>) 1-877-580-2212

LOCATION: S Providence Rd -- Rea Rd/Marvin School Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497108
DATE: Thu, Mar 7 2024



15-Min Count Period Beginning At	S Providence Rd (Northbound)				S Providence Rd (Southbound)				Rea Rd/Marvin School Rd (Eastbound)				Rea Rd/Marvin School Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
2:00 PM	51	149	0	0	0	168	89	0	80	0	73	0	0	0	0	0	610	
2:15 PM	45	159	0	0	0	164	71	0	102	0	77	0	0	0	0	0	618	
2:30 PM	40	152	0	0	0	208	86	0	79	0	60	0	0	0	0	0	625	
2:45 PM	50	180	0	0	0	157	95	0	117	0	72	0	0	0	0	0	671	2524
3:00 PM	69	166	0	0	0	176	84	1	122	0	68	0	0	0	0	0	686	2600
3:15 PM	61	185	0	0	0	173	88	0	114	0	96	0	0	0	0	0	717	2699
3:30 PM	57	172	0	0	0	180	74	0	113	0	91	0	0	0	0	0	687	2761
3:45 PM	47	179	0	0	0	188	93	0	139	0	107	0	0	0	0	0	753	2843
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	188	716	0	0	0	752	372	0	556	0	428	0	0	0	0	0	3012	
Heavy Trucks	0	24	0	0	0	4	8	0	4	0	16	0	0	0	0	0	56	
Buses																		
Pedestrians		0				0				0				0			0	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	0		0	
Scooters																		


Comments:

Report generated on 3/11/2024 1:14 PM

SOURCE: Quality Counts, LLC (<http://www.qualitycounts.net>) 1-877-580-2212

LOCATION: S Providence Rd -- Rea Rd/Marvin School Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497109
DATE: Thu, Mar 7 2024



15-Min Count Period Beginning At	S Providence Rd (Northbound)				S Providence Rd (Southbound)				Rea Rd/Marvin School Rd (Eastbound)				Rea Rd/Marvin School Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
4:00 PM	40	162	0	0	0	158	100	0	101	0	102	0	0	0	0	0	663	
4:15 PM	37	171	0	0	0	168	118	0	136	0	105	0	0	0	0	0	735	
4:30 PM	49	218	0	0	0	170	111	1	134	0	111	0	0	0	0	0	794	
4:45 PM	47	176	0	0	0	171	139	0	146	0	99	0	0	0	0	0	778	2970
5:00 PM	42	204	0	0	0	153	124	0	130	0	66	0	0	0	0	0	719	3026
5:15 PM	59	196	0	0	0	157	153	0	153	0	107	0	0	0	0	0	825	3116
5:30 PM	55	203	0	0	0	163	128	1	146	0	99	0	0	0	0	0	795	3117
5:45 PM	45	189	0	0	0	152	116	0	133	0	89	0	0	0	0	0	724	3063
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	236	784	0	0	0	628	612	0	612	0	428	0	0	0	0	0	3300	
Heavy Trucks	0	36	0	0	0	0	0	0	12	0	0	0	0	0	0	0	48	
Buses																		
Pedestrians		0				0				0				0			0	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	0		0	
Scoters																		


Comments:

Report generated on 3/11/2024 1:14 PM

SOURCE: Quality Counts, LLC (<http://www.qualitycounts.net>) 1-877-580-2212

LOCATION: Cox Rd -- Weddington Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497101
DATE: Thu, Mar 7 2024











LOCATION: Cox Rd -- Weddington Rd**CITY/STATE:** Weddington, NC**QC JOB #:** 16497102**DATE:** Thu, Mar 7 2024

Peak-Hour: 3:00 PM -- 4:00 PM
Peak 15-Min: 3:15 PM -- 3:30 PM



TRUE DATA TO IMPROVE MOBILITY



15-Min Count Period Beginning At	Cox Rd (Northbound)				Cox Rd (Southbound)				Weddington Rd (Eastbound)				Weddington Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
2:00 PM	0	0	0	0	4	0	0	1	1	133	0	0	0	114	10	0	263	
2:15 PM	0	0	0	0	7	0	5	0	1	137	0	0	0	123	5	0	278	
2:30 PM	0	0	0	0	8	0	4	0	3	171	0	0	0	140	5	0	331	
2:45 PM	0	0	0	0	12	0	0	0	1	173	0	0	0	137	11	0	334	1206
3:00 PM	0	0	0	0	10	0	0	0	4	194	0	0	0	117	27	0	352	1295
3:15 PM	0	0	0	0	7	0	4	0	2	175	0	0	0	156	42	0	386	1403
3:30 PM	0	0	0	0	11	0	0	0	3	219	0	0	0	116	13	0	362	1434
3:45 PM	0	0	0	0	17	0	2	0	6	211	0	0	0	119	11	0	366	1466
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	0	0	0	28	0	16	0	8	700	0	0	0	624	168	0	1544	
Heavy Trucks	0	0	0	0	0	0	0	0	0	0	0	0	0	24	12	0	36	
Buses																		
Pedestrians		0				0				0				0			0	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	0		0	
Scooters																		


Comments:

Report generated on 3/11/2024 1:14 PM

SOURCE: Quality Counts, LLC (<http://www.qualitycounts.net>) 1-877-580-2212


LOCATION: Cox Rd -- Weddington Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497103
DATE: Thu, Mar 7 2024




LOCATION: Twelve Mile Creek Rd -- Weddington Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497104
DATE: Thu, Mar 7 2024




LOCATION: Twelve Mile Creek Rd -- Weddington Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497105
DATE: Thu, Mar 7 2024




LOCATION: Twelve Mile Creek Rd -- Weddington Rd
CITY/STATE: Weddington, NC

QC JOB #: 16497106
DATE: Thu, Mar 7 2024



IAU Worksheets






Peak Hour Volume Breakouts Report:
Int #1 Background

Traffic Forecast Release Date:
September-18

Traffic Data Year:
1/1/2018

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #1 Background

Traffic Forecast Release Date:
September-18

Traffic Data Year:
1/1/2040

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #1 Background

Traffic Forecast Release Date:
September-18

Traffic Data Year:
2029 Background

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #2 Background

Traffic Forecast Release Date:
May-12

Traffic Data Year:
1/1/2012

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #3 Background

Traffic Forecast Release Date:
October-23

Traffic Data Year:
1/1/2019

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #3 Background

Traffic Forecast Release Date:
October-23

Traffic Data Year:
1/1/2039

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #3 Background

Traffic Forecast Release Date:
October-23

Traffic Data Year:
2029 Background

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #4 2019 FC Volumes

Traffic Forecast Release Date:
October-23

Traffic Data Year:
1/1/2019

Project:
Deal Lake TIA








Peak Hour Volume Breakouts Report:
Int #4 2039 FC Volumes

Traffic Forecast Release Date:
October-23

Traffic Data Year:
1/1/2039

Project:
Deal Lake TIA







Peak Hour Volume Breakouts Report:
Int #4 2039 FC Volumes

Traffic Forecast Release Date:
October-23

Traffic Data Year:
2029 Background

Project:
Deal Lake TIA



Traffic Forecast Data

Project Level Traffic Forecast



FS-1810D: NC 16 from SR 1316 (Rea Road)
to Mecklenburg County Line

Union County

September 2018



Submitted by:

RK&K



PROJECT LEVEL TRAFFIC FORECAST TECHNICAL MEMORANDUM

**FS-1810D: NC 16 from SR 1316 (Rea Road) to
Mecklenburg County Line
Union County
North Carolina**

WBS No.: 34263.1.1



Prepared By
Rummel, Klepper & Kahl, LLP
900 Ridgefield Drive – Suite 350
Raleigh, NC 27609
(919) 878-9560
September 2018

TRAFFIC FORECAST COVER LETTER

September 2018

TO: Shane York, PE
Feasibility Studies Unit
NCDOT

FROM: Stuart M. Samberg, P.E., PTOE, PTP
RK&K, LLP

SUBJECT: Traffic Forecast for NC 16 Widening
FS-1810D: NC 16 from SR 1316 (Rea Road) to the Mecklenburg County Line in Union County

Please find attached the 2018 Base Year and 2040 Future Year No-Build and Build traffic forecast for the NC 16 Widening Feasibility Study (FS-1810D) from SR 1316 (Rea Road) to the Mecklenburg County Line in Union County. The total project length is approximately 1.8 miles.

This traffic forecast was approved by NCDOT Transportation Planning Division on September 05, 2018.

This traffic forecast includes one Build scenario:

- Widen NC 16 to a six-lane divided facility from SR 1316 (Rea Road) to the Mecklenburg County Line

Traffic forecasts for the following scenarios are provided in this memorandum:

- 2018 Base Year No-Build
- 2018 Base Year Build (Widen to six-lane divided)
- 2040 Future Year No-Build
- 2040 Future Year Build (Widen to six-lane divided)

Certain assumptions were made in the development of this forecast:

Fiscal Constraint:

The traffic forecasts for this project assume the construction of projects within the Charlotte Regional Transportation Planning Organization's (CRTPO) Metropolitan Transportation Plan (MTP) and Metrolina Regional Travel Demand Model. Projects in the MTP which directly affect the proposed project area include:

- U-3467: Construct / Widen NC 84 from NC 16 to Waxhaw-Indian Trail Road (SR 1008), part on New Location
- U-5769: Widen NC 16 from Rea Road (SR 1316) to Cuthbertson Road (SR 1321)

The Charlotte Regional Transportation Planning Organization (CRTPO) Comprehensive Transportation Plan (CTP) includes the North Access Road project intersecting NC 16 just north of existing NC 84. However, this project is not included in the CRTPO 2045 MTP, and therefore not included in the forecast.

Development Activity:

Stuart Basham, Division 10 Planning Engineer was contacted to get information on anticipated developments within the study area. Based on the feedback and the information presented in the GIS based application- Virtual Charlotte (<http://vc.charmeck.org/>), it was observed that there is limited development activity that would be anticipated to alter existing traffic pattern in the Future Year of 2040 within the project study area.



Travel Demand Model:

The Metrolina Regional Model (MRM16) Version 1.0 adopted on October 17, 2017 was used to develop the traffic forecast for the subject project. The model was developed with a Base Year of 2010 using TransCAD Version 5.0 Build 1590.

Forecast Methodology:

Traffic volume and design factor estimates for the 2018 Base Year were developed using traffic counts collected on May 8th and 9th of 2018 and historic Annual Average Daily Traffic (AADT) trends projected to 2018. Growth rates derived from the Metrolina Regional Model and historic growth rates extrapolated from AADT trends were used to estimate Future Year 2040 traffic volumes. Engineering judgment was used as necessary to ensure a balanced forecast.

Interpolation:



Straight-line interpolation may be used to estimate AADT for years between 2018 and 2040. Extrapolation may be used to estimate AADT volumes for up to two years following 2040.

CC (with Attachments):

Tim Boland, PE, Highway Division 10 Project Development Engineer
Randy Bowers, Highway Division 10 Roadway Project Engineer
Stuart Basham, Highway Division 10 Planning Engineer
Lee Ainsworth, PE, Anson & Union County District Engineer
Brenda Moore, PE, CPM Roadway Design Unit
Clark Morrison, PhD, PE, State Pavement Design Engineer
Mike Reese, PE, Congestion Management
John A. Baliey, Western Piedmont Group Supervisor
Keith Dixon, State Traffic Forecast Engineer
Traffic Forecasting GIS Support

File Copy: FS-1810D: NC 16 Union County





2018

AVERAGE ANNUAL
DAILY TRAFFIC

No-Build

Sheet 1 of 1

LEGEND	
###	No. of Vehicles Per Day in 100s
1-	Less than 50 vpd
X	Movement Prohibited
K	Design Hour Factor (%)
PM	PM Peak Period
D	Peak Hour Directional Split (%)
→	Indicates Direction of D
(d, t)	Duals, TT-STs (%)

TIP: N/A

WBS: 34263.1.1

COUNTY: Union



DIVISION: 10

DATE: September 2018

PREPARED BY: **RK&K**

LOCATION: Weddington, NC

PROJECT: FS-1810D: NC 16 from SR 1316 (Rea Road) to the Mecklenburg County Line





2018

AVERAGE ANNUAL
DAILY TRAFFIC



Build

Sheet 1 of 1


LEGEND		
###	No. of Vehicles Per Day in 100s	
1-	Less than 50 vpd	
X	Movement Prohibited	
K	Design Hour Factor (%)	
PM	PM Peak Period	
D	Peak Hour Directional Split (%)	
→	Indicates Direction of D	
(d, t)	Duals, TT-STs (%)	
TIP: N/A		WBS: 34263.1.1
COUNTY: Union		DIVISION: 10
DATE: September 2018		
PREPARED BY: RK&K		
LOCATION: Weddington, NC		
PROJECT: FS-1810D: NC 16 from SR 1316 (Rea Road) to the Mecklenburg County Line		



2040		AVERAGE ANNUAL DAILY TRAFFIC		No-Build		Sheet 1 of 1	
<div>### 1- X <div><div><div>K</div><div>AM</div></div><div>→D</div><div>(d, t)</div></div> K PM D → (d, t)</div>	<div>LEGEND</div> <div>No. of Vehicles Per Day in 100s</div> <div>Less than 50 vpd</div> <div>Movement Prohibited</div> <div>Design Hour Factor (%)</div> <div>PM Peak Period</div> <div>Peak Hour Directional Split (%)</div> <div>Indicates Direction of D</div> <div>Duals, TT-STs (%)</div>			TIP: N/A		WBS: 34263.1.1	
				COUNTY: Union		DIVISION: 10	
				DATE: September 2018			
				PREPARED BY: <div>RK&K</div>			
				LOCATION: Weddington, NC			
				PROJECT: FS-1810D: NC 16 from SR 1316 (Rea Road) to the Mecklenburg County Line			



<h1>2040</h1> <p>AVERAGE ANNUAL DAILY TRAFFIC</p>		Build	Sheet 1 of 1
<p>### No. of Vehicles Per Day in 100s</p> <p>1- Less than 50 vpd</p> <p>X Movement Prohibited</p> <p style="text-align: center;"> $\kappa \xrightarrow{\text{AM}} \text{D}$ (d, t) </p> <p>K Design Hour Factor (%)</p> <p>PM PM Peak Period</p> <p>D Peak Hour Directional Split (%)</p> <p>→ Indicates Direction of D</p> <p>(d, t) Duals, TT-STs (%)</p>	<p>TIP: N/A</p>		<p>WBS: 34263.1.1</p>
	<p>COUNTY: Union</p>		<p>DIVISION: 10</p>
	<p>DATE: September 2018</p>		
	<p>PREPARED BY: RK&K</p>		
	<p>LOCATION: Weddington, NC</p>		
	<p>PROJECT: FS-1810D: NC 16 from SR 1316 (Rea Road) to the Mecklenburg County Line</p>		



**No Build
Sheet 1 - 1**

2012

LEGEND

###	No. of Vehicles Per Day (VPD) in 100s	K	Design Hour Factor (%)
1-	Less than 50 VPD	PM	PM Peak Period
K	Movement Prohibited	D	Peak Hour Directional Split
.....	Proposed Roadway	→	Indicates Direction of D
		(d,t)	Duals, TT-STs (%)

<p>AVERAGE ANNUAL DAILY TRAFFIC</p>		<p>No Build Sheet 1 - 1</p>	
<p>TIP: U-3467</p>	<p>WBS: 39019,1,1</p>		
<p>COUNTY: Union</p>	<p>DIVISION: 10</p>		
<p>DATE: May 9, 2012</p>			
<p>PREPARED BY: Paul Schroeder, PhD, PE</p>			
<p>LOCATION: NC 84 Weddington Road southeast of Charlotte</p>			
<p>PROJECT: SR 1316 Rea Road extension from NC 16 to SR 1008 Indian Trail-Waxhaw Road</p>			





Figure 4

2035		No Build Sheet 1 - 1	
AVERAGE ANNUAL DAILY TRAFFIC		TIP: U-3467	WBS: 39019.1.1
COUNTY: Union		DIVISION: 10	
DATE: January 23, 2013		PREPARED BY: Paul Schroeder, PhD, PE	
LOCATION: NC 84 Weddington Road southeast of Charlotte		PROJECT: SR 1316 Rea Road extension from NC-16 to SR 1008 Indian Trail-Waxhaw Road	

LEGEND

###

No. of Vehicles Per
Day (VPD) in 100s

1-

Less than 50 VPD

x

Movement Prohibited

.....

Proposed Roadway

PM

Design Hour Factor (%)

PM

Peak Hour Period

D

Peak Hour Directional Split


→

Indicates Direction of D

(d, t)

Duals, TT-STs (%)

SR 1344 Weddington
Matthews Rd



Weddington High
School Entrance

Optimist Park
West Entrance

Optimist Park
East Entrance

SR 1338 Antioch
Church Rd

NC 16 Providence Rd

SR 1341 Twelve Mile
Creek Rd

Holister Estates
Entrance

SR 1339 Lester
Davis Rd

SR 1008 Indian Trail-
Waxhaw Rd




Figure 5

2035

Build Sheet 1 - 1		AVERAGE ANNUAL DAILY TRAFFIC	
TIP: U-3467		WBS: 39019.1.1	
COUNTY: Union		DIVISION: 10	
DATE: May 9, 2012			
PREPARED BY: Paul Schroeder, PhD, PE			
LOCATION: NC 84 Weddington Road southeast of Charlotte			
PROJECT: SR 1316 Rea Road extension from NC 16 to SR 1008 Indian Trail-Waxhaw Road			

LEGEND

- ### No. of Vehicles Per Day (VPD) in 100s Less than 50 VPD
- x Movement Prohibited
- Proposed Roadway
- K Design Hour Factor (%)
- PM PM Peak Period
- D Peak Hour Directional Split
- (d,t) Indicates Direction of D
- (d,t) Duals, TT-STs (%)

Mid Peak-Hour Traffic Volume Calculations

Equation:

$$\frac{\text{Background Forecast Volumes}}{\text{existing forecast volumes}} \times \text{midday traffic counts} = \text{midday forecast volumes}$$

#1 Existing

(388) (888) (0)	↑ 0 (0)
608 871 0	← 0 (0)
↙ ↓ ↘	↘ 0 (0)
(608) 388 ↗	↖ ↗ ↘
(0) 0 →	445 888 0
(445) 279 ↘	(279) (871) (0)

#1 Background

(376) (1130) (32)	↑ 32 (32)
599 1126 32	← 268 (164)
↙ ↓ ↘	↘ 78 (77)
(599) 376 ↗	↖ ↗ ↘
(268) 164 →	579 1130 76
(579) 361 ↘	(361) (1126) (78)

NBL: $\frac{579}{445} \times 234 = 305$ $\frac{361}{279} \times 234 = 303 \rightarrow 304$

NBT: $\frac{1130}{888} \times 702 = 893$ $\frac{1126}{871} \times 702 = 908 \rightarrow 901$

NBR: $\frac{76}{0} \times 0 = 0$ $\frac{78}{0} \times 0 = 0 \rightarrow \text{solved using different method} \rightarrow 128$

SBL: $\frac{32}{0} \times 0 = 0$ $\frac{32}{0} \times 0 = 0 \rightarrow \text{solved using different method} \rightarrow 54$

SBT: $\frac{1126}{871} \times 718 = 928$ $\frac{1130}{888} \times 718 = 914 \rightarrow 921$

SNR: $\frac{599}{608} \times 339 = 334$ $\frac{376}{388} \times 339 = 329 \rightarrow 332$

EBL: $\frac{376}{388} \times 488 = 473$ $\frac{599}{608} \times 488 = 481 \rightarrow 477$

EBT: $\frac{164}{0} \times 0 = 0$ $\frac{268}{0} \times 0 = 0 \rightarrow \text{solved using different method} \rightarrow 353$

ENR: $\frac{361}{279} \times 362 = 468$ $\frac{579}{445} \times 362 = 471 \rightarrow 470$

* Westbound

solved on another sheet

WBL: 93
WBT: 256
WBR: 39

• FC = Forecast

Kimley»Horn

Job Deal Lake

Subject #2 MD Volumes

Sheet No. ____ of ____

Job No. ____

Expect More. Experience Better.

Designed By ____

Date ____

Checked By ____

Date ____

EQUATION: $\frac{\text{Background FC}}{\text{Existing FC}} \times \text{Midday traffic Counts}$

#2 Existing FC Volumes

(4)	(21)	
21	48	← 22 (45)
←	→	← 804 (648)

(24)	8	↑
(803)	647	→

#2 Background FC Volumes

(11)	(31)	
26	67	← 32 (64)
←	→	← 746 (596)

(29)	10	↑
(745)	595	→

$$\text{SBL: } \frac{67}{48} \times 45 = 63, \quad \frac{31}{21} \times 45 = 66 \rightarrow 65$$

$$\text{SBR: } \frac{26}{21} \times 6 = 7, \quad \frac{11}{9} \times 6 = 7 \rightarrow 7$$

$$\text{EBL: } \frac{10}{8} \times 15 = 19, \quad \frac{29}{24} \times 15 = 18 \rightarrow 19$$

$$\text{EBT: } \frac{595}{647} \times 799 = 735, \quad \frac{745}{803} \times 799 = 741 \rightarrow 738$$

$$\text{WBT: } \frac{746}{804} \times 508 = 471, \quad \frac{596}{648} \times 508 = 467 \rightarrow 469$$

$$\text{WBR: } \frac{32}{22} \times 93 = 135, \quad \frac{64}{45} \times 93 = 132 \rightarrow 134$$

$$\frac{129}{143} \times 120 = 108, \quad \frac{142}{162} \times 120 = 105 \rightarrow \text{NBL: } 107$$

$$\frac{23}{11} \times 76 = 159, \quad \frac{46}{23} \times 76 = 152 \rightarrow \text{NBT: } 156$$

$$\frac{79}{59} \times 57 = 76, \quad \frac{103}{80} \times 57 = 73 \rightarrow \text{NBT: } 75$$

$$\frac{82}{58} \times 90 = 127, \quad \frac{52}{27} \times 90 = 126 \rightarrow \text{SBL: } 127$$

$$\frac{46}{23} \times 64 = 128, \quad \frac{23}{11} \times 64 = 134 \rightarrow \text{SBT: } 131$$

$$\frac{167}{183} \times 51 = 47, \quad \frac{88}{97} \times 51 = 46 \rightarrow \text{SBR: } 47$$

$$\frac{87}{96} \times 84 = 76, \quad \frac{168}{183} \times 84 = 77 \rightarrow \text{EBL: } 77$$

$$\frac{841}{715} \times 645 = 759, \quad \frac{1041}{883} \times 645 = 760 \rightarrow \text{EBT: } 760$$

$$\frac{139}{159} \times 106 = 93, \quad \frac{131}{144} \times 106 = 96 \rightarrow \text{EBR: } 95$$

$$\frac{105}{82} \times 75 = 96, \quad \frac{78}{58} \times 75 = 101 \rightarrow \text{WBL: } 99$$

$$\frac{1049}{889} \times 435 = 513, \quad \frac{849}{722} \times 435 = 512 \rightarrow \text{WBT: } 513$$

$$\frac{53}{38} \times 124 = 173, \quad \frac{81}{57} \times 124 = 176 \rightarrow \text{WBR: } 175$$

Solving for #4 MD volumes and Int #1 : NBR, SBL, EBT & WB MD volumes using splits

Kimley»Horn

Expect More. Experience Better.

Job Deal Lake

Subject MD volumes

Sheet No. ____ of ____

Job No. ____

Designed By ____ Date ____ Checked By ____ Date ____

$$548 / 1216 = .45 \times 667 = 300$$

$$668 / 1216 = .55 \times 667 = 367$$

$$547 / 1215 = .45 \times 932 = 419$$

$$668 / 1215 = .55 \times 932 = 513$$

$$32 / 326 = .10 \times 388 = 39$$


$$216 / 326 = .66 \times 388 = 256$$

$$78 / 326 = .24 \times 388 = 93$$


$$32 / 325 = .10 \times 535 = 54$$

$$216 / 325 = .66 \times 535 = 353$$

$$77 / 325 = .24 \times 535 = 128$$




Average Forecast Volumes




used for
splits

Average Forecast Volumes




used for
splits

Am/Pm Volumes



Midday Volumes



Approved Developments


Notes

Am (Pm)

Red = Providence & Rea

Blue = Splits

Green = Carried through







Red = Providence; Rea
MO volumes

Blue = split + s

Green = Carried through

* ITE does not provide weekday, midday peak-hour traffic generation rates. The hourly breakdowns provided in ITE generations were applied the Pm peak-hour trip generation to determine midday peak-hour trip generation. It was assumed that midday trips would operate with the same in/out percentage as the Pm peak hour.







BEECHWOOD CAROLINAS
7621 LITTLE AVENUE SUITE 111
CHARLOTTE, NC 28226


0 XX' XX'

SCALE: NTS

PROJECT #: 1088-001
DRAWN BY: CRB
CHECKED BY: REG
JUNE 2024
REVISIONS:

Figure 6






Notes

Red = Weddington Road Office Park


Blue = Splits

Green = Carried through Am (Pm)

Purple = Redistributed



(MO w STIPS)




LEGEND

-  Traffic Signal
-  Stop Sign Control
-  Directional Movement

VOLUMES: No Build (Site) Total

Site
*

Trips	
Enter	44
Exit	9



Note: Volumes were balanced in all Synchro models.

Copyright © 2024 Design Resource Group, PA This plan or drawing and any accompanying documents or calculations are the property of Design Resource Group, PA; and are intended solely for the use of the recipient noted. No third party use or modification is permitted without written authorization.

drG
**DESIGN
RESOURCE
GROUP**

LANDSCAPE ARCHITECTURE
CIVIL ENGINEERING
TRANSPORTATION PLANNING

2459 Wilkinson Blvd, Ste 200 Charlotte, NC 28208
704.343.0608
www.drgroup.com

WEDDINGTON ROAD OFFICE PARK TIA

WEDDINGTON, NC

POLIVKA INTERNATIONAL
13700 PROVIDENCE ROAD SUITE 200
WEDDINGTON, NC 28104

2025 BUILD AM
PEAK HOUR
TRAFFIC
VOLUMES

0 XX XX N
SCALE: NTS

PROJECT #: 1082-001
DRAWN BY: PAH
CHECKED BY: REG

FEBRUARY 2024

REVISIONS:


1. May 2024

Figure 5

LEGEND

-  Traffic Signal
-  Stop Sign Control
-  Directional Movement

VOLUMES: No Build (Site) Total



WEDDINGTON ROAD OFFICE PARK TIA

WEDDINGTON, NC

POLIVKA INTERNATIONAL
13700 PROVIDENCE ROAD SUITE 200
WEDDINGTON, NC 28104

2025 BUILD PM PEAK HOUR TRAFFIC VOLUMES

0 XX XX N
SCALE: NTS

PROJECT #: 1082-001
DRAWN BY: PAH
CHECKED BY: REG

FEBRUARY 2024

REVISIONS:

1. May 2024

Figure 6

Note: Volumes were balanced in all Synchro models.

U-5769A Concept Plans


PLOT DRIVER: PDF.pltcfgr
USER: DATAYLOR
FILE: \

DATE: 8/23/2019

PENTABLE: NCDOT_dshp.fltdi
TIME: 12:26:18 PM

REVISIONS

MATCH LINE -L- STA 328+00 SEE SHEET 28



SEE SHEET NO. 45 FOR -L- PROFILE

U-3467 Concept Plans

8/17/99

-L-
PI Sta 9+14.66
 $\Delta = 0' 33' 07.2''$ (RT)
 $D = 0' 34' 22.6''$
 $L = 96.34'$
 $T = 48.17'$
 $R = 10,000.00'$
 $SE = NC$
 $V = 50$ MPH

NV5

NV5 ENGINEERS & CONSULTANTS, INC.
3300 REGENCY PARKWAY, SUITE 100
CARY, NC 27518
P: 919.851.1912
www.NV5.com
NC License # F4333
Formerly CALVY Engineers & Consultants

PROJECT REFERENCE NO.
U-3467


SHEET NO.
4A

RW SHEET NO.
ROADWAY DESIGN ENGINEER

HYDRAULICS ENGINEER

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

RIGHT OF WAY REVISION - 06/21/2019 - ADDED DRAINAGE UTILITY EASEMENT ON PARCELS 2 AND 13, MODIFIED CONSTRUCTION EASEMENT ON PARCELS 2 AND 13, REMOVED CONSTRUCTION EASEMENT ON PARCELS 112 & 113.
DESIGN REVISION - 3/1/2019 - NC 16 INTERSECTION DESIGN REVISED IN COORDINATION WITH U-5769.



CONC. SIDEWALK /MEDIAN
PAVED SHOULDER

NOTES:
SEE SHEET 31 FOR -L- PROFILE

REVISIONS

RIGHT OF WAY REVISION - 07/06/2018	ADJUSTED PERMANENT UTILITY EASEMENT ON PARCELS 2, 4 AND 5.
RIGHT OF WAY REVISION - 07/06/2018	ADJUSTED CONSTRUCTION EASEMENT ON PARCELS 2 AND 5.
RIGHT OF WAY REVISION - 07/30/2019	ADDED PERMANENT DRAINAGE EASEMENT ON PARCEL 2.
RIGHT OF WAY REVISION - 07/30/2019	ADDED CONSTRUCTION EASEMENT ON PARCEL 2.
RIGHT OF WAY REVISION - 06/21/2019	ADDED ADDITIONAL PERMANENT UTILITY EASEMENT ON PARCEL 2.
RIGHT OF WAY REVISION - 06/21/2019	ADDED ADDITIONAL PERMANENT DRAINAGE EASEMENT ON PARCEL 2.
DESIGN REVISION - 3/11/2019	ADDED PARCEL 14 MODIFIED PERMANENT DRAINAGE EASEMENT ON PARCEL 2, ADDED NOTE "NO CLAIM" ON PARCEL 3.

DESIGN REVISION - 3/11/2019 - NC 16 INTERSECTION DESIGN REVISED IN COORDINATION WITH U-5769.

TRAFFIC DIAGRAM				
ADT 2019	ADT 2039	-Y- NC 16	22,784 30,704	
			7,944 8,664	
SR 1316	23,928	-L-	2,780 3,180	
			12,376 15,256	
18,488	9,968	-Y- NC 16	5,328 6,780	
			21,800 35,600	

NO CLAIM


3

UNION ELECTRIC MEMBERSHIP CORPORATION
DB 6696 PG 637
PC N PG 184

-L-
PI Sta 21+64.93
Δ = 16'14" 32.2" (LT)
D = 4' 46" 28.7"
L = 340.18'
T = 171.24'
R = 1,200.00'
SE = NC
V = 50 MPH

-Y-
PI Sta 24+90.39
Δ = 1' 40" 31.6" (RT)
D = 0' 47" 36.9"
L = 211.13'
T = 105.57'
R = 7,220.00'
SE = NC
V = 50 MPH


-Y-
PI Sta 30+52.85
Δ = 0' 28" 53.5" (RT)
D = 0' 47" 36.9"
L = 60.68'
T = 30.34'
R = 7,220.00'
SE = NC
V = 50 MPH



NV5

NVS ENGINEERS & CONSULTANTS, INC.
3300 REGENCY PARKWAY, SUITE 100
CARY, NC 27518
P: 919.851.1912
F: 919.851.1912
www.nv5.com

PROJECT REFERENCE NO.		SHEET NO.	
U-3467		4	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	



FROM -L- STA. 23+20 TO STA. 24+00 RT
29 TONS CL-B RIP-RAP
W/ 62 SY GEOTEXTILE

EXISTING TRAFFIC SIGNAL
CONC. SIDEWALK / MEDIAN
PAVED SHOULDER


NOTES:
SEE SHEET 31 FOR -L- PROFILE

REVISIONS

RIGHT OF WAY REVISION	07/06/2018	ADJUSTED PERMANENT UTILITY EASEMENT ON PARCELS 4.7 AND 8.
RIGHT OF WAY REVISION	07/06/2018	ADJUSTED DUAL UTILITY EASEMENT ON PARCEL 8.
RIGHT OF WAY REVISION	07/06/2018	ADJUSTED CONSTRUCTION EASEMENT ON PARCELS 6.7 AND 8.
RIGHT OF WAY REVISION	07/06/2018	ADJUSTED PERMANENT UTILITY EASEMENT ON PARCEL 8.
RIGHT OF WAY REVISION	06/21/2019	ADDED PERMANENT UTILITY EASEMENT ON PARCEL 8.
RIGHT OF WAY REVISION	06/21/2019	ADDED PERMANENT DRAINAGE EASEMENT ON PARCEL 8.
RIGHT OF WAY REVISION	06/21/2019	ADDED PERMANENT UTILITY EASEMENT ON PARCEL 4 AND 9.
RIGHT OF WAY REVISION	06/21/2019	ADDED PERMANENT DRAINAGE EASEMENT ON PARCEL 4 AND 9.

DESIGN REVISION - 3/1/2019 - NC 16 INTERSECTION DESIGN REVISED IN COORDINATION WITH U-5769.

10/30/2023
R:\Roadway\Proj\U3467.Rdw_psh_05.dgn
R:\Roadway\Proj\U3467.Rdw_psh_05.dgn









NV5

NVS ENGINEERS & CONSULTANTS, INC.
3300 REGENCY PARKWAY, SUITE 100
CARY, NC 27518
P: 919.851.1912
www.NV5.com
NC License # F4333
Formerly CALVA Engineers & Consultants




PROJECT REFERENCE NO. U-3467		SHEET NO. 5	
RW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



CONCRETE SIDEWALK / MEDIAN

NOTES:
SEE SHEET 31 & 32 FOR -L- PROFILE




NOTES:
SEE SHEET 41 FOR -Y1- PROFILE

REVISIONS
RIGHT OF WAY REVISION - 07/06/2018 - ADJUSTED CONSTRUCTION EASEMENT ON PARCEL 16.

3/17/99

0/30/2023
R:\Roadway\Proj\U3467_Rdy_psh-25.dgn
Print: Aiasbiru

DESIGN REVISION - 6-30-23 - REMOVED U-TURN BULB LEFT AT -L- STA.96+05.00 TO 98+98.00.



PROJECT REFERENCE NO.

U-3467

SHEET NO.

10

RW SHEET NO.

ROADWAY DESIGN ENGINEER

HYDRAULICS ENGINEER

DOCUMENT NOT CONSIDERED FINAL

UNLESS ALL SIGNATURES COMPLETED

NVS

NVS ENGINEERS & CONSULTANTS, INC.

3300 REGENCY PARKWAY, SUITE 100

CARY, NC 27518




P: 919.851.1912

www.NVS.com

NC License # F1333

Formerly CALVEX Engineers & Consultants

-YI-	-L-
PI Sta 12+48.14	PI Sta 98+94.39
$\Delta = 41^{\circ} 17' 05.0''$ (LT)	$\Delta = 33^{\circ} 49' 47.0''$ (RT)
$D = 10^{\circ} 44' 58.8''$	$D = 2^{\circ} 29' 28.0''$
$L = 384.06'$	$L = 1,358.01'$
$T = 200.79'$	$T = 699.45'$
$R = 533.00'$	$R = 2,300.00'$
$SE = RC$	$SE = 03$
* $V = 40$ MPH	$V = 50$ MPH




TRAFFIC DIAGRAM			
ADT 2019	ADT 2039	EXIST NC 84	EXIST 84
12,376	15,256	10,332	12,492
		348	9,984
		588	11,904
		REAR ROAD	
		22,012	26,572


- ★ PROPOSED TRAFFIC SIGNAL
 - ▨ PAVEMENT REMOVAL
 - ▤ CONCRETE SIDEWALK / MEDIAN
 - ▥ PAVED SHOULDER
 - HPB- HISTORIC PROPERTY BOUNDARY
- NOTES:
SEE SHEET 34 FOR -L- PROFILE
SEE SHEET 41 FOR -YI- PROFILE
* HORIZONTAL CURVE RADIUS BELOW
DESIGN SPEED

-L-

PI Sta 122+19.72
 $\Delta = 25^{\circ} 49' 52.8''$ (LT)
 $D = 2^{\circ} 30' 07.2''$
 $L = 1,032.43'$
 $T = 525.14'$
 $R = 2,290.00'$
 $SE = 03$
 $V = 50$ MPH



8/17/99



TRAFFIC DIAGRAM			
ADT 2019		ADT 2039	
-Y2- CREEK		-Y2- CREEK	
2,572		1,508	
1,932		2,548	
20,316		28,396	
-L- NC 84		-L- NC 84	
22,012		2,740	
26,572		2,108	
1,940		3,148	
5,292		6,252	





-L-	-Y2-
PI Sta 122+9.72	PI Sta 13+97.38
$\Delta = 25^\circ 49' 52.8''$ (LT)	$\Delta = 20^\circ 50' 39.2''$ (RT)
$D = 2^\circ 30' 07.2''$	$D = 6^\circ 11' 14.8''$
$L = 1,032.43'$	$L = 336.88'$
$T = 525.14'$	$T = 170.32'$
$R = 2,290.00'$	$R = 926.00'$
$SE = 03$	$SE = 04$
$V = 50$ MPH	$V = 50$ MPH

NV5

NVS ENGINEERS & CONSULTANTS, INC.
3300 REGENCY PARKWAY, SUITE 100
CARY, NC 27518
P: 919.851.1912
www.nv5.com
Formerly CALVE Engineers & Consultants

PROJECT REFERENCE NO.		SHEET NO.	
U-3467		12	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

DESIGN REVISION - 6-30-23 - REMOVED U-TURN BULBS LEFT AT -L- STA.125+22.00 TO 128+90.00




- 22 MAHMOUD K. & MELANIE KIRDAZI DB 3520 PG 465 PC 6 PG 335
- 23 STEVE ESPOSITO LESLIE ESPOSITO DB 621 PG 309 PC 6 PG 88
- 31 DENNIS LIVINGSTON BRENDA LIVINGSTON DB 153 PG 670 PC 6 PG 82

EXISTING TRAFFIC SIGNAL
CONCRETE SIDEWALK / MEDIAN
NOTES:
SEE SHEET 35 FOR -L- PROFILE
SEE SHEET 41 FOR -Y2- PROFILE


PAVED SHOULDER

Redistribution Calculations


Am Peak hour



MD Peak hour



Pm Peak hour



Intersection Volume Development

INTERSECTION VOLUME DEVELOPMENT

S Providence Road (NC 16) and Rea Road/U-3467 AM PEAK HOUR

Description	S Providence Road (NC 16)				S Providence Road (NC 16)				Rea Road				U-3467			
	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	375	947	0	0	0	447	322	0	344	0	199	0	0	0	0	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	375	947	0	0	0	447	322	0	344	0	199	0	0	0	0	0
2024 Existing PHF	0.92	0.91	0.90	0.90	0.90	0.76	0.86	0.90	0.86	0.90	0.74	0.90	0.90	0.90	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	579	1,130	76	0	32	1,126	599	0	376	164	361	0	78	268	32	0
Redistribution	-579	579	12	0	-32	32	579	0	-176	176	78	0	-78	78	176	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	1,709	108	0	0	1,158	1,178	0	0	540	439	0	0	346	408	0
2029 Background Traffic (No AD) w/o STIP	414	1,046	0	0	0	494	356	0	380	0	220	0	0	0	0	0
Providence and Rea	0	2	7	0	0	10	3	0	0	5	4	0	0	1	6	0
Weddington Road Office Park	0	9	0	0	0	2	1	0	0	4	0	0	0	0	4	0
Approved Development Trips w/ STIP	0	11	7	0	0	12	4	0	0	9	4	0	0	1	10	0
2029 Background Traffic w/ Redistribution w/ STIP	0	1,720	115	0	0	1,170	1,182	0	0	549	443	0	0	347	418	0
Providence and Rea	1	1	0	0	0	3	2	0	4	0	4	1	0	0	0	0
Weddington Road Office Park	0	9	0	0	0	2	1	0	0	0	0	0	0	0	0	0
Approved Development Trips w/o STIP	1	10	0	0	0	5	3	0	8	0	4	1	0	0	0	0
2029 Background Traffic w/o STIP	415	1,056	0	0	0	499	359	0	388	0	224	1	0	0	0	0
Percent Inbound Assignment	0%	0%	20%	0%	0%	10%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	0%	0%	30%	10%	0%
Project Trips w/ STIP	0	0	4	0	0	2	0	0	0	3	5	0	0	15	5	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	20%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	0	2	0	0	0	5	10	0	3	0	0	0	0	0	0	0
2029 Buildout Total w/ STIP	0	1,720	119	0	0	1,172	1,182	0	0	552	448	0	0	362	423	0
2029 Buildout Total w/o STIP	415	1,058	0	0	0	504	369	0	391	0	224	1	0	0	0	0

MIDDAY PEAK HOUR

Description	S Providence Road (NC 16)				S Providence Road (NC 16)				Rea Road				U-3467			
	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	234	702	0	0	0	718	339	0	488	0	362	0	0	0	0	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	234	702	0	0	0	718	339	0	488	0	362	0	0	0	0	0
2024 Existing PHF	0.85	0.95	0.90	0.90	0.90	0.96	0.91	0.90	0.88	0.90	0.85	0.90	0.90	0.90	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%	2%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	304	901	128	0	54	921	332	0	477	353	470	0	93	256	39	0
Redistribution	-304	304	54	0	-54	54	304	0	-477	477	93	0	-93	93	477	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	1,205	182	0	0	975	636	0	0	830	563	0	0	349	516	0
2029 Background Traffic (No AD) w/o STIP	258	775	0	0	0	793	374	0	539	0	400	0	0	0	0	0
Providence and Rea	0	6	3	0	0	5	4	0	0	6	3	0	0	3	9	0
Weddington Road Office Park	0	3	0	0	0	11	5	0	0	2	0	0	0	0	2	0
Approved Development Trips w/ STIP	0	9	3	0	0	16	9	0	0	8	3	0	0	3	11	0
2029 Background Traffic w/ Redistribution w/ STIP	0	1,214	185	0	0	991	645	0	0	838	566	0	0	352	527	0
Providence and Rea	3	3	0	0	0	2	1	0	3	0	3	3	0	0	0	0
Weddington Road Office Park	0	3	0	0	0	11	5	0	2	0	0	0	0	0	0	0
Approved Development Trips w/o STIP	3	6	0	0	0	13	6	0	5	0	3	3	0	0	0	0
2029 Background Traffic w/o STIP	261	781	0	0	0	806	380	0	544	0	403	3	0	0	0	0
Percent Inbound Assignment	0%	0%	20%	0%	0%	10%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	0%	0%	30%	10%	0%
Project Trips w/ STIP	0	0	9	0	0	5	0	0	0	9	3	0	0	8	3	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	20%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	0	5	0	0	0	3	5	0	9	0	0	0	0	0	0	0
2029 Buildout Total w/ STIP	0	1,214	194	0	0	996	645	0	0	847	569	0	0	360	530	0
2029 Buildout Total w/o STIP	261	786	0	0	0	809	385	0	553	0	403	3	0	0	0	0

PM PEAK HOUR

	S Providence Road (NC 16)				S Providence Road (NC 16)				Rea Road				U-3467			
Description	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	203	779	0	0	0	645	544	0	575	0	371	0	0	0	0	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	203	779	0	0	0	645	544	0	575	0	371	0	0	0	0	0
2024 Existing PHF	0.86	0.96	0.90	0.90	0.90	0.94	0.89	0.90	0.94	0.90	0.87	0.90	0.90	0.90	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	361	1,126	78	0	32	1,130	376	0	599	268	579	0	77	164	32	0
Redistribution	-361	361	32	0	-32	32	361	0	-599	599	77	0	-77	77	599	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	1,487	110	0	0	1,162	737	0	0	867	656	0	0	241	631	0
2029 Background Traffic (No AD) w/o STIP	224	860	0	0	0	712	601	0	635	0	410	0	0	0	0	0
Providence and Rea	0	8	4	0	0	6	5	0	0	7	3	0	0	4	10	0
Weddington Road Office Park	0	3	0	0	0	8	7	0	0	2	0	0	0	0	2	0
Approved Development Trips w/ STIP	0	11	4	0	0	14	12	0	0	9	3	0	0	4	12	0
2029 Background Traffic w/ Redistribution w/ STIP	0	1,498	114	0	0	1,176	749	0	0	876	659	0	0	245	643	0
Providence and Rea	4	4	0	0	0	2	1	0	3	0	3	4	0	0	0	0
Weddington Road Office Park	0	3	0	0	0	8	7	0	2	0	0	0	0	0	0	0
Approved Development Trips w/o STIP	4	7	0	0	0	10	8	0	3	0	3	4	0	0	0	0
2029 Background Traffic w/o STIP	228	867	0	0	0	722	609	0	640	0	413	4	0	0	0	0
Percent Inbound Assignment	0%	0%	20%	0%	0%	10%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	0%	0%	30%	10%	0%
Project Trips w/ STIP	0	0	10	0	0	5	0	0	0	11	3	0	0	9	3	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	20%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	0	5	0	0	0	3	3	6	11	0	0	0	0	0	0	0
2029 Buildout Total w/ STIP	0	1,498	124	0	0	1,181	749	0	0	887	662	0	0	254	646	0
2029 Buildout Total w/o STIP	228	872	0	0	0	725	615	0	651	0	413	4	0	0	0	0

INTERSECTION VOLUME DEVELOPMENT

**Cox Road and Weddington Road (NC 84)
AM PEAK HOUR**

Description	Northbound				Cox Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	0	0	0	0	120	0	8	0	8	390	0	0	0	710	106	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	0	0	0	0	120	0	8	0	8	390	0	0	0	710	106	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.79	0.90	0.50	0.90	0.67	0.84	0.90	0.90	0.90	0.81	0.78	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	3%	2%	38%	2%	13%	2%	2%	2%	2%	2%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	3%	2%	38%	2%	13%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #2	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	0	0	0	0	67	0	26	0	10	595	0	0	0	746	32	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	0	0	0	67	0	26	0	10	595	0	0	0	746	32	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	132	0	9	0	9	431	0	0	0	784	117	0
Providence and Rea	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w/ STIP	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
2029 Background Traffic w/ Redistribution w/ STIP	0	0	0	0	67	0	26	0	10	598	0	0	0	764	32	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	10	0	0	0	20	0	0
2029 Background Traffic w/o STIP	0	0	0	0	132	0	9	0	9	441	0	0	0	804	117	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	5%	0%
Project Trips w/ STIP	0	0	0	0	1	0	0	0	0	3	0	0	0	10	3	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	60%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	60%	5%	0%
Project Trips w/o STIP	0	0	0	0	1	0	0	0	0	10	0	0	0	29	2	0
2029 Buildout Total w/ STIP	0	0	0	0	68	0	26	0	10	601	0	0	0	774	35	0
2029 Buildout Total w/o STIP	0	0	0	0	133	0	9	0	9	451	0	0	0	833	119	0

MIDDAY PEAK HOUR

Description	Northbound				Cox Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	0	0	0	0	45	0	6	0	15	799	0	0	0	508	93	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	0	0	0	0	45	0	6	0	15	799	0	0	0	508	93	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.66	0.90	0.38	0.90	0.63	0.91	0.90	0.90	0.90	0.81	0.55	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	7%	2%	2%	2%	2%	5%	3%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	7%	2%	2%	2%	2%	5%	3%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #2	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	0	0	0	0	65	0	7	0	19	738	0	0	0	469	134	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	0	0	0	65	0	7	0	19	738	0	0	0	469	134	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	80	0	7	0	17	882	0	0	0	561	103	0
Providence and Rea	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w/ STIP	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
2029 Background Traffic w/ Redistribution w/ STIP	0	0	0	0	65	0	7	0	19	760	0	0	0	476	134	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	25	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	80	0	7	0	17	907	0	0	0	574	103	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	5%	0%
Project Trips w/ STIP	0	0	0	0	2	0	0	0	0	9	0	0	0	5	2	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	60%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	60%	5%	0%
Project Trips w/o STIP	0	0	0	0	2	0	0	0	0	28	0	0	0	16	1	0
2029 Buildout Total w/ STIP	0	0	0	0	67	0	7	0	19	769	0	0	0	481	136	0
2029 Buildout Total w/o STIP	0	0	0	0	82	0	7	0	17	935	0	0	0	590	104	0

PM PEAK HOUR

Description	Northbound				Cox Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	0	0	0	0	58	0	12	0	22	809	0	0	0	557	39	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	0	0	0	0	58	0	12	0	22	809	0	0	0	557	39	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.73	0.90	0.60	0.90	0.69	0.94	0.90	0.90	0.90	0.87	0.75	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	3%	2%	8%	2%	2%	2%	2%	2%	2%	4%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	3%	2%	8%	2%	2%	2%	2%	2%	2%	4%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #2	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w/ STIP	0	0	0	0	31	0	11	0	29	745	0	0	0	596	64	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w/ Redistribution w/ STIP	0	0	0	0	31	0	11	0	29	745	0	0	0	596	64	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	64	0	13	0	24	893	0	0	0	615	43	0
Providence and Rea	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	1	18	0	0	0	6	0	0
Approved Development Trips w/ STIP	0	0	0	0	0	0	0	0	1	18	0	0	0	6	0	0
2029 Background Traffic w/ Redistribution w/ STIP	0	0	0	0	31	0	11	0	30	763	0	0	0	602	64	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	1	18	0	0	0	6	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	1	22	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	64	0	13	0	25	915	0	0	0	628	43	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	5%	0%
Project Trips w/ STIP	0	0	0	0	2	0	0	0	0	11	0	0	0	6	3	0
Percent Inbound Assignment	0%	0%	0%	0%	5%	0%	0%	0%	0%	60%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	60%	5%	0%
Project Trips w/o STIP	0	0	0	0	3	0	0	0	0	33	0	0	0	18	2	0
2029 Buildout Total w/ STIP	0	0	0	0	33	0	11	0	30	774	0	0	0	608	67	0
2029 Buildout Total w/o STIP	0	0	0	0	67	0	13	0	25	948	0	0	0	646	45	0

INTERSECTION VOLUME DEVELOPMENT

Twelve Mile Creek Road and Weddington Road (NC 84) AM PEAK HOUR

Description	Twelve Mile Creek Road Northbound				Twelve Mile Creek Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	210	74	134	0	233	87	116	0	78	416	59	0	39	512	88	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	210	74	134	0	233	87	116	0	78	416	59	0	39	512	88	0
2024 Existing PHF	0.88	0.54	0.51	0.90	0.53	0.68	0.56	0.90	0.56	0.74	0.82	0.90	0.75	0.84	0.76	0.90
2029 Background PHF	0.88	0.54	0.51	0.90	0.53	0.68	0.57	0.90	0.57	0.74	0.82	0.90	0.75	0.84	0.76	0.90
2029 Build PHF	0.88	0.54	0.51	0.90	0.53	0.68	0.57	0.90	0.57	0.74	0.82	0.90	0.75	0.84	0.76	0.90
2024 Existing Heavy Vehicle's	2%	2%	3%	2%	4%	2%	2%	2%	2%	3%	3%	2%	5%	3%	7%	2%
Future Heavy Vehicle %	2%	2%	3%	2%	4%	2%	2%	2%	2%	3%	3%	2%	5%	3%	7%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor K3	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108
2029 Background Traffic (No AD) w STIP	129	23	79	0	82	46	167	0	87	841	139	0	105	1,049	53	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	129	23	79	0	82	46	167	0	87	841	139	0	105	1,049	53	0
2029 Background Traffic (No AD) w/o STIP	232	83	148	0	257	96	128	0	86	459	65	0	43	565	97	0
Providence and Rea	1	0	0	0	0	0	0	0	1	5	1	0	0	1	0	0
Weddington Road Office Park	4	0	0	0	0	0	3	0	1	2	0	0	0	11	0	0
Approved Development Trips w STIP	5	0	0	0	0	0	3	0	2	7	1	0	0	12	0	0
2029 Background Traffic w Redistribution w STIP	134	23	79	0	82	46	170	0	89	848	140	0	105	1,061	53	0
Providence and Rea	1	0	0	0	0	0	0	0	1	5	1	0	0	1	0	0
Weddington Road Office Park	4	0	0	0	0	0	3	0	1	2	0	0	0	11	0	0
Approved Development Trips w/o STIP	5	0	0	0	0	0	3	0	2	7	1	0	0	12	0	0
2029 Background Traffic w/o STIP	237	82	148	0	257	96	131	0	88	466	66	0	43	577	97	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	10%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	55%	0%	0%	0%	0%
Project Trips w STIP	2	0	0	0	0	0	1	0	2	9	4	25	0	3	0	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	0%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	0%	0%	0%	0%	0%
Project Trips w/o STIP	2	0	0	0	0	0	1	0	2	10	3	0	0	3	0	0
2029 Buildout Total w STIP	136	23	79	0	82	46	171	0	91	857	144	29	105	1,064	53	0
2029 Buildout Total w/o STIP	239	82	148	0	257	96	132	0	90	476	71	0	43	580	97	0

MIDDAY PEAK HOUR

Description	Twelve Mile Creek Road Northbound				Twelve Mile Creek Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	120	76	57	0	90	64	51	0	84	645	106	0	75	435	124	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	120	76	57	0	90	64	51	0	84	645	106	0	75	435	124	0
2024 Existing PHF	0.83	0.70	0.71	0.90	0.78	0.57	0.46	0.90	0.72	0.86	0.91	0.90	0.75	0.85	0.74	0.90
2029 Background PHF	0.83	0.70	0.71	0.90	0.78	0.57	0.48	0.90	0.72	0.86	0.91	0.90	0.75	0.85	0.74	0.90
2029 Build PHF	0.82	0.70	0.71	0.90	0.78	0.57	0.49	0.90	0.73	0.86	0.91	0.90	0.75	0.85	0.74	0.90
2024 Existing Heavy Vehicle's	3%	4%	5%	2%	2%	3%	2%	2%	2%	4%	2%	2%	3%	4%	5%	2%
Future Heavy Vehicle %	3%	4%	5%	2%	2%	3%	2%	2%	2%	4%	2%	2%	3%	4%	5%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor K3	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	107	156	75	0	127	131	47	0	77	760	95	0	99	513	175	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	107	156	75	0	127	131	47	0	77	760	95	0	99	513	175	0
2029 Background Traffic (No AD) w/o STIP	122	84	63	0	99	71	56	0	93	712	117	0	83	480	137	0
Providence and Rea	1	0	0	0	0	0	1	0	0	2	1	0	0	4	0	0
Weddington Road Office Park	1	0	0	0	0	0	1	0	2	17	3	0	0	5	0	0
Approved Development Trips w STIP	2	0	0	0	0	0	2	0	2	19	4	0	0	9	0	0
2029 Background Traffic w Redistribution w STIP	109	156	75	0	127	131	49	0	79	779	99	0	99	522	175	0
Providence and Rea	1	0	0	0	0	0	1	0	0	2	1	0	0	4	0	0
Weddington Road Office Park	1	0	0	0	0	0	1	0	2	17	3	0	0	5	0	0
Approved Development Trips w/o STIP	2	0	0	0	0	0	2	0	2	19	4	0	0	9	0	0
2029 Background Traffic w/o STIP	134	84	63	0	99	71	58	0	95	731	121	0	83	489	137	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	10%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	55%	0%	0%	0%	0%
Project Trips w STIP	5	0	0	0	0	0	2	0	1	5	3	20	0	9	0	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	0%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	0%	0%	0%	0%	0%
Project Trips w/o STIP	5	0	0	0	0	0	2	0	1	6	3	0	0	8	0	0
2029 Buildout Total w STIP	114	156	75	0	127	131	51	0	80	784	102	20	99	531	175	0
2029 Buildout Total w/o STIP	139	84	63	0	99	71	60	0	96	737	124	0	83	497	137	0

PM PEAK HOUR

	Twelve Mile Creek Road Northbound				Twelve Mile Creek Road Southbound				Weddington Road (NC 84) Eastbound				Weddington Road (NC 84) Westbound			
Description	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Observed Volumes	103	51	85	0	104	102	48	0	30	684	154	0	78	424	56	0
Balanced Volumes	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2024 Existing Traffic	103	51	85	0	104	102	48	0	30	684	154	0	78	424	56	0
2024 Existing PHF	0.83	0.91	0.76	0.90	0.58	0.65	0.52	0.90	0.58	0.93	0.86	0.90	0.89	0.86	0.78	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle's	3%	2%	2%	2%	8%	2%	0%	2%	3%	2%	2%	2%	3%	3%	2%	2%
Future Heavy Vehicle %	3%	2%	2%	2%	8%	2%	0%	2%	3%	2%	2%	2%	3%	3%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor K3	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	142	46	103	0	52	23	88	0	168	1,041	131	0	78	849	81	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	142	46	103	0	52	23	88	0	168	1,041	131	0	78	849	81	0
2029 Background Traffic (No AD) w/o STIP	114	56	94	0	115	113	53	0	33	755	170	0	86	468	62	0
Providence and Rea	1	0	0	0	0	0	1	0	0	3	1	0	0	5	0	0
Weddington Road Office Park	1	0	0	0	0	0	1	0	1	14	3	0	0	4	0	0
Approved Development Trips w STIP	2	0	0	0	0	0	2	0	1	17	4	0	0	9	0	0
2029 Background Traffic w Redistribution w STIP	144	46	103	0	52	23	90	0	169	1,058	135	0	78	858	81	0
Providence and Rea	1	0	0	0	0	0	1	0	0	3	1	0	0	5	0	0
Weddington Road Office Park	1	0	0	0	0	0	1	0	1	14	3	0	0	4	0	0
Approved Development Trips w/o STIP	2	0	0	0	0	0	2	0	1	17	4	0	0	9	0	0
2029 Background Traffic w/o STIP	116	56	94	0	115	113	55	0	34	772	174	0	86	477	62	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	10%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	55%	0%	0%	0%	0%
Project Trips w STIP	5	0	0	0	0	0	3	0	2	8	3	23	0	12	0	0
Percent Inbound Assignment	10%	0%	0%	0%	0%	0%	5%	0%	0%	0%	0%	0%	0%	20%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	5%	20%	10%	0%	0%	0%	0%	0%
Project Trips w/o STIP	5	0	0	0	0	0	3	0	2	6	3	0	0	10	0	0
2029 Background Total w STIP	149	46	103	0	52	23	93	0	171	1,063	138	0	78	870	81	0
2029 Buildout Total w/o STIP	121	56	94	0	115	113	58	0	36	778	177	0	86	487	62	0

INTERSECTION VOLUME DEVELOPMENT

Weddington Road (NC 84) and U-3467 (Future) AM PEAK HOUR

Description	-				Weddington Road (NC 84)				U-3467 (Future)				Weddington Road (NC 84)			
	<u>Northbound</u>				<u>Southbound</u>				<u>Eastbound</u>				<u>Westbound</u>			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	492	0	22	0	22	600	0	0	0	737	605	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	492	0	22	0	22	600	0	0	0	737	605	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	3	0	0	0	0	0	0	0	0	0	18	0
Approved Development Trips w STIP	0	0	0	0	3	0	0	0	0	7	0	0	0	2	18	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	495	0	22	0	22	607	0	0	0	739	623	0
Percent Inbound Assignment	0%	0%	0%	0%	25%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	25%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	25%	10%
Project Trips w STIP	0	0	0	0	4	0	0	0	0	7	0	0	0	20	13	9
2029 Buildout Total w STIP	0	0	0	0	499	0	22	0	22	614	0	0	0	759	636	9

MIDDAY PEAK HOUR

Description	-				Weddington Road (NC 84)				U-3467 (Future)				Weddington Road (NC 84)			
	<u>Northbound</u>				<u>Southbound</u>				<u>Eastbound</u>				<u>Westbound</u>			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	419	0	21	0	22	513	0	0	0	367	300	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	419	0	21	0	22	513	0	0	0	367	300	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	22	0	0	0	0	0	0	0	0	0	7	0
Approved Development Trips w STIP	0	0	0	0	22	0	0	0	0	3	0	0	0	6	7	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	441	0	21	0	22	516	0	0	0	373	307	0
Percent Inbound Assignment	0%	0%	0%	0%	25%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	25%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	25%	10%
Project Trips w STIP	0	0	0	0	11	0	0	0	0	18	0	0	0	11	7	14
2029 Buildout Total w STIP	0	0	0	0	452	0	21	0	22	534	0	0	0	384	314	14

PM PEAK HOUR

Description	-				Weddington Road (NC 84)				U-3467 (Future)				Weddington Road (NC 84)			
	<u>Northbound</u>				<u>Southbound</u>				<u>Eastbound</u>				<u>Westbound</u>			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	602	0	26	0	26	735	0	0	0	599	490	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	602	0	26	0	26	735	0	0	0	599	490	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	18	0	0	0	0	0	0	0	0	0	6	0
Approved Development Trips w STIP	0	0	0	0	18	0	0	0	0	4	0	0	0	7	6	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	620	0	26	0	26	739	0	0	0	606	496	0
Percent Inbound Assignment	0%	0%	0%	0%	25%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	25%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	25%	10%
Project Trips w STIP	0	0	0	0	13	0	0	0	0	21	0	0	0	12	9	17
2029 Buildout Total w STIP	0	0	0	0	633	0	26	0	26	760	0	0	0	618	505	17

INTERSECTION VOLUME DEVELOPMENT

Weddington Road (NC 84) and Access A (RIRO) AM PEAK HOUR

Description	Access A (RIRO)				Access A (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Left	Northbound Through	Right	U-turn	Left	Southbound Through	Right	U-turn	Left	Eastbound Through	Right	U-turn	Left	Westbound Through	Right	U-turn
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	553	0	0	0	838	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.72	0.90	0.90	0.90	0.81	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,092	0	0	0	1,342	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,092	0	0	0	1,342	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	611	0	0	0	925	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	10	0	0	0	20	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,102	0	0	0	1,362	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	10	0	0	0	20	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	621	0	0	0	945	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	70%	0%	0%	25%	5%	0%
Percent Outbound Assignment	0%	0%	70%	0%	0%	0%	15%	0%	0%	10%	0%	0%	0%	65%	0%	0%
Project Trips w STIP	0	0	35	0	0	0	8	0	0	9	11	0	0	34	1	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	10%	7%	48%	0%	22%	0%	2%	0%
Percent Outbound Assignment	48%	0%	22%	0%	2%	0%	10%	0%	0%	0%	0%	0%	0%	7%	0%	0%
Project Trips w/o STIP	22	0	11	0	1	0	6	0	2	1	8	0	4	3	0	0
2029 Buildout Total w STIP	0	0	33	0	0	0	8	0	0	1,111	11	0	0	1,396	1	0
2029 Buildout Total w/o STIP	22	0	11	0	1	0	6	0	2	822	8	0	4	948	0	0

MIDDAY PEAK HOUR

Description	Access A (RIRO)				Access A (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Left	Northbound Through	Right	U-turn	Left	Southbound Through	Right	U-turn	Left	Eastbound Through	Right	U-turn	Left	Westbound Through	Right	U-turn
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	835	0	0	0	606	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.85	0.90	0.90	0.90	0.81	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%	2%	2%	4%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%	2%	2%	4%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	932	0	0	0	667	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	932	0	0	0	667	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	922	0	0	0	669	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	25	0	0	0	13	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	957	0	0	0	680	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	25	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	947	0	0	0	682	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	70%	0%	0%	25%	5%	0%
Percent Outbound Assignment	0%	0%	70%	0%	0%	0%	15%	0%	0%	10%	0%	0%	0%	65%	0%	0%
Project Trips w STIP	0	0	19	0	0	0	4	0	0	12	31	0	0	29	2	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	10%	7%	48%	0%	22%	0%	2%	0%
Percent Outbound Assignment	48%	0%	22%	0%	2%	0%	10%	0%	0%	0%	0%	0%	0%	7%	0%	0%
Project Trips w/o STIP	12	0	6	0	1	0	3	0	5	4	21	0	10	2	1	0
2029 Buildout Total w STIP	0	0	19	0	0	0	4	0	0	969	31	0	0	709	2	0
2029 Buildout Total w/o STIP	12	0	6	0	1	0	3	0	5	951	21	0	10	684	1	0

PM PEAK HOUR

Description	Access A (RIRO)				Access A (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Left	Southbound Through	Right	U-turn	Left	Northbound Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	868	0	0	0	575	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.91	0.90	0.90	0.90	0.83	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,337	0	0	0	1,089	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,337	0	0	0	1,089	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	958	0	0	0	635	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	18	0	0	0	6	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	22	0	0	0	13	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,359	0	0	0	1,102	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	18	0	0	0	6	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	22	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	980	0	0	0	648	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	70%	0%	0%	25%	5%	0%
Percent Outbound Assignment	0%	0%	70%	0%	0%	0%	15%	0%	0%	10%	0%	0%	0%	65%	0%	0%
Project Trips w STIP	0	0	21	0	0	0	5	0	0	14	37	0	0	33	3	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	10%	7%	48%	0%	22%	0%	2%	0%
Percent Outbound Assignment	48%	0%	22%	0%	2%	0%	10%	0%	0%	0%	0%	0%	0%	7%	0%	0%
Project Trips w/o STIP	15	0	6	0	1	0	3	0	6	4	26	0	12	2	1	0
2029 Buildout Total w STIP	0	0	21	0	0	0	5	0	0	1,373	37	0	0	1,135	3	0
2029 Buildout Total w/o STIP	15	0	6	0	1	0	3	0	6	984	26	0	12	650	1	0

INTERSECTION VOLUME DEVELOPMENT

Weddington Road (NC 84) and Access B (RIRO) AM PEAK HOUR

Description	Access B (RIRO)				Access B (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Northbound		U-turn		Southbound		U-turn		Eastbound		U-turn		Westbound		U-turn	
	Left	Through			Left	Through			Left	Through			Left	Through		
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	553	0	0	0	838	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.72	0.90	0.90	0.90	0.81	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%	2%	3%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,092	0	0	0	1,342	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,092	0	0	0	1,342	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	611	0	0	0	925	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	10	0	0	0	20	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,102	0	0	0	1,362	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	0	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	3	0	0	0	18	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	10	0	0	0	20	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	621	0	0	0	945	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	10%	0%	0%	30%	15%	0%
Percent Outbound Assignment	0%	0%	10%	0%	0%	0%	5%	0%	0%	80%	0%	0%	0%	55%	0%	0%
Project Trips w STIP	0	0	4	0	0	0	3	0	0	40	2	0	0	32	3	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	3%	0%	4%	0%	6%	24%	5%	0%
Percent Outbound Assignment	4%	0%	6%	0%	5%	0%	3%	0%	0%	24%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	2	0	2	0	3	0	1	0	1	12	0	0	1	4	1	0
2029 Buildout Total w STIP	0	0	4	0	0	0	3	0	0	1,142	2	0	0	1,394	3	0
2029 Buildout Total w/o STIP	2	0	2	0	3	0	1	0	1	633	0	0	1	949	1	0

MIDDAY PEAK HOUR

Description	Access B (RIRO)				Access B (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Northbound		U-turn		Southbound		U-turn		Eastbound		U-turn		Westbound		U-turn	
	Left	Through			Left	Through			Left	Through			Left	Through		
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	835	0	0	0	606	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.85	0.90	0.90	0.90	0.81	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%	2%	2%	4%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%	2%	2%	4%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	932	0	0	0	667	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	932	0	0	0	667	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	922	0	0	0	669	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	25	0	0	0	13	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	957	0	0	0	680	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	0	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	22	0	0	0	7	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	25	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	947	0	0	0	682	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	10%	0%	0%	30%	15%	0%
Percent Outbound Assignment	0%	0%	10%	0%	0%	0%	5%	0%	0%	80%	0%	0%	0%	55%	0%	0%
Project Trips w STIP	0	0	2	0	0	0	2	0	0	27	4	0	0	28	8	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	3%	0%	4%	0%	6%	24%	5%	0%
Percent Outbound Assignment	4%	0%	6%	0%	5%	0%	3%	0%	0%	24%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	1	0	2	0	1	0	1	0	2	7	2	0	2	11	2	0
2029 Buildout Total w STIP	0	0	2	0	0	0	2	0	0	964	4	0	0	708	8	0
2029 Buildout Total w/o STIP	1	0	2	0	1	0	1	0	2	954	2	0	2	693	2	0

PM PEAK HOUR

Description	Access B (RIRO)				Access B (RIRO)				Weddington Road (NC 84)				Weddington Road (NC 84)			
	Southbound		U-turn		Southbound		U-turn		Eastbound		U-turn		Westbound		U-turn	
	Left	Through			Left	Through			Left	Through			Left	Through		
2024 Existing Traffic	0	0	0	0	0	0	0	0	0	868	0	0	0	575	0	0
2024 Existing PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.91	0.90	0.90	0.90	0.83	0.90	0.90
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
2024 Existing Heavy Vehicle%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%
Future Heavy Vehicle %	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	3%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,337	0	0	0	1,089	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,337	0	0	0	1,089	0	0
2029 Background Traffic (No AD) w/o STIP	0	0	0	0	0	0	0	0	0	958	0	0	0	635	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	18	0	0	0	6	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	22	0	0	0	13	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,359	0	0	0	1,102	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	18	0	0	0	6	0	0
Approved Development Trips w/o STIP	0	0	0	0	0	0	0	0	0	22	0	0	0	13	0	0
2029 Background Traffic w/o STIP	0	0	0	0	0	0	0	0	0	980	0	0	0	648	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	10%	10%	0%	0%	30%	15%	0%
Percent Outbound Assignment	0%	0%	10%	0%	0%	0%	5%	0%	0%	80%	0%	0%	0%	55%	0%	0%
Project Trips w STIP	0	0	3	0	0	0	2	0	0	30	5	0	0	34	9	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	3%	0%	4%	0%	6%	24%	5%	0%
Percent Outbound Assignment	4%	0%	6%	0%	5%	0%	3%	0%	0%	24%	0%	0%	0%	0%	0%	0%
Project Trips w/o STIP	1	0	2	0	2	0	1	0	2	7	2	0	2	13	3	0
2029 Buildout Total w STIP	0	0	3	0	0	0	2	0	0	1,389	5	0	0	1,136	9	0
2029 Buildout Total w/o STIP	1	0	2	0	2	0	1	0	2	987	2	0	2	661	3	0

INTERSECTION VOLUME DEVELOPMENT**S Providence Road (NC 16) and Northern U-turn bulb
AM PEAK HOUR**

Description	S Providence Road (NC 16)				S Providence Road (NC 16)				-				-			
	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,538	0	0	0	1,757	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	579	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,538	0	579	0	1,757	0	0	0	0	0	0	0	0	0	0
Providence and Rea	0	5	0	1	0	12	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	13	0	0	0	3	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	18	0	1	0	15	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,556	0	580	0	1,772	0	0	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	5	0	0	0	2	0	0	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,561	0	580	0	1,774	0	0	0	0	0	0	0	0	0	0

MIDDAY PEAK HOUR

Description	S Providence Road (NC 16)				S Providence Road (NC 16)				-				-			
	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,417	0	0	0	1,307	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	304	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,417	0	304	0	1,307	0	0	0	0	0	0	0	0	0	0
Providence and Rea	0	12	0	3	0	6	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	5	0	0	0	16	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	17	0	3	0	22	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,434	0	307	0	1,329	0	0	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	3	0	0	0	5	0	0	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,437	0	307	0	1,334	0	0	0	0	0	0	0	0	0	0

PM PEAK HOUR

Description	S Providence Road (NC 16)				S Providence Road (NC 16)				-				-			
	Northbound				Southbound				Eastbound				Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,757	0	0	0	1,538	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	361	0	0	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,757	0	361	0	1,538	0	0	0	0	0	0	0	0	0	0
Providence and Rea	0	7	0	4	0	7	0	0	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	5	0	0	0	15	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	12	0	4	0	22	0	0	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,769	0	365	0	1,560	0	0	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	3	0	0	0	5	0	0	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,772	0	365	0	1,565	0	0	0	0	0	0	0	0	0	0

INTERSECTION VOLUME DEVELOPMENT

S Providence Road (NC 16) and Southern U-turn bulb AM PEAK HOUR

Description	S Providence Road (NC 16) Northbound				S Providence Road (NC 16) Southbound				- Eastbound				- Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,785	0	0	0	1,565	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	0	0	0	0	32	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,785	0	0	0	1,565	0	32	0	0	0	0	0	0	0	0
Providence and Rea	0	2	0	0	0	7	0	7	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	9	0	0	0	2	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	11	0	0	0	9	0	7	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,796	0	0	0	1,574	0	39	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	2	0	0	0	5	0	2	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,798	0	0	0	1,579	0	41	0	0	0	0	0	0	0	0

MIDDAY PEAK HOUR

Description	S Providence Road (NC 16) Northbound				S Providence Road (NC 16) Southbound				- Eastbound				- Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,333	0	0	0	1,484	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	0	0	0	0	54	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,333	0	0	0	1,484	0	54	0	0	0	0	0	0	0	0
Providence and Rea	0	6	0	0	0	5	0	3	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	3	0	0	0	11	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	9	0	0	0	16	0	3	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,342	0	0	0	1,500	0	57	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	4	0	0	0	3	0	5	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,346	0	0	0	1,503	0	62	0	0	0	0	0	0	0	0

PM PEAK HOUR

Description	S Providence Road (NC 16) Northbound				S Providence Road (NC 16) Southbound				- Eastbound				- Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	1,565	0	0	0	1,786	0	0	0	0	0	0	0	0	0	0
Redistribution	0	0	0	0	0	0	0	32	0	0	0	0	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	1,565	0	0	0	1,786	0	32	0	0	0	0	0	0	0	0
Providence and Rea	0	8	0	0	0	5	0	4	0	0	0	0	0	0	0	0
Weddington Road Office Park	0	3	0	0	0	8	0	0	0	0	0	0	0	0	0	0
Approved Development Trips w STIP	0	11	0	0	0	13	0	4	0	0	0	0	0	0	0	0
2029 Background Traffic w Redistribution w STIP	0	1,576	0	0	0	1,799	0	36	0	0	0	0	0	0	0	0
Percent Inbound Assignment	0%	10%	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	10%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Project Trips w STIP	0	5	0	0	0	3	0	5	0	0	0	0	0	0	0	0
2029 Buildout Total w STIP	0	1,581	0	0	0	1,802	0	41	0	0	0	0	0	0	0	0

INTERSECTION VOLUME DEVELOPMENT

Rea Road and Western U-turn Bulb AM PEAK HOUR

Description	Northbound				Southbound				Rea Road Eastbound				Rea Road Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	901	0	0	0	1,446	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	78
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	901	0	0	0	1,446	0	78
Providence and Rea	0	0	0	0	0	0	0	0	0	9	0	0	0	4	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	4	0	0	0	1	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	13	0	0	0	5	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	914	0	0	0	1,451	0	78
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	10%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	3	0	0	0	10	0	5
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	917	0	0	0	1,461	0	83

MIDDAY PEAK HOUR

Description	Northbound				Southbound				Rea Road Eastbound				Rea Road Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,300	0	0	0	892	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	93
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,300	0	0	0	892	0	93
Providence and Rea	0	0	0	0	0	0	0	0	0	9	0	0	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	2	0	0	0	5	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	11	0	0	0	12	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,311	0	0	0	904	0	93
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	10%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	9	0	0	0	5	0	3
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	1,320	0	0	0	909	0	96

PM PEAK HOUR

Description	Northbound				Southbound				Rea Road Eastbound				Rea Road Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	1,446	0	0	0	901	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	77
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,446	0	0	0	901	0	77
Providence and Rea	0	0	0	0	0	0	0	0	0	10	0	0	0	8	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	2	0	0	0	7	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	12	0	0	0	15	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	1,458	0	0	0	916	0	77
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	20%	0%	10%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	11	0	0	0	6	0	3
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	1,469	0	0	0	922	0	80

INTERSECTION VOLUME DEVELOPMENT

Rea Road Extension and Eastern U-turn Bulb AM PEAK HOUR

Description	Northbound				Southbound				Rea Road Extension Eastbound				Rea Road Extension Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	272	0	0	0	378	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	376	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	272	0	376	0	378	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	7	0	5	0	2	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	7	0	9	0	2	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	279	0	385	0	380	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	7	0	0	0	20	0	0
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	286	0	385	0	400	0	0

MIDDAY PEAK HOUR


Description	Northbound				Southbound				Rea Road Extension Eastbound				Rea Road Extension Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	535	0	0	0	388	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	477	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	535	0	477	0	388	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	3	0	6	0	6	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	3	0	8	0	6	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	538	0	485	0	394	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	18	0	0	0	11	0	0
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	556	0	485	0	405	0	0

PM PEAK HOUR

Description	Northbound				Southbound				Rea Road Extension Eastbound				Rea Road Extension Westbound			
	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn	Left	Through	Right	U-turn
Future PHF Future Heavy Vehicle %	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Annual Growth Rate	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
Growth Factor #1	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104	1.104
2029 Background Traffic (No AD) w STIP	0	0	0	0	0	0	0	0	0	378	0	0	0	273	0	0
Redistribution	0	0	0	0	0	0	0	0	0	0	0	599	0	0	0	0
2029 Background Traffic (No AD) w Redistribution w STIP	0	0	0	0	0	0	0	0	0	378	0	599	0	273	0	0
Providence and Rea	0	0	0	0	0	0	0	0	0	4	0	7	0	7	0	0
Weddington Road Office Park	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0
Approved Development Trips w STIP	0	0	0	0	0	0	0	0	0	4	0	9	0	7	0	0
2029 Background Traffic w Redistribution w STIP	0	0	0	0	0	0	0	0	0	382	0	608	0	280	0	0
Percent Inbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%	0%	0%	0%	0%
Percent Outbound Assignment	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	40%	0%	0%
Project Trips w STIP	0	0	0	0	0	0	0	0	0	21	0	0	0	12	0	0
2029 Buildout Total w STIP	0	0	0	0	0	0	0	0	0	403	0	608	0	292	0	0

Signal Plans


PHASING DIAGRAM



SIGNAL FACE	PHASE			
	02+5	02+6	04	FLASH
21,22	G	G	R	Y
41	R	R	G	R
42	R	R	G	R
51,52	R	R	R	R
61	R	G	R	Y
62	R	G	R	Y

Signal Face I.D.

Denotes L.E.D.



2070L LOOP & DETECTOR INSTALLATION

INDUCTIVE LOOPS				DETECTOR PROGRAMMING			
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTENSION
2A/S1	6X6	300	5	Y	2	Y	Y
2B/S2	6X6	300	5	Y	2	Y	Y
4A	6X40	0	2-4-2	-	4	Y	Y
5A	6X40	0	2-4-2	Y	5	Y	Y
5B	6X40	0	2-4-2	Y	5	Y	Y
5C	6X40	0	2-4-2	-	5	Y	Y
6A/S3	6X6	300	5	Y	6	Y	Y
6B	6X40	0	2-4-2	Y	6	Y	Y


3 Phase
Fully Actuated
(NC 16 - Providence Rd CLS)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated July 2006 and "Standard Specifications for Roads and Structures" dated July 2006.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Enable Backup Protect for phase 2 to allow the controller to clear from phase 2+6 to phase 2+5 by progressing through an all red display.
- Reposition existing signal heads numbered 21, 22, 52, 61 and 62.
- Set all detector units to presence mode.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Closed loop system data: Controller Asset #1694.

PHASING DIAGRAM DETECTION LEGEND

- DETECTED MOVEMENT
- UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- PEDESTRIAN MOVEMENT



2070L TIMING CHART

FEATURE	PHASE			
	2	4	5	6
Min Green 1 *	12	7	7	12
Extension 1 *	6.0	2.0	2.0	6.0
Max Green 1 *	60	20	20	60
Yellow Clearance	4.4	4.7	3.0	4.6
Red Clearance	2.0	1.7	3.6	1.9
Red Revert	5.0	2.0	2.0	2.0
Walk 1 *	-	-	-	-
Don't Walk 1	-	-	-	-
Seconds Per Actuation *	1.5	-	-	2.5
Max Variable Initial *	34	-	-	34
Time Before Reduction *	15	-	-	15
Time To Reduce *	30	-	-	30
Minimum Gap	3.0	-	-	3.0
Recall Mode	MIN RECALL	-	-	MIN RECALL
Vehicle Call Memory	YELLOW	-	-	YELLOW
Dual Entry	-	-	-	-
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

- | PROPOSED | EXISTING |
|----------|----------|
| | |
| | N/A |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | N/A |
| | |


Final Signal

	NC 16 (Providence Rd) at SR 2948 (Rea Rd)		
	Division 10	Union County	
	PLAN DATE: July 2007	REVIEWED BY: N.M. Rodevick	
	PREPARED BY: T.R. Terrell	REVIEWED BY: S.T. Franklin	
SCALE: 0 40 1"=40'	REVISIONS	INIT.	DATE
SIG. INVENTORY NO. 10-1694			

HNTB

HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609

PHASING DIAGRAM




PHASING DIAGRAM DETECTION LEGEND

- DETECTED MOVEMENT
- UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- PEDESTRIAN MOVEMENT

SIGNAL FACE	PHASE					
	01+5	01+6	02+5	02+6	04+7	04+8
11						
21, 22	R	R	G	G	R	Y
41	R	R	R	R	G	R
42	R	R	R	R	G	R
51						
61, 62	R	G	R	G	R	Y
81, 82	R	R	R	R	G	R

SIGNAL FACE I.D.

All Heads L.E.D.



OASIS 2070 LOOP & DETECTOR INSTALLATION CHART										
INDUCTIVE LOOPS					DETECTOR PROGRAMMING					
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME	DELAY TIME
1A	6X60	+5	2-4-2	-	1	Y	Y	-	-	15
2A	6X6	300	5	-	2	Y	Y	-	-	3
4A	6X6	300	5	-	4	-	Y	-	3.1	-
4B	6X60	+5	2-4-2	-	4	Y	Y	-	-	5
5A	6X60	+5	2-4-2	-	5	Y	Y	-	-	15
6A	6X6	300	5	-	2	Y	Y	-	-	3
8A	6X6	300	5	-	8	-	Y	-	3.1	-
8B	6X60	+5	2-4-2	-	8	Y	Y	-	-	10

6 Phase
Fully Actuated
Isolated


NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Omit phase 7 during phase 8 on.
- Phase 1 and/or phase 5 may be lagged.
- Reposition existing signal heads numbered 22 and 62.
- Set all detector units to presence mode.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Pavement markings are existing.

OASIS 2070 TIMING CHART							
FEATURE	PHASE						
	1	2	4	5	6	7	8
Min Green 1 *	7	12	7	7	12	7	7
Extension 1 *	1.0	6.0	1.0	1.0	6.0	1.0	1.0
Max Green 1 *	15	90	20	15	90	15	20
Yellow Clearance	3.0	4.7	4.7	3.0	4.7	3.0	4.7
Red Clearance	1.9	1.5	1.5	2.1	1.5	1.9	1.5
Red Revert	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Walk 1 *	-	-	-	-	-	-	-
Don't Walk 1	-	-	-	-	-	-	-
Seconds Per Actuation *	-	2.5	-	-	2.5	-	-
Max Variable Initial *	-	34	-	-	34	-	-
Time Before Reduction *	-	15	-	-	15	-	-
Time To Reduce *	-	30	-	-	30	-	-
Minimum Gap	-	3.0	-	-	3.0	-	-
Recall Mode	-	MIN RECALL	-	-	MIN RECALL	-	-
Vehicle Call Memory	-	YELLOW	-	-	YELLOW	-	-
Dual Entry	-	-	ON	-	-	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown.
Min Green for all other phases should not be lower than 4 seconds.

Install new base-mounted cabinet on existing foundation.



This plan supersedes the one signed and sealed on 5/9/2014.

LEGEND	
PROPOSED	EXISTING

Signal Upgrade

















	NC 84 (Weddington Road) at SR 1341(Twelve Mile Creek Road)		
	Division 10 Union County Weddington		
	PLAN DATE: November 2022	REVIEWED BY: T.J. Williams	
	PREPARED BY: X. Han	REVIEWED BY:	
750 N. Greenfield Pkwy, Garner, NC 27529		DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
SCALE: 0 30 1"=30'		DATE: 11/02/2022	

Intersection Capacity Analysis

2024 Existing Conditions

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2024 Existing AM








							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations			 	 			
Traffic Volume (vph)	344	199	375	947	4	447	322
Future Volume (vph)	344	199	375	947	4	447	322
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	11	12	11	12	12
Grade (%)	-2%			1%		-1%	
Storage Length (ft)	0	0	425		325		0
Storage Lanes	1	1	2		1		1
Taper Length (ft)	0		100		75		
Lane Util. Factor	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt		0.850					0.850
Flt Protected	0.950		0.950		0.950		
Satd. Flow (prot)	1728	1546	3302	3522	1719	1836	1591
Flt Permitted	0.950		0.950		0.275		
Satd. Flow (perm)	1728	1546	3302	3522	498	1836	1591
Right Turn on Red		No					No
Satd. Flow (RTOR)							
Link Speed (mph)	45			45		45	
Link Distance (ft)	1527			1308		1378	
Travel Time (s)	23.1			19.8		20.9	
Peak Hour Factor	0.86	0.74	0.92	0.91	0.90	0.76	0.86
Heavy Vehicles (%)	2%	2%	2%	2%	2%	4%	2%
Adj. Flow (vph)	400	269	408	1041	4	588	374
Shared Lane Traffic (%)							
Lane Group Flow (vph)	400	269	408	1041	4	588	374
Turn Type	Prot	pm+ov	Prot	NA	Perm	NA	pm+ov
Protected Phases	4	5	5	2		6	4
Permitted Phases		4			6		6
Detector Phase	4	5	5	2	6	6	4
Switch Phase							
Minimum Initial (s)	7.0	7.0	7.0	12.0	12.0	12.0	7.0
Minimum Split (s)	13.4	13.6	13.6	18.4	18.5	18.5	13.4
Total Split (s)	30.0	19.0	19.0	60.0	41.0	41.0	30.0
Total Split (%)	33.3%	21.1%	21.1%	66.7%	45.6%	45.6%	33.3%
Maximum Green (s)	23.6	12.4	12.4	53.6	34.5	34.5	23.6
Yellow Time (s)	4.7	3.0	3.0	4.4	4.6	4.6	4.7
All-Red Time (s)	1.7	3.6	3.6	2.0	1.9	1.9	1.7
Lost Time Adjust (s)	-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.4
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag		Lead	Lead		Lag	Lag	
Lead-Lag Optimize?							
Vehicle Extension (s)	2.0	2.0	2.0	6.0	6.0	6.0	2.0
Minimum Gap (s)	2.0	2.0	2.0	3.0	3.0	3.0	2.0
Time Before Reduce (s)	0.0	0.0	0.0	15.0	15.0	15.0	0.0
Time To Reduce (s)	0.0	0.0	0.0	30.0	30.0	30.0	0.0
Recall Mode	None	None	None	C-Max	C-Max	C-Max	None
Act Effect Green (s)	23.7	42.7	14.0	56.3	37.3	37.3	66.0
Actuated g/C Ratio	0.26	0.47	0.16	0.63	0.41	0.41	0.73
v/c Ratio	0.88	0.37	0.80	0.47	0.02	0.77	0.32

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA

2024 Existing AM

							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay	53.6	16.5	49.6	10.1	16.8	31.8	5.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	53.6	16.5	49.6	10.1	16.8	31.8	5.1
LOS	D	B	D	B	B	C	A
Approach Delay	38.7			21.2		21.4	
Approach LOS	D			C		C	
Queue Length 50th (ft)	213	90	117	156	1	289	61
Queue Length 95th (ft)	#338	115	#184	202	8	326	90
Internal Link Dist (ft)	1447			1228		1298	
Turn Bay Length (ft)			425		325		
Base Capacity (vph)	480	735	520	2204	206	761	1190
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.83	0.37	0.78	0.47	0.02	0.77	0.31


Intersection Summary	
Area Type:	Other
Cycle Length: 90	
Actuated Cycle Length: 90	
Offset: 29 (32%), Referenced to phase 2:NBT and 6:SBTU, Start of Green	
Natural Cycle: 75	
Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.88	
Intersection Signal Delay: 25.0	Intersection LOS: C
Intersection Capacity Utilization 67.7%	ICU Level of Service C
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2024 Existing AM



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	8	390	710	106	120	8
Future Volume (vph)	8	390	710	106	120	8
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.982		0.987	
Flt Protected	0.950				0.957	
Satd. Flow (prot)	1491	1801	1707	0	1575	0
Flt Permitted	0.950				0.957	
Satd. Flow (perm)	1491	1801	1707	0	1575	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.67	0.84	0.81	0.78	0.79	0.50
Heavy Vehicles (%)	13%	2%	2%	2%	3%	38%
Adj. Flow (vph)	12	464	877	136	152	16
Shared Lane Traffic (%)						
Lane Group Flow (vph)	12	464	1013	0	168	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 57.6% ICU Level of Service B

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road



















Deal Lake TIA
2024 Existing AM

Intersection						
Int Delay, s/veh	3.9					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	8	390	710	106	120	8
Future Vol, veh/h	8	390	710	106	120	8
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	67	84	81	78	79	50
Heavy Vehicles, %	13	2	2	2	3	38
Mvmt Flow	12	464	877	136	152	16
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	1013	0	-	0	1433	945
Stage 1	-	-	-	-	945	-
Stage 2	-	-	-	-	488	-
Critical Hdwy	4.23	-	-	-	6.43	6.58
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.317	-	-	-	3.527	3.642
Pot Cap-1 Maneuver	643	-	-	-	~ 147	273
Stage 1	-	-	-	-	376	-
Stage 2	-	-	-	-	615	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	643	-	-	-	~ 144	273
Mov Cap-2 Maneuver	-	-	-	-	270	-
Stage 1	-	-	-	-	369	-
Stage 2	-	-	-	-	615	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.3	0		38		
HCM LOS				E		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	643	-	-	-	270	
HCM Lane V/C Ratio	0.019	-	-	-	0.622	
HCM Control Delay (s)	10.7	-	-	-	38	
HCM Lane LOS	B	-	-	-	E	
HCM 95th %tile Q(veh)	0.1	-	-	-	3.8	
Notes						
-: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon						

Lanes, Volumes, Timings













3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing AM

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	78	416	59	39	512	88	210	74	134	233	87	116
Future Volume (vph)	78	416	59	39	512	88	210	74	134	233	87	116
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.983			0.976			0.944			0.964	
Flt Protected	0.950			0.950				0.982			0.972	
Satd. Flow (prot)	1728	1770	0	1653	1721	0	0	1589	0	0	1627	0
Flt Permitted	0.122			0.114				0.589			0.515	
Satd. Flow (perm)	222	1770	0	198	1721	0	0	953	0	0	862	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.56	0.74	0.82	0.75	0.84	0.76	0.88	0.54	0.51	0.53	0.68	0.56
Heavy Vehicles (%)	2%	3%	3%	5%	3%	7%	2%	2%	3%	4%	2%	2%
Adj. Flow (vph)	139	562	72	52	610	116	239	137	263	440	128	207
Shared Lane Traffic (%)												
Lane Group Flow (vph)	139	634	0	52	726	0	0	639	0	0	775	0
Turn Type	D.P+P	NA		D.P+P	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases	6			2			8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	13.0	39.0		12.0	38.0		49.0	49.0		20.0	69.0	
Total Split (%)	10.8%	32.5%		10.0%	31.7%		40.8%	40.8%		16.7%	57.5%	
Maximum Green (s)	7.9	32.8		7.1	31.8		42.8	42.8		15.1	62.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	40.8	36.3		41.8	33.0			44.0			64.0	
Actuated g/C Ratio	0.34	0.30		0.35	0.28			0.37			0.53	
v/c Ratio	0.80	1.19		0.34	1.53			1.83			1.39	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing AM

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	58.9	138.7		30.1	282.4			409.8			212.6	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay	58.9	138.7		30.1	282.4			409.8			212.6	
LOS	E	F		C	F			F			F	
Approach Delay		124.3			265.5			409.8			212.6	
Approach LOS		F			F			F			F	
Queue Length 50th (ft)	71	~617		25	~789			~748			~802	
Queue Length 95th (ft)	70	#623		44	#931			#473			#611	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	176	535		154	474			350			556	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.79	1.19		0.34	1.53			1.83			1.39	

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 119.8

Natural Cycle: 240

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.83

Intersection Signal Delay: 246.0

Intersection LOS: F

Intersection Capacity Utilization 82.0%

ICU Level of Service E

Analysis Period (min) 15

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

















Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Ø1		Ø2		Ø4	
12 s		39 s		69 s	
Ø5		Ø6		Ø7	
13 s		38 s		20 s	49 s

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2024 Existing MID








							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations			 	 			
Traffic Volume (vph)	488	362	234	702	4	718	339
Future Volume (vph)	488	362	234	702	4	718	339
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	11	12	11	12	12
Grade (%)	-2%			1%		-1%	
Storage Length (ft)	0	0	425		325		0
Storage Lanes	1	1	2		1		1
Taper Length (ft)	0		100		75		
Lane Util. Factor	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt		0.850					0.850
Flt Protected	0.950		0.950		0.950		
Satd. Flow (prot)	1728	1531	3302	3487	1719	1872	1576
Flt Permitted	0.950		0.950		0.371		
Satd. Flow (perm)	1728	1531	3302	3487	671	1872	1576
Right Turn on Red		No					No
Satd. Flow (RTOR)							
Link Speed (mph)	45			45		45	
Link Distance (ft)	1527			1308		1378	
Travel Time (s)	23.1			19.8		20.9	
Peak Hour Factor	0.88	0.85	0.85	0.95	0.90	0.96	0.91
Heavy Vehicles (%)	2%	3%	2%	3%	2%	2%	3%
Adj. Flow (vph)	555	426	275	739	4	748	373
Shared Lane Traffic (%)							
Lane Group Flow (vph)	555	426	275	739	4	748	373
Turn Type	Prot	pm+ov	Prot	NA	Perm	NA	pm+ov
Protected Phases	4	5	5	2		6	4
Permitted Phases		4			6		6
Detector Phase	4	5	5	2	6	6	4
Switch Phase							
Minimum Initial (s)	7.0	7.0	7.0	12.0	12.0	12.0	7.0
Minimum Split (s)	13.4	13.6	13.6	18.4	18.5	18.5	13.4
Total Split (s)	34.0	14.0	14.0	56.0	42.0	42.0	34.0
Total Split (%)	37.8%	15.6%	15.6%	62.2%	46.7%	46.7%	37.8%
Maximum Green (s)	27.6	7.4	7.4	49.6	35.5	35.5	27.6
Yellow Time (s)	4.7	3.0	3.0	4.4	4.6	4.6	4.7
All-Red Time (s)	1.7	3.6	3.6	2.0	1.9	1.9	1.7
Lost Time Adjust (s)	-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.4
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag		Lead	Lead		Lag	Lag	
Lead-Lag Optimize?							
Vehicle Extension (s)	2.0	2.0	2.0	6.0	6.0	6.0	2.0
Minimum Gap (s)	2.0	2.0	2.0	3.0	3.0	3.0	2.0
Time Before Reduce (s)	0.0	0.0	0.0	15.0	15.0	15.0	0.0
Time To Reduce (s)	0.0	0.0	0.0	30.0	30.0	30.0	0.0
Recall Mode	None	None	None	C-Max	C-Max	C-Max	None
Act Effect Green (s)	29.0	43.0	9.0	51.0	37.0	37.0	71.0
Actuated g/C Ratio	0.32	0.48	0.10	0.57	0.41	0.41	0.79
v/c Ratio	1.00	0.58	0.83	0.37	0.01	0.97	0.30

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road


Deal Lake TIA

2024 Existing MID

							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay	70.1	21.0	62.2	11.4	16.0	54.1	3.3
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	70.1	21.0	62.2	11.4	16.0	54.1	3.3
LOS	E	C	E	B	B	D	A
Approach Delay	48.8			25.2		37.2	
Approach LOS	D			C		D	
Queue Length 50th (ft)	312	168	80	113	1	407	44
Queue Length 95th (ft)	#509	241	#132	151	8	#652	70
Internal Link Dist (ft)	1447			1228		1298	
Turn Bay Length (ft)			425		325		
Base Capacity (vph)	556	731	330	1975	275	769	1243
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	1.00	0.58	0.83	0.37	0.01	0.97	0.30


Intersection Summary	
Area Type:	Other
Cycle Length: 90	
Actuated Cycle Length: 90	
Offset: 29 (32%), Referenced to phase 2:NBT and 6:SBTU, Start of Green	
Natural Cycle: 90	
Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.00	
Intersection Signal Delay: 36.9	Intersection LOS: D
Intersection Capacity Utilization 84.0%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2024 Existing MID



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	15	799	508	93	45	6
Future Volume (vph)	15	799	508	93	45	6
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.971		0.974	
Flt Protected	0.950				0.961	
Satd. Flow (prot)	1574	1801	1647	0	1627	0
Flt Permitted	0.950				0.961	
Satd. Flow (perm)	1574	1801	1647	0	1627	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.63	0.91	0.81	0.55	0.66	0.38
Heavy Vehicles (%)	7%	2%	5%	3%	2%	2%
Adj. Flow (vph)	24	878	627	169	68	16
Shared Lane Traffic (%)						
Lane Group Flow (vph)	24	878	796	0	84	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 52.1% ICU Level of Service A

Analysis Period (min) 15



















HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2024 Existing MID

Intersection						
Int Delay, s/veh	1.3					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	15	799	508	93	45	6
Future Vol, veh/h	15	799	508	93	45	6
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	63	91	81	55	66	38
Heavy Vehicles, %	7	2	5	3	2	2
Mvmt Flow	24	878	627	169	68	16
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	796	0	-	0	1638	712
Stage 1	-	-	-	-	712	-
Stage 2	-	-	-	-	926	-
Critical Hdwy	4.17	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.263	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	804	-	-	-	111	432
Stage 1	-	-	-	-	486	-
Stage 2	-	-	-	-	386	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	804	-	-	-	108	432
Mov Cap-2 Maneuver	-	-	-	-	242	-
Stage 1	-	-	-	-	471	-
Stage 2	-	-	-	-	386	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.3	0		24.9		
HCM LOS				C		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	804	-	-	-	264	
HCM Lane V/C Ratio	0.03	-	-	-	0.318	
HCM Control Delay (s)	9.6	-	-	-	24.9	
HCM Lane LOS	A	-	-	-	C	
HCM 95th %tile Q(veh)	0.1	-	-	-	1.3	













Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing MID

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	84	645	106	75	435	124	120	76	57	90	64	51
Future Volume (vph)	84	645	106	75	435	124	120	76	57	90	64	51
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.980			0.963			0.968			0.956	
Flt Protected	0.950			0.950				0.979			0.983	
Satd. Flow (prot)	1728	1753	0	1686	1688	0	0	1603	0	0	1645	0
Flt Permitted	0.159			0.061				0.718			0.725	
Satd. Flow (perm)	289	1753	0	108	1688	0	0	1176	0	0	1213	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.72	0.86	0.91	0.75	0.85	0.74	0.81	0.70	0.71	0.78	0.57	0.46
Heavy Vehicles (%)	2%	4%	2%	3%	4%	5%	3%	4%	5%	2%	3%	2%
Adj. Flow (vph)	117	750	116	100	512	168	148	109	80	115	112	111
Shared Lane Traffic (%)												
Lane Group Flow (vph)	117	866	0	100	680	0	0	337	0	0	338	0
Turn Type	D.P+P	NA		D.P+P	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases	6			2			8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	13.0	72.0		12.0	71.0		42.0	42.0		14.0	56.0	
Total Split (%)	9.3%	51.4%		8.6%	50.7%		30.0%	30.0%		10.0%	40.0%	
Maximum Green (s)	7.9	65.8		7.1	64.8		35.8	35.8		9.1	49.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	74.0	67.0		74.0	66.3			37.0			51.0	
Actuated g/C Ratio	0.53	0.48		0.53	0.47			0.26			0.36	
v/c Ratio	0.51	1.03		0.74	0.85			1.09			0.72	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing MID

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	22.4	75.8		54.8	44.4			123.6			47.3	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay	22.4	75.8		54.8	44.4			123.6			47.3	
LOS	C	E		D	D			F			D	
Approach Delay		69.5			45.8			123.6			47.3	
Approach LOS		E			D			F			D	
Queue Length 50th (ft)	48	~844		41	538			~343			245	
Queue Length 95th (ft)	62	#1012		#78	658			#354			195	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	235	838		135	799			310			469	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.50	1.03		0.74	0.85			1.09			0.72	

Intersection Summary

Area Type: Other

Cycle Length: 140

Actuated Cycle Length: 140

Natural Cycle: 140

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.09

Intersection Signal Delay: 66.3

Intersection LOS: E

Intersection Capacity Utilization 77.3%

ICU Level of Service D

Analysis Period (min) 15








~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.









Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

 Ø1	 Ø2	 Ø4
12 s	72 s	56 s
 Ø5	 Ø6	 Ø7
13 s	71 s	14 s
		 Ø8
		42 s

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2024 Existing PM








							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations							
Traffic Volume (vph)	575	371	203	779	4	645	544
Future Volume (vph)	575	371	203	779	4	645	544
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	11	12	11	12	12
Grade (%)	-2%			1%		-1%	
Storage Length (ft)	0	0	425		325		0
Storage Lanes	1	1	2		1		1
Taper Length (ft)	0		100		75		
Lane Util. Factor	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt		0.850					0.850
Flt Protected	0.950		0.950		0.950		
Satd. Flow (prot)	1728	1546	3302	3522	1719	1872	1591
Flt Permitted	0.950		0.950		0.346		
Satd. Flow (perm)	1728	1546	3302	3522	626	1872	1591
Right Turn on Red		No					No
Satd. Flow (RTOR)							
Link Speed (mph)	45			45		45	
Link Distance (ft)	1527			1308		1378	
Travel Time (s)	23.1			19.8		20.9	
Peak Hour Factor	0.94	0.87	0.86	0.96	0.90	0.94	0.89
Adj. Flow (vph)	612	426	236	811	4	686	611
Shared Lane Traffic (%)							
Lane Group Flow (vph)	612	426	236	811	4	686	611
Turn Type	Prot	pm+ov	Prot	NA	Perm	NA	pm+ov
Protected Phases	4	5	5	2		6	4
Permitted Phases		4			6		6
Detector Phase	4	5	5	2	6	6	4
Switch Phase							
Minimum Initial (s)	7.0	7.0	7.0	12.0	12.0	12.0	7.0
Minimum Split (s)	13.4	13.6	13.6	18.4	18.5	18.5	13.4
Total Split (s)	37.0	14.0	14.0	53.0	39.0	39.0	37.0
Total Split (%)	41.1%	15.6%	15.6%	58.9%	43.3%	43.3%	41.1%
Maximum Green (s)	30.6	7.4	7.4	46.6	32.5	32.5	30.6
Yellow Time (s)	4.7	3.0	3.0	4.4	4.6	4.6	4.7
All-Red Time (s)	1.7	3.6	3.6	2.0	1.9	1.9	1.7
Lost Time Adjust (s)	-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.4
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag		Lead	Lead		Lag	Lag	
Lead-Lag Optimize?							
Vehicle Extension (s)	2.0	2.0	2.0	6.0	6.0	6.0	2.0
Minimum Gap (s)	2.0	2.0	2.0	3.0	3.0	3.0	2.0
Time Before Reduce (s)	0.0	0.0	0.0	15.0	15.0	15.0	0.0
Time To Reduce (s)	0.0	0.0	0.0	30.0	30.0	30.0	0.0
Recall Mode	None	None	None	C-Max	C-Max	C-Max	None
Act Effect Green (s)	32.0	46.0	9.0	48.0	34.0	34.0	71.0
Actuated g/C Ratio	0.36	0.51	0.10	0.53	0.38	0.38	0.79
v/c Ratio	1.00	0.54	0.72	0.43	0.02	0.97	0.49
Control Delay	66.4	18.0	52.5	13.6	18.0	56.5	4.8

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA

2024 Existing PM

							
Lane Group	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	66.4	18.0	52.5	13.6	18.0	56.5	4.8
LOS	E	B	D	B	B	E	A
Approach Delay	46.5			22.4		32.1	
Approach LOS	D			C		C	
Queue Length 50th (ft)	343	155	68	138	1	376	90
Queue Length 95th (ft)	#567	230	#108	183	8	#608	136
Internal Link Dist (ft)	1447			1228		1298	
Turn Bay Length (ft)			425		325		
Base Capacity (vph)	614	790	330	1878	236	707	1255
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	1.00	0.54	0.72	0.43	0.02	0.97	0.49

Intersection Summary

Area Type:	Other
Cycle Length: 90	
Actuated Cycle Length: 90	
Offset: 29 (32%), Referenced to phase 2:NBT and 6:SBTU, Start of Green	
Natural Cycle: 90	
Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.00	
Intersection Signal Delay: 33.5	Intersection LOS: C
Intersection Capacity Utilization 84.1%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2024 Existing PM



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	22	809	557	39	58	12
Future Volume (vph)	22	809	557	39	58	12
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.990		0.973	
Flt Protected	0.950				0.962	
Satd. Flow (prot)	1652	1801	1691	0	1596	0
Flt Permitted	0.950				0.962	
Satd. Flow (perm)	1652	1801	1691	0	1596	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.69	0.94	0.87	0.75	0.73	0.60
Heavy Vehicles (%)	2%	2%	4%	2%	3%	8%
Adj. Flow (vph)	32	861	640	52	79	20
Shared Lane Traffic (%)						
Lane Group Flow (vph)	32	861	692	0	99	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other






Control Type: Unsignalized

Intersection Capacity Utilization 53.2% ICU Level of Service A

Analysis Period (min) 15




















HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2024 Existing PM

Intersection						
Int Delay, s/veh	1.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	22	809	557	39	58	12
Future Vol, veh/h	22	809	557	39	58	12
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	69	94	87	75	73	60
Heavy Vehicles, %	2	2	4	2	3	8
Mvmt Flow	32	861	640	52	79	20
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	692	0	-	0	1591	666
Stage 1	-	-	-	-	666	-
Stage 2	-	-	-	-	925	-
Critical Hdwy	4.12	-	-	-	6.43	6.28
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.218	-	-	-	3.527	3.372
Pot Cap-1 Maneuver	903	-	-	-	118	449
Stage 1	-	-	-	-	509	-
Stage 2	-	-	-	-	385	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	903	-	-	-	114	449
Mov Cap-2 Maneuver	-	-	-	-	248	-
Stage 1	-	-	-	-	491	-
Stage 2	-	-	-	-	385	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.3	0		25.6		
HCM LOS				D		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	903	-	-	-	273	
HCM Lane V/C Ratio	0.035	-	-	-	0.364	
HCM Control Delay (s)	9.1	-	-	-	25.6	
HCM Lane LOS	A	-	-	-	D	
HCM 95th %tile Q(veh)	0.1	-	-	-	1.6	













Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing PM

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	30	684	154	78	424	56	103	51	85	104	102	48
Future Volume (vph)	30	684	154	78	424	56	103	51	85	104	102	48
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.971			0.981			0.948			0.971	
Flt Protected	0.950			0.950				0.979			0.980	
Satd. Flow (prot)	1711	1766	0	1686	1743	0	0	1591	0	0	1617	0
Flt Permitted	0.277			0.047				0.690			0.677	
Satd. Flow (perm)	499	1766	0	83	1743	0	0	1121	0	0	1117	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.58	0.93	0.86	0.89	0.86	0.78	0.83	0.91	0.76	0.58	0.65	0.52
Heavy Vehicles (%)	3%	2%	2%	3%	3%	2%	3%	2%	2%	8%	2%	6%
Adj. Flow (vph)	52	735	179	88	493	72	124	56	112	179	157	92
Shared Lane Traffic (%)												
Lane Group Flow (vph)	52	914	0	88	565	0	0	292	0	0	428	0
Turn Type	D.P+P	NA		D.P+P	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases	6			2			8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	13.0	90.0		12.0	89.0		45.0	45.0		23.0	68.0	
Total Split (%)	7.6%	52.9%		7.1%	52.4%		26.5%	26.5%		13.5%	40.0%	
Maximum Green (s)	7.9	83.8		7.1	82.8		38.8	38.8		18.1	61.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	93.0	85.0		92.0	87.2			40.0			63.0	
Actuated g/C Ratio	0.55	0.50		0.54	0.51			0.24			0.37	
v/c Ratio	0.16	1.04		0.80	0.63			1.11			0.92	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2024 Existing PM

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay	17.5	80.7		75.8	34.6			145.4			74.1	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay	17.5	80.7		75.8	34.6			145.4			74.1	
LOS	B	F		E	C			F			E	
Approach Delay		77.3			40.2			145.4			74.1	
Approach LOS		E			D			F			E	
Queue Length 50th (ft)	25	~1090		50	459			~369			409	
Queue Length 95th (ft)	30	#1355		#151	563			#570			348	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	331	883		110	893			263			466	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.16	1.04		0.80	0.63			1.11			0.92	

Intersection Summary

Area Type: Other

Cycle Length: 170

Actuated Cycle Length: 170

Natural Cycle: 180

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.11

Intersection Signal Delay: 74.8

Intersection LOS: E

Intersection Capacity Utilization 81.5%

ICU Level of Service D

Analysis Period (min) 15








~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)













		
Ø1	Ø2	Ø4
12 s	90 s	68 s
		
Ø5	Ø6	Ø7
13 s	89 s	23 s
		
		Ø8
		45 s

2029 Background Conditions w/ STIPs

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension


Deal Lake TIA
2029 Background AM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	549	443	0	347	418	0	1720	115	0	1170	1182
Future Volume (vph)	0	549	443	0	347	418	0	1720	115	0	1170	1182
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2815	0	3539	2787	0	3404	2680	0	3372	2801
Flt Permitted												
Satd. Flow (perm)	0	3575	2815	0	3539	2787	0	3404	2680	0	3372	2801
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%
Adj. Flow (vph)	0	610	492	0	386	464	0	1911	128	0	1300	1313
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	610	492	0	386	464	0	1911	128	0	1300	1313
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		61.0	61.0		61.0	61.0
Total Split (%)		39.0%	39.0%		39.0%	39.0%		61.0%	61.0%		61.0%	61.0%
Maximum Green (s)		32.0	32.0		32.0	32.0		54.0	54.0		54.0	54.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		27.6	27.6		27.6	27.6		62.4	62.4		62.4	62.4
Actuated g/C Ratio		0.28	0.28		0.28	0.28		0.62	0.62		0.62	0.62
v/c Ratio		0.62	0.63		0.40	0.60		0.90	0.08		0.62	0.75

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA
2029 Background AM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)		34.0	35.1		29.9	34.3		20.6	8.4		10.4	13.1
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		34.0	35.1		29.9	34.3		20.6	8.4		10.4	13.1
LOS		C	D		C	C		C	A		B	B
Approach Delay (s/veh)		34.5			32.3			19.8			11.7	
Approach LOS		C			C			B			B	
Queue Length 50th (ft)		177	155		104	144		314	16		164	201
Queue Length 95th (ft)		214	196		134	184		#800	m31		316	445
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1215	957		1203	947		2125	1673		2105	1748
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.50	0.51		0.32	0.49		0.90	0.08		0.62	0.75

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 19 (19%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.90

Intersection Signal Delay (s/veh): 20.7

Intersection LOS: C

Intersection Capacity Utilization 71.1%

ICU Level of Service C


Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.


m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	10	598	764	32	67	26
Future Volume (vph)	10	598	764	32	67	26
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.995		0.962	
Flt Protected	0.950				0.965	
Satd. Flow (prot)	1491	1801	1730	0	1459	0
Flt Permitted	0.950				0.965	
Satd. Flow (perm)	1491	1801	1730	0	1459	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	13%	2%	2%	2%	3%	38%
Adj. Flow (vph)	11	664	849	36	74	29
Shared Lane Traffic (%)						
Lane Group Flow (vph)	11	664	885	0	103	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 54.1% ICU Level of Service A

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background AM w STIP

























Intersection						
Int Delay, s/veh	1.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	10	598	764	32	67	26
Future Vol, veh/h	10	598	764	32	67	26
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	13	2	2	2	3	38
Mvmt Flow	11	664	849	36	74	29
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	885	0	-	0	1553	867
Stage 1	-	-	-	-	867	-
Stage 2	-	-	-	-	686	-
Critical Hdwy	4.23	-	-	-	6.43	6.58
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.317	-	-	-	3.527	3.642
Pot Cap-1 Maneuver	720	-	-	-	124	304
Stage 1	-	-	-	-	410	-
Stage 2	-	-	-	-	498	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	720	-	-	-	122	304
Mov Cap-2 Maneuver	-	-	-	-	258	-
Stage 1	-	-	-	-	404	-
Stage 2	-	-	-	-	498	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		26.5		
HCM LOS				D		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	720	-	-	-	-	269
HCM Lane V/C Ratio	0.015	-	-	-	-	0.384
HCM Control Delay (s/veh)	10.1	-	-	-	-	26.5
HCM Lane LOS	B	-	-	-	-	D
HCM 95th %tile Q (veh)	0	-	-	-	-	1.7

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA

2029 Background AM w STIP













												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	89	848	140	105	1061	53	134	23	79	82	46	170
Future Volume (vph)	89	848	140	105	1061	53	134	23	79	82	46	170
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	450		400	300		375	225		225	175		125
Storage Lanes	1		1	1		1	1		1	1		1
Taper Length (ft)	100			100			150			150		
Lane Util. Factor	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fr _t			0.850			0.850			0.850			0.850
Fl _t Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1787	3540	1584	1710	3487	1502	1752	1844	1552	1753	1881	1599
Fl _t Permitted	0.950			0.950			0.950			0.950		
Satd. Flow (perm)	1787	3540	1584	1710	3487	1502	1752	1844	1552	1753	1881	1599
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.57	0.74	0.82	0.75	0.84	0.76	0.88	0.54	0.51	0.53	0.68	0.57
Heavy Vehicles (%)	2%	3%	3%	5%	3%	7%	2%	2%	3%	4%	2%	2%
Adj. Flow (vph)	156	1146	171	140	1263	70	152	43	155	155	68	298
Shared Lane Traffic (%)												
Lane Group Flow (vph)	156	1146	171	140	1263	70	152	43	155	155	68	298
Turn Type	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm
Protected Phases	5	2		1	6		3	8		7	4	
Permitted Phases			2			6			8			4
Detector Phase	5	2	2	1	6	6	3	8	8	7	4	4
Switch Phase												
Minimum Initial (s)	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0	42.0
Total Split (s)	19.0	59.0	59.0	20.0	60.0	60.0	19.0	42.0	42.0	19.0	42.0	42.0
Total Split (%)	13.6%	42.1%	42.1%	14.3%	42.9%	42.9%	13.6%	30.0%	30.0%	13.6%	30.0%	30.0%
Maximum Green (s)	12.0	52.0	52.0	13.0	53.0	53.0	12.0	35.0	35.0	12.0	35.0	35.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None	None
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		25.0	25.0		23.0	23.0		28.0	28.0		28.0	28.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)	15.8	58.1	58.1	15.7	58.0	58.0	14.0	32.2	32.2	14.0	32.2	32.2
Actuated g/C Ratio	0.11	0.42	0.42	0.11	0.41	0.41	0.10	0.23	0.23	0.10	0.23	0.23
v/c Ratio	0.78	0.78	0.26	0.73	0.88	0.11	0.87	0.10	0.43	0.89	0.16	0.81
Control Delay (s/veh)	86.7	34.0	26.3	82.3	46.4	27.2	102.2	40.9	49.1	105.1	42.2	68.1

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA

2029 Background AM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	86.7	34.0	26.3	82.3	46.4	27.2	102.2	40.9	49.1	105.1	42.2	68.1
LOS	F	C	C	F	D	C	F	D	D	F	D	E
Approach Delay (s/veh)		38.7			48.9			71.1			75.7	
Approach LOS		D			D			E			E	
Queue Length 50th (ft)	144	348	84	123	571	40	139	31	120	142	49	254
Queue Length 95th (ft)	138	354	131	165	605	63	#258	37	97	124	66	202
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	450		400	300		375	225		225	175		125
Base Capacity (vph)	201	1469	657	195	1443	622	175	487	410	175	497	422
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.78	0.78	0.26	0.72	0.88	0.11	0.87	0.09	0.38	0.89	0.14	0.71

Intersection Summary

Area Type: Other

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 91 (65%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 110

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.89

Intersection Signal Delay (s/veh): 50.7

Intersection LOS: D

Intersection Capacity Utilization 61.8%









ICU Level of Service B

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

 Ø1	 Ø2 (R)	 Ø3	 Ø4
20 s	59 s	19 s	42 s
 Ø5	 Ø6 (R)	 Ø7	 Ø8
19 s	60 s	19 s	42 s

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	22	607	4	739	623	495	22
Future Volume (vph)	22	607	4	739	623	495	22
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		2171		725	
Travel Time (s)		97.0		32.9		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	24	674	4	821	692	550	24
Shared Lane Traffic (%)							
Lane Group Flow (vph)	24	674	4	821	692	550	24
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	16.0	64.0	14.0	62.0	62.0	62.0	16.0
Total Split (%)	11.4%	45.7%	10.0%	44.3%	44.3%	44.3%	11.4%
Maximum Green (s)	9.0	57.0	7.0	55.0	55.0	55.0	9.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effect Green (s)	9.9	94.9	9.0	85.6	123.9	32.3	47.2
Actuated g/C Ratio	0.07	0.68	0.06	0.61	0.89	0.23	0.34
v/c Ratio	0.19	0.28	0.04	0.38	0.49	0.69	0.05
Control Delay (s/veh)	64.5	10.6	63.8	8.7	1.9	53.8	28.7
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	64.5	10.6	63.8	8.7	1.9	53.8	28.7

Lanes, Volumes, Timings

4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	E	B	E	A	A	D	C
Approach Delay (s/veh)		12.5		5.8		52.7	
Approach LOS		B		A		D	
Queue Length 50th (ft)	21	109	4	111	59	239	15
Queue Length 95th (ft)	52	219	m4	m130	m59	280	33
Internal Link Dist (ft)		6325		2091		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	141	2399	113	2164	1572	1397	548
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.17	0.28	0.04	0.38	0.44	0.39	0.04

Intersection Summary

Area Type: Other

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 136 (97%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.69

Intersection Signal Delay (s/veh): 17.1

Intersection LOS: B

Intersection Capacity Utilization 52.7%

ICU Level of Service A

Analysis Period (min) 15









m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	2136	0	2352
Future Volume (vph)	0	0	0	2136	0	2352
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35	45		45		
Link Distance (ft)	233	716		681		
Travel Time (s)	4.5	10.8		10.3		
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2373	0	2613
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2373	0	2613
Sign Control	Free	Free		Free		
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	78.1%			ICU Level of Service D		
Analysis Period (min)	15					

Lanes, Volumes, Timings









8: Northern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	580	1556	0	0
Future Volume (vph)	0	0	580	1556	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	644	1729	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	644	1729	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	73.9%		ICU Level of Service D			
Analysis Period (min)	15					







Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1556	0	1772
Future Volume (vph)	0	0	0	1556	0	1772
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1729	0	1969
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1729	0	1969
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	65.3%			ICU Level of Service C		
Analysis Period (min)	15					










Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations				↑↑		↑↑
Traffic Volume (vph)	0	0	0	1835	0	1613
Future Volume (vph)	0	0	0	1835	0	1613
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2039	0	1792
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2039	0	1792
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	63.8%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						 
Traffic Volume (vph)	0	0	0	0	39	1574
Future Volume (vph)	0	0	0	0	39	1574
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	43	1749
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	43	1749
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	63.8%			ICU Level of Service B		
Analysis Period (min)	15					







Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1796	0	1574
Future Volume (vph)	0	0	0	1796	0	1574
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1996	0	1749
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1996	0	1749
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	66.2%			ICU Level of Service C		
Analysis Period (min)	15					










Lanes, Volumes, Timings
15: Rea Road

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	992	0	1529	0	0
Future Volume (vph)	0	992	0	1529	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1102	0	1699	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1102	0	1699	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	56.8%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	78	1451	0	0
Future Volume (vph)	0	0	78	1451	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	87	1612	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	87	1612	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	33.3%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	914	0	1451	0	0
Future Volume (vph)	0	914	0	1451	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1016	0	1612	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1016	0	1612	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	43.4%			ICU Level of Service A		
Analysis Period (min)	15					









Lanes, Volumes, Timings 19: Rea Road Extension

Deal Lake TIA
2029 Background AM w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	664	0	765	0	0
Future Volume (vph)	0	664	0	765	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	738	0	850	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	738	0	850	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	38.5%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings 20: Eastern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	385	279	0	0	0	0
Future Volume (vph)	385	279	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45		45		45	
Link Distance (ft)	164		264		460	
Travel Time (s)	2.5		4.0		7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	428	310	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	428	310	0	0	0	0
Sign Control	Free		Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	37.4%		ICU Level of Service A			
Analysis Period (min)	15					

Lanes, Volumes, Timings

21: Rea Road Extension










Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	279	0	380	0	0
Future Volume (vph)	0	279	0	380	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	310	0	422	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	310	0	422	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	16.6%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	 					 
Traffic Volume (vph)	580	0	0	0	0	1772
Future Volume (vph)	580	0	0	0	0	1772
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	644	0	0	0	0	1969
Shared Lane Traffic (%)						
Lane Group Flow (vph)	644	0	0	0	0	1969
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	29.0					71.0
Total Split (%)	29.0%					71.0%
Maximum Green (s)	22.0					64.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	23.2					66.8
Actuated g/C Ratio	0.23					0.67
v/c Ratio	0.81					0.83
Control Delay (s/veh)	34.9					16.7
Queue Delay	0.0					0.0
Total Delay (s/veh)	34.9					16.7
LOS	C					B
Approach Delay (s/veh)	34.9					16.7
Approach LOS	C					B

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	202					454
Queue Length 95th (ft)	m215					572
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	823					2365
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.78					0.83

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 1 (1%), Referenced to phase 6:SBT, Start of Green

Natural Cycle: 60

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.83

Intersection Signal Delay (s/veh): 21.2

Intersection LOS: C


Intersection Capacity Utilization 73.9%

ICU Level of Service D

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	39	0	0	1796	0	0
Future Volume (vph)	39	0	0	1796	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Fr _t						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	43	0	0	1996	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	43	0	0	1996	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	14.0			86.0		
Total Split (%)	14.0%			86.0%		
Maximum Green (s)	7.0			79.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	9.0			88.6		
Actuated g/C Ratio	0.09			0.89		
v/c Ratio	0.27			0.64		
Control Delay (s/veh)	44.4			4.0		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	44.4			4.0		
LOS	D			A		
Approach Delay (s/veh)	44.4			4.0		
Approach LOS	D			A		

Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	24			217		
Queue Length 95th (ft)	m44			274		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	159			3135		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.27			0.64		

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 20 (20%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 60

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.64

Intersection Signal Delay (s/veh): 4.9

Intersection LOS: A


Intersection Capacity Utilization 63.8%

ICU Level of Service B

Analysis Period (min) 15


m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Background AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↑	
Traffic Volume (vph)	0	914	0	0	78	0
Future Volume (vph)	0	914	0	0	78	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Fr _t						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1016	0	0	87	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1016	0	0	87	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized










Intersection Capacity Utilization 72.0% ICU Level of Service C

Analysis Period (min) 15

Intersection						
Int Delay, s/veh	1.1					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	914	0	0	78	0
Future Vol, veh/h	0	914	0	0	78	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1016	0	0	87	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			508	-
Stage 1	-	-			0	-
Stage 2	-	-			508	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			494	0
Stage 1	0	-			-	0
Stage 2	0	-			569	0
Platoon blocked, %		-				
Mov Cap-1 Maneuver	-	-			494	-
Mov Cap-2 Maneuver	-	-			494	-
Stage 1	-	-			-	-
Stage 2	-	-			569	-
Approach	EB		SB			
HCM Control Delay, s/v	0		13.8			
HCM LOS			B			
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		494			
HCM Lane V/C Ratio	-		0.175			
HCM Control Delay (s/veh)	-		13.8			
HCM Lane LOS	-		B			
HCM 95th %tile Q (veh)	-		0.6			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	0	380	385	0
Future Volume (vph)	0	0	0	380	385	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	422	428	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	422	428	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	38.5%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background AM w STIP













Intersection						
Int Delay, s/veh	7.9					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	380	385	0
Future Vol, veh/h	0	0	0	380	385	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	422	428	0
Major/Minor		Major2		Minor1		
Conflicting Flow All			-	-	211	-
Stage 1			-	-	0	-
Stage 2			-	-	211	-
Critical Hdwy			-	-	6.84	-
Critical Hdwy Stg 1			-	-	-	-
Critical Hdwy Stg 2			-	-	5.84	-
Follow-up Hdwy			-	-	3.52	-
Pot Cap-1 Maneuver			0	-	758	0
Stage 1			0	-	-	0
Stage 2			0	-	804	0
Platoon blocked, %				-		
Mov Cap-1 Maneuver			-	-	758	-
Mov Cap-2 Maneuver			-	-	758	-
Stage 1			-	-	-	-
Stage 2			-	-	804	-
Approach			WB		NB	
HCM Control Delay, s/v			0		15.7	
HCM LOS					C	
Minor Lane/Major Mvmt	NBLn1	WBT				
Capacity (veh/h)	758	-				
HCM Lane V/C Ratio	0.564	-				
HCM Control Delay (s/veh)	15.7	-				
HCM Lane LOS	C	-				
HCM 95th %tile Q (veh)	3.6	-				

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Background MID w STIP













												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	838	566	0	352	527	0	1214	185	0	991	645
Future Volume (vph)	0	838	566	0	352	527	0	1214	185	0	991	645
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2787	0	3539	2787	0	3371	2680	0	3438	2773
Flt Permitted												
Satd. Flow (perm)	0	3575	2787	0	3539	2787	0	3371	2680	0	3438	2773
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	3%	2%	2%	2%	2%	3%	2%	2%	2%	3%
Adj. Flow (vph)	0	931	629	0	391	586	0	1349	206	0	1101	717
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	931	629	0	391	586	0	1349	206	0	1101	717
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		41.0	41.0		41.0	41.0
Total Split (%)		48.8%	48.8%		48.8%	48.8%		51.3%	51.3%		51.3%	51.3%
Maximum Green (s)		32.0	32.0		32.0	32.0		34.0	34.0		34.0	34.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		31.5	31.5		31.5	31.5		38.5	38.5		38.5	38.5
Actuated g/C Ratio		0.39	0.39		0.39	0.39		0.48	0.48		0.48	0.48
v/c Ratio		0.66	0.57		0.28	0.53		0.83	0.16		0.66	0.54

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Background MID w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)		22.2	21.0		16.6	20.3		20.2	11.8		14.1	12.6
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		22.2	21.0		16.6	20.3		20.2	11.8		14.1	12.6
LOS		C	C		B	C		C	B		B	B
Approach Delay (s/veh)		21.7			18.8			19.1			13.5	
Approach LOS		C			B			B			B	
Queue Length 50th (ft)		186	130		65	118		189	28		139	96
Queue Length 95th (ft)		245	181		94	167		#240	46		200	121
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1519	1184		1504	1184		1623	1291		1656	1335
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.61	0.53		0.26	0.49		0.83	0.16		0.66	0.54

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 16 (20%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 80

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.83

Intersection Signal Delay (s/veh): 18.0

Intersection LOS: B

Intersection Capacity Utilization 65.1%


ICU Level of Service C

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings

2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	19	760	476	134	65	7
Future Volume (vph)	19	760	476	134	65	7
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.970		0.986	
Flt Protected	0.950				0.957	
Satd. Flow (prot)	1574	1801	1645	0	1641	0
Flt Permitted	0.950				0.957	
Satd. Flow (perm)	1574	1801	1645	0	1641	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	7%	2%	5%	3%	2%	2%
Adj. Flow (vph)	21	844	529	149	72	8
Shared Lane Traffic (%)						
Lane Group Flow (vph)	21	844	678	0	80	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 50.7% ICU Level of Service A

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background MID w STIP

























Intersection						
Int Delay, s/veh	1.2					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	19	760	476	134	65	7
Future Vol, veh/h	19	760	476	134	65	7
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	7	2	5	3	2	2
Mvmt Flow	21	844	529	149	72	8
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	678	0	-	0	1490	604
Stage 1	-	-	-	-	604	-
Stage 2	-	-	-	-	886	-
Critical Hdwy	4.17	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.263	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	891	-	-	-	136	498
Stage 1	-	-	-	-	546	-
Stage 2	-	-	-	-	403	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	891	-	-	-	133	498
Mov Cap-2 Maneuver	-	-	-	-	269	-
Stage 1	-	-	-	-	533	-
Stage 2	-	-	-	-	403	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		22.7		
HCM LOS				C		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	891	-	-	-	282	
HCM Lane V/C Ratio	0.024	-	-	-	0.284	
HCM Control Delay (s/veh)	9.1	-	-	-	22.7	
HCM Lane LOS	A	-	-	-	C	
HCM 95th %tile Q (veh)	0.1	-	-	-	1.1	













Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA

2029 Background MID w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	79	779	99	99	522	175	109	156	75	127	131	49
Future Volume (vph)	79	779	99	99	522	175	109	156	75	127	131	49
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	450		400	300		375	225		225	175		125
Storage Lanes	1		1	1		1	1		1	1		1
Taper Length (ft)	100			100			150			150		
Lane Util. Factor	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.850			0.850			0.850			0.850
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1787	3506	1599	1744	3454	1530	1735	1809	1523	1787	1863	1599
Flt Permitted	0.950			0.950			0.950			0.950		
Satd. Flow (perm)	1787	3506	1599	1744	3454	1530	1735	1809	1523	1787	1863	1599
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.72	0.86	0.91	0.75	0.85	0.74	0.81	0.70	0.71	0.78	0.57	0.48
Heavy Vehicles (%)	2%	4%	2%	3%	4%	5%	3%	4%	5%	2%	3%	2%
Adj. Flow (vph)	110	906	109	132	614	236	135	223	106	163	230	102
Shared Lane Traffic (%)												
Lane Group Flow (vph)	110	906	109	132	614	236	135	223	106	163	230	102
Turn Type	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm
Protected Phases	5	2		1	6		3	8		7	4	
Permitted Phases			2			6			8			4
Detector Phase	5	2	2	1	6	6	3	8	8	7	4	4
Switch Phase												
Minimum Initial (s)	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0	42.0
Total Split (s)	19.0	42.0	42.0	17.0	40.0	40.0	18.0	42.0	42.0	19.0	43.0	43.0
Total Split (%)	15.8%	35.0%	35.0%	14.2%	33.3%	33.3%	15.0%	35.0%	35.0%	15.8%	35.8%	35.8%
Maximum Green (s)	12.0	35.0	35.0	10.0	33.0	33.0	11.0	35.0	35.0	12.0	36.0	36.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None	None
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		25.0	25.0		23.0	23.0		28.0	28.0		28.0	28.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)	14.7	47.1	47.1	16.2	48.6	48.6	12.7	22.9	22.9	13.8	24.0	24.0
Actuated g/C Ratio	0.12	0.39	0.39	0.14	0.41	0.41	0.11	0.19	0.19	0.12	0.20	0.20
v/c Ratio	0.50	0.66	0.17	0.56	0.44	0.38	0.74	0.65	0.37	0.80	0.62	0.32
Control Delay (s/veh)	60.3	27.3	22.9	57.6	29.0	30.1	75.8	53.0	44.3	78.6	50.4	42.2

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	60.3	27.3	22.9	57.6	29.0	30.1	75.8	53.0	44.3	78.6	50.4	42.2
LOS	E	C	C	E	C	C	E	D	D	E	D	D
Approach Delay (s/veh)		30.1			33.1			57.6			58.0	
Approach LOS		C			C			E			E	
Queue Length 50th (ft)	86	207	42	96	179	127	103	161	72	125	164	68
Queue Length 95th (ft)	113	276	87	131	256	184	#161	169	90	#182	135	56
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	450		400	300		375	225		225	175		125
Base Capacity (vph)	234	1375	627	236	1398	619	187	557	469	208	589	506
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.47	0.66	0.17	0.56	0.44	0.38	0.72	0.40	0.23	0.78	0.39	0.20

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 101 (84%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 110

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.80

Intersection Signal Delay (s/veh): 39.7

Intersection LOS: D

Intersection Capacity Utilization 59.3%









ICU Level of Service B

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

 Ø1	 Ø2 (R)	 Ø3	 Ø4
17 s	42 s	18 s	43 s
 Ø5	 Ø6 (R)	 Ø7	 Ø8
19 s	40 s	19 s	42 s

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	22	516	4	373	307	441	21
Future Volume (vph)	22	516	4	373	307	441	21
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		2171		725	
Travel Time (s)		97.0		32.9		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	24	573	4	414	341	490	23
Shared Lane Traffic (%)							
Lane Group Flow (vph)	24	573	4	414	341	490	23
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	19.0	54.0	17.0	52.0	49.0	49.0	19.0
Total Split (%)	15.8%	45.0%	14.2%	43.3%	40.8%	40.8%	15.8%
Maximum Green (s)	12.0	47.0	10.0	45.0	42.0	42.0	12.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effect Green (s)	9.7	81.9	9.0	75.6	107.9	25.3	40.0
Actuated g/C Ratio	0.08	0.68	0.08	0.63	0.90	0.21	0.33
v/c Ratio	0.17	0.24	0.03	0.19	0.24	0.68	0.04
Control Delay (s/veh)	53.9	8.8	44.3	11.2	1.3	48.0	24.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	53.9	8.8	44.3	11.2	1.3	48.0	24.8

Lanes, Volumes, Timings 4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	D	A	D	B	A	D	C
Approach Delay (s/veh)		10.6		6.9		47.0	
Approach LOS		B		A		D	
Queue Length 50th (ft)	18	73	3	67	34	180	12
Queue Length 95th (ft)	45	161	m8	120	40	222	28
Internal Link Dist (ft)		6325		2091		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	206	2414	177	2229	1547	1258	585
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.24	0.02	0.19	0.22	0.39	0.04

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.68

Intersection Signal Delay (s/veh): 19.1

Intersection LOS: B

Intersection Capacity Utilization 39.2%

ICU Level of Service A

Analysis Period (min) 15









m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1741	0	1636
Future Volume (vph)	0	0	0	1741	0	1636
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	233		716			681
Travel Time (s)	4.5		10.8			10.3
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1934	0	1818
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1934	0	1818
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	64.2%			ICU Level of Service C		
Analysis Period (min)	15					

Lanes, Volumes, Timings









8: Northern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	307	1434	0	0
Future Volume (vph)	0	0	307	1434	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	341	1593	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	341	1593	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	53.8%			ICU Level of Service A		
Analysis Period (min)	15					









Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1434	0	1329
Future Volume (vph)	0	0	0	1434	0	1329
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1593	0	1477
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1593	0	1477
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	49.8%			ICU Level of Service A		
Analysis Period (min)	15					










Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1399	0	1557
Future Volume (vph)	0	0	0	1399	0	1557
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1554	0	1730
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1554	0	1730
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	57.8%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						 
Traffic Volume (vph)	0	0	0	0	57	1500
Future Volume (vph)	0	0	0	0	57	1500
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	63	1667
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	63	1667
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	55.8%			ICU Level of Service B		
Analysis Period (min)	15					

Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1342	0	1500
Future Volume (vph)	0	0	0	1342	0	1500
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1491	0	1667
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1491	0	1667
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	50.3%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings 15: Rea Road

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	1404	0	997	0	0
Future Volume (vph)	0	1404	0	997	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Fr _t				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1560	0	1108	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1560	0	1108	0	0
Sign Control		Free	Free		Free	

Intersection Summary

Area Type: Other










Control Type: Unsignalized

Intersection Capacity Utilization 48.1% ICU Level of Service A

Analysis Period (min) 15











Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	93	904	0	0
Future Volume (vph)	0	0	93	904	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	103	1004	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	103	1004	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.2%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		 		 		
Traffic Volume (vph)	0	1311	0	904	0	0
Future Volume (vph)	0	1311	0	904	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1457	0	1004	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1457	0	1004	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	49.2%			ICU Level of Service A		
Analysis Period (min)	15					









Lanes, Volumes, Timings 19: Rea Road Extension

Deal Lake TIA
2029 Background MID w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	1023	0	879	0	0
Future Volume (vph)	0	1023	0	879	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1137	0	977	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1137	0	977	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.4%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
20: Eastern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	485	538	0	0	0	0
Future Volume (vph)	485	538	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	164			264	460	
Travel Time (s)	2.5			4.0	7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	539	598	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	539	598	0	0	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	43.1%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings

21: Rea Road Extension

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	538	0	394	0	0
Future Volume (vph)	0	538	0	394	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	598	0	438	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	598	0	438	0	0
Sign Control		Free	Free		Free	

Intersection Summary

Area Type: Other











Control Type: Unsignalized

Intersection Capacity Utilization 18.2% ICU Level of Service A

Analysis Period (min) 15

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	 					 
Traffic Volume (vph)	307	0	0	0	0	1329
Future Volume (vph)	307	0	0	0	0	1329
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	341	0	0	0	0	1477
Shared Lane Traffic (%)						
Lane Group Flow (vph)	341	0	0	0	0	1477
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	21.0					59.0
Total Split (%)	26.3%					73.8%
Maximum Green (s)	14.0					52.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	14.5					55.5
Actuated g/C Ratio	0.18					0.69
v/c Ratio	0.55					0.60
Control Delay (s/veh)	25.5					7.9
Queue Delay	0.0					0.0
Total Delay (s/veh)	25.5					7.9
LOS	C					A
Approach Delay (s/veh)	25.5					7.9
Approach LOS	C					A

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	74					177
Queue Length 95th (ft)	m89					243
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	686					2456
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.50					0.60

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 0 (0%), Referenced to phase 6:SBT, Start of Green

Natural Cycle: 40

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.60

Intersection Signal Delay (s/veh): 11.2

Intersection LOS: B


Intersection Capacity Utilization 53.8%

ICU Level of Service A

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	57	0	0	1342	0	0
Future Volume (vph)	57	0	0	1342	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	63	0	0	1491	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	63	0	0	1491	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	16.0			64.0		
Total Split (%)	20.0%			80.0%		
Maximum Green (s)	9.0			57.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	10.0			63.8		
Actuated g/C Ratio	0.13			0.80		
v/c Ratio	0.28			0.53		
Control Delay (s/veh)	32.3			4.8		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	32.3			4.8		
LOS	C			A		
Approach Delay (s/veh)	32.3			4.8		
Approach LOS	C			A		

Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	28			133		
Queue Length 95th (ft)	m49			185		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	243			2820		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.26			0.53		

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 12 (15%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 40

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.53

Intersection Signal Delay (s/veh): 5.9

Intersection LOS: A


Intersection Capacity Utilization 57.8%

ICU Level of Service B

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Background MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↑	
Traffic Volume (vph)	0	1311	0	0	93	0
Future Volume (vph)	0	1311	0	0	93	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Fr _t						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1457	0	0	103	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1457	0	0	103	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized









Intersection Capacity Utilization 67.9% ICU Level of Service C

Analysis Period (min) 15

Intersection						
Int Delay, s/veh	1.3					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	1311	0	0	93	0
Future Vol, veh/h	0	1311	0	0	93	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1457	0	0	103	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			729	-
Stage 1	-	-			0	-
Stage 2	-	-			729	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			358	0
Stage 1	0	-			-	0
Stage 2	0	-			438	0
Platoon blocked, %		-				
Mov Cap-1 Maneuver	-	-			358	-
Mov Cap-2 Maneuver	-	-			358	-
Stage 1	-	-			-	-
Stage 2	-	-			438	-
Approach	EB		SB			
HCM Control Delay, s/v	0		19.1			
HCM LOS			C			
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		358			
HCM Lane V/C Ratio	-		0.289			
HCM Control Delay (s/veh)	-		19.1			
HCM Lane LOS	-		C			
HCM 95th %tile Q (veh)	-		1.2			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	394	485	0
Future Volume (vph)	0	0	0	394	485	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	438	539	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	438	539	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.4%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background MID w STIP













Intersection						
Int Delay, s/veh	11.6					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	394	485	0
Future Vol, veh/h	0	0	0	394	485	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	438	539	0
Major/Minor		Major2		Minor1		
Conflicting Flow All			-	-	219	-
Stage 1			-	-	0	-
Stage 2			-	-	219	-
Critical Hdwy			-	-	6.84	-
Critical Hdwy Stg 1			-	-	-	-
Critical Hdwy Stg 2			-	-	5.84	-
Follow-up Hdwy			-	-	3.52	-
Pot Cap-1 Maneuver			0	-	749	0
Stage 1			0	-	-	0
Stage 2			0	-	796	0
Platoon blocked, %				-		
Mov Cap-1 Maneuver			-	-	749	-
Mov Cap-2 Maneuver			-	-	749	-
Stage 1			-	-	-	-
Stage 2			-	-	796	-
Approach			WB		NB	
HCM Control Delay, s/v			0		21.1	
HCM LOS					C	
Minor Lane/Major Mvmt	NBLn1	WBT				
Capacity (veh/h)	749	-				
HCM Lane V/C Ratio	0.719	-				
HCM Control Delay (s/veh)	21.1	-				
HCM Lane LOS	C	-				
HCM 95th %tile Q (veh)	6.2	-				


Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Background PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	876	659	0	245	643	0	1498	114	0	1176	749
Future Volume (vph)	0	876	659	0	245	643	0	1498	114	0	1176	749
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2815	0	3539	2787	0	3404	2680	0	3438	2801
Flt Permitted												
Satd. Flow (perm)	0	3575	2815	0	3539	2787	0	3404	2680	0	3438	2801
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	973	732	0	272	714	0	1664	127	0	1307	832
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	973	732	0	272	714	0	1664	127	0	1307	832
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		51.0	51.0		51.0	51.0
Total Split (%)		43.3%	43.3%		43.3%	43.3%		56.7%	56.7%		56.7%	56.7%
Maximum Green (s)		32.0	32.0		32.0	32.0		44.0	44.0		44.0	44.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		33.1	33.1		33.1	33.1		46.9	46.9		46.9	46.9
Actuated g/C Ratio		0.37	0.37		0.37	0.37		0.52	0.52		0.52	0.52
v/c Ratio		0.74	0.71		0.21	0.70		0.94	0.09		0.73	0.57
Control Delay (s/veh)		28.7	28.6		19.7	28.3		28.3	8.7		14.6	12.1

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		28.7	28.6		19.7	28.3		28.3	8.7		14.6	12.1
LOS		C	C		B	C		C	A		B	B
Approach Delay (s/veh)		28.7			26.0			26.9			13.6	
Approach LOS		C			C			C			B	
Queue Length 50th (ft)		244	194		53	189		456	11		220	110
Queue Length 95th (ft)		316	266		82	259		#637	17		257	146
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1350	1063		1336	1052		1775	1397		1793	1460
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.72	0.69		0.20	0.68		0.94	0.09		0.73	0.57

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 16 (18%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.94

Intersection Signal Delay (s/veh): 22.9

Intersection LOS: C

Intersection Capacity Utilization 74.0%


ICU Level of Service D

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings 2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	30	763	602	64	31	11
Future Volume (vph)	30	763	602	64	31	11
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.987		0.965	
Flt Protected	0.950				0.964	
Satd. Flow (prot)	1652	1801	1686	0	1582	0
Flt Permitted	0.950				0.964	
Satd. Flow (perm)	1652	1801	1686	0	1582	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	4%	2%	3%	8%
Adj. Flow (vph)	33	848	669	71	34	12
Shared Lane Traffic (%)						
Lane Group Flow (vph)	33	848	740	0	46	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 50.2% ICU Level of Service A

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background PM w STIP

Intersection						
Int Delay, s/veh	0.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	30	763	602	64	31	11
Future Vol, veh/h	30	763	602	64	31	11
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	4	2	3	8
Mvmt Flow	33	848	669	71	34	12

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	740	0	0 1619 705
Stage 1	-	-	- 705 -
Stage 2	-	-	- 914 -
Critical Hdwy	4.12	-	- 6.43 6.28
Critical Hdwy Stg 1	-	-	- 5.43 -
Critical Hdwy Stg 2	-	-	- 5.43 -
Follow-up Hdwy	2.218	-	- 3.527 3.372
Pot Cap-1 Maneuver	867	-	- 113 426
Stage 1	-	-	- 488 -
Stage 2	-	-	- 389 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	867	-	- 109 426
Mov Cap-2 Maneuver	-	-	- 243 -
Stage 1	-	-	- 469 -
Stage 2	-	-	- 389 -

























Approach	EB	WB	SB
HCM Control Delay, s/v	0.4	0	20.8
HCM LOS			C

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	867	-	-	-	274
HCM Lane V/C Ratio	0.038	-	-	-	0.17
HCM Control Delay (s/veh)	9.3	-	-	-	20.8
HCM Lane LOS	A	-	-	-	C
HCM 95th %tile Q (veh)	0.1	-	-	-	0.6

Lanes, Volumes, Timings













3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Background PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	169	1058	135	78	858	81	144	46	103	52	23	90
Future Volume (vph)	169	1058	135	78	858	81	144	46	103	52	23	90
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	450		400	300		375	225		225	175		125
Storage Lanes	1		1	1		1	1		1	1		1
Taper Length (ft)	100			100			150			150		
Lane Util. Factor	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.850			0.850			0.850			0.850
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1770	3575	1599	1744	3487	1575	1735	1844	1568	1688	1881	1539
Flt Permitted	0.950			0.950			0.950			0.950		
Satd. Flow (perm)	1770	3575	1599	1744	3487	1575	1735	1844	1568	1688	1881	1539
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	3%	2%	2%	3%	3%	2%	3%	2%	2%	8%	2%	6%
Adj. Flow (vph)	188	1176	150	87	953	90	160	51	114	58	26	100
Shared Lane Traffic (%)												
Lane Group Flow (vph)	188	1176	150	87	953	90	160	51	114	58	26	100
Turn Type	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm
Protected Phases	5	2		1	6		3	8		7	4	
Permitted Phases			2			6			8			4
Detector Phase	5	2	2	1	6	6	3	8	8	7	4	4
Switch Phase												
Minimum Initial (s)	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0	42.0
Total Split (s)	18.0	47.0	47.0	14.0	43.0	43.0	17.0	45.0	45.0	14.0	42.0	42.0
Total Split (%)	15.0%	39.2%	39.2%	11.7%	35.8%	35.8%	14.2%	37.5%	37.5%	11.7%	35.0%	35.0%
Maximum Green (s)	11.0	40.0	40.0	7.0	36.0	36.0	10.0	38.0	38.0	7.0	35.0	35.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None	None
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		25.0	25.0		23.0	23.0		28.0	28.0		28.0	28.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)	22.7	59.1	59.1	13.7	50.1	50.1	12.0	21.1	21.1	9.0	15.3	15.3
Actuated g/C Ratio	0.19	0.49	0.49	0.11	0.42	0.42	0.10	0.18	0.18	0.08	0.13	0.13
v/c Ratio	0.56	0.67	0.19	0.44	0.65	0.14	0.92	0.16	0.41	0.46	0.11	0.51
Control Delay (s/veh)	49.6	22.4	17.6	55.8	31.9	24.5	105.1	43.7	49.4	65.5	45.2	57.3

3: Twelve Mile Creek Road & Weddington Road (NC 84)

2029 Background PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	49.6	22.4	17.6	55.8	31.9	24.5	105.1	43.7	49.4	65.5	45.2	57.3
LOS	D	C	B	E	C	C	F	D	D	E	D	E
Approach Delay (s/veh)		25.3			33.2			75.9			58.2	
Approach LOS		C			C			E			E	
Queue Length 50th (ft)	144	261	55	64	306	42	125	35	82	44	18	73
Queue Length 95th (ft)	204	393	115	113	430	88	#258	69	135	89	44	125
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	450		400	300		375	225		225	175		125
Base Capacity (vph)	334	1759	786	198	1455	657	173	614	522	126	579	474
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.56	0.67	0.19	0.44	0.65	0.14	0.92	0.08	0.22	0.46	0.04	0.21

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 104 (87%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 110

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.92

Intersection Signal Delay (s/veh): 35.3

Intersection LOS: D

Intersection Capacity Utilization 62.2%









ICU Level of Service B

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

	Ø1		Ø2 (R)		Ø3		Ø4
14 s		47 s		17 s		42 s	
	Ø5		Ø6 (R)		Ø7		Ø8
18 s		43 s		14 s		45 s	

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background PM w STIP




Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	26	739	4	606	496	620	26
Future Volume (vph)	26	739	4	606	496	620	26
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		2171		725	
Travel Time (s)		97.0		32.9		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	29	821	4	673	551	689	29
Shared Lane Traffic (%)							
Lane Group Flow (vph)	29	821	4	673	551	689	29
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	16.0	57.0	14.0	55.0	49.0	49.0	16.0
Total Split (%)	13.3%	47.5%	11.7%	45.8%	40.8%	40.8%	13.3%
Maximum Green (s)	9.0	50.0	7.0	48.0	42.0	42.0	9.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effect Green (s)	9.9	73.8	9.0	64.4	103.9	33.4	48.4
Actuated g/C Ratio	0.08	0.62	0.08	0.54	0.87	0.28	0.40
v/c Ratio	0.20	0.38	0.03	0.35	0.40	0.72	0.05
Control Delay (s/veh)	54.2	13.8	48.8	18.3	1.9	43.2	19.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	54.2	13.8	48.8	18.3	1.9	43.2	19.5

Lanes, Volumes, Timings

4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	D	B	D	B	A	D	B
Approach Delay (s/veh)		15.2		11.0		42.3	
Approach LOS		B		B		D	
Queue Length 50th (ft)	21	145	3	103	37	248	14
Queue Length 95th (ft)	52	286	m6	m209	m37	289	29
Internal Link Dist (ft)		6325		2091		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	165	2175	132	1899	1462	1258	654
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.18	0.38	0.03	0.35	0.38	0.55	0.04

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.72

Intersection Signal Delay (s/veh): 20.3

Intersection LOS: C

Intersection Capacity Utilization 47.6%

ICU Level of Service A

Analysis Period (min) 15









m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	2134	0	1925
Future Volume (vph)	0	0	0	2134	0	1925
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	233		716			681
Travel Time (s)	4.5		10.8			10.3
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2371	0	2139
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2371	0	2139
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	78.0%			ICU Level of Service D		
Analysis Period (min)	15					

Lanes, Volumes, Timings









8: Northern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	365	1769	0	0
Future Volume (vph)	0	0	365	1769	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	406	1966	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	406	1966	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	65.2%		ICU Level of Service C			
Analysis Period (min)	15					









Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1769	0	1560
Future Volume (vph)	0	0	0	1769	0	1560
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1966	0	1733
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1966	0	1733
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	57.9%			ICU Level of Service B		
Analysis Period (min)	15					










Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1612	0	1835
Future Volume (vph)	0	0	0	1612	0	1835
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1791	0	2039
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1791	0	2039
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	67.5%			ICU Level of Service C		
Analysis Period (min)	15					









Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						 
Traffic Volume (vph)	0	0	0	0	36	1799
Future Volume (vph)	0	0	0	0	36	1799
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	40	1999
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	40	1999
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	66.3%			ICU Level of Service C		
Analysis Period (min)	15					


Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1576	0	1799
Future Volume (vph)	0	0	0	1576	0	1799
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1751	0	1999
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1751	0	1999
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	58.5%			ICU Level of Service B		
Analysis Period (min)	15					

Lanes, Volumes, Timings
15: Rea Road

Deal Lake TIA
2029 Background PM w STIP











Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	1535	0	993	0	0
Future Volume (vph)	0	1535	0	993	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1706	0	1103	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1706	0	1103	0	0
Sign Control		Free	Free		Free	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	51.2%
Analysis Period (min)	15
	ICU Level of Service A









Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	0	77	916	0	0
Future Volume (vph)	0	0	77	916	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	86	1018	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	86	1018	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization 48.3%				ICU Level of Service A		
Analysis Period (min) 15						









Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	1458	0	916	0	0
Future Volume (vph)	0	1458	0	916	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1620	0	1018	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1620	0	1018	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	54.3%			ICU Level of Service A		
Analysis Period (min)	15					










Lanes, Volumes, Timings 19: Rea Road Extension

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	990	0	888	0	0
Future Volume (vph)	0	990	0	888	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1100	0	987	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1100	0	987	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	48.1%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings 20: Eastern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		 				
Traffic Volume (vph)	608	382	0	0	0	0
Future Volume (vph)	608	382	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	164			264	460	
Travel Time (s)	2.5			4.0	7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	676	424	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	676	424	0	0	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	46.4%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings 21: Rea Road Extension








Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	382	0	280	0	0
Future Volume (vph)	0	382	0	280	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	424	0	311	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	424	0	311	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type: Unsignalized						
Intersection Capacity Utilization 13.9%				ICU Level of Service A		
Analysis Period (min) 15						

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	365	0	0	0	0	1560
Future Volume (vph)	365	0	0	0	0	1560
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	406	0	0	0	0	1733
Shared Lane Traffic (%)						
Lane Group Flow (vph)	406	0	0	0	0	1733
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	24.0					66.0
Total Split (%)	26.7%					73.3%
Maximum Green (s)	17.0					59.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	17.1					62.9
Actuated g/C Ratio	0.19					0.70
v/c Ratio	0.62					0.70
Control Delay (s/veh)	29.0					10.3
Queue Delay	0.0					0.0
Total Delay (s/veh)	29.0					10.3
LOS	C					B
Approach Delay (s/veh)	29.0					10.3
Approach LOS	C					B

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	101					271
Queue Length 95th (ft)	m114					365
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	724					2473
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.56					0.70

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 0 (0%), Referenced to phase 6:SBT, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.70

Intersection Signal Delay (s/veh): 13.8

Intersection LOS: B


Intersection Capacity Utilization 65.2%

ICU Level of Service C

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	36	0	0	1576	0	0
Future Volume (vph)	36	0	0	1576	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	40	0	0	1751	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	40	0	0	1751	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	16.0			74.0		
Total Split (%)	17.8%			82.2%		
Maximum Green (s)	9.0			67.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	9.8			77.8		
Actuated g/C Ratio	0.11			0.86		
v/c Ratio	0.21			0.57		
Control Delay (s/veh)	34.9			4.1		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	34.9			4.1		
LOS	C			A		
Approach Delay (s/veh)	34.9			4.1		
Approach LOS	C			A		

Lanes, Volumes, Timings 102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	22			170		
Queue Length 95th (ft)	m29			242		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	216			3060		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.19			0.57		

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 84 (93%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.57

Intersection Signal Delay (s/veh): 4.8

Intersection LOS: A


Intersection Capacity Utilization 67.5%

ICU Level of Service C

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Background PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Volume (vph)	0	1458	0	0	77	0
Future Volume (vph)	0	1458	0	0	77	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Frts						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1620	0	0	86	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1620	0	0	86	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized










Intersection Capacity Utilization 72.3% ICU Level of Service C

Analysis Period (min) 15

Intersection						
Int Delay, s/veh	1					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	1458	0	0	77	0
Future Vol, veh/h	0	1458	0	0	77	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1620	0	0	86	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			810	-
Stage 1	-	-			0	-
Stage 2	-	-			810	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			318	0
Stage 1	0	-			-	0
Stage 2	0	-			398	0
Platoon blocked, %	-					
Mov Cap-1 Maneuver	-	-			318	-
Mov Cap-2 Maneuver	-	-			318	-
Stage 1	-	-			-	-
Stage 2	-	-			398	-
Approach	EB		SB			
HCM Control Delay, s/v	0		20.4			
HCM LOS			C			
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		318			
HCM Lane V/C Ratio	-		0.269			
HCM Control Delay (s/veh)	-		20.4			
HCM Lane LOS	-		C			
HCM 95th %tile Q (veh)	-		1.1			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	0	280	608	0
Future Volume (vph)	0	0	0	280	608	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	311	676	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	311	676	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	48.1%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Background PM w STIP

Intersection						
Int Delay, s/veh	18					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	280	608	0
Future Vol, veh/h	0	0	0	280	608	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	311	676	0
Major/Minor			Major2	Minor1		
Conflicting Flow All			-	-	156	-
Stage 1			-	-	0	-
Stage 2			-	-	156	-
Critical Hdwy			-	-	6.84	-
Critical Hdwy Stg 1			-	-	-	-
Critical Hdwy Stg 2			-	-	5.84	-
Follow-up Hdwy			-	-	3.52	-
Pot Cap-1 Maneuver			0	-	820	0
Stage 1			0	-	-	0
Stage 2			0	-	856	0
Platoon blocked, %				-		
Mov Cap-1 Maneuver			-	-	820	-
Mov Cap-2 Maneuver			-	-	820	-
Stage 1			-	-	-	-
Stage 2			-	-	856	-
Approach			WB	NB		
HCM Control Delay, s/v			0	26.3		
HCM LOS				D		
Minor Lane/Major Mvmt	NBLn1	WBT				
Capacity (veh/h)	820	-				
HCM Lane V/C Ratio	0.824	-				
HCM Control Delay (s/veh)	26.3	-				
HCM Lane LOS	D	-				
HCM 95th %tile Q (veh)	9.3	-				













2029 Build-out Conditions w/ STIPs

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Build AM w STIP


												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	552	448	0	362	423	0	1720	119	0	1172	1182
Future Volume (vph)	0	552	448	0	362	423	0	1720	119	0	1172	1182
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2815	0	3539	2787	0	3404	2680	0	3372	2801
Flt Permitted												
Satd. Flow (perm)	0	3575	2815	0	3539	2787	0	3404	2680	0	3372	2801
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	4%	2%
Adj. Flow (vph)	0	613	498	0	402	470	0	1911	132	0	1302	1313
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	613	498	0	402	470	0	1911	132	0	1302	1313
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		61.0	61.0		61.0	61.0
Total Split (%)		39.0%	39.0%		39.0%	39.0%		61.0%	61.0%		61.0%	61.0%
Maximum Green (s)		32.0	32.0		32.0	32.0		54.0	54.0		54.0	54.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		27.7	27.7		27.7	27.7		62.3	62.3		62.3	62.3
Actuated g/C Ratio		0.28	0.28		0.28	0.28		0.62	0.62		0.62	0.62
v/c Ratio		0.62	0.64		0.41	0.61		0.90	0.08		0.62	0.75

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Build AM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)		33.9	35.1		30.0	34.4		20.8	8.5		10.4	13.2
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		33.9	35.1		30.0	34.4		20.8	8.5		10.4	13.2
LOS		C	D		C	C		C	A		B	B
Approach Delay (s/veh)		34.4			32.4			20.0			11.8	
Approach LOS		C			C			B			B	
Queue Length 50th (ft)		177	156		108	146		314	17		164	204
Queue Length 95th (ft)		215	198		139	187		#800	m32		317	446
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1215	957		1203	947		2120	1669		2100	1744
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.50	0.52		0.33	0.50		0.90	0.08		0.62	0.75

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 17 (17%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.90

Intersection Signal Delay (s/veh): 20.8

Intersection LOS: C

Intersection Capacity Utilization 71.1%

ICU Level of Service C


Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings

2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	10	601	774	35	68	26
Future Volume (vph)	10	601	774	35	68	26
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.994		0.963	
Flt Protected	0.950				0.965	
Satd. Flow (prot)	1491	1801	1728	0	1463	0
Flt Permitted	0.950				0.965	
Satd. Flow (perm)	1491	1801	1728	0	1463	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	13%	2%	2%	2%	3%	38%
Adj. Flow (vph)	11	668	860	39	76	29
Shared Lane Traffic (%)						
Lane Group Flow (vph)	11	668	899	0	105	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 54.9% ICU Level of Service A

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build AM w STIP
























Intersection						
Int Delay, s/veh	1.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	10	601	774	35	68	26
Future Vol, veh/h	10	601	774	35	68	26
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	13	2	2	2	3	38
Mvmt Flow	11	668	860	39	76	29
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	899	0	-	0	1570	880
Stage 1	-	-	-	-	880	-
Stage 2	-	-	-	-	690	-
Critical Hdwy	4.23	-	-	-	6.43	6.58
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.317	-	-	-	3.527	3.642
Pot Cap-1 Maneuver	712	-	-	-	121	299
Stage 1	-	-	-	-	404	-
Stage 2	-	-	-	-	496	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	712	-	-	-	119	299
Mov Cap-2 Maneuver	-	-	-	-	255	-
Stage 1	-	-	-	-	398	-
Stage 2	-	-	-	-	496	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		27		
HCM LOS				D		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	712	-	-	-	266	
HCM Lane V/C Ratio	0.016	-	-	-	0.393	
HCM Control Delay (s/veh)	10.1	-	-	-	27	
HCM Lane LOS	B	-	-	-	D	
HCM 95th %tile Q (veh)	0	-	-	-	1.8	

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA

2029 Build AM w STIP

												
Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations												
Traffic Volume (vph)	29	91	857	144	105	1064	53	136	23	79	82	46
Future Volume (vph)	29	91	857	144	105	1064	53	136	23	79	82	46
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)			-2%			1%			2%			-2%
Storage Length (ft)		450		400	300		375	225		225	175	
Storage Lanes		1		1	1		1	1		1	1	
Taper Length (ft)		100			100			150			150	
Lane Util. Factor	0.95	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt				0.850			0.850			0.850		
Flt Protected		0.950			0.950			0.950			0.950	
Satd. Flow (prot)	0	1787	3540	1584	1710	3487	1502	1752	1844	1552	1753	1881
Flt Permitted		0.950			0.950			0.950			0.950	
Satd. Flow (perm)	0	1787	3540	1584	1710	3487	1502	1752	1844	1552	1753	1881
Right Turn on Red				No			No			No		
Satd. Flow (RTOR)												
Link Speed (mph)			45			45			45			45
Link Distance (ft)			1488			1019			1122			1136
Travel Time (s)			22.5			15.4			17.0			17.2
Peak Hour Factor	0.90	0.57	0.74	0.82	0.75	0.84	0.76	0.88	0.54	0.51	0.53	0.68
Heavy Vehicles (%)	2%	2%	3%	3%	5%	3%	7%	2%	2%	3%	4%	2%
Adj. Flow (vph)	32	160	1158	176	140	1267	70	155	43	155	155	68
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	192	1158	176	140	1267	70	155	43	155	155	68
Turn Type	Prot	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA
Protected Phases	5	5	2		1	6		3	8		7	4
Permitted Phases				2			6			8		
Detector Phase	5	5	2	2	1	6	6	3	8	8	7	4
Switch Phase												
Minimum Initial (s)	7.0	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0
Total Split (s)	21.0	21.0	60.0	60.0	19.0	58.0	58.0	19.0	42.0	42.0	19.0	42.0
Total Split (%)	15.0%	15.0%	42.9%	42.9%	13.6%	41.4%	41.4%	13.6%	30.0%	30.0%	13.6%	30.0%
Maximum Green (s)	14.0	14.0	53.0	53.0	12.0	51.0	51.0	12.0	35.0	35.0	12.0	35.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None
Walk Time (s)			7.0	7.0		7.0	7.0		7.0	7.0		7.0
Flash Don't Walk (s)			25.0	25.0		23.0	23.0		28.0	28.0		28.0
Pedestrian Calls (#/hr)			0	0		0	0		0	0		0
Act Effct Green (s)		18.5	58.4	58.4	15.2	55.2	55.2	14.0	32.3	32.3	14.0	32.3
Actuated g/C Ratio		0.13	0.42	0.42	0.11	0.39	0.39	0.10	0.23	0.23	0.10	0.23
v/c Ratio		0.81	0.78	0.27	0.75	0.92	0.12	0.89	0.10	0.43	0.89	0.16
Control Delay (s/veh)		87.5	33.7	25.7	85.0	52.7	28.8	105.1	40.8	49.0	105.1	42.2

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP

Lane Group	SBR
Lane Configurations	↗
Traffic Volume (vph)	171
Future Volume (vph)	171
Ideal Flow (vphpl)	1900
Grade (%)	
Storage Length (ft)	125
Storage Lanes	1
Taper Length (ft)	
Lane Util. Factor	1.00
Frt	0.850
Flt Protected	
Satd. Flow (prot)	1599
Flt Permitted	
Satd. Flow (perm)	1599
Right Turn on Red	No
Satd. Flow (RTOR)	
Link Speed (mph)	
Link Distance (ft)	
Travel Time (s)	
Peak Hour Factor	0.57
Heavy Vehicles (%)	2%
Adj. Flow (vph)	300
Shared Lane Traffic (%)	
Lane Group Flow (vph)	300
Turn Type	Perm
Protected Phases	
Permitted Phases	4
Detector Phase	4
Switch Phase	
Minimum Initial (s)	7.0
Minimum Split (s)	42.0
Total Split (s)	42.0
Total Split (%)	30.0%
Maximum Green (s)	35.0
Yellow Time (s)	5.0
All-Red Time (s)	2.0
Lost Time Adjust (s)	-2.0
Total Lost Time (s)	5.0
Lead/Lag	Lag
Lead-Lag Optimize?	
Vehicle Extension (s)	3.0
Recall Mode	None
Walk Time (s)	7.0
Flash Don't Walk (s)	28.0
Pedestrian Calls (#/hr)	0
Act Effct Green (s)	32.3
Actuated g/C Ratio	0.23
v/c Ratio	0.81
Control Delay (s/veh)	68.3



Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		87.5	33.7	25.7	85.0	52.7	28.8	105.1	40.8	49.0	105.1	42.2
LOS		F	C	C	F	D	C	F	D	D	F	D
Approach Delay (s/veh)			39.6			54.6			72.6			75.8
Approach LOS			D			D			E			E
Queue Length 50th (ft)		178	356	87	124	589	41	142	31	119	142	49
Queue Length 95th (ft)		164	343	128	#177	624	64	#265	37	97	124	66
Internal Link Dist (ft)			1408			939			1042			1056
Turn Bay Length (ft)		450		400	300		375	225		225	175	
Base Capacity (vph)		236	1477	661	186	1374	591	175	487	410	175	497
Starvation Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio		0.81	0.78	0.27	0.75	0.92	0.12	0.89	0.09	0.38	0.89	0.14

Intersection Summary

Area Type: Other

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 83 (59%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 120

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.92

Intersection Signal Delay (s/veh): 53.2

Intersection LOS: D

Intersection Capacity Utilization 70.8%

ICU Level of Service C

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

	Ø1		Ø2 (R)		Ø3		Ø4
19 s		60 s		19 s		42 s	
	Ø5		Ø6 (R)		Ø7		Ø8
21 s		58 s		19 s		42 s	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)


Deal Lake TIA
2029 Build AM w STIP



Lane Group	SBR
Queue Delay	0.0
Total Delay (s/veh)	68.3
LOS	E
Approach Delay (s/veh)	
Approach LOS	
Queue Length 50th (ft)	256
Queue Length 95th (ft)	203
Internal Link Dist (ft)	
Turn Bay Length (ft)	125
Base Capacity (vph)	422
Starvation Cap Reductn	0
Spillback Cap Reductn	0
Storage Cap Reductn	0
Reduced v/c Ratio	0.71
Intersection Summary	

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP




Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	22	614	9	759	636	499	22
Future Volume (vph)	22	614	9	759	636	499	22
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		877		725	
Travel Time (s)		97.0		13.3		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	24	682	10	843	707	554	24
Shared Lane Traffic (%)							
Lane Group Flow (vph)	24	682	10	843	707	554	24
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	16.0	65.0	14.0	63.0	61.0	61.0	16.0
Total Split (%)	11.4%	46.4%	10.0%	45.0%	43.6%	43.6%	11.4%
Maximum Green (s)	9.0	58.0	7.0	56.0	54.0	54.0	9.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effct Green (s)	9.9	94.6	9.2	85.5	123.9	32.4	47.3
Actuated g/C Ratio	0.07	0.68	0.07	0.61	0.89	0.23	0.34
v/c Ratio	0.19	0.29	0.09	0.39	0.50	0.70	0.04
Control Delay (s/veh)	64.5	10.9	77.4	8.0	1.1	53.7	28.6
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	64.5	10.9	77.4	8.0	1.1	53.7	28.6

Lanes, Volumes, Timings

4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	E	B	E	A	A	D	C
Approach Delay (s/veh)		12.7		5.3		52.7	
Approach LOS		B		A		D	
Queue Length 50th (ft)	21	111	10	90	8	240	15
Queue Length 95th (ft)	52	226	m10	m107	m15	282	33
Internal Link Dist (ft)		6325		797		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	141	2391	115	2160	1570	1373	549
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.17	0.29	0.09	0.39	0.45	0.40	0.04

Intersection Summary

Area Type: Other

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.70

Intersection Signal Delay (s/veh): 16.8

Intersection LOS: B


Intersection Capacity Utilization 53.5%

ICU Level of Service A

Analysis Period (min) 15

















m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	1111	11	0	1396	1	0	0	33	0	0	8
Future Volume (vph)	0	1111	11	0	1396	1	0	0	33	0	0	8
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.999							0.865			0.865
Flt Protected												
Satd. Flow (prot)	0	3502	0	0	3505	0	0	0	1611	0	0	1611
Flt Permitted												
Satd. Flow (perm)	0	3502	0	0	3505	0	0	0	1611	0	0	1611
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		877			829			1095			1030	
Travel Time (s)		13.3			12.6			29.9			28.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	3%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	0	1234	12	0	1551	1	0	0	37	0	0	9
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1246	0	0	1552	0	0	0	37	0	0	9
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	48.6%						ICU Level of Service A					
Analysis Period (min)	15											

HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP

Intersection												
Int Delay, s/veh	0.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	1111	11	0	1396	1	0	0	33	0	0	8
Future Vol, veh/h	0	1111	11	0	1396	1	0	0	33	0	0	8
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	3	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	0	1234	12	0	1551	1	0	0	37	0	0	9

Major/Minor	Major1		Major2		Minor1		Minor2	
Conflicting Flow All	-	0	0	-	-	0	-	623
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	*641
Stage 1	0	-	-	0	-	-	0	-
Stage 2	0	-	-	0	-	-	0	-
Platoon blocked, %	-	-	-	-	-	-	-	1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	*641
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-















Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0	11	12.2
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1
Capacity (veh/h)	641	-	-	-	-	510
HCM Lane V/C Ratio	0.057	-	-	-	-	0.017
HCM Control Delay (s/veh)	11	-	-	-	-	12.2
HCM Lane LOS	B	-	-	-	-	B
HCM 95th %tile Q (veh)	0.2	-	-	-	-	0.1

Notes			
-: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP

													
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	
Lane Configurations													
Traffic Volume (vph)	0	1142	2	0	1394	3	0	0	4	0	0	3	
Future Volume (vph)	0	1142	2	0	1394	3	0	0	4	0	0	3	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00	
Frt									0.865				0.865
Flt Protected													
Satd. Flow (prot)	0	3505	0	0	3505	0	0	0	1611	0	0	1611	
Flt Permitted													
Satd. Flow (perm)	0	3505	0	0	3505	0	0	0	1611	0	0	1611	
Link Speed (mph)	45				45				25				
Link Distance (ft)	829				1488				1046				
Travel Time (s)	12.6				22.5				28.5				
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	
Heavy Vehicles (%)	2%	3%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%	
Adj. Flow (vph)	0	1269	2	0	1549	3	0	0	4	0	0	3	
Shared Lane Traffic (%)													
Lane Group Flow (vph)	0	1271	0	0	1552	0	0	0	4	0	0	3	
Sign Control	Free				Free				Stop				
Intersection Summary													
Area Type:	Other												
Control Type:	Unsignalized												
Intersection Capacity Utilization	48.6%				ICU Level of Service A								
Analysis Period (min)	15												









HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM w STIP

Intersection												
Int Delay, s/veh	0											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	1142	2	0	1394	3	0	0	4	0	0	3
Future Vol, veh/h	0	1142	2	0	1394	3	0	0	4	0	0	3
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	3	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	0	1269	2	0	1549	3	0	0	4	0	0	3
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	-	0	0	-	-	0	-	-	636	-	-	776
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	-	6.94	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	-	3.32	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	0	*619	0	0	*510
Stage 1	0	-	-	0	-	-	0	0	-	0	0	-
Stage 2	0	-	-	0	-	-	0	0	-	0	0	-
Platoon blocked, %		-	-		-	-			1			1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	-	*619	-	-	*510
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			10.9			12.1		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1						
Capacity (veh/h)	619	-	-	-	-	510						
HCM Lane V/C Ratio	0.007	-	-	-	-	0.007						
HCM Control Delay (s/veh)	10.9	-	-	-	-	12.1						
HCM Lane LOS	B	-	-	-	-	B						
HCM 95th %tile Q (veh)	0	-	-	-	-	0						
Notes												
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon			

Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	2141	0	2354
Future Volume (vph)	0	0	0	2141	0	2354
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	233		716			681
Travel Time (s)	4.5		10.8			10.3
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2379	0	2616
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2379	0	2616
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	78.2%			ICU Level of Service D		
Analysis Period (min)	15					

Lanes, Volumes, Timings









8: Northern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	580	1561	0	0
Future Volume (vph)	0	0	580	1561	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	644	1734	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	644	1734	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	73.9%			ICU Level of Service D		
Analysis Period (min)	15					









Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1561	0	1774
Future Volume (vph)	0	0	0	1561	0	1774
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1734	0	1971
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1734	0	1971
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	65.4%			ICU Level of Service C		
Analysis Period (min)	15					










Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1839	0	1620
Future Volume (vph)	0	0	0	1839	0	1620
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2043	0	1800
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2043	0	1800
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	63.9%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						 
Traffic Volume (vph)	0	0	0	0	41	1579
Future Volume (vph)	0	0	0	0	41	1579
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	46	1754
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	46	1754
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	63.9%			ICU Level of Service B		
Analysis Period (min)	15					

Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1798	0	1579
Future Volume (vph)	0	0	0	1798	0	1579
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1998	0	1754
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1998	0	1754
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	66.2%			ICU Level of Service C		
Analysis Period (min)	15					

Lanes, Volumes, Timings
15: Rea Road









Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	1000	0	1544	0	0
Future Volume (vph)	0	1000	0	1544	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1111	0	1716	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1111	0	1716	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	57.3%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	0	83	1461	0	0
Future Volume (vph)	0	0	83	1461	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	92	1623	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	92	1623	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	33.3%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	0	917	0	1461	0	0
Future Volume (vph)	0	917	0	1461	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1019	0	1623	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1019	0	1623	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type: Unsignalized						
Intersection Capacity Utilization 43.7%				ICU Level of Service A		
Analysis Period (min) 15						









Lanes, Volumes, Timings 19: Rea Road Extension

Deal Lake TIA
2029 Build AM w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	671	0	785	0	0
Future Volume (vph)	0	671	0	785	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	746	0	872	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	746	0	872	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	39.1%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
20: Eastern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	385	286	0	0	0	0
Future Volume (vph)	385	286	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	164			264	460	
Travel Time (s)	2.5			4.0	7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	428	318	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	428	318	0	0	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	38.0%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings

21: Rea Road Extension








Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	286	0	400	0	0
Future Volume (vph)	0	286	0	400	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	318	0	444	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	318	0	444	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	17.3%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	580	0	0	0	0	1774
Future Volume (vph)	580	0	0	0	0	1774
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	644	0	0	0	0	1971
Shared Lane Traffic (%)						
Lane Group Flow (vph)	644	0	0	0	0	1971
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	29.0					71.0
Total Split (%)	29.0%					71.0%
Maximum Green (s)	22.0					64.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	23.2					66.8
Actuated g/C Ratio	0.23					0.67
v/c Ratio	0.81					0.83
Control Delay (s/veh)	34.9					16.8
Queue Delay	0.0					0.0
Total Delay (s/veh)	34.9					16.8
LOS	C					B
Approach Delay (s/veh)	34.9					16.8
Approach LOS	C					B

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	201					455
Queue Length 95th (ft)	m215					573
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	823					2365
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.78					0.83

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 99 (99%), Referenced to phase 6: SBT, Start of Green

Natural Cycle: 60

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.83

Intersection Signal Delay (s/veh): 21.2

Intersection LOS: C


Intersection Capacity Utilization 73.9%

ICU Level of Service D

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	41	0	0	1798	0	0
Future Volume (vph)	41	0	0	1798	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	46	0	0	1998	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	46	0	0	1998	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	14.0			86.0		
Total Split (%)	14.0%			86.0%		
Maximum Green (s)	7.0			79.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	9.0			88.6		
Actuated g/C Ratio	0.09			0.89		
v/c Ratio	0.29			0.64		
Control Delay (s/veh)	45.3			4.1		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	45.3			4.1		
LOS	D			A		
Approach Delay (s/veh)	45.3			4.1		
Approach LOS	D			A		

Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	26			218		
Queue Length 95th (ft)	m47			275		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	159			3135		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.29			0.64		

Intersection Summary

Area Type: Other

Cycle Length: 100

Actuated Cycle Length: 100

Offset: 18 (18%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 60

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.64

Intersection Signal Delay (s/veh): 5.0

Intersection LOS: A


Intersection Capacity Utilization 63.9%

ICU Level of Service B

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Build AM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↑	
Traffic Volume (vph)	0	917	0	0	83	0
Future Volume (vph)	0	917	0	0	83	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Fr _t						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1019	0	0	92	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1019	0	0	92	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized










Intersection Capacity Utilization 72.4% ICU Level of Service C

Analysis Period (min) 15

Intersection						
Int Delay, s/veh	1.2					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	917	0	0	83	0
Future Vol, veh/h	0	917	0	0	83	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1019	0	0	92	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			510	-
Stage 1	-	-			0	-
Stage 2	-	-			510	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			493	0
Stage 1	0	-			-	0
Stage 2	0	-			568	0
Platoon blocked, %		-				
Mov Cap-1 Maneuver	-	-			493	-
Mov Cap-2 Maneuver	-	-			493	-
Stage 1	-	-			-	-
Stage 2	-	-			568	-
Approach	EB		SB			
HCM Control Delay, s/v	0				14	
HCM LOS					B	
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		493			
HCM Lane V/C Ratio	-		0.187			
HCM Control Delay (s/veh)	-		14			
HCM Lane LOS	-		B			
HCM 95th %tile Q (veh)	-		0.7			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Build AM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	0	400	385	0
Future Volume (vph)	0	0	0	400	385	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	444	428	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	444	428	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	39.1%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Build AM w STIP

Intersection						
Int Delay, s/veh	7.9					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	400	385	0
Future Vol, veh/h	0	0	0	400	385	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	444	428	0

Major/Minor	Major2	Minor1
Conflicting Flow All	-	222
Stage 1	-	0
Stage 2	-	222
Critical Hdwy	-	6.84
Critical Hdwy Stg 1	-	-
Critical Hdwy Stg 2	-	5.84
Follow-up Hdwy	-	3.52
Pot Cap-1 Maneuver	0	746
Stage 1	0	-
Stage 2	0	794
Platoon blocked, %	-	-
Mov Cap-1 Maneuver	-	746
Mov Cap-2 Maneuver	-	746
Stage 1	-	-
Stage 2	-	794

Approach	WB	NB
HCM Control Delay, s/v	0	16.1
HCM LOS		C













Minor Lane/Major Mvmt	NBLn1	WBT
Capacity (veh/h)	746	-
HCM Lane V/C Ratio	0.573	-
HCM Control Delay (s/veh)	16.1	-
HCM Lane LOS	C	-
HCM 95th %tile Q (veh)	3.7	-













Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Build MID w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	847	569	0	360	530	0	1214	194	0	996	645
Future Volume (vph)	0	847	569	0	360	530	0	1214	194	0	996	645
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2787	0	3539	2787	0	3371	2680	0	3438	2773
Flt Permitted												
Satd. Flow (perm)	0	3575	2787	0	3539	2787	0	3371	2680	0	3438	2773
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	3%	2%	2%	2%	2%	3%	2%	2%	2%	3%
Adj. Flow (vph)	0	941	632	0	400	589	0	1349	216	0	1107	717
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	941	632	0	400	589	0	1349	216	0	1107	717
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		41.0	41.0		41.0	41.0
Total Split (%)		48.8%	48.8%		48.8%	48.8%		51.3%	51.3%		51.3%	51.3%
Maximum Green (s)		32.0	32.0		32.0	32.0		34.0	34.0		34.0	34.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		31.6	31.6		31.6	31.6		38.4	38.4		38.4	38.4
Actuated g/C Ratio		0.40	0.40		0.40	0.40		0.48	0.48		0.48	0.48
v/c Ratio		0.67	0.57		0.29	0.53		0.83	0.17		0.67	0.54

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)		22.2	20.9		16.6	20.2		20.5	11.9		14.3	12.7
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		22.2	20.9		16.6	20.2		20.5	11.9		14.3	12.7
LOS		C	C		B	C		C	B		B	B
Approach Delay (s/veh)		21.6			18.7			19.3			13.6	
Approach LOS		C			B			B			B	
Queue Length 50th (ft)		186	128		65	118		190	30		140	97
Queue Length 95th (ft)		248	182		97	168		#243	47		193	123
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1519	1184		1504	1184		1616	1285		1648	1329
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.62	0.53		0.27	0.50		0.83	0.17		0.67	0.54

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 16 (20%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 80

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.83

Intersection Signal Delay (s/veh): 18.1

Intersection LOS: B

Intersection Capacity Utilization 65.3%


ICU Level of Service C

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	19	769	481	136	67	7
Future Volume (vph)	19	769	481	136	67	7
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.970		0.987	
Flt Protected	0.950				0.957	
Satd. Flow (prot)	1574	1801	1645	0	1642	0
Flt Permitted	0.950				0.957	
Satd. Flow (perm)	1574	1801	1645	0	1642	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	7%	2%	5%	3%	2%	2%
Adj. Flow (vph)	21	854	534	151	74	8
Shared Lane Traffic (%)						
Lane Group Flow (vph)	21	854	685	0	82	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 51.3% ICU Level of Service A

Analysis Period (min) 15
























HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build MID w STIP

Intersection						
Int Delay, s/veh	1.3					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	19	769	481	136	67	7
Future Vol, veh/h	19	769	481	136	67	7
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	7	2	5	3	2	2
Mvmt Flow	21	854	534	151	74	8
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	685	0	-	0	1506	610
Stage 1	-	-	-	-	610	-
Stage 2	-	-	-	-	896	-
Critical Hdwy	4.17	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.263	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	885	-	-	-	133	494
Stage 1	-	-	-	-	542	-
Stage 2	-	-	-	-	399	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	885	-	-	-	130	494
Mov Cap-2 Maneuver	-	-	-	-	265	-
Stage 1	-	-	-	-	529	-
Stage 2	-	-	-	-	399	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		23.4		
HCM LOS	C					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	885	-	-	-	277	
HCM Lane V/C Ratio	0.024	-	-	-	0.297	
HCM Control Delay (s/veh)	9.2	-	-	-	23.4	
HCM Lane LOS	A	-	-	-	C	
HCM 95th %tile Q (veh)	0.1	-	-	-	1.2	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

												
Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations												
Traffic Volume (vph)	20	80	784	102	99	531	175	114	156	75	127	131
Future Volume (vph)	20	80	784	102	99	531	175	114	156	75	127	131
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)			-2%			1%			2%			-2%
Storage Length (ft)		450		400	300		375	225		225	175	
Storage Lanes		1		1	1		1	1		1	1	
Taper Length (ft)		100			100			150			150	
Lane Util. Factor	0.95	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt				0.850			0.850			0.850		
Flt Protected		0.950			0.950			0.950			0.950	
Satd. Flow (prot)	0	1787	3506	1599	1744	3454	1530	1735	1809	1523	1787	1863
Flt Permitted		0.950			0.950			0.950			0.950	
Satd. Flow (perm)	0	1787	3506	1599	1744	3454	1530	1735	1809	1523	1787	1863
Right Turn on Red				No			No			No		
Satd. Flow (RTOR)												
Link Speed (mph)			45			45			45			45
Link Distance (ft)			1488			1019			1122			1136
Travel Time (s)			22.5			15.4			17.0			17.2
Peak Hour Factor	0.90	0.73	0.86	0.91	0.75	0.85	0.74	0.82	0.70	0.71	0.78	0.57
Heavy Vehicles (%)	2%	2%	4%	2%	3%	4%	5%	3%	4%	5%	2%	3%
Adj. Flow (vph)	22	110	912	112	132	625	236	139	223	106	163	230
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	132	912	112	132	625	236	139	223	106	163	230
Turn Type	Prot	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA
Protected Phases	5	5	2		1	6		3	8		7	4
Permitted Phases				2			6			8		
Detector Phase	5	5	2	2	1	6	6	3	8	8	7	4
Switch Phase												
Minimum Initial (s)	7.0	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0
Total Split (s)	20.0	20.0	42.0	42.0	17.0	39.0	39.0	18.0	42.0	42.0	19.0	43.0
Total Split (%)	16.7%	16.7%	35.0%	35.0%	14.2%	32.5%	32.5%	15.0%	35.0%	35.0%	15.8%	35.8%
Maximum Green (s)	13.0	13.0	35.0	35.0	10.0	32.0	32.0	11.0	35.0	35.0	12.0	36.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None
Walk Time (s)			7.0	7.0		7.0	7.0		7.0	7.0		7.0
Flash Don't Walk (s)			25.0	25.0		23.0	23.0		28.0	28.0		28.0
Pedestrian Calls (#/hr)			0	0		0	0		0	0		0
Act Effct Green (s)		16.1	47.1	47.1	16.2	47.2	47.2	12.8	22.9	22.9	13.8	23.9
Actuated g/C Ratio		0.13	0.39	0.39	0.14	0.39	0.39	0.11	0.19	0.19	0.12	0.20
v/c Ratio		0.55	0.66	0.18	0.56	0.46	0.39	0.76	0.65	0.37	0.80	0.62
Control Delay (s/veh)		60.0	27.4	22.6	57.6	30.4	31.5	77.6	53.0	44.3	78.6	50.5

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

Lane Group	SBR
Lane Configurations	↗
Traffic Volume (vph)	51
Future Volume (vph)	51
Ideal Flow (vphpl)	1900
Grade (%)	
Storage Length (ft)	125
Storage Lanes	1
Taper Length (ft)	
Lane Util. Factor	1.00
Frt	0.850
Flt Protected	
Satd. Flow (prot)	1599
Flt Permitted	
Satd. Flow (perm)	1599
Right Turn on Red	No
Satd. Flow (RTOR)	
Link Speed (mph)	
Link Distance (ft)	
Travel Time (s)	
Peak Hour Factor	0.49
Heavy Vehicles (%)	2%
Adj. Flow (vph)	104
Shared Lane Traffic (%)	
Lane Group Flow (vph)	104
Turn Type	Perm
Protected Phases	
Permitted Phases	4
Detector Phase	4
Switch Phase	
Minimum Initial (s)	7.0
Minimum Split (s)	42.0
Total Split (s)	43.0
Total Split (%)	35.8%
Maximum Green (s)	36.0
Yellow Time (s)	5.0
All-Red Time (s)	2.0
Lost Time Adjust (s)	-2.0
Total Lost Time (s)	5.0
Lead/Lag	Lag
Lead-Lag Optimize?	
Vehicle Extension (s)	3.0
Recall Mode	None
Walk Time (s)	7.0
Flash Don't Walk (s)	28.0
Pedestrian Calls (#/hr)	0
Act Effct Green (s)	23.9
Actuated g/C Ratio	0.20
v/c Ratio	0.33
Control Delay (s/veh)	42.4



Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		60.0	27.4	22.6	57.6	30.4	31.5	77.6	53.0	44.3	78.6	50.5
LOS		E	C	C	E	C	C	E	D	D	E	D
Approach Delay (s/veh)			30.6			34.3			58.3			58.0
Approach LOS			C			C			E			E
Queue Length 50th (ft)		104	216	45	96	187	130	106	161	72	125	164
Queue Length 95th (ft)		131	273	88	131	267	188	#173	169	90	#182	135
Internal Link Dist (ft)			1408			939			1042			1056
Turn Bay Length (ft)		450		400	300		375	225		225	175	
Base Capacity (vph)		255	1375	627	236	1357	601	187	557	469	208	589
Starvation Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio		0.52	0.66	0.18	0.56	0.46	0.39	0.74	0.40	0.23	0.78	0.39

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 87 (73%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 110

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.80

Intersection Signal Delay (s/veh): 40.3

Intersection LOS: D

Intersection Capacity Utilization 59.4%


ICU Level of Service B

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)


Deal Lake TIA
2029 Build MID w STIP



Lane Group	SBR
Queue Delay	0.0
Total Delay (s/veh)	42.4
LOS	D
Approach Delay (s/veh)	
Approach LOS	
Queue Length 50th (ft)	69
Queue Length 95th (ft)	58
Internal Link Dist (ft)	
Turn Bay Length (ft)	125
Base Capacity (vph)	506
Starvation Cap Reductn	0
Spillback Cap Reductn	0
Storage Cap Reductn	0
Reduced v/c Ratio	0.21
Intersection Summary	

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP




Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	22	534	14	384	314	452	21
Future Volume (vph)	22	534	14	384	314	452	21
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		877		725	
Travel Time (s)		97.0		13.3		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	24	593	16	427	349	502	23
Shared Lane Traffic (%)							
Lane Group Flow (vph)	24	593	16	427	349	502	23
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	19.0	52.0	19.0	52.0	49.0	49.0	19.0
Total Split (%)	15.8%	43.3%	15.8%	43.3%	40.8%	40.8%	15.8%
Maximum Green (s)	12.0	45.0	12.0	45.0	42.0	42.0	12.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effect Green (s)	9.7	78.3	9.3	75.2	107.9	25.7	40.4
Actuated g/C Ratio	0.08	0.65	0.08	0.63	0.90	0.21	0.34
v/c Ratio	0.17	0.26	0.12	0.19	0.25	0.68	0.04
Control Delay (s/veh)	53.9	10.8	56.1	8.9	0.6	47.9	24.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	53.9	10.8	56.1	8.9	0.6	47.9	24.5

Lanes, Volumes, Timings

4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	D	B	E	A	A	D	C
Approach Delay (s/veh)		12.5		6.2		46.9	
Approach LOS		B		A		D	
Queue Length 50th (ft)	18	78	13	54	8	185	12
Queue Length 95th (ft)	45	173	m27	70	6	227	28
Internal Link Dist (ft)		6325		797		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	206	2309	206	2217	1544	1258	590
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.26	0.08	0.19	0.23	0.40	0.04

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.68

Intersection Signal Delay (s/veh): 19.2

Intersection LOS: B


Intersection Capacity Utilization 39.5%

ICU Level of Service A

Analysis Period (min) 15















m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	969	31	0	709	2	0	0	19	0	0	4
Future Volume (vph)	0	969	31	0	709	2	0	0	19	0	0	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.995							0.865			0.865
Flt Protected												
Satd. Flow (prot)	0	3456	0	0	3471	0	0	0	1611	0	0	1611
Flt Permitted												
Satd. Flow (perm)	0	3456	0	0	3471	0	0	0	1611	0	0	1611
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		877			829			1095			1026	
Travel Time (s)		13.3			12.6			29.9			28.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	4%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	0	1077	34	0	788	2	0	0	21	0	0	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1111	0	0	790	0	0	0	21	0	0	4
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	37.8%						ICU Level of Service A					
Analysis Period (min)	15											















HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

Intersection												
Int Delay, s/veh	0.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	969	31	0	709	2	0	0	19	0	0	4
Future Vol, veh/h	0	969	31	0	709	2	0	0	19	0	0	4
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	4	2	2	4	2	2	2	2	2	2	2
Mvmt Flow	0	1077	34	0	788	2	0	0	21	0	0	4
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	-	0	0	-	-	0	-	-	556	-	-	395
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	-	6.94	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	-	3.32	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	0	*695	0	0	*797
Stage 1	0	-	-	0	-	-	0	0	-	0	0	-
Stage 2	0	-	-	0	-	-	0	0	-	0	0	-
Platoon blocked, %		-	-		-	-			1			1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	-	*695	-	-	*797
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			10.3			9.5		
HCM LOS							B			A		
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1						
Capacity (veh/h)	695	-	-	-	-	797						
HCM Lane V/C Ratio	0.03	-	-	-	-	0.006						
HCM Control Delay (s/veh)	10.3	-	-	-	-	9.5						
HCM Lane LOS	B	-	-	-	-	A						
HCM 95th %tile Q (veh)	0.1	-	-	-	-	0						
Notes												
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon			

Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	984	4	0	708	8	0	0	2	0	0	2
Future Volume (vph)	0	984	4	0	708	8	0	0	2	0	0	2
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.999			0.998				0.865			0.865
Flt Protected												
Satd. Flow (prot)	0	3468	0	0	3465	0	0	0	1611	0	0	1611
Flt Permitted												
Satd. Flow (perm)	0	3468	0	0	3465	0	0	0	1611	0	0	1611
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		829			1488			1046			1028	
Travel Time (s)		12.6			22.5			28.5			28.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	4%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	0	1093	4	0	787	9	0	0	2	0	0	2
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1097	0	0	796	0	0	0	2	0	0	2
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	37.3%						ICU Level of Service A					
Analysis Period (min)	15											

HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MID w STIP

Intersection												
Int Delay, s/veh	0											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	984	4	0	708	8	0	0	2	0	0	2
Future Vol, veh/h	0	984	4	0	708	8	0	0	2	0	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	4	2	2	4	2	2	2	2	2	2	2
Mvmt Flow	0	1093	4	0	787	9	0	0	2	0	0	2

Major/Minor	Major1		Major2		Minor1		Minor2	
Conflicting Flow All	-	0	0	-	-	0	-	549
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	*695
Stage 1	0	-	-	0	-	-	0	-
Stage 2	0	-	-	0	-	-	0	-
Platoon blocked, %	-	-	-	-	-	-	-	1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	*695
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-









Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0	10.2	9.5
HCM LOS			B	A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1
Capacity (veh/h)	695	-	-	-	-	797
HCM Lane V/C Ratio	0.003	-	-	-	-	0.003
HCM Control Delay (s/veh)	10.2	-	-	-	-	9.5
HCM Lane LOS	B	-	-	-	-	A
HCM 95th %tile Q (veh)	0	-	-	-	-	0

Notes			
-: Volume exceeds capacity	\$. Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1744	0	1641
Future Volume (vph)	0	0	0	1744	0	1641
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	233		716			681
Travel Time (s)	4.5		10.8			10.3
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1938	0	1823
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1938	0	1823
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	64.3%			ICU Level of Service C		
Analysis Period (min)	15					

Lanes, Volumes, Timings









8: Northern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	307	1437	0	0
Future Volume (vph)	0	0	307	1437	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	341	1597	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	341	1597	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	54.0%		ICU Level of Service A			
Analysis Period (min)	15					







Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	0	0	0	1437	0	1334
Future Volume (vph)	0	0	0	1437	0	1334
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1597	0	1482
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1597	0	1482
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	50.0%			ICU Level of Service A		
Analysis Period (min)	15					











Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations				↑↑		↑↑
Traffic Volume (vph)	0	0	0	1408	0	1565
Future Volume (vph)	0	0	0	1408	0	1565
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Fr _t						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1564	0	1739
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1564	0	1739
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	58.1%			ICU Level of Service B		
Analysis Period (min)	15					









Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						  
Traffic Volume (vph)	0	0	0	0	62	1503
Future Volume (vph)	0	0	0	0	62	1503
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	69	1670
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	69	1670
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	55.9%			ICU Level of Service B		
Analysis Period (min)	15					

Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1346	0	1503
Future Volume (vph)	0	0	0	1346	0	1503
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1496	0	1670
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1496	0	1670
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	50.4%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
15: Rea Road










Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	1416	0	1005	0	0
Future Volume (vph)	0	1416	0	1005	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1573	0	1117	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1573	0	1117	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	48.5%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	96	909	0	0
Future Volume (vph)	0	0	96	909	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	107	1010	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	107	1010	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.5%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Build MID w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	1320	0	909	0	0
Future Volume (vph)	0	1320	0	909	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1467	0	1010	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1467	0	1010	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	49.5%			ICU Level of Service A		
Analysis Period (min)	15					









Lanes, Volumes, Timings
19: Rea Road Extension

Deal Lake TIA
2029 Build MID w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	1041	0	890	0	0
Future Volume (vph)	0	1041	0	890	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1157	0	989	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1157	0	989	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.7%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
20: Eastern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	485	556	0	0	0	0
Future Volume (vph)	485	556	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	164			264	460	
Travel Time (s)	2.5			4.0	7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	539	618	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	539	618	0	0	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	43.4%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings

21: Rea Road Extension









Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	556	0	405	0	0
Future Volume (vph)	0	556	0	405	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	618	0	450	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	618	0	450	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type: Unsignalized						
Intersection Capacity Utilization 18.7%				ICU Level of Service A		
Analysis Period (min) 15						

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	307	0	0	0	0	1334
Future Volume (vph)	307	0	0	0	0	1334
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	341	0	0	0	0	1482
Shared Lane Traffic (%)						
Lane Group Flow (vph)	341	0	0	0	0	1482
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	21.0					59.0
Total Split (%)	26.3%					73.8%
Maximum Green (s)	14.0					52.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	14.5					55.5
Actuated g/C Ratio	0.18					0.69
v/c Ratio	0.55					0.60
Control Delay (s/veh)	26.0					8.0
Queue Delay	0.0					0.0
Total Delay (s/veh)	26.0					8.0
LOS	C					A
Approach Delay (s/veh)	26.0					8.0
Approach LOS	C					A

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	74					178
Queue Length 95th (ft)	m91					243
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	686					2456
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.50					0.60

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 1 (1%), Referenced to phase 6:SBT, Start of Green

Natural Cycle: 40

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.60

Intersection Signal Delay (s/veh): 11.3

Intersection LOS: B


Intersection Capacity Utilization 54.0%

ICU Level of Service A

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	62	0	0	1346	0	0
Future Volume (vph)	62	0	0	1346	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	69	0	0	1496	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	69	0	0	1496	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	16.0			64.0		
Total Split (%)	20.0%			80.0%		
Maximum Green (s)	9.0			57.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	10.1			63.7		
Actuated g/C Ratio	0.13			0.80		
v/c Ratio	0.31			0.53		
Control Delay (s/veh)	32.6			4.8		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	32.6			4.8		
LOS	C			A		
Approach Delay (s/veh)	32.6			4.8		
Approach LOS	C			A		

Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	31			137		
Queue Length 95th (ft)	m53			186		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	243			2816		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.28			0.53		

Intersection Summary

Area Type: Other

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 12 (15%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 40

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.53

Intersection Signal Delay (s/veh): 6.0

Intersection LOS: A


Intersection Capacity Utilization 58.1%

ICU Level of Service B

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Build MID w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↑	
Traffic Volume (vph)	0	1320	0	0	96	0
Future Volume (vph)	0	1320	0	0	96	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Frts						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1467	0	0	107	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1467	0	0	107	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized










Intersection Capacity Utilization 68.3% ICU Level of Service C

Analysis Period (min) 15

Intersection						
Int Delay, s/veh	1.3					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	1320	0	0	96	0
Future Vol, veh/h	0	1320	0	0	96	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1467	0	0	107	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			734	-
Stage 1	-	-			0	-
Stage 2	-	-			734	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			355	0
Stage 1	0	-			-	0
Stage 2	0	-			436	0
Platoon blocked, %	-					
Mov Cap-1 Maneuver	-	-			355	-
Mov Cap-2 Maneuver	-	-			355	-
Stage 1	-	-			-	-
Stage 2	-	-			436	-
Approach	EB		SB			
HCM Control Delay, s/v	0		19.4			
HCM LOS			C			
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		355			
HCM Lane V/C Ratio	-		0.3			
HCM Control Delay (s/veh)	-		19.4			
HCM Lane LOS	-		C			
HCM 95th %tile Q (veh)	-		1.2			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Build MID w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	0	405	485	0
Future Volume (vph)	0	0	0	405	485	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	450	539	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	450	539	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	44.7%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Build MID w STIP


Intersection						
Int Delay, s/veh	11.7					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	405	485	0
Future Vol, veh/h	0	0	0	405	485	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	450	539	0
Major/Minor	Major2		Minor1			
Conflicting Flow All			-	-	225	-
Stage 1			-	-	0	-
Stage 2			-	-	225	-
Critical Hdwy			-	-	6.84	-
Critical Hdwy Stg 1			-	-	-	-
Critical Hdwy Stg 2			-	-	5.84	-
Follow-up Hdwy			-	-	3.52	-
Pot Cap-1 Maneuver			0	-	743	0
Stage 1			0	-	-	0
Stage 2			0	-	791	0
Platoon blocked, %			-			
Mov Cap-1 Maneuver			-	-	743	-
Mov Cap-2 Maneuver			-	-	743	-
Stage 1			-	-	-	-
Stage 2			-	-	791	-
Approach	WB		NB			
HCM Control Delay, s/v	0		21.5			
HCM LOS			C			
Minor Lane/Major Mvmt	NBLn1	WBT				
Capacity (veh/h)	743	-				
HCM Lane V/C Ratio	0.725	-				
HCM Control Delay (s/veh)	21.5	-				
HCM Lane LOS	C	-				
HCM 95th %tile Q (veh)	6.3	-				

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Build PM w STIP













												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑		↑↑	↑↑
Traffic Volume (vph)	0	887	662	0	254	646	0	1498	124	0	1181	749
Future Volume (vph)	0	887	662	0	254	646	0	1498	124	0	1181	749
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	12	12	12	12	12	11	11	11	12	11	12
Grade (%)		-2%			0%			1%			-1%	
Storage Length (ft)	0		750	0		425	0		375	0		500
Storage Lanes	0		2	0		2	0		2	0		2
Taper Length (ft)	0			25			0			0		
Lane Util. Factor	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88	1.00	0.95	0.88
Frt			0.850			0.850			0.850			0.850
Flt Protected												
Satd. Flow (prot)	0	3575	2815	0	3539	2787	0	3404	2680	0	3438	2801
Flt Permitted												
Satd. Flow (perm)	0	3575	2815	0	3539	2787	0	3404	2680	0	3438	2801
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		910			646			587			716	
Travel Time (s)		13.8			9.8			8.9			10.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	986	736	0	282	718	0	1664	138	0	1312	832
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	986	736	0	282	718	0	1664	138	0	1312	832
Turn Type		NA	Perm		NA	Perm		NA	Perm		NA	Perm
Protected Phases		4			8			2			6	
Permitted Phases			4			8			2			6
Detector Phase		4	4		8	8		2	2		6	6
Switch Phase												
Minimum Initial (s)		7.0	7.0		7.0	7.0		12.0	12.0		12.0	12.0
Minimum Split (s)		38.0	38.0		39.0	39.0		40.0	40.0		40.0	40.0
Total Split (s)		39.0	39.0		39.0	39.0		51.0	51.0		51.0	51.0
Total Split (%)		43.3%	43.3%		43.3%	43.3%		56.7%	56.7%		56.7%	56.7%
Maximum Green (s)		32.0	32.0		32.0	32.0		44.0	44.0		44.0	44.0
Yellow Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
All-Red Time (s)		2.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0		-2.0	-2.0
Total Lost Time (s)		5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0
Lead/Lag												
Lead-Lag Optimize?												
Vehicle Extension (s)		3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0
Recall Mode		None	None		None	None		C-Max	C-Max		C-Max	C-Max
Walk Time (s)		7.0	7.0		7.0	7.0		7.0	7.0		7.0	7.0
Flash Don't Walk (s)		24.0	24.0		25.0	25.0		26.0	26.0		26.0	26.0
Pedestrian Calls (#/hr)		0	0		0	0		0	0		0	0
Act Effct Green (s)		33.1	33.1		33.1	33.1		46.9	46.9		46.9	46.9
Actuated g/C Ratio		0.37	0.37		0.37	0.37		0.52	0.52		0.52	0.52
v/c Ratio		0.75	0.71		0.22	0.70		0.94	0.10		0.73	0.57
Control Delay (s/veh)		29.0	28.7		19.8	28.4		28.0	10.9		14.7	12.2

Lanes, Volumes, Timings

1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Deal Lake TIA

2029 Build PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Queue Delay		0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0
Total Delay (s/veh)		29.0	28.7		19.8	28.4		28.0	10.9		14.7	12.2
LOS		C	C		B	C		C	B		B	B
Approach Delay (s/veh)		28.8			26.0			26.7			13.8	
Approach LOS		C			C			C			B	
Queue Length 50th (ft)		249	196		55	190		237	19		211	111
Queue Length 95th (ft)		323	268		84	260		#623	34		269	152
Internal Link Dist (ft)		830			566			507			636	
Turn Bay Length (ft)			750			425			375			500
Base Capacity (vph)		1350	1063		1336	1052		1773	1396		1791	1459
Starvation Cap Reductn		0	0		0	0		0	0		0	0
Spillback Cap Reductn		0	0		0	0		0	0		0	0
Storage Cap Reductn		0	0		0	0		0	0		0	0
Reduced v/c Ratio		0.73	0.69		0.21	0.68		0.94	0.10		0.73	0.57

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 18 (20%), Referenced to phase 2:NBT and 6:SBT, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.94

Intersection Signal Delay (s/veh): 23.0

Intersection LOS: C

Intersection Capacity Utilization 74.3%


ICU Level of Service D

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	30	774	608	67	33	11
Future Volume (vph)	30	774	608	67	33	11
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.987		0.967	
Flt Protected	0.950				0.964	
Satd. Flow (prot)	1652	1801	1686	0	1586	0
Flt Permitted	0.950				0.964	
Satd. Flow (perm)	1652	1801	1686	0	1586	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1162		1160	
Travel Time (s)		18.2	17.6		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	4%	2%	3%	8%
Adj. Flow (vph)	33	860	676	74	37	12
Shared Lane Traffic (%)						
Lane Group Flow (vph)	33	860	750	0	49	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 50.7% ICU Level of Service A

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road
























Deal Lake TIA
2029 Build PM w STIP

Intersection						
Int Delay, s/veh	0.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	30	774	608	67	33	11
Future Vol, veh/h	30	774	608	67	33	11
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	4	2	3	8
Mvmt Flow	33	860	676	74	37	12
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	750	0	-	0	1639	713
Stage 1	-	-	-	-	713	-
Stage 2	-	-	-	-	926	-
Critical Hdwy	4.12	-	-	-	6.43	6.28
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.218	-	-	-	3.527	3.372
Pot Cap-1 Maneuver	859	-	-	-	110	422
Stage 1	-	-	-	-	484	-
Stage 2	-	-	-	-	384	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	859	-	-	-	106	422
Mov Cap-2 Maneuver	-	-	-	-	240	-
Stage 1	-	-	-	-	466	-
Stage 2	-	-	-	-	384	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.3	0		21.3		
HCM LOS				C		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	859	-	-	-	269	
HCM Lane V/C Ratio	0.039	-	-	-	0.182	
HCM Control Delay (s/veh)	9.4	-	-	-	21.3	
HCM Lane LOS	A	-	-	-	C	
HCM 95th %tile Q (veh)	0.1	-	-	-	0.7	

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

												
Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations												
Traffic Volume (vph)	23	171	1063	138	78	870	81	149	46	103	52	23
Future Volume (vph)	23	171	1063	138	78	870	81	149	46	103	52	23
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Grade (%)			-2%			1%			2%			-2%
Storage Length (ft)		450		400	300		375	225		225	175	
Storage Lanes		1		1	1		1	1		1	1	
Taper Length (ft)		100			100			150			150	
Lane Util. Factor	0.95	1.00	0.95	1.00	1.00	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt				0.850			0.850			0.850		
Flt Protected		0.950			0.950			0.950			0.950	
Satd. Flow (prot)	0	1772	3575	1599	1744	3487	1575	1735	1844	1568	1688	1881
Flt Permitted		0.950			0.950			0.950			0.950	
Satd. Flow (perm)	0	1772	3575	1599	1744	3487	1575	1735	1844	1568	1688	1881
Right Turn on Red				No			No			No		
Satd. Flow (RTOR)												
Link Speed (mph)			45			45			45			45
Link Distance (ft)			1492			1019			1122			1136
Travel Time (s)			22.6			15.4			17.0			17.2
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	3%	2%	2%	3%	3%	2%	3%	2%	2%	8%	2%
Adj. Flow (vph)	26	190	1181	153	87	967	90	166	51	114	58	26
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	216	1181	153	87	967	90	166	51	114	58	26
Turn Type	Prot	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA
Protected Phases	5	5	2		1	6		3	8		7	4
Permitted Phases				2			6			8		
Detector Phase	5	5	2	2	1	6	6	3	8	8	7	4
Switch Phase												
Minimum Initial (s)	7.0	7.0	12.0	12.0	7.0	12.0	12.0	7.0	7.0	7.0	7.0	7.0
Minimum Split (s)	14.0	14.0	39.0	39.0	14.0	37.0	37.0	14.0	42.0	42.0	14.0	42.0
Total Split (s)	20.0	20.0	47.0	47.0	14.0	41.0	41.0	18.0	45.0	45.0	14.0	41.0
Total Split (%)	16.7%	16.7%	39.2%	39.2%	11.7%	34.2%	34.2%	15.0%	37.5%	37.5%	11.7%	34.2%
Maximum Green (s)	13.0	13.0	40.0	40.0	7.0	34.0	34.0	11.0	38.0	38.0	7.0	34.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)		-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag
Lead-Lag Optimize?												
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	C-Max	C-Max	None	C-Max	C-Max	None	None	None	None	None
Walk Time (s)			7.0	7.0		7.0	7.0		7.0	7.0		7.0
Flash Don't Walk (s)			25.0	25.0		23.0	23.0		28.0	28.0		28.0
Pedestrian Calls (#/hr)			0	0		0	0		0	0		0
Act Effct Green (s)		24.5	57.9	57.9	13.7	47.0	47.0	13.0	22.3	22.3	9.0	15.5
Actuated g/C Ratio		0.20	0.48	0.48	0.11	0.39	0.39	0.11	0.19	0.19	0.08	0.13
v/c Ratio		0.60	0.69	0.20	0.44	0.71	0.15	0.89	0.15	0.39	0.46	0.11
Control Delay (s/veh)		48.7	22.8	17.3	55.8	35.5	26.7	95.0	42.5	47.7	65.5	45.0

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

Lane Group	SBR
Lane Configurations	↗
Traffic Volume (vph)	93
Future Volume (vph)	93
Ideal Flow (vphpl)	1900
Grade (%)	
Storage Length (ft)	125
Storage Lanes	1
Taper Length (ft)	
Lane Util. Factor	1.00
Frt	0.850
Flt Protected	
Satd. Flow (prot)	1539
Flt Permitted	
Satd. Flow (perm)	1539
Right Turn on Red	No
Satd. Flow (RTOR)	
Link Speed (mph)	
Link Distance (ft)	
Travel Time (s)	
Peak Hour Factor	0.90
Heavy Vehicles (%)	6%
Adj. Flow (vph)	103
Shared Lane Traffic (%)	
Lane Group Flow (vph)	103
Turn Type	Perm
Protected Phases	
Permitted Phases	4
Detector Phase	4
Switch Phase	
Minimum Initial (s)	7.0
Minimum Split (s)	42.0
Total Split (s)	41.0
Total Split (%)	34.2%
Maximum Green (s)	34.0
Yellow Time (s)	5.0
All-Red Time (s)	2.0
Lost Time Adjust (s)	-2.0
Total Lost Time (s)	5.0
Lead/Lag	Lag
Lead-Lag Optimize?	
Vehicle Extension (s)	3.0
Recall Mode	None
Walk Time (s)	7.0
Flash Don't Walk (s)	28.0
Pedestrian Calls (#/hr)	0
Act Effct Green (s)	15.5
Actuated g/C Ratio	0.13
v/c Ratio	0.52
Control Delay (s/veh)	57.3



Lane Group	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		48.7	22.8	17.3	55.8	35.5	26.7	95.0	42.5	47.7	65.5	45.0
LOS		D	C	B	E	D	C	F	D	D	E	D
Approach Delay (s/veh)			25.8			36.3			70.7			58.1
Approach LOS			C			D			E			E
Queue Length 50th (ft)		166	273	58	64	328	45	129	34	81	44	18
Queue Length 95th (ft)		226	399	121	113	#468	93	#258	68	133	89	44
Internal Link Dist (ft)			1412			939			1042			1056
Turn Bay Length (ft)		450		400	300		375	225		225	175	
Base Capacity (vph)		361	1723	770	198	1366	617	187	614	522	126	564
Starvation Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio		0.60	0.69	0.20	0.44	0.71	0.15	0.89	0.08	0.22	0.46	0.05

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 91 (76%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 110

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.89

Intersection Signal Delay (s/veh): 36.1

Intersection LOS: D

Intersection Capacity Utilization 65.6%


ICU Level of Service C

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP



Lane Group	SBR
Queue Delay	0.0
Total Delay (s/veh)	57.3
LOS	E
Approach Delay (s/veh)	
Approach LOS	
Queue Length 50th (ft)	76
Queue Length 95th (ft)	128
Internal Link Dist (ft)	
Turn Bay Length (ft)	125
Base Capacity (vph)	461
Starvation Cap Reductn	0
Spillback Cap Reductn	0
Storage Cap Reductn	0
Reduced v/c Ratio	0.22
Intersection Summary	

Lanes, Volumes, Timings
4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
Lane Configurations							
Traffic Volume (vph)	26	760	17	618	505	633	26
Future Volume (vph)	26	760	17	618	505	633	26
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425		425		400	325	125
Storage Lanes	1		1		1	1	1
Taper Length (ft)	100		100			100	
Lane Util. Factor	1.00	0.95	1.00	0.95	1.00	0.97	1.00
Frt					0.850		0.850
Flt Protected	0.950		0.950			0.950	
Satd. Flow (prot)	1770	3539	1770	3539	1583	3433	1583
Flt Permitted	0.950		0.950			0.950	
Satd. Flow (perm)	1770	3539	1770	3539	1583	3433	1583
Right Turn on Red					No		No
Satd. Flow (RTOR)							
Link Speed (mph)		45		45		45	
Link Distance (ft)		6405		877		725	
Travel Time (s)		97.0		13.3		11.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	29	844	19	687	561	703	29
Shared Lane Traffic (%)							
Lane Group Flow (vph)	29	844	19	687	561	703	29
Turn Type	Prot	NA	Prot	NA	pm+ov	Prot	pm+ov
Protected Phases	5	2	1	6	7	7	5
Permitted Phases					6		7
Detector Phase	5	2	1	6	7	7	5
Switch Phase							
Minimum Initial (s)	7.0	12.0	7.0	12.0	7.0	7.0	7.0
Minimum Split (s)	14.0	19.0	14.0	41.0	36.0	36.0	14.0
Total Split (s)	16.0	56.0	16.0	56.0	48.0	48.0	16.0
Total Split (%)	13.3%	46.7%	13.3%	46.7%	40.0%	40.0%	13.3%
Maximum Green (s)	9.0	49.0	9.0	49.0	41.0	41.0	9.0
Yellow Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
All-Red Time (s)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Lost Time Adjust (s)	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0
Total Lost Time (s)	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag	Lead	Lag	Lead	Lag			Lead
Lead-Lag Optimize?							
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	C-Max	None	C-Max	None	None	None
Walk Time (s)				7.0	7.0	7.0	
Flash Don't Walk (s)				27.0	22.0	22.0	
Pedestrian Calls (#/hr)				0	0	0	
Act Effect Green (s)	9.9	70.1	9.5	64.0	103.9	33.8	48.8
Actuated g/C Ratio	0.08	0.58	0.08	0.53	0.87	0.28	0.41
v/c Ratio	0.20	0.41	0.14	0.36	0.41	0.73	0.05
Control Delay (s/veh)	54.2	16.6	62.0	11.9	1.2	43.2	19.3
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	54.2	16.6	62.0	11.9	1.2	43.2	19.3

Lanes, Volumes, Timings

4: Rea Road Extension & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBU	WBT	WBR	SBL	SBR
LOS	D	B	E	B	A	D	B
Approach Delay (s/veh)		17.8		7.9		42.2	
Approach LOS		B		A		D	
Queue Length 50th (ft)	21	152	15	78	5	254	14
Queue Length 95th (ft)	52	307	m24	m117	m17	294	29
Internal Link Dist (ft)		6325		797		645	
Turn Bay Length (ft)	425		425		400	325	125
Base Capacity (vph)	165	2066	162	1888	1447	1230	659
Starvation Cap Reductn	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0
Reduced v/c Ratio	0.18	0.41	0.12	0.36	0.39	0.57	0.04

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:EBT and 6:WBT, Start of Green

Natural Cycle: 95

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.73

Intersection Signal Delay (s/veh): 19.7

Intersection LOS: B

Intersection Capacity Utilization 48.0%

ICU Level of Service A

Analysis Period (min) 15

















m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Rea Road Extension & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	1373	37	0	1135	3	0	0	21	0	0	5
Future Volume (vph)	0	1373	37	0	1135	3	0	0	21	0	0	5
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.996							0.865			0.865
Flt Protected												
Satd. Flow (prot)	0	3525	0	0	3505	0	0	0	1611	0	0	1611
Flt Permitted												
Satd. Flow (perm)	0	3525	0	0	3505	0	0	0	1611	0	0	1611
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		877			829			1095			1028	
Travel Time (s)		13.3			12.6			29.9			28.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	0	1526	41	0	1261	3	0	0	23	0	0	6
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1567	0	0	1264	0	0	0	23	0	0	6
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	49.1%						ICU Level of Service A					
Analysis Period (min)	15											















HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

Intersection												
Int Delay, s/veh	0.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	1373	37	0	1135	3	0	0	21	0	0	5
Future Vol, veh/h	0	1373	37	0	1135	3	0	0	21	0	0	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	0	1526	41	0	1261	3	0	0	23	0	0	6
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	-	0	0	-	-	0	-	-	784	-	-	632
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	-	6.94	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	-	3.32	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	0	*516	0	0	*618
Stage 1	0	-	-	0	-	-	0	0	-	0	0	-
Stage 2	0	-	-	0	-	-	0	0	-	0	0	-
Platoon blocked, %		-	-		-	-			1			1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	-	*516	-	-	*618
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			12.3			10.9		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1						
Capacity (veh/h)	516	-	-	-	-	618						
HCM Lane V/C Ratio	0.045	-	-	-	-	0.009						
HCM Control Delay (s/veh)	12.3	-	-	-	-	10.9						
HCM Lane LOS	B	-	-	-	-	B						
HCM 95th %tile Q (veh)	0.1	-	-	-	-	0						
Notes												
~: Volume exceeds capacity		\$: Delay exceeds 300s				+: Computation Not Defined				*: All major volume in platoon		

Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	1389	5	0	1136	9	0	0	3	0	0	2
Future Volume (vph)	0	1389	5	0	1136	9	0	0	3	0	0	2
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.999			0.999				0.865			0.865
Flt Protected												
Satd. Flow (prot)	0	3536	0	0	3502	0	0	0	1611	0	0	1611
Flt Permitted												
Satd. Flow (perm)	0	3536	0	0	3502	0	0	0	1611	0	0	1611
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		829			1492			1046			1028	
Travel Time (s)		12.6			22.6			28.5			28.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	0	1543	6	0	1262	10	0	0	3	0	0	2
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1549	0	0	1272	0	0	0	3	0	0	2
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	48.6%						ICU Level of Service A					
Analysis Period (min)	15											









HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM w STIP

Intersection												
Int Delay, s/veh	0											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↑↑			↑↑				↑			↑
Traffic Vol, veh/h	0	1389	5	0	1136	9	0	0	3	0	0	2
Future Vol, veh/h	0	1389	5	0	1136	9	0	0	3	0	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	0	-	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	0	1543	6	0	1262	10	0	0	3	0	0	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	-	0	0	-	-	0	-	-	775	-	-	636
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	-	-	-	-	-	-	6.94	-	-	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	-	-	-	-	-	-	3.32	-	-	3.32
Pot Cap-1 Maneuver	0	-	-	0	-	-	0	0	*516	0	0	*618
Stage 1	0	-	-	0	-	-	0	0	-	0	0	-
Stage 2	0	-	-	0	-	-	0	0	-	0	0	-
Platoon blocked, %		-	-		-	-			1			1
Mov Cap-1 Maneuver	-	-	-	-	-	-	-	-	*516	-	-	*618
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			12			10.8		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBT	WBR	SBLn1						
Capacity (veh/h)	516	-	-	-	-	618						
HCM Lane V/C Ratio	0.006	-	-	-	-	0.004						
HCM Control Delay (s/veh)	12	-	-	-	-	10.8						
HCM Lane LOS	B	-	-	-	-	B						
HCM 95th %tile Q (veh)	0	-	-	-	-	0						
Notes												
~: Volume exceeds capacity		\$: Delay exceeds 300s				+: Computation Not Defined				*: All major volume in platoon		

Lanes, Volumes, Timings
7: S Providence Road (NC 16)









Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	2137	0	1930
Future Volume (vph)	0	0	0	2137	0	1930
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	233		716			681
Travel Time (s)	4.5		10.8			10.3
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	2374	0	2144
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	2374	0	2144
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	78.1%			ICU Level of Service D		
Analysis Period (min)	15					

Lanes, Volumes, Timings







8: Northern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	365	1772	0	0
Future Volume (vph)	0	0	365	1772	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	0.95	0.88	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	3539	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	0	3539	2787	0	0
Link Speed (mph)	35		45			45
Link Distance (ft)	1544		233			454
Travel Time (s)	30.1		3.5			6.9
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	406	1969	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	406	1969	0	0
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	65.3%			ICU Level of Service C		
Analysis Period (min)	15					







Lanes, Volumes, Timings
9: S Providence Road (NC 16)

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations				↑↑		↑↑
Traffic Volume (vph)	0	0	0	1772	0	1565
Future Volume (vph)	0	0	0	1772	0	1565
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Frt						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	1094			1544	1022	
Travel Time (s)	21.3			23.4	15.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1969	0	1739
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1969	0	1739
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	58.1%			ICU Level of Service B		
Analysis Period (min)	15					










Lanes, Volumes, Timings
11: S Providence Road (NC 16)

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations				↑↑		↑↑
Traffic Volume (vph)	0	0	0	1622	0	1843
Future Volume (vph)	0	0	0	1622	0	1843
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	0.88
Fr _t						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	3539	0	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	3539	0	2787
Link Speed (mph)	35			45	45	
Link Distance (ft)	153			579	587	
Travel Time (s)	3.0			8.8	8.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1802	0	2048
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1802	0	2048
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	67.8%			ICU Level of Service C		
Analysis Period (min)	15					








Lanes, Volumes, Timings 12: Southern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						 
Traffic Volume (vph)	0	0	0	0	41	1802
Future Volume (vph)	0	0	0	0	41	1802
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	0.88
Fr _t						0.850
Flt Protected						
Satd. Flow (prot)	0	0	0	0	1863	2787
Flt Permitted						
Satd. Flow (perm)	0	0	0	0	1863	2787
Link Speed (mph)	45			35	45	
Link Distance (ft)	1018			449	153	
Travel Time (s)	15.4			8.7	2.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	0	46	2002
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	46	2002
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	66.4%			ICU Level of Service C		
Analysis Period (min)	15					

Lanes, Volumes, Timings
13: S Providence Road (NC 16)

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	0	0	0	1581	0	1802
Future Volume (vph)	0	0	0	1581	0	1802
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.88	1.00	0.95
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	0	0	0	2787	0	3539
Flt Permitted						
Satd. Flow (perm)	0	0	0	2787	0	3539
Link Speed (mph)	35		45			45
Link Distance (ft)	580		1041			1018
Travel Time (s)	11.3		15.8			15.4
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	1757	0	2002
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	1757	0	2002
Sign Control	Free		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	58.6%			ICU Level of Service B		
Analysis Period (min)	15					

Lanes, Volumes, Timings
15: Rea Road

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	1549	0	1002	0	0
Future Volume (vph)	0	1549	0	1002	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		406	910		187	
Travel Time (s)		6.2	13.8		2.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1721	0	1113	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1721	0	1113	0	0
Sign Control		Free	Free		Free	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	51.7%
Analysis Period (min)	15
	ICU Level of Service A

Lanes, Volumes, Timings
16: Western U-turn Bulb & Rea Road

Deal Lake TIA
2029 Build PM w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations			↘	↗		
Traffic Volume (vph)	0	0	80	922	0	0
Future Volume (vph)	0	0	80	922	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected			0.950			
Satd. Flow (prot)	0	0	1770	3539	0	0
Flt Permitted			0.950			
Satd. Flow (perm)	0	0	1770	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	462			187	223	
Travel Time (s)	7.0			2.8	3.4	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	89	1024	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	89	1024	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization 48.6%				ICU Level of Service A		
Analysis Period (min) 15						

Lanes, Volumes, Timings
17: Rea Road

Deal Lake TIA
2029 Build PM w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	1469	0	922	0	0
Future Volume (vph)	0	1469	0	922	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	1324			462	242	
Travel Time (s)	20.1			7.0	3.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1632	0	1024	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1632	0	1024	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	54.7%			ICU Level of Service A		
Analysis Period (min)	15					









Lanes, Volumes, Timings 19: Rea Road Extension

Deal Lake TIA
2029 Build PM w STIP

	→	↘	↙	←	↖	↗
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations		↗↗		↖↖		
Traffic Volume (vph)	0	1011	0	900	0	0
Future Volume (vph)	0	1011	0	900	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	0.95	1.00	1.00
Frt		0.850				
Flt Protected						
Satd. Flow (prot)	0	2787	0	3539	0	0
Flt Permitted						
Satd. Flow (perm)	0	2787	0	3539	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	646			423	164	
Travel Time (s)	9.8			6.4	2.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1123	0	1000	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1123	0	1000	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	48.4%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
20: Eastern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	608	403	0	0	0	0
Future Volume (vph)	608	403	0	0	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.88	1.00	1.00	1.00	1.00
Frt	0.850					
Flt Protected						
Satd. Flow (prot)	1863	2787	0	0	0	0
Flt Permitted						
Satd. Flow (perm)	1863	2787	0	0	0	0
Link Speed (mph)	45			45	45	
Link Distance (ft)	164			264	460	
Travel Time (s)	2.5			4.0	7.0	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	676	448	0	0	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	676	448	0	0	0	0
Sign Control	Free			Free	Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	46.7%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
21: Rea Road Extension








Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑		↑↑		
Traffic Volume (vph)	0	403	0	292	0	0
Future Volume (vph)	0	403	0	292	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	0.88	1.00	1.00
Frt				0.850		
Flt Protected						
Satd. Flow (prot)	0	3539	0	2787	0	0
Flt Permitted						
Satd. Flow (perm)	0	3539	0	2787	0	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		460	6405		203	
Travel Time (s)		7.0	97.0		3.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	448	0	324	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	448	0	324	0	0
Sign Control		Free	Free		Free	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	14.5%			ICU Level of Service A		
Analysis Period (min)	15					

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	365	0	0	0	0	1565
Future Volume (vph)	365	0	0	0	0	1565
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	450	0		0	0	
Storage Lanes	0	0		0	0	
Taper Length (ft)	100				25	
Lane Util. Factor	0.97	1.00	1.00	1.00	1.00	0.95
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	3433	0	0	0	0	3539
Flt Permitted	0.950					
Satd. Flow (perm)	3433	0	0	0	0	3539
Right Turn on Red	No	No		No		
Satd. Flow (RTOR)						
Link Speed (mph)	35		45			45
Link Distance (ft)	454		681			1094
Travel Time (s)	8.8		10.3			16.6
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	406	0	0	0	0	1739
Shared Lane Traffic (%)						
Lane Group Flow (vph)	406	0	0	0	0	1739
Turn Type	Prot					NA
Protected Phases	3					6
Permitted Phases						
Detector Phase	3					6
Switch Phase						
Minimum Initial (s)	7.0					12.0
Minimum Split (s)	14.0					19.0
Total Split (s)	23.0					67.0
Total Split (%)	25.6%					74.4%
Maximum Green (s)	16.0					60.0
Yellow Time (s)	5.0					5.0
All-Red Time (s)	2.0					2.0
Lost Time Adjust (s)	-2.0					-2.0
Total Lost Time (s)	5.0					5.0
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0					3.0
Recall Mode	None					C-Max
Act Effct Green (s)	16.7					63.3
Actuated g/C Ratio	0.19					0.70
v/c Ratio	0.64					0.70
Control Delay (s/veh)	29.8					10.0
Queue Delay	0.0					0.0
Total Delay (s/veh)	29.8					10.0
LOS	C					A
Approach Delay (s/veh)	29.8					10.0
Approach LOS	C					A

Lanes, Volumes, Timings
101: S Providence Road (NC 16) & Northern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Queue Length 50th (ft)	102					272
Queue Length 95th (ft)	m118					352
Internal Link Dist (ft)	374		601			1014
Turn Bay Length (ft)	450					
Base Capacity (vph)	686					2488
Starvation Cap Reductn	0					0
Spillback Cap Reductn	0					0
Storage Cap Reductn	0					0
Reduced v/c Ratio	0.59					0.70

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 2 (2%), Referenced to phase 6:SBT, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.70

Intersection Signal Delay (s/veh): 13.7

Intersection LOS: B


Intersection Capacity Utilization 65.3%

ICU Level of Service C

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 101: S Providence Road (NC 16) & Northern U-turn Bulb



Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Volume (vph)	41	0	0	1581	0	0
Future Volume (vph)	41	0	0	1581	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)	425	0	0			0
Storage Lanes	0	0	0			0
Taper Length (ft)	100		25			
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected	0.950					
Satd. Flow (prot)	1770	0	0	3539	0	0
Flt Permitted	0.950					
Satd. Flow (perm)	1770	0	0	3539	0	0
Right Turn on Red	No	No				No
Satd. Flow (RTOR)						
Link Speed (mph)	35			45	45	
Link Distance (ft)	449			580	579	
Travel Time (s)	8.7			8.8	8.8	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	46	0	0	1757	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	46	0	0	1757	0	0
Turn Type	Prot			NA		
Protected Phases	7			2		
Permitted Phases						
Detector Phase	7			2		
Switch Phase						
Minimum Initial (s)	7.0			12.0		
Minimum Split (s)	14.0			19.0		
Total Split (s)	16.0			74.0		
Total Split (%)	17.8%			82.2%		
Maximum Green (s)	9.0			67.0		
Yellow Time (s)	5.0			5.0		
All-Red Time (s)	2.0			2.0		
Lost Time Adjust (s)	-2.0			-2.0		
Total Lost Time (s)	5.0			5.0		
Lead/Lag						
Lead-Lag Optimize?						
Vehicle Extension (s)	3.0			3.0		
Recall Mode	None			C-Max		
Act Effct Green (s)	9.9			77.7		
Actuated g/C Ratio	0.11			0.86		
v/c Ratio	0.24			0.58		
Control Delay (s/veh)	39.0			4.2		
Queue Delay	0.0			0.0		
Total Delay (s/veh)	39.0			4.2		
LOS	D			A		
Approach Delay (s/veh)	39.0			4.2		
Approach LOS	D			A		

Lanes, Volumes, Timings
102: S Providence Road (NC 16) & Southern U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBR	NBL	NBT	SBT	SBR
Queue Length 50th (ft)	24			175		
Queue Length 95th (ft)	m35			245		
Internal Link Dist (ft)	369			500	499	
Turn Bay Length (ft)	425					
Base Capacity (vph)	216			3055		
Starvation Cap Reductn	0			0		
Spillback Cap Reductn	0			0		
Storage Cap Reductn	0			0		
Reduced v/c Ratio	0.21			0.58		

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 15 (17%), Referenced to phase 2:NBT, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.58

Intersection Signal Delay (s/veh): 5.1

Intersection LOS: A


Intersection Capacity Utilization 67.8%

ICU Level of Service C

Analysis Period (min) 15

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 102: S Providence Road (NC 16) & Southern U-turn Bulb



Lanes, Volumes, Timings
103: Rea Road & Western U-turn Bulb

Deal Lake TIA
2029 Build PM w STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↑	
Traffic Volume (vph)	0	1469	0	0	80	0
Future Volume (vph)	0	1469	0	0	80	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	0.95	1.00	1.00	1.00	1.00
Fr _t						
Flt Protected					0.950	
Satd. Flow (prot)	0	3539	0	0	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	3539	0	0	1770	0
Link Speed (mph)		45	45		35	
Link Distance (ft)		242	406		223	
Travel Time (s)		3.7	6.2		4.3	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	1632	0	0	89	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	1632	0	0	89	0
Sign Control		Free	Free		Stop	










Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	72.8%
Analysis Period (min)	15
	ICU Level of Service C

Intersection						
Int Delay, s/veh	1.1					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑↑			↓	
Traffic Vol, veh/h	0	1469	0	0	80	0
Future Vol, veh/h	0	1469	0	0	80	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	1632	0	0	89	0
Major/Minor	Major1		Minor2			
Conflicting Flow All	-	0			816	-
Stage 1	-	-			0	-
Stage 2	-	-			816	-
Critical Hdwy	-	-			6.84	-
Critical Hdwy Stg 1	-	-			-	-
Critical Hdwy Stg 2	-	-			5.84	-
Follow-up Hdwy	-	-			3.52	-
Pot Cap-1 Maneuver	0	-			315	0
Stage 1	0	-			-	0
Stage 2	0	-			395	0
Platoon blocked, %		-				
Mov Cap-1 Maneuver	-	-			315	-
Mov Cap-2 Maneuver	-	-			315	-
Stage 1	-	-			-	-
Stage 2	-	-			395	-
Approach	EB		SB			
HCM Control Delay, s/v	0		20.9			
HCM LOS			C			
Minor Lane/Major Mvmt	EBT SBLn1					
Capacity (veh/h)	-		315			
HCM Lane V/C Ratio	-		0.282			
HCM Control Delay (s/veh)	-		20.9			
HCM Lane LOS	-		C			
HCM 95th %tile Q (veh)	-		1.1			

Lanes, Volumes, Timings
104: Eastern U-turn Bulb & Rea Road Extension

Deal Lake TIA
2029 Build PM w STIP

						
Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				 		
Traffic Volume (vph)	0	0	0	292	608	0
Future Volume (vph)	0	0	0	292	608	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	0		500	0
Storage Lanes		0	0		0	0
Taper Length (ft)			25		100	
Lane Util. Factor	1.00	1.00	1.00	0.95	1.00	1.00
Frt						
Flt Protected					0.950	
Satd. Flow (prot)	0	0	0	3539	1770	0
Flt Permitted					0.950	
Satd. Flow (perm)	0	0	0	3539	1770	0
Link Speed (mph)	45			45	35	
Link Distance (ft)	423			203	264	
Travel Time (s)	6.4			3.1	5.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	0	0	0	324	676	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	324	676	0
Sign Control	Free			Free	Stop	
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	48.4%			ICU Level of Service A		
Analysis Period (min)	15					

HCM 6th TWSC
104: Eastern U-turn Bulb & Rea Road Extension
















Deal Lake TIA
2029 Build PM w STIP

Intersection						
Int Delay, s/veh	18.3					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations				↑↑	↑	
Traffic Vol, veh/h	0	0	0	292	608	0
Future Vol, veh/h	0	0	0	292	608	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	0	0	324	676	0
Major/Minor		Major2		Minor1		
Conflicting Flow All			-	-	162	-
Stage 1			-	-	0	-
Stage 2			-	-	162	-
Critical Hdwy			-	-	6.84	-
Critical Hdwy Stg 1			-	-	-	-
Critical Hdwy Stg 2			-	-	5.84	-
Follow-up Hdwy			-	-	3.52	-
Pot Cap-1 Maneuver			0	-	813	0
Stage 1			0	-	-	0
Stage 2			0	-	850	0
Platoon blocked, %			-			
Mov Cap-1 Maneuver			-	-	813	-
Mov Cap-2 Maneuver			-	-	813	-
Stage 1			-	-	-	-
Stage 2			-	-	850	-
Approach			WB		NB	
HCM Control Delay, s/v			0		27.1	
HCM LOS					D	
Minor Lane/Major Mvmt	NBLn1	WBT				
Capacity (veh/h)	813	-				
HCM Lane V/C Ratio	0.831	-				
HCM Control Delay (s/veh)	27.1	-				
HCM Lane LOS	D	-				
HCM 95th %tile Q (veh)	9.5	-				

2029 Background Conditions
w/o STIPs

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background AM wo STIP

								
Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations								
Traffic Volume (vph)	4	388	224	415	1056	4	499	359
Future Volume (vph)	4	388	224	415	1056	4	499	359
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1546	3302	3522	1719	1836	1591
Flt Permitted		0.950		0.950		0.241		
Satd. Flow (perm)	0	1728	1546	3302	3522	436	1836	1591
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								399
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	4%	2%
Adj. Flow (vph)	4	431	249	461	1173	4	554	399
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	435	249	461	1173	4	554	399
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	32.0	32.0	20.0	20.0	58.0	38.0	38.0	38.0
Total Split (%)	35.6%	35.6%	22.2%	22.2%	64.4%	42.2%	42.2%	42.2%
Maximum Green (s)	25.6	25.6	13.4	13.4	51.6	31.5	31.5	31.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effct Green (s)		25.5	45.6	15.1	54.5	34.4	34.4	34.4
Actuated g/C Ratio		0.28	0.51	0.17	0.61	0.38	0.38	0.38
v/c Ratio		0.89	0.32	0.83	0.55	0.02	0.79	0.47

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background AM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay (s/veh)		52.3	14.0	50.8	12.1	19.0	35.3	4.2
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		52.3	14.0	50.8	12.1	19.0	35.3	4.2
LOS		D	B	D	B	B	D	A
Approach Delay (s/veh)		38.4			23.0		22.2	
Approach LOS		D			C		C	
Queue Length 50th (ft)		230	76	132	199	1	281	0
Queue Length 95th (ft)		#392	126	#209	256	9	#457	57
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		518	786	559	2131	166	701	854
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		0.84	0.32	0.82	0.55	0.02	0.79	0.47

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 29 (32%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 75

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.89

Intersection Signal Delay (s/veh): 26.0

Intersection LOS: C

Intersection Capacity Utilization 73.4%


ICU Level of Service D

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background AM wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	9	441	804	117	132	9
Future Volume (vph)	9	441	804	117	132	9
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.983		0.991	
Flt Protected	0.950				0.955	
Satd. Flow (prot)	1491	1801	1709	0	1595	0
Flt Permitted	0.950				0.955	
Satd. Flow (perm)	1491	1801	1709	0	1595	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	13%	2%	2%	2%	3%	38%
Adj. Flow (vph)	10	490	893	130	147	10
Shared Lane Traffic (%)						
Lane Group Flow (vph)	10	490	1023	0	157	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 63.9% ICU Level of Service B

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background AM wo STIP

Intersection						
Int Delay, s/veh	3.5					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	9	441	804	117	132	9
Future Vol, veh/h	9	441	804	117	132	9
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	13	2	2	2	3	38
Mvmt Flow	10	490	893	130	147	10

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	1023	0	0 1468 958
Stage 1	-	-	- 958 -
Stage 2	-	-	- 510 -
Critical Hdwy	4.23	-	- 6.43 6.58
Critical Hdwy Stg 1	-	-	- 5.43 -
Critical Hdwy Stg 2	-	-	- 5.43 -
Follow-up Hdwy	2.317	-	- 3.527 3.642
Pot Cap-1 Maneuver	638	-	- ~ 140 268
Stage 1	-	-	- 371 -
Stage 2	-	-	- 601 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	638	-	- ~ 138 268
Mov Cap-2 Maneuver	-	-	- 265 -
Stage 1	-	-	- 365 -
Stage 2	-	-	- 601 -

Approach	EB	WB	SB
HCM Control Delay, s/v	0.2	0	36.5
HCM LOS			E




















Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	638	-	-	-	265
HCM Lane V/C Ratio	0.016	-	-	-	0.591
HCM Control Delay (s/veh)	10.7	-	-	-	36.5
HCM Lane LOS	B	-	-	-	E
HCM 95th %tile Q (veh)	0	-	-	-	3.5

Notes			
-: Volume exceeds capacity	\$. Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Lanes, Volumes, Timings













3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Background AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	88	466	66	43	577	97	237	82	148	257	96	131
Future Volume (vph)	88	466	66	43	577	97	237	82	148	257	96	131
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.983			0.976			0.945			0.964	
Flt Protected	0.950			0.950				0.981			0.972	
Satd. Flow (prot)	1728	1770	0	1653	1721	0	0	1589	0	0	1627	0
Flt Permitted	0.950			0.950				0.571			0.510	
Satd. Flow (perm)	1728	1770	0	1653	1721	0	0	925	0	0	854	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.57	0.74	0.82	0.75	0.84	0.76	0.88	0.54	0.51	0.53	0.68	0.57
Heavy Vehicles (%)	2%	3%	3%	5%	3%	7%	2%	2%	3%	4%	2%	2%
Adj. Flow (vph)	154	630	80	57	687	128	269	152	290	485	141	230
Shared Lane Traffic (%)												
Lane Group Flow (vph)	154	710	0	57	815	0	0	711	0	0	856	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	13.0	40.0		12.0	39.0		48.0	48.0		20.0	68.0	
Total Split (%)	10.8%	33.3%		10.0%	32.5%		40.0%	40.0%		16.7%	56.7%	
Maximum Green (s)	7.9	33.8		7.1	32.8		41.8	41.8		15.1	61.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	8.0	37.4		7.0	34.0			43.0			63.0	
Actuated g/C Ratio	0.07	0.31		0.06	0.28			0.36			0.53	
v/c Ratio	1.34	1.29		0.59	1.67			2.15			1.57	

3: Twelve Mile Creek Road & Weddington Road (NC 84)

2029 Background AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	242.5	177.9		80.4	341.8			549.9			290.5	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	242.5	177.9		80.4	341.8			549.9			290.5	
LOS	F	F		F	F			F			F	
Approach Delay (s/veh)		189.4			324.7			549.9			290.5	
Approach LOS		F			F			F			F	
Queue Length 50th (ft)	~155	~728		44	~921			~879			~941	
Queue Length 95th (ft)	#152	#717		74	#1058			#561			#789	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	115	552		96	487			331			544	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	1.34	1.29		0.59	1.67			2.15			1.57	

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Natural Cycle: 240

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 2.15

Intersection Signal Delay (s/veh): 328.9

Intersection LOS: F

Intersection Capacity Utilization 89.2%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.
















Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background MD wo STIP

								
Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations								
Traffic Volume (vph)	4	544	403	261	781	4	806	380
Future Volume (vph)	4	544	403	261	781	4	806	380
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1531	3302	3487	1719	1872	1576
Flt Permitted		0.950		0.950		0.327		
Satd. Flow (perm)	0	1728	1531	3302	3487	592	1872	1576
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								287
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	3%	2%	3%	2%	2%	3%
Adj. Flow (vph)	4	604	448	290	868	4	896	422
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	608	448	290	868	4	896	422
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	44.0	44.0	16.0	16.0	76.0	60.0	60.0	60.0
Total Split (%)	36.7%	36.7%	13.3%	13.3%	63.3%	50.0%	50.0%	50.0%
Maximum Green (s)	37.6	37.6	9.4	9.4	69.6	53.5	53.5	53.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effct Green (s)		39.0	55.0	11.0	71.0	55.0	55.0	55.0
Actuated g/C Ratio		0.33	0.46	0.09	0.59	0.46	0.46	0.46
v/c Ratio		1.08	0.64	0.96	0.42	0.01	1.04	0.48

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background MD wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay (s/veh)		101.6	30.1	97.1	14.1	18.3	75.5	8.7
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		101.6	30.1	97.1	14.1	18.3	75.5	8.7
LOS		F	C	F	B	B	E	A
Approach Delay (s/veh)		71.3			34.9		54.0	
Approach LOS		E			C		D	
Queue Length 50th (ft)		~527	260	117	181	2	~753	61
Queue Length 95th (ft)		#751	377	#205	226	8	#999	144
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		561	701	302	2063	271	858	877
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		1.08	0.64	0.96	0.42	0.01	1.04	0.48

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 120

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.08

Intersection Signal Delay (s/veh): 52.9

Intersection LOS: D

Intersection Capacity Utilization 92.7%

ICU Level of Service F

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background MD wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	17	907	574	103	50	7
Future Volume (vph)	17	907	574	103	50	7
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.980		0.983	
Flt Protected	0.950				0.958	
Satd. Flow (prot)	1574	1801	1660	0	1637	0
Flt Permitted	0.950				0.958	
Satd. Flow (perm)	1574	1801	1660	0	1637	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	7%	2%	5%	3%	2%	2%
Adj. Flow (vph)	19	1008	638	114	56	8
Shared Lane Traffic (%)						
Lane Group Flow (vph)	19	1008	752	0	64	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 57.7% ICU Level of Service B

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road




















Deal Lake TIA
2029 Background MD wo STIP

Intersection						
Int Delay, s/veh	1					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	17	907	574	103	50	7
Future Vol, veh/h	17	907	574	103	50	7
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	7	2	5	3	2	2
Mvmt Flow	19	1008	638	114	56	8
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	752	0	-	0	1741	695
Stage 1	-	-	-	-	695	-
Stage 2	-	-	-	-	1046	-
Critical Hdwy	4.17	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.263	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	835	-	-	-	95	442
Stage 1	-	-	-	-	495	-
Stage 2	-	-	-	-	338	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	835	-	-	-	93	442
Mov Cap-2 Maneuver	-	-	-	-	222	-
Stage 1	-	-	-	-	484	-
Stage 2	-	-	-	-	338	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		25.8		
HCM LOS				D		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	835	-	-	-	236	
HCM Lane V/C Ratio	0.023	-	-	-	0.268	
HCM Control Delay (s/veh)	9.4	-	-	-	25.8	
HCM Lane LOS	A	-	-	-	D	
HCM 95th %tile Q (veh)	0.1	-	-	-	1	

Lanes, Volumes, Timings













3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Background MD wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	95	731	121	83	489	137	134	84	63	99	71	58
Future Volume (vph)	95	731	121	83	489	137	134	84	63	99	71	58
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.980			0.963			0.968			0.956	
Flt Protected	0.950			0.950				0.978			0.983	
Satd. Flow (prot)	1728	1753	0	1686	1688	0	0	1601	0	0	1645	0
Flt Permitted	0.950			0.950				0.675			0.716	
Satd. Flow (perm)	1728	1753	0	1686	1688	0	0	1105	0	0	1198	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.72	0.86	0.91	0.75	0.85	0.74	0.81	0.70	0.71	0.78	0.57	0.48
Heavy Vehicles (%)	2%	4%	2%	3%	4%	5%	3%	4%	5%	2%	3%	2%
Adj. Flow (vph)	132	850	133	111	575	185	165	120	89	127	125	121
Shared Lane Traffic (%)												
Lane Group Flow (vph)	132	983	0	111	760	0	0	374	0	0	373	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	19.0	94.0		16.0	91.0		55.0	55.0		15.0	70.0	
Total Split (%)	10.6%	52.2%		8.9%	50.6%		30.6%	30.6%		8.3%	38.9%	
Maximum Green (s)	13.9	87.8		11.1	84.8		48.8	48.8		10.1	63.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	14.0	89.0		11.0	86.0			50.0			65.0	
Actuated g/C Ratio	0.08	0.49		0.06	0.48			0.28			0.36	
v/c Ratio	0.99	1.14		1.08	0.94			1.22			0.82	

3: Twelve Mile Creek Road & Weddington Road (NC 84)

2029 Background MD wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	153.1	116.3		184.7	65.1			177.6			66.1	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	153.1	116.3		184.7	65.1			177.6			66.1	
LOS	F	F		F	E			F			E	
Approach Delay (s/veh)		120.6			80.3			177.6			66.1	
Approach LOS		F			F			F			E	
Queue Length 50th (ft)	159	~1344		~146	845			~539			365	
Queue Length 95th (ft)	#217	#1493		#221	#1017			#508			271	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	134	866		103	806			306			457	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.99	1.14		1.08	0.94			1.22			0.82	

Intersection Summary

Area Type: Other

Cycle Length: 180

Actuated Cycle Length: 180

Natural Cycle: 180

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.22

Intersection Signal Delay (s/veh): 108.1

Intersection LOS: F

Intersection Capacity Utilization 84.9%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.









Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background PM wo STIP

								
Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations								
Traffic Volume (vph)	4	640	413	228	867	4	722	609
Future Volume (vph)	4	640	413	228	867	4	722	609
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1546	3302	3522	1719	1872	1591
Flt Permitted		0.950		0.950		0.286		
Satd. Flow (perm)	0	1728	1546	3302	3522	518	1872	1591
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								471
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	4	711	459	253	963	4	802	677
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	715	459	253	963	4	802	677
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	51.0	51.0	15.0	15.0	69.0	54.0	54.0	54.0
Total Split (%)	42.5%	42.5%	12.5%	12.5%	57.5%	45.0%	45.0%	45.0%
Maximum Green (s)	44.6	44.6	8.4	8.4	62.6	47.5	47.5	47.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effct Green (s)		46.0	61.0	10.0	64.0	49.0	49.0	49.0
Actuated g/C Ratio		0.38	0.51	0.08	0.53	0.41	0.41	0.41
v/c Ratio		1.08	0.58	0.92	0.51	0.02	1.05	0.73
Control Delay (s/veh)		94.6	24.4	92.0	19.2	21.8	81.6	13.7

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Background PM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		94.6	24.4	92.0	19.2	21.8	81.6	13.7
LOS		F	C	F	B	C	F	B
Approach Delay (s/veh)		67.2			34.3		50.4	
Approach LOS		E			C		D	
Queue Length 50th (ft)		-619	241	102	242	2	-677	128
Queue Length 95th (ft)		#852	348	#181	300	9	#917	285
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		662	785	275	1878	211	764	928
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		1.08	0.58	0.92	0.51	0.02	1.05	0.73

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 120

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.08

Intersection Signal Delay (s/veh): 50.5

Intersection LOS: D

Intersection Capacity Utilization 92.7%

ICU Level of Service F

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background PM wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	25	915	628	43	64	13
Future Volume (vph)	25	915	628	43	64	13
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.991		0.978	
Flt Protected	0.950				0.960	
Satd. Flow (prot)	1652	1801	1692	0	1604	0
Flt Permitted	0.950				0.960	
Satd. Flow (perm)	1652	1801	1692	0	1604	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	4%	2%	3%	8%
Adj. Flow (vph)	28	1017	698	48	71	14
Shared Lane Traffic (%)						
Lane Group Flow (vph)	28	1017	746	0	85	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 59.2% ICU Level of Service B

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Background PM wo STIP

Intersection						
Int Delay, s/veh	1.5					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	25	915	628	43	64	13
Future Vol, veh/h	25	915	628	43	64	13
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	4	2	3	8
Mvmt Flow	28	1017	698	48	71	14

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	746	0	0 1795 722
Stage 1	-	-	- 722 -
Stage 2	-	-	- 1073 -
Critical Hdwy	4.12	-	- 6.43 6.28
Critical Hdwy Stg 1	-	-	- 5.43 -
Critical Hdwy Stg 2	-	-	- 5.43 -
Follow-up Hdwy	2.218	-	- 3.527 3.372
Pot Cap-1 Maneuver	862	-	- 88 417
Stage 1	-	-	- 479 -
Stage 2	-	-	- 327 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	862	-	- 85 417
Mov Cap-2 Maneuver	-	-	- 212 -
Stage 1	-	-	- 464 -
Stage 2	-	-	- 327 -




















Approach	EB	WB	SB
HCM Control Delay, s/v	0.2	0	29.5
HCM LOS			D













Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	862	-	-	-	231
HCM Lane V/C Ratio	0.032	-	-	-	0.37
HCM Control Delay (s/veh)	9.3	-	-	-	29.5
HCM Lane LOS	A	-	-	-	D
HCM 95th %tile Q (veh)	0.1	-	-	-	1.6

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Background PM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	34	772	174	86	477	62	116	56	94	115	113	55
Future Volume (vph)	34	772	174	86	477	62	116	56	94	115	113	55
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.972			0.983			0.952			0.974	
Flt Protected	0.950			0.950				0.979			0.980	
Satd. Flow (prot)	1711	1768	0	1686	1746	0	0	1597	0	0	1625	0
Flt Permitted	0.950			0.950				0.712			0.682	
Satd. Flow (perm)	1711	1768	0	1686	1746	0	0	1162	0	0	1131	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	3%	2%	2%	3%	3%	2%	3%	2%	2%	8%	2%	6%
Adj. Flow (vph)	38	858	193	96	530	69	129	62	104	128	126	61
Shared Lane Traffic (%)												
Lane Group Flow (vph)	38	1051	0	96	599	0	0	295	0	0	315	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	14.0	87.0		13.0	86.0		37.0	37.0		13.0	50.0	
Total Split (%)	9.3%	58.0%		8.7%	57.3%		24.7%	24.7%		8.7%	33.3%	
Maximum Green (s)	8.9	80.8		8.1	79.8		30.8	30.8		8.1	43.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	7.7	82.0		8.0	84.7			32.0			45.0	
Actuated g/C Ratio	0.05	0.55		0.05	0.56			0.21			0.30	
v/c Ratio	0.44	1.09		1.08	0.61			1.19			0.86	

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	84.2	89.0		181.6	25.8			169.2			71.5	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	84.2	89.0		181.6	25.8			169.2			71.5	
LOS	F	F		F	C			F			E	
Approach Delay (s/veh)		88.8			47.3			169.2			71.5	
Approach LOS		F			D			F			E	
Queue Length 50th (ft)	37	~1152		~104	387			~347			269	
Queue Length 95th (ft)	78	#1415		#229	531			#540			#441	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	102	966		89	985			247			365	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.37	1.09		1.08	0.61			1.19			0.86	

Intersection Summary

Area Type: Other

Cycle Length: 150

Actuated Cycle Length: 150

Natural Cycle: 150

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.19

Intersection Signal Delay (s/veh): 84.4

Intersection LOS: F

Intersection Capacity Utilization 89.5%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



2029 Build-out Conditions
w/o STIPs

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build AM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations		↰	↰	↰	↰	↰	↰	↰
Traffic Volume (vph)	4	391	224	415	1058	4	504	369
Future Volume (vph)	4	391	224	415	1058	4	504	369
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1546	3302	3522	1719	1836	1591
Flt Permitted		0.950		0.950		0.240		
Satd. Flow (perm)	0	1728	1546	3302	3522	434	1836	1591
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								410
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	4%	2%
Adj. Flow (vph)	4	434	249	461	1176	4	560	410
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	438	249	461	1176	4	560	410
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	32.0	32.0	20.0	20.0	58.0	38.0	38.0	38.0
Total Split (%)	35.6%	35.6%	22.2%	22.2%	64.4%	42.2%	42.2%	42.2%
Maximum Green (s)	25.6	25.6	13.4	13.4	51.6	31.5	31.5	31.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effct Green (s)		25.6	45.7	15.0	54.4	34.3	34.3	34.3
Actuated g/C Ratio		0.28	0.51	0.17	0.60	0.38	0.38	0.38
v/c Ratio		0.89	0.32	0.84	0.55	0.02	0.80	0.48

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build AM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay (s/veh)		52.6	14.0	51.2	12.1	19.0	35.9	4.2
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		52.6	14.0	51.2	12.1	19.0	35.9	4.2
LOS		D	B	D	B	B	D	A
Approach Delay (s/veh)		38.6			23.1		22.5	
Approach LOS		D			C		C	
Queue Length 50th (ft)		232	76	132	200	1	286	0
Queue Length 95th (ft)		#395	126	#209	257	9	#464	58
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		518	787	557	2127	165	700	860
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		0.85	0.32	0.83	0.55	0.02	0.80	0.48

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 29 (32%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 75

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.89

Intersection Signal Delay (s/veh): 26.2

Intersection LOS: C

Intersection Capacity Utilization 73.6%


ICU Level of Service D

Analysis Period (min) 15

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build AM wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	9	451	833	119	133	9
Future Volume (vph)	9	451	833	119	133	9
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.983		0.991	
Flt Protected	0.950				0.955	
Satd. Flow (prot)	1491	1801	1709	0	1595	0
Flt Permitted	0.950				0.955	
Satd. Flow (perm)	1491	1801	1709	0	1595	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	13%	2%	2%	2%	3%	38%
Adj. Flow (vph)	10	501	926	132	148	10
Shared Lane Traffic (%)						
Lane Group Flow (vph)	10	501	1058	0	158	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 65.6% ICU Level of Service C

Analysis Period (min) 15



















HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build AM wo STIP

Intersection						
Int Delay, s/veh	3.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	9	451	833	119	133	9
Future Vol, veh/h	9	451	833	119	133	9
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	13	2	2	2	3	38
Mvmt Flow	10	501	926	132	148	10
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	1058	0	-	0	1513	992
Stage 1	-	-	-	-	992	-
Stage 2	-	-	-	-	521	-
Critical Hdwy	4.23	-	-	-	6.43	6.58
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.317	-	-	-	3.527	3.642
Pot Cap-1 Maneuver	618	-	-	-	~ 131	255
Stage 1	-	-	-	-	357	-
Stage 2	-	-	-	-	594	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	618	-	-	-	~ 129	255
Mov Cap-2 Maneuver	-	-	-	-	255	-
Stage 1	-	-	-	-	351	-
Stage 2	-	-	-	-	594	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		39.6		
HCM LOS				E		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	618	-	-	-	255	
HCM Lane V/C Ratio	0.016	-	-	-	0.619	
HCM Control Delay (s/veh)	10.9	-	-	-	39.6	
HCM Lane LOS	B	-	-	-	E	
HCM 95th %tile Q (veh)	0	-	-	-	3.7	
Notes						
-: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon						













Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	90	476	71	43	580	97	239	82	148	257	96	132
Future Volume (vph)	90	476	71	43	580	97	239	82	148	257	96	132
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.982			0.977			0.945			0.963	
Flt Protected	0.950			0.950				0.981			0.973	
Satd. Flow (prot)	1728	1769	0	1653	1723	0	0	1589	0	0	1627	0
Flt Permitted	0.950			0.950				0.575			0.513	
Satd. Flow (perm)	1728	1769	0	1653	1723	0	0	932	0	0	858	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1033			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.57	0.74	0.82	0.75	0.84	0.76	0.88	0.54	0.51	0.53	0.68	0.57
Heavy Vehicles (%)	2%	3%	3%	5%	3%	7%	2%	2%	3%	4%	2%	2%
Adj. Flow (vph)	158	643	87	57	690	128	272	152	290	485	141	232
Shared Lane Traffic (%)												
Lane Group Flow (vph)	158	730	0	57	818	0	0	714	0	0	858	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	13.0	41.0		12.0	40.0		48.0	48.0		19.0	67.0	
Total Split (%)	10.8%	34.2%		10.0%	33.3%		40.0%	40.0%		15.8%	55.8%	
Maximum Green (s)	7.9	34.8		7.1	33.8		41.8	41.8		14.1	60.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	8.0	38.4		7.0	35.0			43.0			62.0	
Actuated g/C Ratio	0.07	0.32		0.06	0.29			0.36			0.52	
v/c Ratio	1.37	1.29		0.59	1.63			2.14			1.61	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	255.2	178.5		80.4	322.5			548.1			306.8	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	255.2	178.5		80.4	322.5			548.1			306.8	
LOS	F	F		F	F			F			F	
Approach Delay (s/veh)		192.2			306.7			548.1			306.8	
Approach LOS		F			F			F			F	
Queue Length 50th (ft)	~162	~749		44	~914			~882			~953	
Queue Length 95th (ft)	#155	#733		74	#1052			#563			#800	
Internal Link Dist (ft)		953			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	115	566		96	502			333			533	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	1.37	1.29		0.59	1.63			2.14			1.61	

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Natural Cycle: 240

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 2.14

Intersection Signal Delay (s/veh): 327.9

Intersection LOS: F

Intersection Capacity Utilization 89.3%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.
















Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	2	622	8	4	948	0	22	0	11	1	0	6
Future Volume (vph)	2	622	8	4	948	0	22	0	11	1	0	6
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.998						0.955			0.882	
Flt Protected								0.968			0.994	
Satd. Flow (prot)	0	1841	0	0	1845	0	0	1722	0	0	1633	0
Flt Permitted								0.968			0.994	
Satd. Flow (perm)	0	1841	0	0	1845	0	0	1722	0	0	1633	0
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		1486			829			1088			1008	
Travel Time (s)		22.5			12.6			29.7			27.5	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	3%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	2	691	9	4	1053	0	24	0	12	1	0	7
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	702	0	0	1057	0	0	36	0	0	8	0
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	65.8%						ICU Level of Service C					
Analysis Period (min)	15											
















HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

Intersection												
Int Delay, s/veh	1.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		⬆⬇⬆			⬆⬇⬆			⬆⬇⬆			⬆⬇⬆	
Traffic Vol, veh/h	2	622	8	4	948	0	22	0	11	1	0	6
Future Vol, veh/h	2	622	8	4	948	0	22	0	11	1	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	3	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	2	691	9	4	1053	0	24	0	12	1	0	7
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	1053	0	0	700	0	0	1765	1761	696	1767	1765	1053
Stage 1	-	-	-	-	-	-	700	700	-	1061	1061	-
Stage 2	-	-	-	-	-	-	1065	1061	-	706	704	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	661	-	-	897	-	-	65	84	442	65	84	275
Stage 1	-	-	-	-	-	-	430	441	-	271	300	-
Stage 2	-	-	-	-	-	-	269	300	-	427	440	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	661	-	-	897	-	-	63	83	442	62	83	275
Mov Cap-2 Maneuver	-	-	-	-	-	-	63	83	-	62	83	-
Stage 1	-	-	-	-	-	-	428	439	-	270	297	-
Stage 2	-	-	-	-	-	-	260	297	-	413	438	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			72.4			25.4		
HCM LOS							F			D		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	88	661	-	-	897	-	-	184				
HCM Lane V/C Ratio	0.417	0.003	-	-	0.005	-	-	0.042				
HCM Control Delay (s/veh)	72.4	10.5	0	-	9	0	-	25.4				
HCM Lane LOS	F	B	A	-	A	A	-	D				
HCM 95th %tile Q (veh)	1.7	0	-	-	0	-	-	0.1				





Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	1	633	0	1	949	1	2	0	2	3	0	1
Future Volume (vph)	1	633	0	1	949	1	2	0	2	3	0	1
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt								0.932				0.966
Flt Protected								0.976				0.964
Satd. Flow (prot)	0	1845	0	0	1845	0	0	1694	0	0	1735	0
Flt Permitted								0.976				0.964
Satd. Flow (perm)	0	1845	0	0	1845	0	0	1694	0	0	1735	0
Link Speed (mph)	45				45		25				25	
Link Distance (ft)	829				534		1082				1049	
Travel Time (s)	12.6				8.1		29.5				28.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	3%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	1	703	0	1	1054	1	2	0	2	3	0	1
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	704	0	0	1056	0	0	4	0	0	4	0
Sign Control	Free				Free		Stop				Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	60.8%				ICU Level of Service B							
Analysis Period (min)	15											

HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build AM wo STIP

Intersection												
Int Delay, s/veh	0.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	1	633	0	1	949	1	2	0	2	3	0	1
Future Vol, veh/h	1	633	0	1	949	1	2	0	2	3	0	1
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	3	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	1	703	0	1	1054	1	2	0	2	3	0	1
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	1055	0	0	703	0	0	1762	1762	703	1763	1762	1055
Stage 1	-	-	-	-	-	-	705	705	-	1057	1057	-
Stage 2	-	-	-	-	-	-	1057	1057	-	706	705	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	660	-	-	895	-	-	66	84	438	66	84	274
Stage 1	-	-	-	-	-	-	427	439	-	272	302	-
Stage 2	-	-	-	-	-	-	272	302	-	427	439	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	660	-	-	895	-	-	65	84	438	65	84	274
Mov Cap-2 Maneuver	-	-	-	-	-	-	65	84	-	65	84	-
Stage 1	-	-	-	-	-	-	426	438	-	271	301	-
Stage 2	-	-	-	-	-	-	270	301	-	424	438	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			38.2			52.6		
HCM LOS							E			F		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	113	660	-	-	895	-	-	80				
HCM Lane V/C Ratio	0.039	0.002	-	-	0.001	-	-	0.056				
HCM Control Delay (s/veh)	38.2	10.5	0	-	9	0	-	52.6				
HCM Lane LOS	E	B	A	-	A	A	-	F				
HCM 95th %tile Q (veh)	0.1	0	-	-	0	-	-	0.2				

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build MD wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations		↩	↩	↩	↩	↩	↩	↩
Traffic Volume (vph)	4	553	403	261	786	4	809	385
Future Volume (vph)	4	553	403	261	786	4	809	385
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1531	3302	3487	1719	1872	1576
Flt Permitted		0.950		0.950		0.325		
Satd. Flow (perm)	0	1728	1531	3302	3487	588	1872	1576
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								290
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	3%	2%	3%	2%	2%	3%
Adj. Flow (vph)	4	614	448	290	873	4	899	428
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	618	448	290	873	4	899	428
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	44.0	44.0	16.0	16.0	76.0	60.0	60.0	60.0
Total Split (%)	36.7%	36.7%	13.3%	13.3%	63.3%	50.0%	50.0%	50.0%
Maximum Green (s)	37.6	37.6	9.4	9.4	69.6	53.5	53.5	53.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effect Green (s)		39.0	55.0	11.0	71.0	55.0	55.0	55.0
Actuated g/C Ratio		0.33	0.46	0.09	0.59	0.46	0.46	0.46
v/c Ratio		1.10	0.64	0.96	0.42	0.01	1.05	0.49

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build MD wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Control Delay (s/veh)		107.4	30.1	97.1	14.1	18.3	76.5	8.8
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		107.4	30.1	97.1	14.1	18.3	76.5	8.8
LOS		F	C	F	B	B	E	A
Approach Delay (s/veh)		74.9			34.8		54.6	
Approach LOS		E			C		D	
Queue Length 50th (ft)		~544	260	117	183	2	~758	62
Queue Length 95th (ft)		#769	377	#205	228	8	#1004	148
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		561	701	302	2063	269	858	879
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		1.10	0.64	0.96	0.42	0.01	1.05	0.49

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 120

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.10

Intersection Signal Delay (s/veh): 54.2

Intersection LOS: D

Intersection Capacity Utilization 93.4%

ICU Level of Service F

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build MD wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	17	935	590	104	52	7
Future Volume (vph)	17	935	590	104	52	7
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.980		0.984	
Flt Protected	0.950				0.958	
Satd. Flow (prot)	1574	1801	1660	0	1639	0
Flt Permitted	0.950				0.958	
Satd. Flow (perm)	1574	1801	1660	0	1639	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	7%	2%	5%	3%	2%	2%
Adj. Flow (vph)	19	1039	656	116	58	8
Shared Lane Traffic (%)						
Lane Group Flow (vph)	19	1039	772	0	66	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 59.2% ICU Level of Service B

Analysis Period (min) 15




















HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road













Deal Lake TIA
2029 Build MD wo STIP

Intersection						
Int Delay, s/veh	1					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	17	935	590	104	52	7
Future Vol, veh/h	17	935	590	104	52	7
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	7	2	5	3	2	2
Mvmt Flow	19	1039	656	116	58	8
Major/Minor	Major1	Major2	Minor2			
Conflicting Flow All	772	0	-	0	1791	714
Stage 1	-	-	-	-	714	-
Stage 2	-	-	-	-	1077	-
Critical Hdwy	4.17	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.263	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	821	-	-	-	89	431
Stage 1	-	-	-	-	485	-
Stage 2	-	-	-	-	327	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	821	-	-	-	87	431
Mov Cap-2 Maneuver	-	-	-	-	215	-
Stage 1	-	-	-	-	474	-
Stage 2	-	-	-	-	327	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		26.9		
HCM LOS				D		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	821	-	-	-	229	
HCM Lane V/C Ratio	0.023	-	-	-	0.286	
HCM Control Delay (s/veh)	9.5	-	-	-	26.9	
HCM Lane LOS	A	-	-	-	D	
HCM 95th %tile Q (veh)	0.1	-	-	-	1.1	

Lanes, Volumes, Timings
3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MD wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	96	737	124	83	497	137	139	84	63	99	71	60
Future Volume (vph)	96	737	124	83	497	137	139	84	63	99	71	60
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.979			0.964			0.968			0.956	
Flt Protected	0.950			0.950				0.978			0.983	
Satd. Flow (prot)	1728	1751	0	1686	1690	0	0	1601	0	0	1645	0
Flt Permitted	0.950			0.950				0.671			0.719	
Satd. Flow (perm)	1728	1751	0	1686	1690	0	0	1099	0	0	1203	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.73	0.86	0.91	0.75	0.85	0.74	0.82	0.70	0.71	0.78	0.57	0.49
Heavy Vehicles (%)	2%	4%	2%	3%	4%	5%	3%	4%	5%	2%	3%	2%
Adj. Flow (vph)	132	857	136	111	585	185	170	120	89	127	125	122
Shared Lane Traffic (%)												
Lane Group Flow (vph)	132	993	0	111	770	0	0	379	0	0	374	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	18.0	89.0		15.0	86.0		52.0	52.0		14.0	66.0	
Total Split (%)	10.6%	52.4%		8.8%	50.6%		30.6%	30.6%		8.2%	38.8%	
Maximum Green (s)	12.9	82.8		10.1	79.8		45.8	45.8		9.1	59.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	13.0	84.0		10.0	81.0			47.0			61.0	
Actuated g/C Ratio	0.08	0.49		0.06	0.48			0.28			0.36	
v/c Ratio	1.00	1.15		1.12	0.96			1.25			0.82	

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	153.6	119.2		193.9	65.4			185.8			64.2	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	153.6	119.2		193.9	65.4			185.8			64.2	
LOS	F	F		F	E			F			E	
Approach Delay (s/veh)		123.2			81.6			185.8			64.2	
Approach LOS		F			F			F			E	
Queue Length 50th (ft)	150	~1292		~142	815			~524			346	
Queue Length 95th (ft)	#217	#1447		#215	#993			#498			258	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	132	865		99	805			303			455	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	1.00	1.15		1.12	0.96			1.25			0.82	

Intersection Summary

Area Type: Other

Cycle Length: 170

Actuated Cycle Length: 170

Natural Cycle: 170

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.25

Intersection Signal Delay (s/veh): 110.5

Intersection LOS: F

Intersection Capacity Utilization 86.1%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

















Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MD wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	5	951	21	10	684	1	12	0	6	1	0	3
Future Volume (vph)	5	951	21	10	684	1	12	0	6	1	0	3
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.997						0.953			0.899		
Flt Protected				0.999			0.969			0.988		
Satd. Flow (prot)	0	1822	0	0	1826	0	0	1720	0	0	1655	0
Flt Permitted				0.999			0.969			0.988		
Satd. Flow (perm)	0	1822	0	0	1826	0	0	1720	0	0	1655	0
Link Speed (mph)	45			45			25			25		
Link Distance (ft)	1486			829			1236			1149		
Travel Time (s)	22.5			12.6			33.7			31.3		
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	4%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	6	1057	23	11	760	1	13	0	7	1	0	3
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1086	0	0	772	0	0	20	0	0	4	0
Sign Control	Free			Free			Stop			Stop		
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	64.1%						ICU Level of Service C					
Analysis Period (min)	15											

HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MD wo STIP

Intersection												
Int Delay, s/veh	0.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	5	951	21	10	684	1	12	0	6	1	0	3
Future Vol, veh/h	5	951	21	10	684	1	12	0	6	1	0	3
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	4	2	2	4	2	2	2	2	2	2	2
Mvmt Flow	6	1057	23	11	760	1	13	0	7	1	0	3

















Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	761	0	0	1080	0	0	1865	1864	1069	1867	1875	761
Stage 1	-	-	-	-	-	-	1081	1081	-	783	783	-
Stage 2	-	-	-	-	-	-	784	783	-	1084	1092	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	851	-	-	646	-	-	56	73	269	55	72	405
Stage 1	-	-	-	-	-	-	264	294	-	387	404	-
Stage 2	-	-	-	-	-	-	386	404	-	263	291	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	851	-	-	646	-	-	54	70	269	52	69	405
Mov Cap-2 Maneuver	-	-	-	-	-	-	54	70	-	52	69	-
Stage 1	-	-	-	-	-	-	259	289	-	380	392	-
Stage 2	-	-	-	-	-	-	371	392	-	252	286	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0.2	70.8	29.7
HCM LOS			F	D

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	74	851	-	-	646	-	-	150
HCM Lane V/C Ratio	0.27	0.007	-	-	0.017	-	-	0.03
HCM Control Delay (s/veh)	70.8	9.3	0	-	10.7	0	-	29.7
HCM Lane LOS	F	A	A	-	B	A	-	D
HCM 95th %tile Q (veh)	1	0	-	-	0.1	-	-	0.1





Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MD wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	2	954	2	2	693	2	1	0	2	1	0	1
Future Volume (vph)	2	954	2	2	693	2	1	0	2	1	0	1
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt								0.910				0.932
Flt Protected								0.984				0.976
Satd. Flow (prot)	0	1827	0	0	1827	0	0	1668	0	0	1694	0
Flt Permitted								0.984				0.976
Satd. Flow (perm)	0	1827	0	0	1827	0	0	1668	0	0	1694	0
Link Speed (mph)	45				45		25				25	
Link Distance (ft)	829				530		1177				1454	
Travel Time (s)	12.6				8.0		32.1				39.7	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	4%	2%	2%	4%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	2	1060	2	2	770	2	1	0	2	1	0	1
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1064	0	0	774	0	0	3	0	0	2	0
Sign Control	Free				Free		Stop				Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	61.8%				ICU Level of Service B							
Analysis Period (min)	15											

HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build MD wo STIP

Intersection												
Int Delay, s/veh	0.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	2	954	2	2	693	2	1	0	2	1	0	1
Future Vol, veh/h	2	954	2	2	693	2	1	0	2	1	0	1
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	4	2	2	4	2	2	2	2	2	2	2
Mvmt Flow	2	1060	2	2	770	2	1	0	2	1	0	1
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	772	0	0	1062	0	0	1841	1841	1061	1841	1841	771
Stage 1	-	-	-	-	-	-	1065	1065	-	775	775	-
Stage 2	-	-	-	-	-	-	776	776	-	1066	1066	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	843	-	-	656	-	-	58	75	272	58	75	400
Stage 1	-	-	-	-	-	-	269	299	-	391	408	-
Stage 2	-	-	-	-	-	-	390	407	-	269	299	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	843	-	-	656	-	-	57	74	272	57	74	400
Mov Cap-2 Maneuver	-	-	-	-	-	-	57	74	-	57	74	-
Stage 1	-	-	-	-	-	-	267	297	-	389	406	-
Stage 2	-	-	-	-	-	-	387	405	-	265	297	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0			35.9			41.8		
HCM LOS							E			E		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	120	843	-	-	656	-	-	100				
HCM Lane V/C Ratio	0.028	0.003	-	-	0.003	-	-	0.022				
HCM Control Delay (s/veh)	35.9	9.3	0	-	10.5	0	-	41.8				
HCM Lane LOS	E	A	A	-	B	A	-	E				
HCM 95th %tile Q (veh)	0.1	0	-	-	0	-	-	0.1				

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build PM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Lane Configurations								
Traffic Volume (vph)	4	651	413	228	872	4	725	615
Future Volume (vph)	4	651	413	228	872	4	725	615
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	12	11	11	11	12	11	12	12
Grade (%)		-2%			1%		-1%	
Storage Length (ft)		0	0	425		325		0
Storage Lanes		1	1	2		1		1
Taper Length (ft)		0		100		75		
Lane Util. Factor	1.00	1.00	1.00	0.97	0.95	1.00	1.00	1.00
Frt			0.850					0.850
Flt Protected		0.950		0.950		0.950		
Satd. Flow (prot)	0	1728	1546	3302	3522	1719	1872	1591
Flt Permitted		0.950		0.950		0.283		
Satd. Flow (perm)	0	1728	1546	3302	3522	512	1872	1591
Right Turn on Red			No					Yes
Satd. Flow (RTOR)								473
Link Speed (mph)		45			45		45	
Link Distance (ft)		1527			1308		1378	
Travel Time (s)		23.1			19.8		20.9	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Adj. Flow (vph)	4	723	459	253	969	4	806	683
Shared Lane Traffic (%)								
Lane Group Flow (vph)	0	727	459	253	969	4	806	683
Turn Type	Prot	Prot	pm+ov	Prot	NA	Perm	NA	Perm
Protected Phases	4	4	5	5	2		6	
Permitted Phases			4			6		6
Detector Phase	4	4	5	5	2	6	6	6
Switch Phase								
Minimum Initial (s)	7.0	7.0	7.0	7.0	12.0	12.0	12.0	12.0
Minimum Split (s)	13.4	13.4	13.6	13.6	18.4	18.5	18.5	18.5
Total Split (s)	51.0	51.0	15.0	15.0	69.0	54.0	54.0	54.0
Total Split (%)	42.5%	42.5%	12.5%	12.5%	57.5%	45.0%	45.0%	45.0%
Maximum Green (s)	44.6	44.6	8.4	8.4	62.6	47.5	47.5	47.5
Yellow Time (s)	4.7	4.7	3.0	3.0	4.4	4.6	4.6	4.6
All-Red Time (s)	1.7	1.7	3.6	3.6	2.0	1.9	1.9	1.9
Lost Time Adjust (s)		-1.4	-1.6	-1.6	-1.4	-1.5	-1.5	-1.5
Total Lost Time (s)		5.0	5.0	5.0	5.0	5.0	5.0	5.0
Lead/Lag			Lead	Lead		Lag	Lag	Lag
Lead-Lag Optimize?								
Vehicle Extension (s)	2.0	2.0	2.0	2.0	6.0	6.0	6.0	6.0
Minimum Gap (s)	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0
Time Before Reduce (s)	0.0	0.0	0.0	0.0	15.0	15.0	15.0	15.0
Time To Reduce (s)	0.0	0.0	0.0	0.0	30.0	30.0	30.0	30.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Act Effct Green (s)		46.0	61.0	10.0	64.0	49.0	49.0	49.0
Actuated g/C Ratio		0.38	0.51	0.08	0.53	0.41	0.41	0.41
v/c Ratio		1.10	0.58	0.92	0.52	0.02	1.05	0.74
Control Delay (s/veh)		100.6	24.4	92.0	19.3	21.8	83.2	13.9

Lanes, Volumes, Timings
1: S Providence Road (NC 16) & Rea Road

Deal Lake TIA
2029 Build PM wo STIP



Lane Group	EBU	EBL	EBR	NBL	NBT	SBU	SBT	SBR
Queue Delay		0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)		100.6	24.4	92.0	19.3	21.8	83.2	13.9
LOS		F	C	F	B	C	F	B
Approach Delay (s/veh)		71.1			34.3		51.3	
Approach LOS		E			C		D	
Queue Length 50th (ft)		~638	241	102	244	2	~683	132
Queue Length 95th (ft)		#873	348	#181	301	9	#925	291
Internal Link Dist (ft)		1447			1228		1298	
Turn Bay Length (ft)				425		325		
Base Capacity (vph)		662	785	275	1878	209	764	929
Starvation Cap Reductn		0	0	0	0	0	0	0
Spillback Cap Reductn		0	0	0	0	0	0	0
Storage Cap Reductn		0	0	0	0	0	0	0
Reduced v/c Ratio		1.10	0.58	0.92	0.52	0.02	1.05	0.74

Intersection Summary

Area Type: Other

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBTU, Start of Green

Natural Cycle: 120

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.10

Intersection Signal Delay (s/veh): 52.0

Intersection LOS: D

Intersection Capacity Utilization 93.5%

ICU Level of Service F

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 1: S Providence Road (NC 16) & Rea Road



Lanes, Volumes, Timings
2: Weddington Road (NC 84) & Cox Road

Deal Lake TIA
2029 Build PM wo STIP



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	25	948	646	45	67	13
Future Volume (vph)	25	948	646	45	67	13
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Width (ft)	10	11	10	12	10	12
Storage Length (ft)	125			0	0	0
Storage Lanes	1			0	1	0
Taper Length (ft)	75				0	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.991		0.979	
Flt Protected	0.950				0.960	
Satd. Flow (prot)	1652	1801	1692	0	1606	0
Flt Permitted	0.950				0.960	
Satd. Flow (perm)	1652	1801	1692	0	1606	0
Link Speed (mph)		45	45		45	
Link Distance (ft)		1199	1025		1160	
Travel Time (s)		18.2	15.5		17.6	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	4%	2%	3%	8%
Adj. Flow (vph)	28	1053	718	50	74	14
Shared Lane Traffic (%)						
Lane Group Flow (vph)	28	1053	768	0	88	0
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type: Other





Control Type: Unsignalized

Intersection Capacity Utilization 61.1% ICU Level of Service B

Analysis Period (min) 15

HCM 6th TWSC
2: Weddington Road (NC 84) & Cox Road








Deal Lake TIA
2029 Build PM wo STIP













Intersection						
Int Delay, s/veh	1.6					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	25	948	646	45	67	13
Future Vol, veh/h	25	948	646	45	67	13
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	125	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	4	2	3	8
Mvmt Flow	28	1053	718	50	74	14
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	768	0	-	0	1852	743
Stage 1	-	-	-	-	743	-
Stage 2	-	-	-	-	1109	-
Critical Hdwy	4.12	-	-	-	6.43	6.28
Critical Hdwy Stg 1	-	-	-	-	5.43	-
Critical Hdwy Stg 2	-	-	-	-	5.43	-
Follow-up Hdwy	2.218	-	-	-	3.527	3.372
Pot Cap-1 Maneuver	846	-	-	-	81	405
Stage 1	-	-	-	-	468	-
Stage 2	-	-	-	-	314	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	846	-	-	-	78	405
Mov Cap-2 Maneuver	-	-	-	-	203	-
Stage 1	-	-	-	-	453	-
Stage 2	-	-	-	-	314	-
Approach	EB	WB		SB		
HCM Control Delay, s/v	0.2	0		31.8		
HCM LOS	D					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	846	-	-	-	221	
HCM Lane V/C Ratio	0.033	-	-	-	0.402	
HCM Control Delay (s/veh)	9.4	-	-	-	31.8	
HCM Lane LOS	A	-	-	-	D	
HCM 95th %tile Q (veh)	0.1	-	-	-	1.8	

Lanes, Volumes, Timings

3: Twelve Mile Creek Road & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	36	778	177	86	487	62	121	56	94	115	113	58
Future Volume (vph)	36	778	177	86	487	62	121	56	94	115	113	58
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Width (ft)	11	11	12	11	11	12	12	10	12	12	10	12
Grade (%)		-2%			1%			2%			-2%	
Storage Length (ft)	100		0	100		0	0		0	0		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	100			100			0			0		
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.972			0.983			0.953			0.973	
Flt Protected	0.950			0.950				0.978			0.980	
Satd. Flow (prot)	1711	1768	0	1686	1746	0	0	1597	0	0	1623	0
Flt Permitted	0.950			0.950				0.707			0.690	
Satd. Flow (perm)	1711	1768	0	1686	1746	0	0	1155	0	0	1143	0
Right Turn on Red			No			No			No			No
Satd. Flow (RTOR)												
Link Speed (mph)		45			45			45			45	
Link Distance (ft)		1035			1019			1122			1136	
Travel Time (s)		15.7			15.4			17.0			17.2	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	3%	2%	2%	3%	3%	2%	3%	2%	2%	8%	2%	6%
Adj. Flow (vph)	40	864	197	96	541	69	134	62	104	128	126	64
Shared Lane Traffic (%)												
Lane Group Flow (vph)	40	1061	0	96	610	0	0	300	0	0	318	0
Turn Type	Prot	NA		Prot	NA		Perm	NA		pm+pt	NA	
Protected Phases	5	2		1	6			8		7	4	
Permitted Phases							8			4		
Detector Phase	5	2		1	6		8	8		7	7	
Switch Phase										4	4	
Minimum Initial (s)	7.0	12.0		7.0	12.0		7.0	7.0		7.0	7.0	
Minimum Split (s)	12.1	18.2		11.9	18.2		13.2	13.2		11.9	13.2	
Total Split (s)	14.0	86.0		13.0	85.0		38.0	38.0		13.0	51.0	
Total Split (%)	9.3%	57.3%		8.7%	56.7%		25.3%	25.3%		8.7%	34.0%	
Maximum Green (s)	8.9	79.8		8.1	78.8		31.8	31.8		8.1	44.8	
Yellow Time (s)	3.0	4.7		3.0	4.7		4.7	4.7		3.0	4.7	
All-Red Time (s)	2.1	1.5		1.9	1.5		1.5	1.5		1.9	1.5	
Lost Time Adjust (s)	-0.1	-1.2		0.1	-1.2			-1.2			-1.2	
Total Lost Time (s)	5.0	5.0		5.0	5.0			5.0			5.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lag	Lag		Lead		
Lead-Lag Optimize?												
Vehicle Extension (s)	1.0	6.0		1.0	6.0		1.0	1.0		1.0	1.0	
Minimum Gap (s)	1.0	3.0		1.0	3.0		1.0	1.0		1.0	1.0	
Time Before Reduce (s)	0.0	15.0		0.0	15.0		0.0	0.0		0.0	0.0	
Time To Reduce (s)	0.0	30.0		0.0	30.0		0.0	0.0		0.0	0.0	
Recall Mode	None	Min		None	Min		None	None		None	None	
Act Effect Green (s)	7.8	81.0		8.0	83.7			33.0			46.0	
Actuated g/C Ratio	0.05	0.54		0.05	0.56			0.22			0.31	
v/c Ratio	0.45	1.11		1.08	0.63			1.18			0.85	

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Control Delay (s/veh)	85.5	98.2		181.6	27.0			163.8			68.3	
Queue Delay	0.0	0.0		0.0	0.0			0.0			0.0	
Total Delay (s/veh)	85.5	98.2		181.6	27.0			163.8			68.3	
LOS	F	F		F	C			F			E	
Approach Delay (s/veh)		97.7			48.0			163.8			68.3	
Approach LOS		F			D			F			E	
Queue Length 50th (ft)	39	~1184		~104	404			~351			269	
Queue Length 95th (ft)	81	#1448		#229	555			#546			#434	
Internal Link Dist (ft)		955			939			1042			1056	
Turn Bay Length (ft)	100			100								
Base Capacity (vph)	102	954		89	974			254			376	
Starvation Cap Reductn	0	0		0	0			0			0	
Spillback Cap Reductn	0	0		0	0			0			0	
Storage Cap Reductn	0	0		0	0			0			0	
Reduced v/c Ratio	0.39	1.11		1.08	0.63			1.18			0.85	

Intersection Summary

Area Type: Other

Cycle Length: 150

Actuated Cycle Length: 150

Natural Cycle: 150

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 1.18

Intersection Signal Delay (s/veh): 87.6

Intersection LOS: F

Intersection Capacity Utilization 90.7%

ICU Level of Service E

Analysis Period (min) 15


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

















Queue shown is maximum after two cycles.

Splits and Phases: 3: Twelve Mile Creek Road & Weddington Road (NC 84)



Lanes, Volumes, Timings
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	6	984	26	12	650	4	15	4	6	4	4	4
Future Volume (vph)	6	984	26	12	650	4	15	4	6	4	4	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.997			0.999			0.966			0.955	
Flt Protected					0.999			0.971			0.984	
Satd. Flow (prot)	0	1857	0	0	1841	0	0	1747	0	0	1750	0
Flt Permitted					0.999			0.971			0.984	
Satd. Flow (perm)	0	1857	0	0	1841	0	0	1747	0	0	1750	0
Link Speed (mph)		45			45			25			25	
Link Distance (ft)		1481			827			1039			1032	
Travel Time (s)		22.4			12.5			28.3			28.1	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	7	1093	29	13	722	4	17	4	7	4	4	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1129	0	0	739	0	0	28	0	0	12	0
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	66.5%						ICU Level of Service C					
Analysis Period (min)	15											

HCM 6th TWSC
5: Access A & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM wo STIP

Intersection												
Int Delay, s/veh	2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	6	984	26	12	650	4	15	4	6	4	4	4
Future Vol, veh/h	6	984	26	12	650	4	15	4	6	4	4	4
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	7	1093	29	13	722	4	17	4	7	4	4	4
















Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	726	0	0	1122	0	0	1876	1874	1108	1877	1886	724
Stage 1	-	-	-	-	-	-	1122	1122	-	750	750	-
Stage 2	-	-	-	-	-	-	754	752	-	1127	1136	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	877	-	-	623	-	-	55	72	255	55	71	426
Stage 1	-	-	-	-	-	-	250	281	-	403	419	-
Stage 2	-	-	-	-	-	-	401	418	-	249	277	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	877	-	-	623	-	-	50	68	255	49	67	426
Mov Cap-2 Maneuver	-	-	-	-	-	-	50	68	-	49	67	-
Stage 1	-	-	-	-	-	-	245	275	-	395	404	-
Stage 2	-	-	-	-	-	-	379	403	-	234	271	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.1			0.2			96.6			58.8		
HCM LOS							F			F		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	65	877	-	-	623	-	-	80
HCM Lane V/C Ratio	0.427	0.008	-	-	0.021	-	-	0.167
HCM Control Delay (s/veh)	96.6	9.1	0	-	10.9	0	-	58.8
HCM Lane LOS	F	A	A	-	B	A	-	F
HCM 95th %tile Q (veh)	1.7	0	-	-	0.1	-	-	0.6

Lanes, Volumes, Timings
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM wo STIP

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	4	987	4	4	661	4	4	4	4	4	4	4
Future Volume (vph)	4	987	4	4	661	4	4	4	4	4	4	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt					0.999				0.955		0.955	
Flt Protected									0.984		0.984	
Satd. Flow (prot)	0	1863	0	0	1843	0	0	1750	0	0	1750	0
Flt Permitted									0.984		0.984	
Satd. Flow (perm)	0	1863	0	0	1843	0	0	1750	0	0	1750	0
Link Speed (mph)	45				45				25		25	
Link Distance (ft)	827				528				1010		1072	
Travel Time (s)	12.5				8.0				27.5		29.2	
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
Heavy Vehicles (%)	2%	2%	2%	2%	3%	2%	2%	2%	2%	2%	2%	2%
Adj. Flow (vph)	4	1097	4	4	734	4	4	4	4	4	4	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	1105	0	0	742	0	0	12	0	0	12	0
Sign Control	Free				Free				Stop		Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	64.9%				ICU Level of Service C							
Analysis Period (min)	15											

HCM 6th TWSC
6: Access B & Weddington Road (NC 84)

Deal Lake TIA
2029 Build PM wo STIP

Intersection												
Int Delay, s/veh	0.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		+			+			+			+	
Traffic Vol, veh/h	4	987	4	4	661	4	4	4	4	4	4	4
Future Vol, veh/h	4	987	4	4	661	4	4	4	4	4	4	4
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	3	2	2	2	2	2	2	2
Mvmt Flow	4	1097	4	4	734	4	4	4	4	4	4	4

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	738	0	0	1101	0	0	1855	1853	1099	1855	1853	736
Stage 1	-	-	-	-	-	-	1107	1107	-	744	744	-
Stage 2	-	-	-	-	-	-	748	746	-	1111	1109	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	868	-	-	634	-	-	57	74	258	57	74	419
Stage 1	-	-	-	-	-	-	255	286	-	407	421	-
Stage 2	-	-	-	-	-	-	404	421	-	254	285	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	868	-	-	634	-	-	53	72	258	52	72	419
Mov Cap-2 Maneuver	-	-	-	-	-	-	53	72	-	52	72	-
Stage 1	-	-	-	-	-	-	252	283	-	402	416	-
Stage 2	-	-	-	-	-	-	391	416	-	243	282	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0.1	57.2	55.8
HCM LOS			F	F

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	82	868	-	-	634	-	-	84
HCM Lane V/C Ratio	0.163	0.005	-	-	0.007	-	-	0.159
HCM Control Delay (s/veh)	57.2	9.2	0	-	10.7	0	-	55.8
HCM Lane LOS	F	A	A	-	B	A	-	F
HCM 95th %tile Q (veh)	0.5	0	-	-	0	-	-	0.5

Queuing and Blocking Reports

2024 Existing Conditions

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	L	R	L	L	T	T	U	T	R
Maximum Queue (ft)	396	158	210	239	217	186	28	373	155
Average Queue (ft)	205	65	114	156	131	79	4	184	73
95th Queue (ft)	347	130	201	222	203	172	19	315	132
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)									
Queuing Penalty (veh)									
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								1	
Queuing Penalty (veh)								0	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	29	152
Average Queue (ft)	3	55
95th Queue (ft)	17	117
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	924	60	200	1037	1106	1142
Average Queue (ft)	92	454	9	68	839	551	517
95th Queue (ft)	214	944	95	198	1257	1243	1256
Link Distance (ft)		976	2797		985	1088	1098
Upstream Blk Time (%)		3			55	25	23
Queuing Penalty (veh)		15			0	0	0
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	4	50		0	69		
Queuing Penalty (veh)	21	42		1	27		

Network Summary

Network wide Queuing Penalty: 106

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	L	R	L	L	T	T	U	T	R
Maximum Queue (ft)	636	315	182	212	225	204	325	1084	680
Average Queue (ft)	343	137	75	123	130	77	14	616	187
95th Queue (ft)	619	261	171	198	206	176	123	1173	775
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)								5	3
Queuing Penalty (veh)								0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								39	
Queuing Penalty (veh)								2	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	40	107
Average Queue (ft)	6	33
95th Queue (ft)	26	80
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	1043	450	199	597	512	352
Average Queue (ft)	83	578	78	76	275	193	122
95th Queue (ft)	204	1090	411	180	541	420	280
Link Distance (ft)		976	2797		985	1088	1098
Upstream Blk Time (%)		10			0		
Queuing Penalty (veh)		87			0		
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	2	47		4	32		
Queuing Penalty (veh)	12	39		27	25		

Network Summary

Network wide Queuing Penalty: 192

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	L	R	L	L	T	T	U	T	R
Maximum Queue (ft)	809	460	160	186	236	218	177	869	379
Average Queue (ft)	475	158	62	110	151	101	10	455	125
95th Queue (ft)	868	361	143	176	225	199	98	861	403
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)								1	0
Queuing Penalty (veh)								0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								31	
Queuing Penalty (veh)								1	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	44	128
Average Queue (ft)	9	41
95th Queue (ft)	31	89
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	199	1071	764	192	447	592	547
Average Queue (ft)	31	765	164	70	209	252	204
95th Queue (ft)	125	1178	633	156	386	544	455
Link Distance (ft)		976	2797		985	1088	1098
Upstream Blk Time (%)		19					
Queuing Penalty (veh)		167					
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	0	50		3	22		
Queuing Penalty (veh)	0	15		16	18		

Network Summary

Network wide Queuing Penalty: 217

2029 Background Conditions w/ STIPs

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	294	174	184	205	140	158	166	170	509	519	433	21
Average Queue (ft)	162	92	96	116	78	92	82	89	348	351	53	1
95th Queue (ft)	254	155	168	193	129	146	161	166	528	535	285	13
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)									5	6	0	
Queuing Penalty (veh)									51	55	0	
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										13		
Queuing Penalty (veh)										15		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	262	328	468	466
Average Queue (ft)	149	171	277	291
95th Queue (ft)	224	309	464	456
Link Distance (ft)	631	631		
Upstream Blk Time (%)		0		
Queuing Penalty (veh)		3		
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)		0	1	1
Queuing Penalty (veh)		0	7	7

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	45	2	143
Average Queue (ft)	6	0	55
95th Queue (ft)	26	2	109
Link Distance (ft)		1102	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	SB
Directions Served	L	T	T	R	L	T	T	R	L	T	R	L
Maximum Queue (ft)	347	478	458	248	358	516	529	236	231	128	168	280
Average Queue (ft)	94	229	234	92	113	256	273	33	130	23	50	85
95th Queue (ft)	245	405	404	203	246	442	458	139	228	106	122	211
Link Distance (ft)		964	964			975	975			1061		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)	450			400	300			375	225		225	175
Storage Blk Time (%)	0	1	2			6	4		4	0		7
Queuing Penalty (veh)	1	1	3			8	3		5	1		24

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	SB	SB
Directions Served	T	R
Maximum Queue (ft)	349	224
Average Queue (ft)	85	107
95th Queue (ft)	246	200
Link Distance (ft)	1072	
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		125
Storage Blk Time (%)	6	10
Queuing Penalty (veh)	20	18

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	76	207	216	29	202	220	123	284	296	150
Average Queue (ft)	23	91	97	3	82	97	55	154	168	13
95th Queue (ft)	56	177	182	18	156	178	106	243	258	71
Link Distance (ft)		6341	6341		2100	2100			636	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)								0	24	
Queuing Penalty (veh)								0	64	

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB	SB	SB
Directions Served	R	R	T	T
Maximum Queue (ft)	100	104	8	40
Average Queue (ft)	6	7	0	3
95th Queue (ft)	44	48	8	46
Link Distance (ft)	631	631	542	542
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB	NB	NB
Directions Served	T	T	R	R
Maximum Queue (ft)	44	79	62	58
Average Queue (ft)	2	6	4	6
95th Queue (ft)	25	43	34	31
Link Distance (ft)	189	189	189	189
Upstream Blk Time (%)		0	0	
Queuing Penalty (veh)		0	0	
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	176	221
Average Queue (ft)	15	24
95th Queue (ft)	96	120
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	NB	NB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	331	342	169	157
Average Queue (ft)	60	63	29	28
95th Queue (ft)	287	296	105	101
Link Distance (ft)	489	489	491	491
Upstream Blk Time (%)	0	0		
Queuing Penalty (veh)	1	2		
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	44	58
Average Queue (ft)	2	5
95th Queue (ft)	21	28
Link Distance (ft)	86	86
Upstream Blk Time (%)	0	0
Queuing Penalty (veh)	0	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	121	100
Average Queue (ft)	13	9
95th Queue (ft)	72	65
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	33	14
Average Queue (ft)	1	1
95th Queue (ft)	16	10
Link Distance (ft)	839	839
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 16: Western U-turn Bulb & Rea Road

Movement		
Directions Served		
Maximum Queue (ft)		
Average Queue (ft)		
95th Queue (ft)		
Link Distance (ft)		
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	62	87
Average Queue (ft)	3	5
95th Queue (ft)	29	41
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB
Directions Served	R
Maximum Queue (ft)	62
Average Queue (ft)	4
95th Queue (ft)	29
Link Distance (ft)	576
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB
Directions Served	T	R
Maximum Queue (ft)	138	18
Average Queue (ft)	44	1
95th Queue (ft)	119	15
Link Distance (ft)	120	120
Upstream Blk Time (%)	1	0
Queuing Penalty (veh)	2	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	16	19
Average Queue (ft)	1	1
95th Queue (ft)	8	10
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	263	289	467	538
Average Queue (ft)	144	205	207	282
95th Queue (ft)	235	287	395	482
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)	0	2		
Queuing Penalty (veh)	1	6		
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	90	194	199
Average Queue (ft)	36	79	79
95th Queue (ft)	78	170	171
Link Distance (ft)	360	536	536
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	SB
Directions Served	L
Maximum Queue (ft)	82
Average Queue (ft)	38
95th Queue (ft)	67
Link Distance (ft)	107
Upstream Blk Time (%)	0
Queuing Penalty (veh)	0
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	NB
Directions Served	L
Maximum Queue (ft)	125
Average Queue (ft)	92
95th Queue (ft)	133
Link Distance (ft)	118
Upstream Blk Time (%)	3
Queuing Penalty (veh)	10
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Network Summary

Network wide Queuing Penalty: 308

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	256	196	184	216	114	122	156	157	386	370	105	60
Average Queue (ft)	152	118	93	122	51	60	64	85	198	204	24	7
95th Queue (ft)	224	179	163	199	93	102	145	159	327	326	74	36
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										1		
Queuing Penalty (veh)										1		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	215	226	243	254
Average Queue (ft)	128	139	122	135
95th Queue (ft)	195	205	209	223
Link Distance (ft)	631	631		
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	44	4	112
Average Queue (ft)	9	0	41
95th Queue (ft)	32	3	84
Link Distance (ft)		1102	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	SB
Directions Served	L	T	T	R	L	T	T	R	L	T	R	L
Maximum Queue (ft)	148	362	344	129	180	238	255	233	188	229	115	195
Average Queue (ft)	68	196	201	58	83	114	121	91	82	92	39	97
95th Queue (ft)	125	306	306	113	148	200	212	180	154	179	92	169
Link Distance (ft)		964	964			975	975			1061		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)	450			400	300			375	225		225	175
Storage Blk Time (%)			0						0	0		2
Queuing Penalty (veh)			0						1	1		4

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	SB	SB
Directions Served	T	R
Maximum Queue (ft)	247	170
Average Queue (ft)	87	31
95th Queue (ft)	186	103
Link Distance (ft)	1072	
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		125
Storage Blk Time (%)	5	0
Queuing Penalty (veh)	12	0

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	64	153	164	28	152	150	95	240	243	115
Average Queue (ft)	20	62	68	3	53	52	36	128	142	10
95th Queue (ft)	52	127	136	17	111	119	80	204	215	56
Link Distance (ft)		6341	6341		2100	2100			636	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)									15	
Queuing Penalty (veh)									36	

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	67	51
Average Queue (ft)	4	2
95th Queue (ft)	34	22
Link Distance (ft)	631	631
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	40	45
Average Queue (ft)	3	3
95th Queue (ft)	19	21
Link Distance (ft)	189	189
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	55	65
Average Queue (ft)	3	5
95th Queue (ft)	24	34
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	137	136
Average Queue (ft)	19	23
95th Queue (ft)	77	84
Link Distance (ft)	491	491
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	15	49
Average Queue (ft)	1	4
95th Queue (ft)	10	26
Link Distance (ft)	86	86
Upstream Blk Time (%)		0
Queuing Penalty (veh)		0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	46	34
Average Queue (ft)	3	1
95th Queue (ft)	24	15
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	EB	WB
Directions Served	T	R
Maximum Queue (ft)	5	8
Average Queue (ft)	0	0
95th Queue (ft)	5	4
Link Distance (ft)	329	839
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 16: Western U-turn Bulb & Rea Road

Movement	WB
Directions Served	L
Maximum Queue (ft)	27
Average Queue (ft)	1
95th Queue (ft)	13
Link Distance (ft)	143
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	193	256
Average Queue (ft)	15	19
95th Queue (ft)	158	182
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	130	10
Average Queue (ft)	14	0
95th Queue (ft)	78	8
Link Distance (ft)	576	576
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB	EB
Directions Served	T	R	R
Maximum Queue (ft)	137	25	12
Average Queue (ft)	49	0	1
95th Queue (ft)	128	13	8
Link Distance (ft)	120	120	120
Upstream Blk Time (%)	2	0	
Queuing Penalty (veh)	6	0	
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	28	37
Average Queue (ft)	1	2
95th Queue (ft)	26	29
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	158	184	144	201
Average Queue (ft)	74	100	78	113
95th Queue (ft)	128	157	130	177
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	106	134	145
Average Queue (ft)	48	60	59
95th Queue (ft)	94	123	125
Link Distance (ft)	360	536	536
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	EB	SB
Directions Served	T	L
Maximum Queue (ft)	2	114
Average Queue (ft)	0	50
95th Queue (ft)	2	93
Link Distance (ft)	198	107
Upstream Blk Time (%)		2
Queuing Penalty (veh)		2
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	NB
Directions Served	L
Maximum Queue (ft)	124
Average Queue (ft)	97
95th Queue (ft)	134
Link Distance (ft)	118
Upstream Blk Time (%)	3
Queuing Penalty (veh)	17
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Network Summary

Network wide Queuing Penalty: 81

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	464	230	260	291	86	96	214	213	458	473	270	21
Average Queue (ft)	263	124	146	175	42	48	116	130	238	246	23	1
95th Queue (ft)	423	205	238	271	78	85	202	201	435	443	161	15
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)									1	1	0	
Queuing Penalty (veh)									8	9	0	
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										5		
Queuing Penalty (veh)										6		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	265	282	221	229
Average Queue (ft)	154	166	131	144
95th Queue (ft)	236	247	199	213
Link Distance (ft)	631	631		
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	47	2	67
Average Queue (ft)	12	0	25
95th Queue (ft)	37	2	55
Link Distance (ft)		1102	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	B28	B28	WB	WB	WB	WB	NB	NB
Directions Served	L	T	T	R	T	T	L	T	T	R	L	T
Maximum Queue (ft)	262	419	420	169	9	18	176	339	357	123	249	209
Average Queue (ft)	134	235	246	67	0	0	70	196	207	43	141	44
95th Queue (ft)	230	369	373	135	0	7	136	302	325	94	249	165
Link Distance (ft)		964	964		2100	2100		975	975			1061
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)	450			400			300			375	225	
Storage Blk Time (%)		0	1					1	0		5	0
Queuing Penalty (veh)		0	1					1	0		7	0

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	NB	SB	SB	SB
Directions Served	R	L	T	R
Maximum Queue (ft)	173	121	150	143
Average Queue (ft)	56	46	26	57
95th Queue (ft)	129	99	86	114
Link Distance (ft)			1072	
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)	225	175		125
Storage Blk Time (%)		0	1	1
Queuing Penalty (veh)		0	1	1

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	82	231	243	37	240	250	157	287	305	171
Average Queue (ft)	23	115	119	5	114	125	59	169	182	19
95th Queue (ft)	61	206	214	22	209	220	120	256	269	97
Link Distance (ft)		6341	6341		2100	2100			636	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)								0	23	0
Queuing Penalty (veh)								0	77	0

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	79	90
Average Queue (ft)	6	6
95th Queue (ft)	40	40
Link Distance (ft)	631	631
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	68	57
Average Queue (ft)	7	10
95th Queue (ft)	35	37
Link Distance (ft)	189	189
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	72	109
Average Queue (ft)	6	12
95th Queue (ft)	38	60
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	NB	NB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	91	98	155	172
Average Queue (ft)	8	9	37	38
95th Queue (ft)	63	68	110	119
Link Distance (ft)	489	489	491	491
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	41	83
Average Queue (ft)	3	12
95th Queue (ft)	26	48
Link Distance (ft)	86	86
Upstream Blk Time (%)	0	0
Queuing Penalty (veh)	0	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	92	108
Average Queue (ft)	7	6
95th Queue (ft)	53	59
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	45	31
Average Queue (ft)	4	3
95th Queue (ft)	57	52
Link Distance (ft)	839	839
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 16: Western U-turn Bulb & Rea Road

Movement	WB
Directions Served	L
Maximum Queue (ft)	70
Average Queue (ft)	6
95th Queue (ft)	48
Link Distance (ft)	143
Upstream Blk Time (%)	1
Queuing Penalty (veh)	4
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	318	388
Average Queue (ft)	34	46
95th Queue (ft)	263	321
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	183	10
Average Queue (ft)	43	0
95th Queue (ft)	136	8
Link Distance (ft)	576	576
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB	EB
Directions Served	T	R	R
Maximum Queue (ft)	154	63	26
Average Queue (ft)	94	5	1
95th Queue (ft)	161	46	17
Link Distance (ft)	120	120	120
Upstream Blk Time (%)	5	0	0
Queuing Penalty (veh)	15	1	0
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	8	8
Average Queue (ft)	0	0
95th Queue (ft)	6	5
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	170	195	210	246
Average Queue (ft)	92	123	114	155
95th Queue (ft)	147	179	186	230
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	80	136	157
Average Queue (ft)	32	53	57
95th Queue (ft)	69	130	142
Link Distance (ft)	360	536	536
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	EB	SB
Directions Served	T	L
Maximum Queue (ft)	2	119
Average Queue (ft)	0	55
95th Queue (ft)	2	105
Link Distance (ft)	198	107
Upstream Blk Time (%)		6
Queuing Penalty (veh)		4
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	WB	NB
Directions Served	T	L
Maximum Queue (ft)	2	126
Average Queue (ft)	0	108
95th Queue (ft)	2	136
Link Distance (ft)	159	118
Upstream Blk Time (%)		4
Queuing Penalty (veh)		27
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Network Summary

Network wide Queuing Penalty: 164

2029 Build-out Conditions w/ STIPs

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	278	190	186	216	144	161	184	174	508	516	391	28
Average Queue (ft)	160	98	97	116	81	93	84	91	350	350	66	2
95th Queue (ft)	241	165	173	196	130	145	176	173	538	541	317	15
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)									5	6	0	
Queuing Penalty (veh)									49	53	0	
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										14		
Queuing Penalty (veh)										17		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	287	420	463	454
Average Queue (ft)	152	196	287	295
95th Queue (ft)	242	413	498	481
Link Distance (ft)	631	631		
Upstream Blk Time (%)		1		
Queuing Penalty (veh)		14		
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)		0	4	4
Queuing Penalty (veh)		0	25	25

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	37	155
Average Queue (ft)	5	58
95th Queue (ft)	24	121
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	SB
Directions Served	UL	T	T	R	L	T	T	R	L	T	R	L
Maximum Queue (ft)	283	414	415	225	362	601	631	401	260	146	167	305
Average Queue (ft)	118	212	218	93	121	283	301	53	142	20	52	91
95th Queue (ft)	241	361	360	192	269	515	539	218	254	91	125	223
Link Distance (ft)		1418	1418			975	975			1061		
Upstream Blk Time (%)							0					
Queuing Penalty (veh)							0					
Storage Bay Dist (ft)	450			400	300			375	225		225	175
Storage Blk Time (%)		0	1			9	7		7	0	0	6
Queuing Penalty (veh)		0	1			11	4		5	0	0	18

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	SB	SB
Directions Served	T	R
Maximum Queue (ft)	461	224
Average Queue (ft)	117	112
95th Queue (ft)	346	211
Link Distance (ft)	1072	
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		125
Storage Blk Time (%)	6	11
Queuing Penalty (veh)	20	20

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	72	196	203	37	183	192	161	292	313	208
Average Queue (ft)	20	85	91	8	76	92	48	162	180	24
95th Queue (ft)	53	173	178	27	147	161	118	247	267	115
Link Distance (ft)		6341	6341		814	814			643	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)								0	27	
Queuing Penalty (veh)								0	74	

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	NB	SB
Directions Served	R	R
Maximum Queue (ft)	55	35
Average Queue (ft)	20	7
95th Queue (ft)	47	28
Link Distance (ft)	1046	982
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	WB	NB	SB
Directions Served	TR	R	R
Maximum Queue (ft)	10	29	30
Average Queue (ft)	0	4	3
95th Queue (ft)	10	20	19
Link Distance (ft)	1418	998	982
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB	SB
Directions Served	R	R	T
Maximum Queue (ft)	82	86	109
Average Queue (ft)	7	6	19
95th Queue (ft)	41	40	162
Link Distance (ft)	631	631	542
Upstream Blk Time (%)			0
Queuing Penalty (veh)			0
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB	NB	NB
Directions Served	T	T	R	R
Maximum Queue (ft)	19	54	37	48
Average Queue (ft)	1	3	4	6
95th Queue (ft)	17	31	22	29
Link Distance (ft)	189	189	189	189
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	176	193
Average Queue (ft)	15	21
95th Queue (ft)	84	102
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	NB	NB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	287	280	139	151
Average Queue (ft)	50	50	23	28
95th Queue (ft)	245	245	82	98
Link Distance (ft)	489	489	491	491
Upstream Blk Time (%)	0	0		
Queuing Penalty (veh)	2	2		
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	20	64
Average Queue (ft)	0	8
95th Queue (ft)	7	37
Link Distance (ft)	86	86
Upstream Blk Time (%)	0	0
Queuing Penalty (veh)	0	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	140	136
Average Queue (ft)	16	13
95th Queue (ft)	81	85
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	29	26
Average Queue (ft)	1	1
95th Queue (ft)	19	17
Link Distance (ft)	839	839
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 16: Western U-turn Bulb & Rea Road

Movement	WB
Directions Served	L
Maximum Queue (ft)	3
Average Queue (ft)	0
95th Queue (ft)	4
Link Distance (ft)	143
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	57	65
Average Queue (ft)	3	5
95th Queue (ft)	35	48
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB
Directions Served	R
Maximum Queue (ft)	89
Average Queue (ft)	5
95th Queue (ft)	37
Link Distance (ft)	576
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB
Directions Served	T	R
Maximum Queue (ft)	132	9
Average Queue (ft)	40	0
95th Queue (ft)	114	9
Link Distance (ft)	120	120
Upstream Blk Time (%)	1	
Queuing Penalty (veh)	2	
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	3	18
Average Queue (ft)	0	1
95th Queue (ft)	3	10
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	263	287	501	564
Average Queue (ft)	143	197	218	293
95th Queue (ft)	227	280	458	535
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)	0	1		
Queuing Penalty (veh)	0	3		
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	86	218	216
Average Queue (ft)	37	90	87
95th Queue (ft)	76	219	217
Link Distance (ft)	360	536	536
Upstream Blk Time (%)		0	0
Queuing Penalty (veh)		1	2
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	SB
Directions Served	L
Maximum Queue (ft)	82
Average Queue (ft)	40
95th Queue (ft)	69
Link Distance (ft)	107
Upstream Blk Time (%)	0
Queuing Penalty (veh)	0
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	NB
Directions Served	L
Maximum Queue (ft)	122
Average Queue (ft)	93
95th Queue (ft)	134
Link Distance (ft)	118
Upstream Blk Time (%)	3
Queuing Penalty (veh)	10
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Network Summary

Network wide Queuing Penalty: 359

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	258	200	184	206	111	120	159	164	346	345	135	78
Average Queue (ft)	151	119	89	124	52	62	74	89	194	200	28	12
95th Queue (ft)	226	177	163	195	91	103	152	162	304	307	90	51
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										0		
Queuing Penalty (veh)										1		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	208	210	220	235
Average Queue (ft)	123	135	126	142
95th Queue (ft)	187	192	196	212
Link Distance (ft)	631	631		
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	38	10	108
Average Queue (ft)	8	0	43
95th Queue (ft)	30	7	89
Link Distance (ft)		1102	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	SB
Directions Served	UL	T	T	R	L	T	T	R	L	T	R	L
Maximum Queue (ft)	179	344	352	136	180	246	256	221	193	224	129	188
Average Queue (ft)	81	195	203	58	82	129	132	93	98	98	52	100
95th Queue (ft)	149	307	312	113	159	214	222	184	171	185	105	169
Link Distance (ft)		1419	1419			975	975			1060		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)	450			400	300			375	225		225	175
Storage Blk Time (%)			0			0			0	0		2
Queuing Penalty (veh)			0			0			0	1		5

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	SB	SB
Directions Served	T	R
Maximum Queue (ft)	271	165
Average Queue (ft)	94	34
95th Queue (ft)	197	102
Link Distance (ft)	1072	
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		125
Storage Blk Time (%)	6	0
Queuing Penalty (veh)	16	0

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	71	167	163	40	98	117	90	224	238	108
Average Queue (ft)	20	62	64	10	36	45	29	136	151	11
95th Queue (ft)	54	133	135	31	76	94	71	201	216	57
Link Distance (ft)		6341	6341		814	814			643	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)									18	
Queuing Penalty (veh)									46	

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	WB	NB	SB
Directions Served	T	R	R
Maximum Queue (ft)	3	42	29
Average Queue (ft)	0	15	4
95th Queue (ft)	0	39	20
Link Distance (ft)	767	1046	978
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	NB	SB
Directions Served	R	R
Maximum Queue (ft)	26	25
Average Queue (ft)	2	3
95th Queue (ft)	12	17
Link Distance (ft)	998	982
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	58	47
Average Queue (ft)	3	2
95th Queue (ft)	29	21
Link Distance (ft)	631	631
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	32	44
Average Queue (ft)	2	3
95th Queue (ft)	16	22
Link Distance (ft)	189	189
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	59	75
Average Queue (ft)	3	5
95th Queue (ft)	24	36
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	109	118
Average Queue (ft)	18	20
95th Queue (ft)	73	78
Link Distance (ft)	491	491
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	20	53
Average Queue (ft)	1	4
95th Queue (ft)	11	28
Link Distance (ft)	86	86
Upstream Blk Time (%)	0	0
Queuing Penalty (veh)	0	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	52	50
Average Queue (ft)	2	2
95th Queue (ft)	24	27
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	WB
Directions Served	R
Maximum Queue (ft)	16
Average Queue (ft)	1
95th Queue (ft)	11
Link Distance (ft)	839
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 16: Western U-turn Bulb & Rea Road

Movement	WB
Directions Served	L
Maximum Queue (ft)	28
Average Queue (ft)	2
95th Queue (ft)	16
Link Distance (ft)	143
Upstream Blk Time (%)	
Queuing Penalty (veh)	
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	84	178
Average Queue (ft)	5	12
95th Queue (ft)	38	97
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	115	24
Average Queue (ft)	11	1
95th Queue (ft)	65	16
Link Distance (ft)	576	576
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB	EB
Directions Served	T	R	R
Maximum Queue (ft)	134	62	12
Average Queue (ft)	50	3	0
95th Queue (ft)	126	33	7
Link Distance (ft)	120	120	120
Upstream Blk Time (%)	1	0	
Queuing Penalty (veh)	4	0	
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	23	48
Average Queue (ft)	1	2
95th Queue (ft)	12	19
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	149	172	166	197
Average Queue (ft)	69	101	80	114
95th Queue (ft)	119	152	133	178
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	111	146	151
Average Queue (ft)	48	63	63
95th Queue (ft)	92	130	133
Link Distance (ft)	360	536	536
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	EB	SB
Directions Served	T	L
Maximum Queue (ft)	2	117
Average Queue (ft)	0	55
95th Queue (ft)	2	103
Link Distance (ft)	198	107
Upstream Blk Time (%)		2
Queuing Penalty (veh)		2
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	WB	NB
Directions Served	T	L
Maximum Queue (ft)	2	124
Average Queue (ft)	0	100
95th Queue (ft)	2	135
Link Distance (ft)	159	118
Upstream Blk Time (%)		3
Queuing Penalty (veh)		17
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Network Summary

Network wide Queuing Penalty: 91

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	NB
Directions Served	T	T	R	R	T	T	R	R	T	T	R	R
Maximum Queue (ft)	453	256	267	296	95	109	208	208	472	484	276	35
Average Queue (ft)	255	130	143	171	48	51	112	129	268	276	22	2
95th Queue (ft)	406	216	225	252	86	90	198	198	433	441	146	17
Link Distance (ft)	839	839			576	576			491	491		
Upstream Blk Time (%)									1	1	0	
Queuing Penalty (veh)									6	7	0	
Storage Bay Dist (ft)			750	750			425	425			375	375
Storage Blk Time (%)										5		
Queuing Penalty (veh)										6		

Intersection: 1: S Providence Road (NC 16) & Rea Road/Rea Road Extension

Movement	SB	SB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	263	260	212	222
Average Queue (ft)	149	159	127	143
95th Queue (ft)	229	233	198	216
Link Distance (ft)	631	631		
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)			500	500
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	43	80
Average Queue (ft)	12	27
95th Queue (ft)	36	60
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	EB	EB	WB	WB	WB	WB	NB	NB	NB	SB
Directions Served	UL	T	T	R	L	T	T	R	L	T	R	L
Maximum Queue (ft)	332	391	405	217	195	379	408	148	278	266	152	126
Average Queue (ft)	159	242	254	83	72	222	234	49	160	60	58	46
95th Queue (ft)	282	372	378	167	160	350	368	127	272	181	122	101
Link Distance (ft)		1417	1417			975	975			1056		
Upstream Blk Time (%)												
Queuing Penalty (veh)												
Storage Bay Dist (ft)	450			400	300			375	225		225	175
Storage Blk Time (%)	0	0	1			2	1		8	0		0
Queuing Penalty (veh)	1	0	1			2	1		12	0		0

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	SB	SB
Directions Served	T	R
Maximum Queue (ft)	169	156
Average Queue (ft)	28	62
95th Queue (ft)	100	126
Link Distance (ft)	1072	
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		125
Storage Blk Time (%)	1	2
Queuing Penalty (veh)	2	1

Intersection: 4: Rea Road Extension & Weddington Road (NC 84)

Movement	EB	EB	EB	WB	WB	WB	WB	SB	SB	SB
Directions Served	L	T	T	U	T	T	R	L	L	R
Maximum Queue (ft)	74	251	261	59	173	185	112	289	314	193
Average Queue (ft)	23	123	127	15	81	96	51	180	194	22
95th Queue (ft)	58	215	225	44	150	167	99	266	284	104
Link Distance (ft)		6341	6341		813	813			643	
Upstream Blk Time (%)										
Queuing Penalty (veh)										
Storage Bay Dist (ft)	425			425			400	325		125
Storage Blk Time (%)								0	26	
Queuing Penalty (veh)								0	90	

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	NB	SB
Directions Served	R	R
Maximum Queue (ft)	57	31
Average Queue (ft)	17	5
95th Queue (ft)	46	24
Link Distance (ft)	1047	983
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	NB	SB
Directions Served	R	R
Maximum Queue (ft)	23	25
Average Queue (ft)	2	3
95th Queue (ft)	13	17
Link Distance (ft)	998	982
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 7: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	72	78
Average Queue (ft)	7	7
95th Queue (ft)	38	41
Link Distance (ft)	631	631
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 8: Northern U-turn Bulb

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	52	56
Average Queue (ft)	8	10
95th Queue (ft)	34	39
Link Distance (ft)	189	189
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 9: S Providence Road (NC 16)

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	84	96
Average Queue (ft)	6	10
95th Queue (ft)	42	55
Link Distance (ft)	994	994
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 11: S Providence Road (NC 16)

Movement	NB	NB	SB	SB
Directions Served	T	T	R	R
Maximum Queue (ft)	75	82	167	172
Average Queue (ft)	6	6	36	41
95th Queue (ft)	53	52	115	127
Link Distance (ft)	489	489	491	491
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 12: Southern U-turn Bulb

Movement	SB	SB
Directions Served	R	R
Maximum Queue (ft)	60	63
Average Queue (ft)	3	9
95th Queue (ft)	26	39
Link Distance (ft)	86	86
Upstream Blk Time (%)	0	0
Queuing Penalty (veh)	0	0
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 13: S Providence Road (NC 16)

Movement	NB	NB
Directions Served	R	R
Maximum Queue (ft)	53	50
Average Queue (ft)	3	2
95th Queue (ft)	29	24
Link Distance (ft)	1013	1013
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 15: Rea Road

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	16	20
Average Queue (ft)	1	1
95th Queue (ft)	17	21
Link Distance (ft)	839	839
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 16: Western U-turn Bulb & Rea Road

Movement	WB
Directions Served	L
Maximum Queue (ft)	69
Average Queue (ft)	7
95th Queue (ft)	45
Link Distance (ft)	143
Upstream Blk Time (%)	0
Queuing Penalty (veh)	1
Storage Bay Dist (ft)	
Storage Blk Time (%)	
Queuing Penalty (veh)	

Intersection: 17: Rea Road

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	335	372
Average Queue (ft)	24	29
95th Queue (ft)	184	216
Link Distance (ft)	1296	1296
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 19: Rea Road Extension

Movement	EB	EB
Directions Served	R	R
Maximum Queue (ft)	236	23
Average Queue (ft)	50	1
95th Queue (ft)	161	15
Link Distance (ft)	576	576
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 20: Eastern U-turn Bulb

Movement	EB	EB	EB
Directions Served	T	R	R
Maximum Queue (ft)	153	89	16
Average Queue (ft)	95	5	1
95th Queue (ft)	164	46	8
Link Distance (ft)	120	120	120
Upstream Blk Time (%)	5	0	
Queuing Penalty (veh)	17	0	
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 21: Rea Road Extension

Movement	WB	WB
Directions Served	R	R
Maximum Queue (ft)	23	28
Average Queue (ft)	1	1
95th Queue (ft)	15	15
Link Distance (ft)	6341	6341
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 101: S Providence Road (NC 16) & Northern U-turn Bulb

Movement	WB	WB	SB	SB
Directions Served	L	L	T	T
Maximum Queue (ft)	169	200	197	251
Average Queue (ft)	87	117	108	145
95th Queue (ft)	142	175	173	218
Link Distance (ft)	287	287	1050	1050
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 102: S Providence Road (NC 16) & Southern U-turn Bulb

Movement	EB	NB	NB
Directions Served	L	T	T
Maximum Queue (ft)	98	151	162
Average Queue (ft)	37	59	61
95th Queue (ft)	83	141	146
Link Distance (ft)	360	536	536
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 103: Rea Road & Western U-turn Bulb

Movement	EB	SB
Directions Served	T	L
Maximum Queue (ft)	25	116
Average Queue (ft)	1	58
95th Queue (ft)	26	109
Link Distance (ft)	198	107
Upstream Blk Time (%)	0	7
Queuing Penalty (veh)	0	6
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 104: Eastern U-turn Bulb & Rea Road Extension

Movement	WB	NB
Directions Served	T	L
Maximum Queue (ft)	2	126
Average Queue (ft)	0	109
95th Queue (ft)	2	135
Link Distance (ft)	159	118
Upstream Blk Time (%)		5
Queuing Penalty (veh)		29
Storage Bay Dist (ft)		
Storage Blk Time (%)		
Queuing Penalty (veh)		

Network Summary

Network wide Queuing Penalty: 182

2029 Background Conditions
w/o STIPs

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	380	176	204	237	244	220	29	465	194
Average Queue (ft)	212	76	123	159	153	109	2	236	88
95th Queue (ft)	335	144	196	218	227	206	14	419	153
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)									
Queuing Penalty (veh)									
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								5	
Queuing Penalty (veh)								0	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	37	11	193
Average Queue (ft)	5	0	74
95th Queue (ft)	23	7	150
Link Distance (ft)		965	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	1004	264	199	1045	1132	1140
Average Queue (ft)	124	560	45	61	998	628	562
95th Queue (ft)	241	1081	267	180	1091	1322	1318
Link Distance (ft)		976	2797		985	1088	1098
Upstream Blk Time (%)		11			82	37	32
Queuing Penalty (veh)		62			0	0	0
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	20	56		0	72		
Queuing Penalty (veh)	113	51		0	31		

Network Summary

Network wide Queuing Penalty: 257

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	1158	953	222	247	265	236	175	1323	1322
Average Queue (ft)	666	325	127	163	162	115	12	895	639
95th Queue (ft)	1203	819	216	231	243	217	107	1570	1603
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)	2	2						22	21
Queuing Penalty (veh)	0	0						0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								48	
Queuing Penalty (veh)								2	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	40	2	89
Average Queue (ft)	7	0	36
95th Queue (ft)	28	2	71
Link Distance (ft)		965	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	1076	1598	199	932	867	433
Average Queue (ft)	126	845	448	114	475	345	165
95th Queue (ft)	226	1239	1577	215	953	750	354
Link Distance (ft)		976	2797		985	1088	1098
Upstream Blk Time (%)		24			6	0	
Queuing Penalty (veh)		237			0	0	
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	27	47		18	39		
Queuing Penalty (veh)	233	45		114	33		

Network Summary

Network wide Queuing Penalty: 664

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	1193	955	233	258	293	261	210	1356	1360
Average Queue (ft)	724	404	124	158	192	152	14	806	588
95th Queue (ft)	1339	1078	222	238	275	250	122	1475	1468
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)	5	5						16	15
Queuing Penalty (veh)	0	0						0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								46	
Queuing Penalty (veh)								2	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	SB
Directions Served	L	LR
Maximum Queue (ft)	46	113
Average Queue (ft)	11	47
95th Queue (ft)	35	95
Link Distance (ft)		1127
Upstream Blk Time (%)		
Queuing Penalty (veh)		
Storage Bay Dist (ft)	125	
Storage Blk Time (%)		
Queuing Penalty (veh)		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	B12	WB	WB	NB	SB
Directions Served	L	TR	T	T	L	TR	LTR	LTR
Maximum Queue (ft)	199	1076	1940	89	199	616	784	408
Average Queue (ft)	54	961	726	8	112	271	436	233
95th Queue (ft)	155	1246	2119	110	205	534	828	402
Link Distance (ft)		976	2797	965		985	1088	1098
Upstream Blk Time (%)		38	2			0	1	
Queuing Penalty (veh)		378	19			0	0	
Storage Bay Dist (ft)	100				100			
Storage Blk Time (%)	0	47			23	26		
Queuing Penalty (veh)	4	16			126	22		

Network Summary

Network wide Queuing Penalty: 568

2029 Build-out Conditions
w/o STIPs

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	387	173	213	243	253	216	66	414	253
Average Queue (ft)	218	76	127	164	153	110	5	235	92
95th Queue (ft)	340	142	212	229	232	207	47	379	177
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)									
Queuing Penalty (veh)									
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								4	
Queuing Penalty (veh)								0	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	36	6	162
Average Queue (ft)	5	0	68
95th Queue (ft)	25	6	127
Link Distance (ft)		965	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	1063	382	199	1044	1129	1148
Average Queue (ft)	125	617	99	69	993	599	577
95th Queue (ft)	247	1185	398	199	1104	1298	1344
Link Distance (ft)		973	478		985	1086	1098
Upstream Blk Time (%)		21	4		81	34	35
Queuing Penalty (veh)		136	26		0	0	0
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	26	55		1	71		
Queuing Penalty (veh)	149	50		4	30		

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	EB	WB	NB	SB
Directions Served	LTR	LTR	LTR	LTR
Maximum Queue (ft)	51	35	53	30
Average Queue (ft)	3	2	22	7
95th Queue (ft)	25	16	50	28
Link Distance (ft)	1427	769	1059	977
Upstream Blk Time (%)				
Queuing Penalty (veh)				
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	EB	NB	SB
Directions Served	LTR	LTR	LTR
Maximum Queue (ft)	344	29	33
Average Queue (ft)	48	4	3
95th Queue (ft)	281	20	19
Link Distance (ft)	769	1052	1021
Upstream Blk Time (%)	0		
Queuing Penalty (veh)	0		
Storage Bay Dist (ft)			
Storage Blk Time (%)			
Queuing Penalty (veh)			

Network Summary

Network wide Queuing Penalty: 397

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	1290	1132	225	247	260	236	140	1357	1325
Average Queue (ft)	752	438	128	163	166	111	10	876	569
95th Queue (ft)	1378	1179	218	226	245	217	98	1494	1444
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)	5	4						14	14
Queuing Penalty (veh)	0	0						0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								48	
Queuing Penalty (veh)								2	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	WB	SB
Directions Served	L	TR	LR
Maximum Queue (ft)	39	2	97
Average Queue (ft)	8	0	38
95th Queue (ft)	29	2	78
Link Distance (ft)		965	1127
Upstream Blk Time (%)			
Queuing Penalty (veh)			
Storage Bay Dist (ft)	125		
Storage Blk Time (%)			
Queuing Penalty (veh)			

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	200	1084	487	200	1007	864	478
Average Queue (ft)	110	865	219	123	533	365	180
95th Queue (ft)	210	1270	589	227	1010	800	394
Link Distance (ft)		976	473		985	1087	1098
Upstream Blk Time (%)		29	9		7	1	
Queuing Penalty (veh)		280	82		0	0	
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	20	48		23	41		
Queuing Penalty (veh)	177	46		149	35		

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	EB	B12	WB	NB	SB
Directions Served	LTR	T	LTR	LTR	LTR
Maximum Queue (ft)	751	15	153	55	32
Average Queue (ft)	122	1	12	16	4
95th Queue (ft)	598	16	75	47	22
Link Distance (ft)	1428	965	772	1206	1120
Upstream Blk Time (%)	0				
Queuing Penalty (veh)	3				
Storage Bay Dist (ft)					
Storage Blk Time (%)					
Queuing Penalty (veh)					

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	EB	WB	NB	SB
Directions Served	LTR	LTR	LTR	LTR
Maximum Queue (ft)	782	52	35	24
Average Queue (ft)	230	2	4	2
95th Queue (ft)	766	27	21	13
Link Distance (ft)	772	473	1148	1425
Upstream Blk Time (%)	3			
Queuing Penalty (veh)	30			
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Network Summary

Network wide Queuing Penalty: 804

Intersection: 1: S Providence Road (NC 16) & Rea Road

Movement	EB	EB	NB	NB	NB	NB	SB	SB	SB
Directions Served	UL	R	L	L	T	T	U	T	R
Maximum Queue (ft)	1301	1214	213	241	288	260	171	1230	1221
Average Queue (ft)	906	590	114	149	194	149	13	810	563
95th Queue (ft)	1556	1431	206	223	273	248	116	1451	1423
Link Distance (ft)	1480	1480			1262			1326	1326
Upstream Blk Time (%)	10	9						15	15
Queuing Penalty (veh)	0	0						0	0
Storage Bay Dist (ft)			425	425		450	325		
Storage Blk Time (%)								48	
Queuing Penalty (veh)								2	

Intersection: 2: Weddington Road (NC 84) & Cox Road

Movement	EB	EB	WB	SB
Directions Served	L	T	TR	LR
Maximum Queue (ft)	57	120	4	182
Average Queue (ft)	13	22	0	64
95th Queue (ft)	53	258	3	198
Link Distance (ft)		1180	965	1127
Upstream Blk Time (%)		1		
Queuing Penalty (veh)		0		
Storage Bay Dist (ft)	125			
Storage Blk Time (%)		2		
Queuing Penalty (veh)		1		

Intersection: 3: Twelve Mile Creek Road & Weddington Road (NC 84)

Movement	EB	EB	B13	WB	WB	NB	SB
Directions Served	L	TR	T	L	TR	LTR	LTR
Maximum Queue (ft)	198	1078	481	199	682	880	462
Average Queue (ft)	49	954	272	115	299	464	251
95th Queue (ft)	139	1225	635	206	571	913	431
Link Distance (ft)		976	466		985	1088	1098
Upstream Blk Time (%)		38	10		0	5	
Queuing Penalty (veh)		376	102		0	0	
Storage Bay Dist (ft)	100			100			
Storage Blk Time (%)	1	47		27	29		
Queuing Penalty (veh)	6	17		148	25		

Intersection: 5: Access A & Weddington Road (NC 84)

Movement	EB	B12	WB	NB	SB
Directions Served	LTR	T	LTR	LTR	LTR
Maximum Queue (ft)	1036	214	235	70	30
Average Queue (ft)	291	45	24	19	3
95th Queue (ft)	1099	354	139	53	16
Link Distance (ft)	1420	965	754	1002	999
Upstream Blk Time (%)	7	0			
Queuing Penalty (veh)	66	2			
Storage Bay Dist (ft)					
Storage Blk Time (%)					
Queuing Penalty (veh)					

Intersection: 6: Access B & Weddington Road (NC 84)

Movement	EB	WB	NB	SB
Directions Served	LTR	LTR	LTR	LTR
Maximum Queue (ft)	755	22	32	29
Average Queue (ft)	319	1	4	4
95th Queue (ft)	898	15	21	19
Link Distance (ft)	754	466	976	1037
Upstream Blk Time (%)	5			
Queuing Penalty (veh)	49			
Storage Bay Dist (ft)				
Storage Blk Time (%)				
Queuing Penalty (veh)				

Network Summary

Network wide Queuing Penalty: 794

Auxiliary Turn-Lane Warrants


Warrant for Left and Right-Turn Lanes AT GRADE, UNSIGNALIZED INTERSECTIONS

- Right Turn Storage Lengths are based on opposing volume of 100 VPH (MINIMUM)
S=STORAGE LENGTH REQUIRED

2029 BUILD-OUT

AM	MD	PM
$V_{WBR} = 1$	$V_{WBR} = 2$	$V_{WBR} = 3$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBR} = 11$	$V_{EBR} = 31$	$V_{EBR} = 37$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$

OPPOSING VOLUME: V



V_L : LEFT TURNING VOLUME (VPH)
 V_R : RIGHT TURNING VOLUME (VPH)

Note: Where adjacent signalization may provide opportunities for gaps in the traffic stream a reduction in the above storage values can be considered on a case by case basis.


Warrant for Left and Right-Turn Lanes AT GRADE, UNSIGNALIZED INTERSECTIONS

- Right Turn Storage Lengths are based on opposing volume of 100 VPH (MINIMUM)
S=STORAGE LENGTH REQUIRED

2029 BUILD-OUT

AM	MD	PM
$V_{WBR} = 3$	$V_{WBR} = 8$	$V_{WBR} = 9$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBR} = 2$	$V_{EBR} = 4$	$V_{EBR} = 5$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$

TOTAL OPPOSING VOL: V



V_L : LEFT TURNING VOLUME (VPH)
 V_R : RIGHT TURNING VOLUME (VPH)

Note: Where adjacent signalization may provide opportunities for gaps in the traffic stream a reduction in the above storage values can be considered on a case by case basis.


Warrant for Left and Right-Turn Lanes AT GRADE, UNSIGNALIZED INTERSECTIONS

- Right Turn Storage Lengths are based on opposing volume of 100 VPH (MINIMUM)
S=STORAGE LENGTH REQUIRED

Policy On Street And Driveway Access to North Carolina Highways

2029 BUILD-OUT

AM	MD	PM
$V_{WBR} = 0$	$V_{WBR} = 1$	$V_{WBR} = 1$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBR} = 8$	$V_{EBR} = 21$	$V_{EBR} = 26$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{WBL} = 4$	$V_{WBL} = 10$	$V_{WBL} = 12$
$V_o = 632$	$V_o = 977$	$V_o = 1016$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBL} = 2$	$V_{EBL} = 5$	$V_{EBL} = 6$
$V_o = 952$	$V_o = 695$	$V_o = 663$
$S = 0'$	$S = 0'$	$S = 0'$



Int. # 6: Weddington Road (NC 84) and Access B (FM)


Warrant for Left and Right-Turn Lanes AT GRADE, UNSIGNALIZED INTERSECTIONS

- Right Turn Storage Lengths are based on opposing volume of 100 VPH (MINIMUM)
S=STORAGE LENGTH REQUIRED

Policy On Street And Driveway Access to North Carolina Highways

2029 BUILD-OUT

AM	MD	PM
$V_{WBR} = 1$	$V_{WBR} = 2$	$V_{WBR} = 3$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBR} = 0$	$V_{EBR} = 2$	$V_{EBR} = 2$
$V_o = 100$	$V_o = 100$	$V_o = 100$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{WBL} = 1$	$V_{WBL} = 2$	$V_{WBL} = 2$
$V_o = 634$	$V_o = 958$	$V_o = 991$
$S = 0'$	$S = 0'$	$S = 0'$
$V_{EBL} = 1$	$V_{EBL} = 2$	$V_{EBL} = 2$
$V_o = 951$	$V_o = 697$	$V_o = 666$
$S = 0'$	$S = 0'$	$S = 0'$



July 2003

November 18, 2024

Mr. Greg Gordos
Town Planner
Town of Weddington
1924 Weddington Road
Weddington, NC 28104

RE: Review of Traffic Impact Analysis (TIA)
Deal Lake
Town of Weddington, NC

Mr. Gordos:

Pursuant to your request, LaBella Associates has reviewed the Updated Traffic Impact Analysis (TIA) for the proposed subject development, prepared for Toll Brothers, by Laura Reid, PE, Kimley Horn & Associates, dated October 2024.

This updated TIA is essentially the same as the TIA submitted in August 2024 with the exception of the addition of the mitigation changes required by NCDOT without the TIP project scenario.

The Updated TIA includes the mitigation for the Access A and Access B without the TIP projects. The changes are listed below for the two intersections:

- **Weddington Road (NC 84) and Access A**
 - Access A will operate as Right-in/Right-Out (RIRO) with one ingress lane, one egress lane, stop controlled with internal protected stem (IPS) of 100 feet.
 - Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.
- **Weddington Road (NC 84) and Access B**
 - Access B will operate as Right-in/Right-out (RIRO) with one ingress lane, one egress lane, stop controlled with internal protected stem (IPS) of 100 feet.
 - Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

The above changes will not affect the results of the studied intersection and the review letter submitted by LaBella Associates, dated September 13, 2024 is valid for this October 2024 updated TIA.

All the requested updates are included appropriately in the Updated TIA, dated October 2024 and are considered acceptable.



We trust the information herein is sufficient for your immediate needs. Please do not hesitate to contact me at 914-269-5610 or Mr. Watson at 704-941-2112 should you have any questions

Respectfully submitted,

Bernard Adler, P.E.
Senior Transportation Consultant
LaBella Associates
One North Broadway, Suite 803
White Plains, NY 10601

Danny L. Watson, PE, CFM, PMP
Senior Civil Engineer
Project Manager

From: [Lipsky, Amber L CIV USARMY CESAW \(USA\)](#)
To: [Robert Price](#)
Cc: [Drew Lucas](#); jpropst0731@gmail.com
Subject: SAW-2024-01918 Deal Lake Delineation Concurrence
Date: Thursday, November 7, 2024 1:33:56 PM
Attachments: [SAW-2024-01918 Delineation Concurrence.pdf](#)

This message came from outside Toll Brothers

This message came from a sender outside Toll Brothers. Please be careful before clicking on or opening any links. If you are unsure about any of the contents, click the "Report Suspicious" button to report this email to Information Security and they will determine if the email is secure.

[Report Suspicious](#)

Dear Mr. Price,

Please reference your DELINEATION CONCURRENCE OR PRELIMINARY JURISDICTIONAL DETERMINATION (PJD) request for the above referenced property, Corps Action ID: SAW-2024-01918. By copy of this e-mail, we are confirming that the delineation depicted on the attached map labeled "Approximate Delineation of Surface Waters and Wetlands" and dated November 5, 2024, is verified by our office and is a sufficiently accurate representation of the geographic boundaries of the aquatic resources located on the site.

Regulatory Guidance Letter (RGL) 16-01 provides guidance for Jurisdictional Determinations (JDs) and states, "The Corps generally does not issue a JD of any type where no JD has been requested" and in "certain circumstances where a JD would not be necessary." This delineation may be relied upon for use in the permit evaluation process with our office, including determining proposed impacts and compensatory mitigation. This delineation verification is not an Approved Jurisdictional Determination (AJD) and is not an appealable action under the Regulatory Program Administrative Appeal Process (33 CFR Part 331).

Unless a future request is received that requires additional review, no further correspondence will be forthcoming, and the Corps considers this request complete.

Best Regards,


Amber Lipsky, PWS (she/her)
Regulatory Specialist, Charlotte Regulatory Field Office
U.S. Army Corps of Engineers, Wilmington District
8430 University Executive Park Drive, Suite 615
Charlotte, NC 28262



Email: Amber.L.Lipsky@usace.army.mil

Office: (704)510-1441

Mobile: (704)962-6947

The Wilmington District is committed to providing the highest level of support to the public. To help us ensure we continue to do so, please complete the Customer Satisfaction Survey located at our website at <https://regulatory.ops.usace.army.mil/customer-service-survey/> to complete the survey online.



 Figure 1: Approximate Delineation of Surface Waters and Wetlands	Project Name:	Deal Lake Development		 Date: 11-05-2024
	Owner / Developer:	Toll Brothers		
	City / County:	Weddington/Union		
	Tax PIN(s):	06129109, 06126001, 06126017, 06126017C, 06126017B		
	Coordinates:	Lat: 35.003186	Long: -80.740517	

NC DWQ Stream Identification Form Version 4.11

SF1

Date: 2024-11-05	Project/Site: Deal Lake	Latitude: 35.0031004
Evaluator: DL PI	County: Union	Longitude: -80.73942405
Total Points: 15 <i>Stream is at least intermittent if ≥ 19 or perennial if ≥ 30*</i>	Stream Determination (circle one) <u>Ephemeral</u> Intermittent Perennial	Other e.g. Quad Name:

A. Geomorphology (Subtotal= <u>8</u>)	Absent	Weak	Moderate	Strong
1 ^a Continuity of channel bed and bank	0	1	(2)	3
2. Sinuosity of channel along thalweg	0	(1)	2	3
3. In-channel structure: ex. riffle-pool, step-pool, ripple-pool sequence	0	(1)	2	3
4. Particle size of stream substrate	0	(1)	2	3
5. Active/relict floodplain	0	(1)	2	3
6. Depositional bars or benches	(0)	1	2	3
7. Recent alluvial deposits	(0)	1	2	3
8. Headcuts	0	(1)	2	3
9. Grade control	0	(0.5)	1	1.5
10. Natural valley	0	(0.5)	1	1.5
11. Second or greater order channel	(No = 0)		Yes = 3	

^a artificial ditches are not rated; see discussions in manual

B. Hydrology (Subtotal = 4)

12. Presence of Baseflow	(0)	1	2	3
13. Iron oxidizing bacteria	(0)	1	2	3
14. Leaf litter	1.5	1	(0.5)	0
15. Sediment on plants or debris	(0)	0.5	1	1.5
16. Organic debris lines or piles	0	(0.5)	1	1.5
17. Soil-based evidence of high water table?	No = 0		(Yes = 3)	

C. Biology (Subtotal = 3)

18. Fibrous roots in streambed	3	2	(1)	0
19. Rooted upland plants in streambed	3	(2)	1	0
20. Macrobenthos (note diversity and abundance)	(0)	1	2	3
21. Aquatic Mollusks	(0)	1	2	3
22. Fish	(0)	0.5	1	1.5
23. Crayfish	(0)	0.5	1	1.5
24. Amphibians	(0)	0.5	1	1.5
25. Algae	(0)	0.5	1	1.5
26. Wetland plants in streambed	FACW = 0.75; OBL = 1.5 (Other = 0)			

*perennial streams may also be identified using other methods. See p. 35 of manual.

Notes:

Sketch:

NC DWQ Stream Identification Form Version 4.11

SF2

Date: 2024-11-05	Project/Site: Deal Lake	Latitude: 35.00043858
Evaluator: DL PI	County: Union	Longitude: -80.74331405
Total Points: 14 <i>Stream is at least intermittent if ≥ 19 or perennial if ≥ 30*</i>	Stream Determination (circle one) <u>Ephemeral</u> Intermittent Perennial	Other e.g. Quad Name:

A. Geomorphology (Subtotal= <u>7.5</u>)	Absent	Weak	Moderate	Strong
1 ^a Continuity of channel bed and bank	0	(1)	2	3
2. Sinuosity of channel along thalweg	0	(1)	2	3
3. In-channel structure: ex. riffle-pool, step-pool, ripple-pool sequence	0	(1)	2	3
4. Particle size of stream substrate	0	(1)	2	3
5. Active/relict floodplain	0	(1)	2	3
6. Depositional bars or benches	0	(1)	2	3
7. Recent alluvial deposits	(0)	1	2	3
8. Headcuts	0	(1)	2	3
9. Grade control	(0)	0.5	1	1.5
10. Natural valley	0	(0.5)	1	1.5
11. Second or greater order channel	(No = 0)		Yes = 3	

^a artificial ditches are not rated; see discussions in manual

B. Hydrology (Subtotal = 3.5)

12. Presence of Baseflow	(0)	1	2	3
13. Iron oxidizing bacteria	(0)	1	2	3
14. Leaf litter	1.5	1	(0.5)	0
15. Sediment on plants or debris	(0)	0.5	1	1.5
16. Organic debris lines or piles	(0)	0.5	1	1.5
17. Soil-based evidence of high water table?	No = 0		(Yes = 3)	

C. Biology (Subtotal = 3)

18. Fibrous roots in streambed	3	(2)	1	0
19. Rooted upland plants in streambed	3	2	(1)	0
20. Macroinvertebrates (note diversity and abundance)	(0)	1	2	3
21. Aquatic Mollusks	(0)	1	2	3
22. Fish	(0)	0.5	1	1.5
23. Crayfish	(0)	0.5	1	1.5
24. Amphibians	(0)	0.5	1	1.5
25. Algae	(0)	0.5	1	1.5
26. Wetland plants in streambed	FACW = 0.75; OBL = 1.5 (Other = 0)			

*perennial streams may also be identified using other methods. See p. 35 of manual.

Notes:

Sketch:

PRELIMINARY JURISDICTIONAL DETERMINATION (PJD) FORM

BACKGROUND INFORMATION

A. REPORT COMPLETION DATE FOR PJD: DATE

B. NAME AND ADDRESS OF PERSON REQUESTING PJD: Toll Brothers, Robert Price, 9130 Kings Parade Boulevard, Charlotte, NC 28273

C. DISTRICT OFFICE, FILE NAME, AND NUMBER: Wilmington District, Deal Lake, FILE NUMBER

D. PROJECT LOCATION(S) AND BACKGROUND INFORMATION: 35.003186, -80.740517
(USE THE TABLE BELOW TO DOCUMENT MULTIPLE AQUATIC RESOURCES AND/OR AQUATIC RESOURCES AT DIFFERENT SITES)

State: NORTH CAROLINA County: UNION City: WEDDINGTON

Center coordinates of site (lat/long in degree decimal format): Latitude: 35.003186 Longitude: -80.740517

Universal Transverse Mercator:

Name of nearest waterbody: MUNDYS RUN

E. REVIEW PERFORMED FOR SITE EVALUATION (CHECK ALL THAT APPLY):

☐ Office (Desk) Determination. Date:

☐ Field Determination. Date(s):

TABLE OF AQUATIC RESOURCES IN REVIEW AREA WHICH "MAY BE" SUBJECT TO REGULATORY JURISDICTION.

Site Number	Latitude (decimal degrees)	Longitude (decimal degrees)	Estimated amount of aquatic resources in review area (acreage and linear feet, if applicable)	Type of aquatic resources (i.e., wetland vs. non-wetland waters)	Geographic authority to which the aquatic resource "may be" subject (i.e., Section 404 or Section 10/404)
Tributary 1	35.00109666	-80.74142730	2550 LF	Non-wetland waters	Section 404
Tributary 1 (Intermittent)	35.00348043	-80.74014818	560 LF	Non-wetland waters	Section 404
Tributary 1A	34.99985250	-80.74331051	365 LF	Non-wetland waters	Section 404
Tributary 1B	35.00091427	-80.74098959	300 LF	Non-wetland waters	Section 404
Tributary 1C	35.00170824	-80.74147163	155 LF	Non-wetland waters	Section 404
Tributary 1D	35.00294732	-80.73980400	250 LF	Non-wetland waters	Section 404
Tributary 2	35.00094090	-80.74837775	1740 LF	Non-wetland waters	Section 404
Tributary 2A	35.00075785	-80.74507598	790 LF	Non-wetland waters	Section 404

Tributary 2B	35.00232819	-80.74747898	150 LF	Non-wetland waters	Section 404
Tributary 2C	35.00386054	-80.74333226	495 LF	Non-wetland waters	Section 404
Tributary 3	35.00648853	-80.73595660	1095 LF	Non-wetland waters	Section 404
Tributary 4	35.00762700	-80.73563047	1145 LF	Non-wetland waters	Section 404
Wetland A1000	35.00381713	-80.74020477	0.01 ac	Wetland	Section 404
Wetland A1100	35.00354778	-80.74029627	0.01 ac	Wetland	Section 404
Wetland A1200	35.00342276	-80.74007443	0.07 ac	Wetland	Section 404
Wetland A1300	35.00327878	-80.74043033	0.03 ac	Wetland	Section 404
Wetland AA1300	35.002735	-80.740246	0.01 ac	Wetland	Section 404
Wetland A1400	34.99898782	-80.74358061	0.86 ac	Wetland	Section 404
Wetland A1500	35.00371368	-80.74284901	0.02 ac	Wetland	Section 404
Wetland A1600	35.00090816	-80.74797045	3.94 ac	Wetland	Section 404
Wetland A2000	35.00657855	-80.73699165	0.03 ac	Wetland	Section 404
Wetland A2100	35.00678194	-80.73811916	0.52 ac	Wetland	Section 404
Pond 1	35.00453497	-80.73995187	0.7 ac	Non-Wetland	Section 404
Pond 2	34.99869269	-80.74491660	4.73 ac	Non-Wetland	Section 404

- 1) The Corps of Engineers believes that there may be jurisdictional aquatic resources in the review area, and the requestor of this PJD is hereby advised of his or her option to request and obtain an approved JD (AJD) for that review area based on an informed decision after having discussed the various types of JDs and their characteristics and circumstances when they may be appropriate.
- 2) In any circumstance where a permit applicant obtains an individual permit, or a Nationwide General Permit (NWP) or other general permit verification requiring "pre- construction notification" (PCN), or requests verification for a non-reporting NWP or other general permit, and the permit applicant has not requested an AJD for the activity, the permit applicant is hereby made aware that: (1) the permit applicant has elected to seek a permit authorization based on a PJD, which does not make an official

determination of jurisdictional aquatic resources; (2) the applicant has the option to request an AJD before accepting the terms and conditions of the permit authorization, and that basing a permit authorization on an AJD could possibly result in less compensatory mitigation being required or different special conditions; (3) the applicant has the right to request an individual permit rather than accepting the terms and conditions of the NWP or other general permit authorization; (4) the applicant can accept a permit authorization and thereby agree to comply with all the terms and conditions of that permit, including whatever mitigation requirements the Corps has determined to be necessary; (5) undertaking any activity in reliance upon the subject permit authorization without requesting an AJD constitutes the applicant's acceptance of the use of the PJD; (6) accepting a permit authorization (e.g., signing a proffered individual permit) or undertaking any activity in reliance on any form of Corps permit authorization based on a PJD constitutes agreement that all aquatic resources in the review area affected in any way by that activity will be treated as jurisdictional, and waives any challenge to such jurisdiction in any administrative or judicial compliance or enforcement action, or in any administrative appeal or in any Federal court; and (7) whether the applicant elects to use either an AJD or a PJD, the JD will be processed as soon as practicable. Further, an AJD, a proffered individual permit (and all terms and conditions contained therein), or individual permit denial can be administratively appealed pursuant to 33 C.F.R. Part 331. If, during an administrative appeal, it becomes appropriate to make an official determination whether geographic jurisdiction exists over aquatic resources in the review area, or to provide an official delineation of jurisdictional aquatic resources in the review area, the Corps will provide an AJD to accomplish that result, as soon as is practicable. This PJD finds that there *"may be"* waters of the U.S. and/or that there *"may be"* navigable waters of the U.S. on the subject review area, and identifies all aquatic features in the review area that could be affected by the proposed activity, based on the following information:

SUPPORTING DATA. Data reviewed for PJD (check all that apply)

Checked items should be included in subject file. Appropriately reference sources below where indicated for all checked items:

- ☒ Maps, plans, plots or plat submitted by or on behalf of the PJD requestor:
Map: Resource maps and delineation sketch submitted by W&W consultant__
- ☐ Data sheets prepared/submitted by or on behalf of the PJD requestor.
 - ☐ Office concurs with data sheets/delineation report.
 - ☐ Office does not concur with data sheets/delineation report. Rationale:_____
- ☐ Data sheets prepared by the Corps:_____
- ☐ Corps navigable waters' study:_____
- ☐ U.S. Geological Survey Hydrologic Atlas:_____
- ☐ USGS NHD data.
- ☐ USGS 8 and 12 digit HUC maps.
- ☒ U.S. Geological Survey map(s). Cite scale & quad name: Figure 3, 05-03-2024__
- ☒ Natural Resources Conservation Service Soil Survey. Citation: Figure 4, 05-03-2024_____
- ☒ National wetlands inventory map(s). Cite name: Figure 5, 05-03-2024_
- ☐ State/local wetland inventory map(s):_____
- ☒ FEMA/FIRM maps: Figure 6, 05-03-2024_____
- ☐ 100-year Floodplain Elevation is:_____ (National Geodetic Vertical Datum of 1929)
- ☒ Photographs: ☒ Aerial (Name & Date): County GIS, Figure 2, 05-03-2024_____
or ☒ Other (Name & Date): Field Photos, 01-15-2024_____
- ☐ Previous determination(s). File no. and date of response letter:_____

☐ Other information (please specify): _____

IMPORTANT NOTE: The information recorded on this form has not necessarily been verified by the Corps and should not be relied upon for later jurisdictional determinations.

Signature and date of Regulatory
staff member completing PJD

DATE

Signature and date of person requesting PJD
(REQUIRED, unless obtaining the signature is
impracticable)¹

¹ Districts may establish timeframes for requester to return signed PJD forms. If the requester does not respond within the established time frame, the district may presume concurrence and no additional follow up is necessary prior to finalizing an action.



PIEDMONT ENVIRONMENTAL ASSOCIATES, P.A.

October 10, 2024

Project # 5792

Applied Resource Management
Attn: Mr. Walter Giese
257 Transfer Station Rd.
Hampstead, NC 28443

RE: Soil Report for Detailed Evaluation, PINS 06129109, 06126017, 06126001, total of 185.2 acres on Weddington Road Union County.

Dear Mr. Giese,

Request: You requested that we map these tracts in detail, except for 15 acres on the south side of Weddington Rd. The map is intended to be used for guidance during the planning stages of a proposed residential development. The soil areas were delineated by septic system types, including conventional systems, low-profile chamber systems, and drip irrigation systems.

Evaluation: The evaluation took place on October 2nd and 3rd, 2024. Six hundred ninety-seven hand-auger borings, landscape, vegetative patterns, and surface colors were evaluated. The evaluation was conducted under the direction of LSS James Beeson. Delineations were mapped, and soil characterizations were stored using global positioning systems in concert with base maps provided by your office.

Findings: A PDF digital map, digital shape files, and an AutoCAD file have been emailed to you, showing the areas usable for the system types mentioned above. Typically, we recommend that you attempt to minimize the use of the drip irrigation areas for primary systems during the planning stages. These systems are normally three times the cost of a conventional system and require an operator. The area required in the drip irrigation limits for a primary or repair system would be approximately 1,000 square feet per bedroom, which meets all setbacks listed in Attachment I. Please remember that the dwellings require an initial system and a repair area. Often the drip irrigation areas are used to fulfill the repair area requirement since the repair area is not initially installed.

The Low-Profile Chamber type areas will require approximately 1,250 square feet per bedroom, which meets the setbacks listed in Attachment I for either the initial or repair systems. Conventional areas can utilize chamber technology or panel block technology to reduce the footprint of the required area. We still recommend that you allocate 1,000 square feet per bedroom for each primary or repair system.

These area projections are a crude way to allocate areas needed for systems. A more accurate way is to flag the proposed trenches in the field. The length of the trench is governed by the number of bedrooms, the system type, and the soil's long-term acceptance rate. We can mix and match system types and do further work once the lot lines are designated.

Off-site systems require the same amount of area, but if systems from different houses are combined, the separation setbacks are eliminated. This technique is commonly referred to as “ganged” systems. I would recommend limiting ganged systems to less than 3,000 gallons per day, which is a threshold that triggers the requirement for additional hydrology assessments.

Recommendations: The maps produced are on state plane coordinates and can be used to calculate areas within lots or designated drain fields. Remember that further work can be done if homes with more bedrooms are desired, or site planes impact the proposed system areas. System areas cannot be graded under any circumstance! Areas designated for septic systems and any associated setbacks should be fenced during all construction phases of this project.

Disclaimer: This report discusses the general location of potentially usable soils for on-site wastewater disposal and the soil and site limitations on the property at the time of the evaluation. Piedmont Environmental Associates, PA (“Piedmont”) provides professional consulting specializing in soil science and wastewater management. Piedmont is, therefore, hired for its professional opinion regarding these matters. Laws and rules governing wastewater treatment and disposal are forever evolving and subject to the interpretation and opinion of individuals employed by local and state agencies that govern these laws and rules. Due to this fact, Piedmont cannot guarantee that any area located in the field, shown on a sketch, or discussed with the client will be permitted by any of these agencies. It is for this reason that Piedmont strongly recommends that anyone considering a financial commitment on any piece of property be completely aware of all permit requirements on that property before purchasing and obtaining those permits before a final financial commitment. We are pleased to be of service in this matter. If you have further questions, please call (336)215-8820. This map and report may not be reproduced or shared in any way without the express written permission of Piedmont Environmental Associates, PA. This map and report may not be reproduced or shared in any way without the express written permission of Piedmont Environmental Associates, PA.

Sincerely,



James L. Beeson
NC Licensed Soil Scientist # 1114
Piedmont Environmental Associates, P.A.

Attachment I

TABLE IX: Minimum setbacks from all wastewater systems to site features

Setback (Feet)

Site Features

Any transient or non-transient non-community water supply well, community well, shared water supply well, well that complies with 15A NCAC 18A .1700, or water supply spring	100
A private drinking water well or upslope spring serving a single-family dwelling unit	50
Any other well or source not listed in this table, excluding monitoring wells	50
Surface waters classified WS-I, from ordinary high-water mark	100
Waters classified SA, from mean high-water mark	100
Any Class I or Class II reservoir, from normal water level	100
Lake or pond, from normal water level	50
Any other stream, non-water supply spring, or other surface waters, from the ordinary high-water mark	50
Tidal influenced waters, such as marshes and coastal waters, from mean high-water mark	50
Permanent stormwater retention basin, from normal water level	50
Any water line, unless the requirements of Paragraph (i) have been met	10
Closed loop geothermal wells	15
Building foundation and deck supports	5
Patio, porch, stoop, lighting fixtures, or signage, including supporting structures such as posts or pilings	1
Any basement, cellar, or in-ground swimming pool	15
Buried storage tank or basin, except stormwater	10
Above ground swimming pool and appurtenances that require a building permit	5
Top of slope of embankment or cuts of two feet or more vertical height with a slope greater than 50 percent	15
Top of slope of embankment or cuts of two feet or more vertical height with a slope greater than 33 percent and less than or equal to 50 percent.	15
If the site has suitable soil depth that extends for a minimum horizontal distance of 15 feet from the edge of the dispersal field, no minimum setback is required.	
Top of slope of embankment or cuts of two feet or more vertical height with a slope less than 33 percent	0
Groundwater lowering system, as measured on the ground surface from the edge of the feature	25
Downslope interceptor drains and surface water diversions with a vertical cut of more than two feet, as measured on the ground surface from the edge of the feature	15
Upslope and side slope interceptor drain and surface water diversions with a vertical cut of more than two feet, as measured on the ground surface from the edge of the feature	10
A stormwater collection system as defined in 15A NCAC 02H .1002(48), excluding gutter drains that connect to a stormwater collection system, with a vertical cut of more than two feet as measured from the center of the collection system	10
Bio-retention area, injection well, infiltration system, or dry pond	25
Any other dispersal field, except designated dispersal field repair area for project site	20
Any property line	10
Burial plot or graveyard boundary	10
Above ground storage tank from dripline or foundation pad, whichever is more limiting	5
Utility transmission and distribution line poles and towers, including guy wires, unless a greater setback is required by the utility company	5
Utility transformer, ground-surface mounted	5
Underground utilities	5

Note: Systems over 3000 GPD or an individual nitrification fields with a capacity of 1500 GPD or more have more restrictive setback requirements, see .0601 for specifics.



PIEDMONT
ENVIRONMENTAL
ASSOCIATES, P.A.

Detailed Soil Map Weddington Rd

216 S. Swing Rd. Suite 1
Greensboro, NC 27409
piedmontsoil.com

Job# 5792
Date: October 10 2024
Client: Applied Resource Management
County: Union



MAP NOT VALID WITHOUT REPORT

Legend

usable_Area

type


- <Null>
- Conv
- Drip
- LPC
- <all other values>
- PropertyLine__V3
- projectedusablearea



Esri Community Maps Contributors, mecklenburg, Union County, State of North Carolina DOT
SafeGraph, GeoTechnique


1 inch = 600 feet

0 15000 600 900 1,200 US Feet



April 17, 2024

I, Karen E. Dewey, Town Administrator/Clerk for the Town of Weddington, do hereby certify that the attached documents, which give notification of a Community Meeting for property located at 610 Weddington Road were mailed on Wednesday, April 17, 2024 via first class mail to property owners within 1300 feet of the properties. These owners' names and addresses are shown on the attached pages.


Karen E. Dewey, Town Administrator/Clerk

BOULOS HOLDINGS LLC 1200 NATIONAL DR WINSTON SALEM, NC 27103	TYSON DAVID W 14314 LISSADELL CIR CHARLOTTE, NC 28277	LAKE FOREST PRESERVE HOMEOWNERS ASSOCIATION INC 6162 MILITARY CUTOFF RD STE 108 WILMINGTON, NC 28403
WINSTON GLADYS B 6901 DEEP SPRINGS RD PEACHLAND, NC 28133	NBI INVESTMENTS LLC % MCCLANCY SEASONING 1 SPICE ROAD FORT MILL, SC 29707	SKYE PARTNERS %MELISSA MCLEOD MILLETTE 500 MONCURE DRIVE CHARLOTTE, NC 28209
DEPARTMENT OF TRANSPORTATION 1546 MAIL SERVICE CENTER RALEIGH, NC 27611	SCHMIDT ROBERT 1209 WEDDINGTON HILLS DR MATTHEWS, NC 28104	ZHANG JI 1217 WEDDINGTON HILLS DR MATTHEWS, NC 28104
FOX CHARLES IVAN 1221 WEDDINGTON HILLS DR MATTHEWS, NC 28104	HUTAFF RICHARD R 1227 WEDDINGTON HILLS DR WEDDINGTON, NC 28104	HAHN GREGORY R CO TRUSTEE 1233 WEDDINGTON HILLS DR MATTHEWS, NC 28104
BAILEY BRIAN JEFFREY 1305 WEDDINGTON HILLS DR MATTHEWS, NC 281049030	POST JEANINE M 1302 WEDDINGTON HILLS DR MATTHEWS, NC 28104	HASSFURTER GEORGE A 1310 WEDDINGTON HILLS DR MATTHEWS, NC 28104
POWERS MARK STRICKLAND 1512 BLUEBIRD HILL LN MATTHEWS, NC 281047252	JONES MATTHEW W 1504 BLUEBIRD HILL LN MATTHEWS, NC 28104	QUINN JAMES V 1503 BLUEBIRD HILL LANE MATTHEWS, NC 28104
GONZALES THOMAS A 1523 BLUEBIRD HILL LN MATTHEWS, NC 281047253	DAOU JIHAD 1230 WEDDINGTON HILLS DR WEDDINGTON, NC 28104	LONG JIE TRUSTEE 1254 REGENCY DR SAN JOSE, CA 95129
MCNULTY JAMES ALAN 1214 WEDDINGTON HILLS DR MATTHEWS, NC 28104	SMITH JASON 1206 WEDDINGTON HILLS DR MATTHEWS, NC 28104	SMITH BRYAN J 1200 WEDDINGTON HILLS DR MATTHEWS, NC 28104
DICARLO DENNIS J 4020 TWELVE MILE CREEK RD WEDDINGTON, NC 28104	GUPTA PARTHA SEN 1021 SHIPPON LN WAXHAW, NC 28173	THURBON ROBERT W JR 1334 WEDDINGTON HILLS DR MATTHEWS, NC 28104
ABBATE RICHARD 1400 WEDDINGTON HILLS DR WEDDINGTON, NC 28104	FRAZIER KENNETH N 1408 WEDDINGTON HILLS DR WEDDINGTON, NC 28104	STONE FREDERICK B 1424 WEDDINGTON HILLS DR MATTHEWS, NC 28104

ZIEMBIEC JOSHUA 1434 WEDDINGTON HILLS MATTHEWS, NC 28104	WILLIAMS ROBERT DEAN TRUSTEE 1440 WEDDINGTON HILLS DR MATTHEWS, NC 28104	CUSUMANO DAVID PASQUALE 1431 WEDDINGTON HILLS DR MATTHEWS, NC 28104
POWELL WILLIAM W JR 1423 WEDDINGTON HILLS DR MATTHEWS, NC 28104	FARFOUR KELLY WATSON 1417 WEDDINGTON HILLS DR MATTHEWS, NC 28104	LABAER LOREN MICHAEL 1405 WEDDINGTON HILLS DR MATTHEWS, NC 28104
GUMMADI DURGA D 6154 BLUEBIRD HILL LN MATTHEWS, NC 28104	MARTINO RYAN TAYLOR 5900 BLUEBIRD HILL LANE WEDDINGTON, NC 281047254	NEWSOME WILLIAM CRAIG 6146 BLUEBIRD HILL LN MATTHEWS, NC 28104
COLLINSON NICHOLAS 6138 BLUEBIRD HILL LN MATTHEWS, NC 28104	MACK HELEN 6130 BLUEBIRD HILL LN MATTHEWS, NC 28104	HOOPER RONALD D 1203 GOLDFINCH LANE MATTHEWS, NC 281047257
DORTON JAMES W III 1207 GOLDFINCH LN MATTHEWS, NC 28105	GUEORGUI STOYNEV 1208 GOLDFINCH LN MATTHEWS, NC 28104	NOVO-SCHWARTZ NIVIA 8420 SW 142ST MIAMI, FL 33158
REECE MICHAEL SCOTT 5918 BLUEBIRD HILL LN MATTHEWS, NC 28104	TCHOUPO GUY N 5910 BLUEBIRD HILL LN MATTHEWS, NC 28104	DAPOLITO JASON C 3987 MOURNING DOVE DR MATTHEWS, NC 28104
KUNICH JOHN 1026 LAKE FOREST DR MATTHEWS, NC 28104	SUAREZ DAVID H 1022 LAKE FOREST DR MATTHEWS, NC 28104	TAREEN TAMOUR KHAN 1018 LAKE FOREST DR MATTHEWS, NC 28104
SHAH DHARMEN K 1014 LAKE FOREST DRIVE MATTHEWS, NC 281047411	SHAH SMITESH P 1010 LAKE FOREST DR MATTHEWS, NC 28104	VENUGOPAL DILIP 1006 LAKE FOREST DR MATTHEWS, NC 28104
BOILLA CHANDRASEKHAR REDDY 701 RIDGELAKE DR MATTHEWS, NC 281047412	MASA DAMODAR 707 RIDGELAKE DR WEDDINGTON, NC 281047412	AYYAGARI RAM SANDEEP 711 RIDGELAKE DR MATTHEWS, NC 281047412
KANSAL ANIL 716 RIDGELAKE DR WEDDINGTON, NC 281047412	EMEKA IFEANYI O 712 RIDGELAKE DR MATTHEWS, NC 28104	KUMAR ANJUR KAPALI RAVI 708 RIDGELAKE DR WEDDINGTON, NC 281047412

SLUTZ DAMON M
1011 LAKE FOREST DR
MATTHEWS, NC 28104

ELIE JAY II
1013 LAKE FOREST DR
MATTHEWS, NC 28104

CARRAI GARY B
1017 LAKE FOREST DR
MATTHEWS, NC 28104

LEE JAEBONG
1021 LAKE FOREST DR
MATTHEWS, NC 28104

LI XIAOQIN
1025 LAKE FOREST DR
WEDDINGTON, NC 28104

CIESIELSKI DAVID M
1029 LAKE FOREST DR
MATTHEWS, NC 28104

IP ANDREW
1033 LAKE FOREST DR
MATTHEWS, NC 28104

EDOSOMWAN ESTHER EIGBE
1037 LAKE FOREST DR
WEDDINGTON, NC 28104

PATEL HARISH B
1041 LAKE FOREST DR
MATTHEWS, NC 28104

SAGGOO JASPREET K
1045 LAKE FOREST DR
MATTHEWS, NC 28104

ALBERS CHRIS R
1048 LAKE FOREST DR
WEDDINGTON, NC 28104

MANCHI RAMA
1044 LAKE FORREST DR
MATTHEWS, NC 281047411

REEVES GORDON R
1040 LAKE FOREST DR
MATTHEWS, NC 28104

CHRISTODOULIAS JIMMIE J
601 MAPLE VALLEY CT
WEDDINGTON, NC 28104

PATEL SANJIV R
605 MAPLE VALLEY CT
MATTHEWS, NC 28104

SUN YAN
609 MAPLE VALLEY CT
MATTHEWS, NC 28104

COHEN NADAV TRUSTEE
613 MAPLE VALLEY CT
MATTHEWS, NC 28104

TWO HONEYBEES LLC
135 ST GEORGE PL
ATHENS, GA 30606

BOYD BARRINGTON
628 MAPLE VALLEY CT
WEDDINGTON, NC 28104

SZKLINSKI JOHN A
624 MAPLE VALLEY CT
WEDDINGTON, NC 28104

MCGRATH SEAN E
620 MAPLE VALLEY CT
WEDDINGTON, NC 28104

PEREZ CARLOS E
614 MAPLE VALLEY CT
WEDDINGTON, NC 28104

GIATTINO JOHN F
610 MAPLE VALLEY CT
WEDDINGTON, NC 28104

FYANS JOHN
606 MAPLE VALLEY CT
MATTHEWS, NC 28104

CONTE JOHN
602 MAPLE VALLEY CT
MATTHEWS, NC 28104

KENNARD TIMOTHY PATRICK
805 PINE VALLEY COURT
MATTHEWS, NC 28104

SCHEINSON LAWRENCE
809 PINE VALLEY CT
WEDDINGTON, NC 28104

DUBEY MARISSA
813 PINE VALLEY CT
MATTHEWS, NC 28104

HENNINGS FREDERICK W
817 PINE VALLEY CT
WEDDINGTON, NC 28104

PINGEL JAN
816 PINE VALLEY CT
WEDDINGTON, NC 28104

KNOWLTON INEAL JR
812 PINE VALLEY CT
WEDDINGTON, NC 28104

BAILEY WILLIAM
810 PINE VALLEY CT
WEDDINGTON, NC 28104

ARTHUR MICHAEL D
808 PINE VALLEY CT
MATTHEWS, NC 28104

DAVE SEJAL A
804 PINE VALLEY CT
WEDDINGTON, NC 28104

PALMER JAMES D JR
305 FIR PLACE CT
WEDDINGTON, NC 28104

TAYLOR MATTHEW THOMAS
309 FIR PLACE CT
MATTHEWS, NC 28104

ACKELS STEPHEN M
313 FIR PLACE CT
WEDDINGTON, NC 28104

MASON CHRISTOPHER
314 FIR PLACE CT
WEDDINGTON, NC 28104

HAMMOND JENNIFER ASHLEY PHILLI
1056 LAKE FOREST DR
WEDDINGTON, NC 28104

VARADARAJAN RAVISANKAR
1060 LAKE FOREST DR
MATTHEWS, NC 28104

MUKKERA HARITHA
1064 LAKE FOREST DRIVE
WEDDINGTON, NC 281047411

KOLLIPARA HIMABINDU
1068 LAKE FOREST DR
WEDDINGTON, NC 28104

DIAZ ALLAN RODRIGUEZ
3063 TWIN LAKES DR
MATTHEWS, NC 28104

GORANTLA RAMANAMOHAN K
1055 LAKE FOREST DR
MATTHEWS, NC 28104

ANDERSON SCOTT K
1059 LAKE FOREST DR
WEDDINGTON, NC 28104

GOPALSAMY ANANDARAJ
1063 LAKE FOREST DR
WEDDINGTON, NC 28104

BENNETT KATHRYN G
1067 LAKE FOREST DR
MATTHEWS, NC 28104

DRAVIDA SHANTHARAM
3076 TWIN LAKES DR
WEDDINGTON, NC 28104

PRODDATURU MITHUN REDDY
3080 TWIN LAKES DR
WEDDINGTON, NC 28104

RITCHIE CRAIG
3084 TWIN LAKES DR
WEDDINGTON, NC 28104

ANNAMRAJU VENKATESHWER R
3088 TWIN LAKES DR
WEDDINGTON, NC 28104

KANTIMAHANATHI RICHARD ROSHAN
402 TIMBER TOP CT
WEDDINGTON, NC 28104

GIRARDI EDUARDO
406 TIMBER TOP CT
MATTHEWS, NC 28104

SURPRENANT MARC
410 TIMBER TOP CT
WEDDINGTON, NC 28104

TWARAKAVI SREERAMKUMAR
409 TIMBER TOP CT
WEDDINGTON, NC 28104

PERLA SREEDHAR BABU
405 TIMBERTOP CT
WEDDINGTON, NC 28104

GANDHE VIJAYA L
401 TIMBER TOP CT
MATTHEWS, NC 28104

OSTROW LANE ET AL
502 PINE NEEDLE CT
MATTHEWS, NC 28104

LAMANTIA VINCENT J
506 PINE NEEDLE CT
MATTHEWS, NC 28104

SURESHKUMAR MOSES S
510 PINE NEEDLE CT
WEDDINGTON, NC 28104

COLANDRA ANTHONY J
514 PINE NEEDLE CT
WEDDINGTON, NC 28104

WESLAKE PAUL B
513 PINE NEEDLE CT
WEDDINGTON, NC 28104

WAN SHAOSHAN
509 PINE NEEDLE CT
WEDDINGTON, NC 28104

DAVIS RUSSELL A
505 PINE NEEDLE CT
WEDDINGTON, NC 28104

MORFORD RYAN T
501 PINE NEEDLE CT
WEDDINGTON, NC 28104

PINO RICHARD R REYES
3103 TWIN LAKES DR
MATTHEWS, NC 28104

KEARNS DAVID
3099 TWIN LAKES DR
WEDDINGTON, NC 28104

THIRUMANIVASAGAM ANAND
3095 TWIN LAKES DR
WEDDINGTON, NC 28104

GAVIN SHANE PATRICK CO TRUSTEE
3091 TWIN LAKES DR
MATTHEWS, NC 28104

MAKWANA DHARMENDRA
3087 TWIN LAKES DRIVE
MATTHEWS, NC 28104

BOSEFSKI DAVID
3083 TWIN LAKES DR
WEDDINGTON, NC 28104

CHINTALA DREW
3079 TWIN LAKES DR
WEDDINGTON, NC 28104

JEFFERS DAVID A
3075 TWIN LAKES DR
WEDDINGTON, NC 28104

JUDGE DANIEL J
3071 TWIN LAKES DR
WEDDINGTON, NC 28104

HANEY MICHAEL J
3067 TWIN LAKE DR
MATTHEWS, NC 281046114

DEAL FARM LLC THE
3610 ETHAN CT
CHARLOTTE, NC 28226

WEDDINGTON 270 LLC
2627 BREKONRIDGE CENTRE DR
MONROE, NC 28110

SUGAR MAGNOLIA WEDDINGTON LLC
5615 POTTER RD
MATTHEWS, NC 28104

KBB DEVELOPERS INC
301 S MCDOWELL STREET
STE 320
CHARLOTTE, NC 28204

AMON JOHN R
744 SKYTOP DR
WAXHAW, NC 281739329

PROPST ELIZABETH D
601 WEDDINGTON RD
MATTHEWS, NC 28104

PROPST JANICE G
531 WEDDINGTON RD
WEDDINGTON, NC 28104

FRENETTE GARY P
6065 OXFORDSHIRE RD
WAXHAW, NC 28173

GAO XLAOJIE
726 SKYTOP RD
WAXHAW, NC 28173

MCNEILL WILLIAM CHAD
PO BOX 159
MONROE, NC 28111

MARTINEZ ANDREW
2114 OVERWOODS LN
INDIAN TRAIL, NC 28079

ALLISON JOHN D
714 SKYTOP RD
WEDDINGTON, NC 28173

CLEMENTS NATHAN D JR
6062 OXFORDSHIRE RD
WAXHAW, NC 28173

COCKRELL KEITH
6056 OXFORDSHIRE RD
WAXHAW, NC 28173

BARAJAS CHRISTOPHER M
6072 OXFORDSHIRE RD
WAXHAW, NC 28173

TUREK FRANK III
665 BARON RD
WAXHAW, NC 28173

HANNON EDWARD F
643 BARON RD
WAXHAW, NC 28173

MONA ZEYAD
637 BARON RD
WAXHAW, NC 28173

MONA ZEYAD
637 BARON RD
WAXHAW, NC 28173

WAGNER JORDAN
601 BARON RD
WAXHAW, NC 28173

WISE MANAGEMENT & REALTY LLC
110 SEVENDALES DR
GOLDSBORO, NC 27534

BALLETTA JUSTIN TRUSTEE
17235 WESTMILL LN
CHARLOTTE, NC 28277

TASE ALBERT G III
634 BARON RD
WAXHAW, NC 28173

NYBY BRIAN M
646 BARON RD
WAXHAW, NC 28173

SNYDER MARK WAYNE
610 BRANDY CT
WAXHAW, NC 28173

PERRY SCOTT M
628 BRANDY CT
WAXHAW, NC 28173

BONDURANT CHARLES W
646 BRANDY CT
WAXHAW, NC 28173

QUEEN DAN H JR
660 BRANDY CT
WEDDINGTON, NC 28173

WILKERSON ANDREW M
680 BRANDY CT
WAXHAW, NC 28173

JOUBERT JACOB DANIEL DE BRUYN
679 BRANDY CT
WAXHAW, NC 28173

BALLARD DAVID B
653 BRANDY COURTS
WAXHAW, NC 281739326

ANTON MICHAEL J
730 BARON RD
WEDDINGTON, NC 28173

ASHCRAFT MARK FRANKLIN
718 BARON RD
WAXHAW, NC 28173

GOOD TIMOTHY M
621 BRANDY CT
WAXHAW, NC 281799326

DOWLESS JO GRADY
607 BRANDY CTS
WAXHAW, NC 281739326

OAKLEY GARRETT K
704 BARON RD
WAXHAW, NC 28173

SZYDLOWSKI VICTOR
713 SKY TOP RD
WAXHAW, NC 28173

KLINKERT NICOLAAS
757 SKYTOP RD
WAXHAW, NC 28173

PODREBARAC DREW
552 KIRBY LANE
MATTHEWS, NC 28104

NEW TRADITION HOMES OF NC LLC
1005 WOODS LOOP
WAXHAW, NC 28173

PATEL UDAY
719 EAGLE RD
WAXHAW, NC 28173

RYALS RONNIE GLYNN
980 BARON RD
WAXHAW, NC 281738360

BURITICA MICHAEL
942 BARON RD
WAXHAW, NC 28173

MOFFAT DEBORAH MARCELLE
936 BARON RD
WAXHAW, NC 28173

MCDONALD TAMARA
930 BARON RD
WAXHAW, NC 28173

NEEL W ERSKINE JR
924 BARON RD
WEDDINGTON, NC 28173

SMITH JOSEPH J
906 BARON RD
WAXHW, NC 28173

WELFARE JOHN S
909 BARON RD
WAXHAW, NC 28173

CURRIE KENNETH III
1217 BARON RD
WAXHAW, NC 28173

AERO PLANTATION ASSOC
1025 WOODS LOOP
WEDDINGTON, NC 28173

OELSCHLAEGER TERRY D
959 BARON RD
WAXHAW, NC 28173

LINER GAINES H
937 BARON RD
WEDDINGTON, NC 28173

DEAL LAKE PROPERTY LLC
3610 ETHAN CT
CHARLOTTE, NC 28226

HORENSTEIN LAWRENCE
617 LOCHAVEN ROAD
WAXHAW, NC 28173

BLOCK DAVID P
621 LOCHAVEN RD
MATTHEWS, NC 28173

IVANNIKOV ALEXANDER
623 LOCHAVEN RD
WAXHAW, NC 28173

LEE JONATHAN STEPHEN TRUSTEE
629 LOCHAVEN RD
WAXHAW, NC 28173

TEODOROVICI EMILIA M
635 LOCHAVEN ROAD
WAXHAW, NC 28173

IOFFE DMITRIY
633 LOCHAVEN RD
WAXHAW, NC 28173

GUEAR TODD J
6048 OXFORDSHIRE RD
WAXHAW, NC 28173

HEDRICK P SCOTT ET AL
130 MARTINGALE LN
WILMINGTON, NC 28409

WALLER MICHAEL R
606 LOCHAVEN RD
WAXHAW, NC 28173

CUBINA JAVIER SANTOS
630 LOCHAVEN RD
WAXHAW, NC 28173

IGLESIAS TINA
640 LOCHAVEN RD
WAXHAW, NC 28173

WASDELL RAYMOND V
PO BOX 472
BOWLING GREEN, SC 29703

ECKHART MARK STEVEN
542 LOCHAVEN RD
WAXHAW, NC 28173

KALYUZHNYI YURIY V
5907 PARKSTONE DR
MATTHEWS, NC 28104

MCAREAVY STEVEN C
762 LOCKHAVEN RD
WAXHAW, NC 28173

LITTLE WILLIAM E JR
748 LOCHAVEN RD
WAXHAW, NC 28173

DEAN ONIKA
754 LOCHAVEN RD
WAXHAW, NC 28173

SIDNEY KENNETH D
625 LOCHAVEN RD
WAXHAW, NC 28173

STAMATELATOS GEORGE CHRISTOS
6068 OXFORDSHIRE RD #64
WAXHAW, NC 28173

SALAMI SAID ZIAOLDIN
205 RUNNING HORSE LN
WAXHAW, NC 28173

ALLEN MORGAN STEWART TRUSTEE
639 LOCHAVEN RD
WAXHAW, NC 28173

MAYNARD WILLIAM ARTHUR
647 LOCHAVEN RD
WAXHAW, NC 28173

HOULT MARION
655 LOCHAVEN RD
WAXHAW, NC 28173

WEIL JOSEPH D
654 LOCKHAVEN RD
WAXHAW, NC 28173

HEUSTESS LAUREN
210 HIDDEN HAVEN TRL
WAXHAW, NC 28173

MCDOWELL DOUGLAS D
720 TEMPLETON AVE
CHARLOTTE, NC 28203

VOLK ALEKSANDR
6052 OXFORDSHIRE RD
WAXHAW, NC 28173

STRUBBE DAVID S
225 HIDDEN HAVEN TRAIL
WAXHAW, NC 28173

MCDONNELL ROBERT
205 HIDDEN HAVEN TRL
WAXHAW, NC 28173

DAVIS THOMAS
6064 OXFORDSHIRE RD
WAXHAW, NC 28173

PUROHIT MOHIT
316 WESTLAKE DR
WAXHAW, NC 28173

DZHUGA SERGEY
537 LOCHAVEN RD
WAXHAW, NC 28173

HEDRICK P SCOTT ET AL
130 MARTINGALE LN
WILMINGTON, NC 28409

MEAD PAUL W
534 LOCHAVEN RD
WAXHAW, NC 28173

DEFIORE MICHAEL
757 LOCHAVEN RD
WAXHAW, NC 28173

ENGLISH ROBERT THOMAS
744 LOCHAVEN RD
WAXHAW, NC 28173

PARKER MICHAEL ERIC
6037 OXFORDSHIRE RD
WEDDINGTON, NC 28173

LOMBARDO THOMAS S
6041 OXFORDSHIRE RD
WAXHAW, NC 28173

NEER RICHARD
6045 OXFORDSHIRE RD
WAXHAW, NC 28173

SIAO TAISHEN
6040 OXFORDSHIRE RD
WAXHAW, NC 28173

WILLIAMS PHILLIP R
6036 OXFORDSHIRE RD
WAXHAW, NC 28173

KOTHADIA JAMNAD M
6049 OXFORDSHIRE RD
WAXHAW, NC 28173

RORIE JAMES W
6053 OXFORDSHIRE RD
WAXHAW, NC 28173

HAMILTON GARY R
6057 OXFORDSHIRE RD
WAXHAW, NC 28173

Community Meeting Notice

NOTICE TO INTERESTED PARTIES OF A REZONING PETITION

Subject: Rezoning Petition
Petitioner/Developer: Toll Brothers
Current Land Use: Residential & Vacant
Existing Zoning: R-CD
Rezoning Requested: R-CD

Date and Time of Meeting: **Thursday, May 2, 2024, at 6:00 PM**

Meeting Location ***St. Margaret's Episcopal Church
8515 Rea Road
Waxhaw, NC 28173***

Meeting Registration: ***Please send an email to Drenna Hannon at
drennahannon@mvalaw.com
to confirm your attendance.***

Date of Notice: 4/17/2024

Moore & Van Allen is assisting Toll Brothers (the "Petitioner") on a recently filed request to rezone an approximately 167.48-acre site located at 610 Weddington Road (and other nearby parcels) in Weddington, North Carolina (the "Site") to R-CD. The request is to allow the Site to be developed with a residential community consisting of ±93 homes. Access to the site will be from Weddington Road.


The Petitioner will hold an **In-Person Community Meeting** to discuss this rezoning proposal with nearby property owners and organizations. The Town of Weddington Planning Department's records indicate that you are either a representative of a registered neighborhood organization or an owner of property near the site. **Accordingly, we are extending an invitation to participate in the upcoming Community Meeting to be held on Thursday, May 2, 2024, at 6:00 p.m. at St. Margaret's Episcopal Church.** Please contact Drenna Hannon at email: drennahannon@mvalaw.com to RSVP and reference the location of the meeting.


Residents who expect they will be unable to attend the community meeting or have questions about this matter are asked to email bridgetgrant@mvalaw.com or call **704-301-3137** to make alternative arrangements to receive the presentation information. Presentation materials will be shared upon request after the meeting.

Representatives of the Petitioner look forward to discussing this exciting rezoning proposal with you at the Community Meeting. Thank you.

cc: Greg Gordos, AICP, Town Planner, Town of Weddington, NC
Robert Price, Toll Brothers
Bridget Grant, Moore & Van Allen, PLLC


Site location:





March 31, 2025

I, Karen E. Dewey, Town Administrator/Clerk for the Town of Weddington, do hereby certify that the attached documents, which give notification of a public hearing for a conditional zoning application from Toll Brothers for a 62-lot subdivision on Weddington Road (parcel numbers 06126001, 06126017, 06126017B, 06126017C, 06129109) were mailed on Friday March 28, 2025 via first class mail to adjacent property owners. These owners' names and addresses are shown on the attached pages.



Karen E. Dewey, Town Administrator/Clerk

CUSUMANO DAVID PASQUALE
1431 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

DEPARTMENT OF TRANSPORTATION
1546 MAIL SERVICE CENTER
RALEIGH, NC 27611

SCHMIDT ROBERT
1209 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

FOX CHARLES IVAN
1221 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

HUTAFF RICHARD R
1227 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

MOFFAT DEBORAH MARCELLE
936 BARON RD
WAXHAW, NC 28173

AERO PLANTATION ASSOC
1025 WOODS LOOP
WAXHAW, NC 28173

DEAL FARM LLC THE
3610 ETHAN CT
CHARLOTTE, NC 28226

PROPST RICHARD GAYLE TRUSTEE ET AL
601 WEDDINGTON RD
MATTHEWS, NC 28104

ELIZABETH AND RICHARD PROPST FAMILY
LIMITED PARTNERSHIP
601 WEDDINGTON RD
MATTHEWS, NC 28104

SNYDER MARK WAYNE
610 BRANDY CT
WAXHAW, NC 28173

FRENETTE GARY P
6065 OXFORDSHIRE RD
WAXHAW, NC 28173

FRENETTE GARY P
6065 OXFORDSHIRE RD
WAXHAW, NC 28173

WEDDINGTON 270 LLC
2627 BREKONRIDGE CENTRE DR
MONROE, NC 28110

PROPST JANICE G
531 WEDDINGTON RD
MATTHEWS, NC 28104

BALLETTA JUSTIN TRUSTEE
17235 WESTMILL LN
CHARLOTTE, NC 28277

NYBY BRIAN M
646 BARON RD
WAXHAW, NC 28173

BONDURANT CHARLES W
646 BRANDY CT
WAXHAW, NC 28173

HORENSTEIN LAWRENCE
617 LOCHAVEN RD
WAXHAW, NC 28173

HAMILTON GARY R
6057 OXFORDSHIRE RD
WAXHAW, NC 28173

FRENETTE GARY P
6065 OXFORDSHIRE RD
WAXHAW, NC 28173

WILKINSON MICHAEL
6072 OXFORDSHIRE RD
WAXHAW, NC 28173

DEAL LAKE PROPERTY LLC
3610 ETHAN CT
CHARLOTTE, NC 28226

LEE JONATHAN STEPHEN TRUSTEE
629 LOCHAVEN RD
WAXHAW, NC 28173

MOFFAT DEBORAH MARCELLE
936 BARON RD
WAXHAW, NC 28173

ELIZABETH AND RICHARD PROPST FAMILY
LIMITED PARTNE
601 WEDDINGTON RD
MATTHEWS, NC 28104

WISE MANAGEMENT LLC
110 SEVENDALES DR
GOLDSBORO, NC 27534

TASE ALBERT G III
634 BARON RD
WAXHAW, NC 28173

PERRY SCOTT M
628 BRANDY CT
WAXHAW, NC 28173

LAKE FOREST PRESERVE HOMEOWNERS
ASSOCIATION INC
1612 MILITARY CUTOFF RD STE 108
WILMINGTON, NC 28403

ZHANG JI
1217 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

WILLIAMS ROBERT DEAN TRUSTEE
1440 WEDDINGTON HILLS DR
MATTHEWS, NC 28104


QUEEN DAN H JR
660 BRANDY CT
WAXHAW, NC 28173

HEUSTESS LAUREN
210 HIDDEN HAVEN TRL
WAXHAW, NC 28173

TOWN OF WEDDINGTON
NOTICE OF PUBLIC HEARING

Notice is hereby given that a Public Hearing will be held by the Weddington Town Council at the Weddington Town Hall, 1924 Weddington Road, Weddington, NC on Monday, April 14, 2025 at 7:00 p.m. for the purpose of collecting public comment on an application from Toll Brothers for subdivision up to 62 lots located at/near 610 Weddington Road and 601 Weddington Road, parcel numbers 06129109, 06126001, 06126017, 06126017B, 06126017C.

The Town of Weddington does not discriminate based on disability. Individuals requiring auxiliary aids or services or other accommodations for participation in a meeting may contact Karen Dewey, Town Administrator/Clerk, at 704-846-2709. Requests should be made at least 4 days prior to the meeting.



Name	email/phone/ address
Tom Waters	tom.e.providentdev.com
Peter Billetta	630 BARON RD. 262 RUNNR@GMAIL.COM 704-576-9168
Linda Cashion	704-256-5444 1142 Baron Rd / Linda Cashion@gmail.com
Chad Emmons	chademerr@gmail.com
MAX ASKAT	MAX ASKAT AOL 718 420 1000
Bob & Linda Williams	williams19@carolina.rr.com 1440 Weddington Hills Dr. (104) 996-8825
Bill & Patty Powell	synamaeatt.net Billpowell1423@gmail.com
Jami & Alan Bertolucci	jami.bertolucci@aol.com alan.bertolucci@aol.com

COMMUNITY MEETING REPORT FOR REZONING PETITION NO. TBD

Petitioner: Toll Brothers
Rezoning Petition No.: TBD
Property: ±167 acres located at 610 Weddington Road

This Community Meeting Report is being filed with the Town of Weddington Town Clerk and the Town of Weddington Planning Department pursuant to section C. 5. of the Town of Weddington Unified Development Ordinance.

PERSONS AND ORGANIZATIONS CONTACTED WITH DATES AND EXPLANATIONS OF HOW CONTACTED:

A representative of the Town of Weddington mailed a written notice of the date, time and details of the Community Meeting to the individuals and organizations set out on **Exhibit A** by depositing the Community Meeting Notice in the U.S. mail on 4/12/2024. A copy of the written notice is attached as **Exhibit B**.

TIME AND DATE OF MEETING:

The Community Meeting required by the Ordinance was held on Thursday, May 2, 2024, at 6:00 PM at St. Margaret's Episcopal Church, 8515 Rea Road, Waxhaw, NC, 28173.

PERSONS IN ATTENDANCE AT MEETING:

The list of attendees from the required Community Meeting is attached as **Exhibit C**. The Petitioner's representative at the required Community Meeting were Robert Price, Ryan Switzer, Max Bank, and George Walsh from Toll Brothers, Tracey McCormick and Kenny Draffen with McKim & Creed, the landscape architects. Also in attendance were Bridget Grant and Drenna Hannon with Moore & Van Allen, PLLC.

SUMMARY OF ISSUES DISCUSSED AT MEETING:

I. Overview of Petitioner's Presentation.

Introduction and Overview of Development Plan.

Ms. Grant with Moore & Van Allen welcomed and thanked the participants for their interest in the Toll Brothers Deal Lake petition. Ms. Grant and the petitioner's representatives provided the following information during the presentation:

Ms. Grant explained the difference between by-right and conditional zoning. She also provided the location of the 167-acre site at 610 Weddington Road. The site is located on both sides of Weddington Road, south of Cox Road and north of Twelve Mile Creek Road. The Deal family history was explained dating back to the 1800s. Ms. Grant explained the various Deal properties that have been sold over the past 100 years to develop multiple communities in Weddington and the broader county. The Deal family is preserving the Deal homeplace with ±15 acres. Farming is no longer a sustainable option.

The site is zoned R-CD for Residential Conditional and the proposed zoning is R-CD CZ which is conservation residential development to allow the site to be developed with 93 single family homes. The Weddington Comprehensive Plan recommendation is conservation residential. Ms. Grant shared the proposed conceptual site plan with labeling for the conservation areas, flood plain, community septic system

stormwater management areas, 100' roadside buffers, the open space for amenities and the ±15 acres to be subdivided to seller. She shared the typical lot size and that buffers are not required around the site periphery with a comparison of a traditional form compared to the cluster form proposed. Precedent residential images were shown along with buffer landscape concepts. A comparison was made of the various wastewater treatment facilities. The four types of facilities are wastewater treatment plant, package plan, community septic system and lot septic. Ms. Grant explained the differences between each. She then shared the project would have a community septic system which is regulated by the county, maintained by a private utility or HOA, it serves a single community, there's no known smell, and the facilities are under ground and not visible. Ms. Grant shared the communities in Weddington that currently have community septic: Stratford on Providence, Weddington Oaks and Lake Providence. The Lake Forest Preserve, Aero Plantation, Weddington Hills and Lochaven communities have private septic.

Ms. Grant explained the plan benefits which include:

- 112.88 acres of conservation area
- Conservation areas closest to existing communities
- 100' roadside buffers to maintain road corridor character
- 50' structure setback around perimeter of site (actual distance is much greater)
- Commitment to no fishing/piers around lake
- Architectural commitments/certainty on homes to be built
- Cluster development is more "environmentally friendly" and,
- Creates large swaths of uninterrupted open spaces and natural areas protected by HOA.

The anticipated rezoning schedule is for a May 28, 2024, Planning Board meeting and a Public Hearing on June 10, 2024.

The meeting was then opened for questions and answers.

II. Summary of Questions/Comments and Responses:

The Participants inquiries centered around two primary concerns, septic and traffic. They also asked the Town of Weddington representatives questions about the plan. The following is a high-level summary of questions and responses based on information available at the time of the community meeting.

A participant asked if a traffic impact study has been completed; representatives confirmed it was submitted to the town. The representative from Kimley Horn explained the study results. There is a 100' setback along Weddington Road (landscape buffer). An attendee asked if this will be impacted by the right of way dedication, and it was stated that this has already been included. The road expansion dates were originally for 2017 however the new expansion date is 2029. Someone asked if the development will be halted due to the road expansion project being later than expected. It was explained that the development is not contingent on the build out of the extension. The development has already accounted for the required widening in the layout and the dedication to NCDOT is specified.

Questions about the site plan were also asked. When asked about the lot area/width, the team specified what was provided in the plan. A participant wanted to know why they were not all one (1) acre lots stating that they feel these look better. Toll Brothers likes the option of the cluster development to promote greener community, provide more open space and to keep the perimeter trees. Cluster development benefits we highlighted. The team also stated that a yield plan has been submitted and it is a sketch plan created for the town and for review by LaBella, a third-party reviewing agency the town employs. The sketch plan is used to determine the number of lots that can be achieved based on ordinance requirements. It was asked how many acres were located on the east side of the development and it was stated there are 41 acres with 31

lots. Per the ordinance, if the site is split by a main roadway, one portion of the site cannot be overloaded. It was noted and the team will review the layout.

A participant asked if the town was present, and the mayor and mayor pro tem were in attendance. They were asked when the town council will vote. The mayor explained that this is one of the opportunities for residents to speak and be heard regarding the proposed development. They can also attend the public hearing. The team was asked about the registration information and who has access, a concern about privacy noted. The information was collected as a requirement for the town to show who is in attendance and if they are residents of Weddington. The information is reported as a requirement of the rezoning process. The information will not be used by the developer or sold. The town representatives stated that they hear the resident's concerns, and this is a good venue to voice concerns. One resident stated that the Weddington website states, "Rural Living Redefined" and they moved to Weddington for this reason. It was felt that this development does not fit a rural plan. It was stated that the development is in line with the land use plan with all the green space provided. It was stated by a resident that council is not listening to the 87% in a recent survey that want to keep the rural feel. Council does take into consideration community feedback for their decisions.

The team were asked if conventional lots should have individual septic systems. The developer team stated that they feel the conservation option is a better layout for maintaining the natural resources and provides a buffer from the existing communities abutting the site. They were asked if they have done perc tests and it was stated that they have been performed in the proposed community system area, not for individual, conventional lot layout. It was confirmed that approval of the community septic could open more chances for future proposed community septic. The community questioned the accuracy of the other community systems presented. They stated that there are a few homes that are on a joint system but no other community systems. A petitioner representative explained that these systems are very common in other areas of the state and that he has designed them. It was stated that Stratford on Providence does not have a community septic. It was noted that all except 26 have individual septic. One resident asked for an explanation about how reserves are created. Toll Brothers explained how they typically establish a reserve fund for other communities that have amenities such as a building/clubhouse, pool, etc. The community system is treated in this manner. They have a financial advisor that helps the developer determine how much of the initial HOA dues are earmarked for reserve. If the lake goes eutrophic or is ruined, who will be liable? The HOA will be responsible for maintenance of the community septic system and will be responsible for repairs if there is failure. The advisor takes into consideration all required budget items and formulates annual dues and how the funds are distributed within the budget. The representative answered a question about pretreatment and that the specific system for the site has not been decided. He explained a couple different examples. It was stated that on November 10, 2014, a law was passed stating that there should be only one septic system/leach field per lot. Why is this not being followed? It was stated that the land use plans are being updated by the town.

There being no further questions, the participants were thanked for their time and interest in the development.

CHANGES MADE TO PETITION AS A RESULT OF THE MEETING:


The development team will continue to coordinate efforts with City Staff.

cc: Greg Gordos, AICP, Town Planner, Town of Weddington, NC
Robert Price, Toll Brothers
Bridget Grant, Moore & Van Allen, PLLC



April 17, 2024

I, Karen E. Dewey, Town Administrator/Clerk for the Town of Weddington, do hereby certify that the attached documents, which give notification of a Community Meeting for property located at 610 Weddington Road were mailed on Wednesday, April 17, 2024 via first class mail to property owners within 1300 feet of the properties. These owners' names and addresses are shown on the attached pages.



Karen E. Dewey, Town Administrator/Clerk

Exhibit A

Adjacent Owners:

BOULOS HOLDINGS LLC
1200 NATIONAL DR
WINSTON SALEM, NC 27103

WINSTON GLADYS B
6901 DEEP SPRINGS RD
PEACHLAND, NC 28133

DEPARTMENT OF TRANSPORTATION
1546 MAIL SERVICE CENTER
RALEIGH, NC 27611

FOX CHARLES IVAN
1221 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

BAILEY BRIAN JEFFREY
1305 WEDDINGTON HILLS DR
MATTHEWS, NC 281049030

POWERS MARK STRICKLAND
1512 BLUEBIRD HILL LN
MATTHEWS, NC 281047252

GONZALES THOMAS A
1523 BLUEBIRD HILL LN
MATTHEWS, NC 281047253

MCNULTY JAMES ALAN
1214 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

DICARLO DENNIS J
4020 TWELVE MILE CREEK RD
WEDDINGTON, NC 28104

ABBATE RICHARD
1400 WEDDINGTON HILLS DR
WEDDINGTON, NC 28104

TYSON DAVID W
14314 LISSADELL CIR
CHARLOTTE, NC 28277

NBI INVESTMENTS LLC
% MCCLANCY SEASONING
1 SPICE ROAD
FORT MILL, SC 29707

SCHMIDT ROBERT
1209 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

HUTAFF RICHARD R
1227 WEDDINGTON HILLS DR
WEDDINGTON, NC 28104

POST JEANINE M
1302 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

JONES MATTHEW W
1504 BLUEBIRD HILL LN
MATTHEWS, NC 28104

DAOU JIHAD
1230 WEDDINGTON HILLS DR
WEDDINGTON, NC 28104

SMITH JASON
1206 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

GUPTA PARTHA SEN
1021 SHIPPON LN
WAXHAW, NC 28173

FRAZIER KENNETH N
1408 WEDDINGTON HILLS DR
WEDDINGTON, NC 28104

LAKE FOREST PRESERVE HOMEOWNERS
ASSOCIATION INC
1612 MILITARY CUTOFF RD STE 108
WILMINGTON, NC 28403

SKYE PARTNERS
%MELISSA MCLEOD MILLETTE
500 MONCURE DRIVE
CHARLOTTE, NC 28209

ZHANG JI
1217 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

HAHN GREGORY R CO TRUSTEE
1233 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

HASSFURTER GEORGE A
1310 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

QUINN JAMES V
1503 BLUEBIRD HILL LANE
MATTHEWS, NC 28104

LONG JIE TRUSTEE
1254 REGENCY DR
SAN JOSE, CA 95129

SMITH BRYAN J
1200 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

THURBON ROBERT W JR
1334 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

STONE FREDERICK B
1424 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

Exhibit A (Cont.)

ZIEMBIEC JOSHUA
1434 WEDDINGTON HILLS
MATTHEWS, NC 28104

WILLIAMS ROBERT DEAN TRUSTEE
1440 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

CUSUMANO DAVID PASQUALE
1431 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

POWELL WILLIAM W JR
1423 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

FARFOUR KELLY WATSON
1417 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

LABAER LOREN MICHAEL
1405 WEDDINGTON HILLS DR
MATTHEWS, NC 28104

GUMMADI DURGA D
6154 BLUEBIRD HILL LN
MATTHEWS, NC 28104

MARTINO RYAN TAYLOR
5900 BLUEBIRD HILL LANE
WEDDINGTON, NC 281047254

NEWSOME WILLIAM CRAIG
6146 BLUEBIRD HILL LN
MATTHEWS, NC 28104

COLLINSON NICHOLAS
6138 BLUEBIRD HILL LN
MATTHEWS, NC 28104

MACK HELEN
6130 BLUEBIRD HILL LN
MATTHEWS, NC 28104

HOOPER RONALD D
1203 GOLDFINCH LANE
MATTHEWS, NC 281047257

DORTON JAMES W III
1207 GOLDFINCH LN
MATTHEWS, NC 28105

GUEORGUI STOYNEV
1208 GOLDFINCH LN
MATTHEWS, NC 28104

NOVO-SCHWARTZ NIVIA
8420 SW 142ST
MIAMI, FL 33158

REECE MICHAEL SCOTT
5918 BLUEBIRD HILL LN
MATTHEWS, NC 28104

TCHOUPPO GUY N
5910 BLUEBIRD HILL LN
MATTHEWS, NC 28104

DAPOLITO JASON C
3987 MOURNING DOVE DR
MATTHEWS, NC 28104

KUNICH JOHN
1026 LAKE FOREST DR
MATTHEWS, NC 28104

SUAREZ DAVID H
1022 LAKE FOREST DR
MATTHEWS, NC 28104

TAREEN TAMOUR KHAN
1018 LAKE FOREST DR
MATTHEWS, NC 28104

SHAH DHARMEN K
1014 LAKE FOREST DRIVE
MATTHEWS, NC 281047411

SHAH SMITESH P
1010 LAKE FOREST DR
MATTHEWS, NC 28104

VENUGOPAL DILIP
1006 LAKE FOREST DR
MATTHEWS, NC 28104

BOILLA CHANDRASEKHAR REDDY
701 RIDGELAKE DR
MATTHEWS, NC 281047412

MASA DAMODAR
707 RIDGELAKE DR
WEDDINGTON, NC 281047412

AYYAGARI RAM SANDEEP
711 RIDGELAKE DR
MATTHEWS, NC 281047412

KANSAL ANIL
716 RIDGELAKE DR
WEDDINGTON, NC 281047412

EMEKA IFEANYI O
712 RIDGELAKE DR
MATTHEWS, NC 28104

KUMAR ANJUR KAPALI RAVI
708 RIDGELAKE DR
WEDDINGTON, NC 281047412

Exhibit A (Cont.)

SLUTZ DAMON M
1011 LAKE FOREST DR
MATTHEWS, NC 28104

ELIE JAY II
1013 LAKE FOREST DR
MATTHEWS, NC 28104

CARRAI GARY B
1017 LAKE FOREST DR
MATTHEWS, NC 28104

LEE JAE BONG
1021 LAKE FOREST DR
MATTHEWS, NC 28104

LI XIAOQIN
1025 LAKE FOREST DR
WEDDINGTON, NC 28104

CIESIELSKI DAVID M
1029 LAKE FOREST DR
MATTHEWS, NC 28104

IP ANDREW
1033 LAKE FOREST DR
MATTHEWS, NC 28104

EDOSOMWAN ESTHER EIGBE
1037 LAKE FOREST DR
WEDDINGTON, NC 28104

PATEL HARISH B
1041 LAKE FOREST DR
MATTHEWS, NC 28104

SAGGOO JASPREET K
1045 LAKE FOREST DR
MATTHEWS, NC 28104

ALBERS CHRIS R
1048 LAKE FOREST DR
WEDDINGTON, NC 28104

MANCHI RAMA
1044 LAKE FORREST DR
MATTHEWS, NC 281047411

REEVES GORDON R
1040 LAKE FOREST DR
MATTHEWS, NC 28104

CHRISTODOULIAS JIMMIE J
601 MAPLE VALLEY CT
WEDDINGTON, NC 28104

PATEL SANJIV R
605 MAPLE VALLEY CT
MATTHEWS, NC 28104

SUN YAN
609 MAPLE VALLEY CT
MATTHEWS, NC 28104

COHEN NADAV TRUSTEE
613 MAPLE VALLEY CT
MATTHEWS, NC 28104

TWO HONEYBEES LLC
135 ST GEORGE PL
ATHENS, GA 30606

BOYD BARRINGTON
628 MAPLE VALLEY CT
WEDDINGTON, NC 28104

SZKLINSKI JOHN A
624 MAPLE VALLEY CT
WEDDINGTON, NC 28104

MCGRATH SEAN E
620 MAPLE VALLEY CT
WEDDINGTON, NC 28104

PEREZ CARLOS E
614 MAPLE VALLEY CT
WEDDINGTON, NC 28104

GIATTINO JOHN F
610 MAPLE VALLEY CT
WEDDINGTON, NC 28104

FYANS JOHN
606 MAPLE VALLEY CT
MATTHEWS, NC 28104

CONTE JOHN
602 MAPLE VALLEY CT
MATTHEWS, NC 28104

KENNARD TIMOTHY PATRICK
805 PINE VALLEY COURT
MATTHEWS, NC 28104

SCHEINSON LAWRENCE
809 PINE VALLEY CT
WEDDINGTON, NC 28104

DUBEY MARISSA
813 PINE VALLEY CT
MATTHEWS, NC 28104

HENNINGS FREDERICK W
817 PINE VALLEY CT
WEDDINGTON, NC 28104

PINGEL JAN
816 PINE VALLEY CT
WEDDINGTON, NC 28104

Exhibit A (Cont.)

KNOWLTON INEAL JR
812 PINE VALLEY CT
WEDDINGTON, NC 28104

BAILEY WILLIAM
810 PINE VALLEY CT
WEDDINGTON, NC 28104

ARTHUR MICHAEL D
808 PINE VALLEY CT
MATTHEWS, NC 28104

DAVE SEJAL A
804 PINE VALLEY CT
WEDDINGTON, NC 28104

PALMER JAMES D JR
305 FIR PLACE CT
WEDDINGTON, NC 28104

TAYLOR MATTHEW THOMAS
309 FIR PLACE CT
MATTHEWS, NC 28104

ACKELS STEPHEN M
313 FIR PLACE CT
WEDDINGTON, NC 28104

MASON CHRISTOPHER
314 FIR PLACE CT
WEDDINGTON, NC 28104

HAMMOND JENNIFER ASHLEY PHILLI
1056 LAKE FOREST DR
WEDDINGTON, NC 28104

VARADARAJAN RAVISANKAR
1060 LAKE FOREST DR
MATTHEWS, NC 28104

MUKKERA HARITHA
1064 LAKE FOREST DRIVE
WEDDINGTON, NC 281047411

KOLLIPARA HIMABINDU
1068 LAKE FOREST DR
WEDDINGTON, NC 28104

DIAZ ALLAN RODRIGUEZ
3063 TWIN LAKES DR
MATTHEWS, NC 28104

GORANTLA RAMANAMOHAN K
1055 LAKE FOREST DR
MATTHEWS, NC 28104

ANDERSON SCOTT K
1059 LAKE FOREST DR
WEDDINGTON, NC 28104

GOPALSAMY ANANDARAJ
1063 LAKE FOREST DR
WEDDINGTON, NC 28104

BENNETT KATHRYN G
1067 LAKE FOREST DR
MATTHEWS, NC 28104

DRAVIDA SHANTHARAM
3076 TWIN LAKES DR
WEDDINGTON, NC 28104

PRODDATURU MITHUN REDDY
3080 TWIN LAKES DR
WEDDINGTON, NC 28104

RITCHIE CRAIG
3084 TWIN LAKES DR
WEDDINGTON, NC 28104

ANNAMRAJU VENKATESHWER R
3088 TWIN LAKES DR
WEDDINGTON, NC 28104

KANTIMAHANATHI RICHARD ROSHAN
402 TIMBER TOP CT
WEDDINGTON, NC 28104

GIRARDI EDUARDO
406 TIMBER TOP CT
MATTHEWS, NC 28104

SURPRENANT MARC
410 TIMBER TOP CT
WEDDINGTON, NC 28104

TWARAKAVI SREERAMKUMAR
409 TIMBER TOP CT
WEDDINGTON, NC 28104

PERLA SREEDHAR BABU
405 TIMBERTOP CT
WEDDINGTON, NC 28104

GANDHE VIJAYA L
401 TIMBER TOP CT
MATTHEWS, NC 28104

OSTROW LANE ET AL
502 PINE NEEDLE CT
MATTHEWS, NC 28104

LAMANTIA VINCENT J
506 PINE NEEDLE CT
MATTHEWS, NC 28104

SURESHKUMAR MOSES S
510 PINE NEEDLE CT
WEDDINGTON, NC 28104

Exhibit A (Cont.)

COLANDRA ANTHONY J
514 PINE NEEDLE CT
WEDDINGTON, NC 28104

DAVIS RUSSELL A
505 PINE NEEDLE CT
WEDDINGTON, NC 28104

KEARNS DAVID
3099 TWIN LAKES DR
WEDDINGTON, NC 28104

MAKWANA DHARMENDRA
3087 TWIN LAKES DRIVE
MATTHEWS, NC 28104

JEFFERS DAVID A
3075 TWIN LAKES DR
WEDDINGTON, NC 28104

DEAL FARM LLC THE
3610 ETHAN CT
CHARLOTTE, NC 28226

KBB DEVELOPERS INC
301 S MCDOWELL STREET
STE 320
CHARLOTTE, NC 28204

PROPST JANICE G
531 WEDDINGTON RD
WEDDINGTON, NC 28104

MCNEILL WILLIAM CHAD
PO BOX 159
MONROE, NC 28111

CLEMENTS NATHAN D JR
6062 OXFORDSHIRE RD
WAXHAW, NC 28173

WESLAKE PAUL B
513 PINE NEEDLE CT
WEDDINGTON, NC 28104

MORFORD RYAN T
501 PINE NEEDLE CT
WEDDINGTON, NC 28104

THIRUMANIVASAGAM ANAND
3095 TWIN LAKES DR
WEDDINGTON, NC 28104

BOSEFSKI DAVID
3083 TWIN LAKES DR
WEDDINGTON, NC 28104

JUDGE DANIEL J
3071 TWIN LAKES DR
WEDDINGTON, NC 28104

WEDDINGTON 270 LLC
2627 BREKONRIDGE CENTRE DR
MONROE, NC 28110

AMON JOHN R
744 SKYTOP DR
WAXHAW, NC 281739329

FRENETTE GARY P
6065 OXFORDSHIRE RD
WAXHAW, NC 28173

MARTINEZ ANDREW
2114 OVERWOODS LN
INDIAN TRAIL, NC 28079

COCKRELL KEITH
6056 OXFORDSHIRE RD
WAXHAW, NC 28173

WAN SHAOSHAN
509 PINE NEEDLE CT
WEDDINGTON, NC 28104

PINO RICHARD R REYES
3103 TWIN LAKES DR
MATTHEWS, NC 28104

GAVIN SHANE PATRICK CO TRUSTEE
3091 TWIN LAKES DR
MATTHEWS, NC 28104

CHINTALA DREW
3079 TWIN LAKES DR
WEDDINGTON, NC 28104

HANEY MICHAEL J
3067 TWIN LAKE DR
MATTHEWS, NC 281046114

SUGAR MAGNOLIA WEDDINGTON LLC
5615 POTTER RD
MATTHEWS, NC 28104

PROPST ELIZABETH D
601 WEDDINGTON RD
MATTHEWS, NC 28104

GAO XLAOJIE
726 SKYTOP RD
WAXHAW, NC 28173

ALLISON JOHN D
714 SKYTOP RD
WEDDINGTON, NC 28173

BARAJAS CHRISTOPHER M
6072 OXFORDSHIRE RD
WAXHAW, NC 28173

Exhibit A (Cont.)

TUREK FRANK III
665 BARON RD
WAXHAW, NC 28173

HANNON EDWARD F
643 BARON RD
WAXHAW, NC 28173

MONA ZEYAD
637 BARON RD
WAXHAW, NC 28173

MONA ZEYAD
637 BARON RD
WAXHAW, NC 28173

WAGNER JORDAN
601 BARON RD
WAXHAW, NC 28173

WISE MANAGEMENT & REALTY LLC
110 SEVENDALES DR
GOLDSBORO, NC 27534

BALLETTA JUSTIN TRUSTEE
17235 WESTMILL LN
CHARLOTTE, NC 28277

TASE ALBERT G III
634 BARON RD
WAXHAW, NC 28173

NYBY BRIAN M
646 BARON RD
WAXHAW, NC 28173

SNYDER MARK WAYNE
610 BRANDY CT
WAXHAW, NC 28173

PERRY SCOTT M
628 BRANDY CT
WAXHAW, NC 28173

BONDURANT CHARLES W
646 BRANDY CT
WAXHAW, NC 28173

QUEEN DAN H JR
660 BRANDY CT
WEDDINGTON, NC 28173

WILKERSON ANDREW M
680 BRANDY CT
WAXHAW, NC 28173

JOUBERT JACOB DANIEL DE BRUYN
679 BRANDY CT
WAXHAW, NC 28173

BALLARD DAVID B
653 BRANDY COURTS
WAXHAW, NC 281739326

ANTON MICHAEL J
730 BARON RD
WEDDINGTON, NC 28173

ASHCRAFT MARK FRANKLIN
718 BARON RD
WAXHAW, NC 28173

GOOD TIMOTHY M
621 BRANDY CT
WAXHAW, NC 281799326

DOWLESS JO GRADY
607 BRANDY CTS
WAXHAW, NC 281739326

OAKLEY GARRETT K
704 BARON RD
WAXHAW, NC 28173

SZYDLOWSKI VICTOR
713 SKY TOP RD
WAXHAW, NC 28173

KLINKERT NICOLAAS
757 SKYTOP RD
WAXHAW, NC 28173

PODREBARAC DREW
552 KIRBY LANE
MATTHEWS, NC 28104

NEW TRADITION HOMES OF NC LLC
1005 WOODS LOOP
WAXHAW, NC 28173

PATEL UDAY
719 EAGLE RD
WAXHAW, NC 28173

RYALS RONNIE GLYNN
980 BARON RD
WAXHAW, NC 281738360

BURITICA MICHAEL
942 BARON RD
WAXHAW, NC 28173

MOFFAT DEBORAH MARCELLE
936 BARON RD
WAXHAW, NC 28173

MCDONALD TAMARA
930 BARON RD
WAXHAW, NC 28173

Exhibit A (Cont.)

NEEL W ERSKINE JR
924 BARON RD
WEDDINGTON, NC 28173

CURRIE KENNETH III
1217 BARON RD
WAXHAW, NC 28173

LINER GAINES H
937 BARON RD
WEDDINGTON, NC 28173

BLOCK DAVID P
621 LOCHAVEN RD
MATTHEWS, NC 28173

TEODOROVICI EMILIA M
635 LOCHAVEN ROAD
WAXHAW, NC 28173

HEDRICK P SCOTT ET AL
130 MARTINGALE LN
WILMINGTON, NC 28409

IGLESIAS TINA
640 LOCHAVEN RD
WAXHAW, NC 28173

KALYUZHNYI YURIY V
5907 PARKSTONE DR
MATTHEWS, NC 28104

DEAN ONIKA
754 LOCHAVEN RD
WAXHAW, NC 28173

SALAMI SAID ZIAOLDIN
205 RUNNING HORSE LN
WAXHAW, NC 28173

SMITH JOSEPH J
906 BARON RD
WAXHW, NC 28173

AERO PLANTATION ASSOC
1025 WOODS LOOP
WEDDINGTON, NC 28173

DEAL LAKE PROPERTY LLC
3610 ETHAN CT
CHARLOTTE, NC 28226

IVANNIKOV ALEXANDER
623 LOCHAVEN RD
WAXHAW, NC 28173

IOFFE DMITRIY
633 LOCHAVEN RD
WAXHAW, NC 28173

WALLER MICHAEL R
606 LOCHAVEN RD
WAXHAW, NC 28173

WASDELL RAYMOND V
PO BOX 472
BOWLING GREEN, SC 29703

MCAREAVY STEVEN C
762 LOCKHAVEN RD
WAXHAW, NC 28173

SIDNEY KENNETH D
625 LOCHAVEN RD
WAXHAW, NC 28173

ALLEN MORGAN STEWART TRUSTEE
639 LOCHAVEN RD
WAXHAW, NC 28173

WELFARE JOHN S
909 BARON RD
WAXHAW, NC 28173

OELSCHLAEGEER TERRY D
959 BARON RD
WAXHAW, NC 28173

HORENSTEIN LAWRENCE
617 LOCHAVEN ROAD
WAXHAW, NC 28173

LEE JONATHAN STEPHEN TRUSTEE
629 LOCHAVEN RD
WAXHAW, NC 28173

GUEAR TODD J
6048 OXFORDSHIRE RD
WAXHAW, NC 28173

CUBINA JAVIER SANTOS
630 LOCHAVEN RD
WAXHAW, NC 28173

ECKHART MARK STEVEN
542 LOCHAVEN RD
WAXHAW, NC 28173

LITTLE WILLIAM E JR
748 LOCHAVEN RD
WAXHAW, NC 28173

STAMATELATOS GEORGE CHRISTOS
6068 OXFORDSHIRE RD #64
WAXHAW, NC 28173

MAYNARD WILLIAM ARTHUR
647 LOCHAVEN RD
WAXHAW, NC 28173

Exhibit A (Cont.)

HOULT MARION
655 LOCHAVEN RD
WAXHAW, NC 28173

WEIL JOSEPH D
654 LOCKHAVEN RD
WAXHAW, NC 28173

HEUSTESS LAUREN
210 HIDDEN HAVEN TRL
WAXHAW, NC 28173

MCDOWELL DOUGLAS D
720 TEMPLETON AVE
CHARLOTTE, NC 28203

VOLK ALEKSANDR
6052 OXFORDSHIRE RD
WAXHAW, NC 28173

STRUBBE DAVID S
225 HIDDEN HAVEN TRAIL
WAXHAW, NC 28173

MCDONNELL ROBERT
205 HIDDEN HAVEN TRL
WAXHAW, NC 28173

DAVIS THOMAS
6064 OXFORDSHIRE RD
WAXHAW, NC 28173

PUROHIT MOHIT
316 WESTLAKE DR
WAXHAW, NC 28173

DZHUGA SERGEY
537 LOCHAVEN RD
WAXHAW, NC 28173

HEDRICK P SCOTT ET AL
130 MARTINGALE LN
WILMINGTON, NC 28409

MEAD PAUL W
534 LOCHAVEN RD
WAXHAW, NC 28173

DEFIORE MICHAEL
757 LOCHAVEN RD
WAXHAW, NC 28173

ENGLISH ROBERT THOMAS
744 LOCHAVEN RD
WAXHAW, NC 28173

PARKER MICHAEL ERIC
6037 OXFORDSHIRE RD
WEDDINGTON, NC 28173

LOMBARDO THOMAS S
6041 OXFORDSHIRE RD
WAXHAW, NC 28173

NEER RICHARD
6045 OXFORDSHIRE RD
WAXHAW, NC 28173

SIAO TAISHEN
6040 OXFORDSHIRE RD
WAXHAW, NC 28173

WILLIAMS PHILLIP R
6036 OXFORDSHIRE RD
WAXHAW, NC 28173

KOTHADIA JAMNAD M
6049 OXFORDSHIRE RD
WAXHAW, NC 28173

RORIE JAMES W
6053 OXFORDSHIRE RD
WAXHAW, NC 28173

HAMILTON GARY R
6057 OXFORDSHIRE RD
WAXHAW, NC 28173

Exhibit B

Community Meeting Notice

NOTICE TO INTERESTED PARTIES OF A REZONING PETITION

Subject: Rezoning Petition
Petitioner/Developer: Toll Brothers
Current Land Use: Residential & Vacant
Existing Zoning: R-CD
Rezoning Requested: R-CD

Date and Time of Meeting: ***Thursday, May 2, 2024, at 6:00 PM***

Meeting Location ***St. Margaret's Episcopal Church
8515 Rea Road
Waxhaw, NC 28173***

Meeting Registration: ***Please send an email to Drenna Hannon at
drennahannon@mvalaw.com
to confirm your attendance.***

Date of Notice: 4/17/2024

Moore & Van Allen is assisting Toll Brothers (the "Petitioner") on a recently filed request to rezone an approximately 167.48-acre site located at 610 Weddington Road (and other nearby parcels) in Weddington, North Carolina (the "Site") to R-CD. The request is to allow the Site to be developed with a residential community consisting of ±93 homes. Access to the site will be from Weddington Road.

The Petitioner will hold an **In-Person Community Meeting** to discuss this rezoning proposal with nearby property owners and organizations. The Town of Weddington Planning Department's records indicate that you are either a representative of a registered neighborhood organization or an owner of property near the site. **Accordingly, we are extending an invitation to participate in the upcoming Community Meeting to be held on Thursday, May 2, 2024, at 6:00 p.m. at St. Margaret's Episcopal Church.** Please contact Drenna Hannon at email: drennahannon@mvalaw.com to RSVP and reference the location of the meeting.

Residents who expect they will be unable to attend the community meeting or have questions about this matter are asked to email bridgetgrant@mvalaw.com or call **704-301-3137** to make alternative arrangements to receive the presentation information. Presentation materials will be shared upon request after the meeting.

Representatives of the Petitioner look forward to discussing this exciting rezoning proposal with you at the Community Meeting. Thank you.

cc: Greg Gordos, AICP, Town Planner, Town of Weddington, NC
Robert Price, Toll Brothers
Bridget Grant, Moore & Van Allen, PLLC

13577201v1

Exhibit B (continued)

Site location:




















Exhibit C

TOLL BROTHERS DEAL LAKE COMMUNITY MEETING

	Name	Email	Attendees Signature
2	Bob & Linda Williams	RWILLIAMS19@carolina.rr.com	
1	Christopher Neve	christopherneve@gmail.com	
1	Marcia Vigil	johnkunich@aol.com	
1	Stephen L. Houser, Jr.	shouserjr@carolina.rr.com	
2	Christian & Nicky Beltz	beltzcg@gmail.com	
1	Srikanth Devarapalli	sri.devarapalli@gmail.com	
2	Frank & Stephanie Turek	fturek@me.com	
1	David Bosefski	david.bosefski@gmail.com	
1	Cathy Killough Brown	ckbrown0219@gmail.com	
2	Ken & Lynn Taylor	lynn.taylor508@gmail.com	
1	Sylvia Newsome	samalexzac@aol.com	
1	Kerry (KJ) Greenwood	kjgreenwood.gps@gmail.com	
1	Randy Carder	randy.carder@gmail.com	
2	Bernard & Monika Schnacke	bus202@frieling.com	
1	Gayle Butler	gaylethomas1@gmail.com	
2	Tom & Katherine Lombardo	tslombardo@msn.com	
1	Debbie Moffat	dmoffat215@gmail.com	
1	Debra Badalamenti	debra@nthomes.com	
1	Richard & Addeline Abbate		
1	Erin Cusumano	erincusumano@yahoo.com	

5/2/2024

Exhibit C (Cont.)

TOLL BROTHERS DEAL LAKE
COMMUNITY MEETING

1	David Cusumano	david.p.cusumano@gmail.com	<i>Ez Cusumano</i>
3	Chad & Melissa Emerine	chademer@gmail.com	<i>Chad Emerine</i>
2	Gall and John Giattino	john@giattino.net	
2	Craig and Lorraine Horn	lhorn@carolina.rr.com	<i>Lorraine Horn</i>
1	Harsh Vasavada	vasavada.h@gmail.com	<i>Vasavada</i>
1	Mike Waller	mikewaller@gmail.com	<i>Mike Waller</i>
1	Chris Faulk	cfaulk@metrolinasurveyors.com	
1	Reid Wilkerson	reid.wilkerson@mcclancy.com	<i>Reid Wilkerson</i>
1	Jim Bell	jbelle@media-comm.com	<i>J. Bell</i>
1	Joshua Ziembiec	jziembiec@gmail.com	
1	Charlie BonDurant	Charlie.BonDurant@cokeconsolidated.com	<i>Charlie BonDurant</i>
1	Charlie Fox	Charlesifox@gmail.com	<i>Charlie Fox</i>
1	Ginger Edgeworth	gingeredgeworth26@gmail.com	
1	Kenn Frazier	kenbosama@gmail.com	<i>Kenn Frazier</i>
1	Elizabeth Cable ^{Holley}	ecable@att.net	<i>Elizabeth Cable</i>
1	Laura Kaplan	laura.kaplan10@gmail.com	<i>Laura Kaplan</i>
2	Bill & Patty Powell		<i>Bill & Patty Powell</i>

45

47

5/2/2024

Exhibit C (Cont.)

Community Meeting Attendance Sheet

** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD
Date: May 2, 2024

Name	Address	Phone	Email
JOHN DROH2AL	950 Eagle Rd	917 750 3667	jdreh2al222@ Cmeatline
Stephen Siegfried	1037 Baron Rd	561-427-4443	SKS.Ziggy@yahoo.com
Bob Hornick	1526 E Fraher St Chapel Hill, NC	919 929 3905	hornick@brayl.com brayl.com
Chris Huysman	510 SNOW LN SPARTA, NC	336.406.0906	
Jim Topolian	130 Bluebird Lane	704-514-8918	K&F Famil properties johnamon@ @.com
John R Amm	744 SKYTOP R	980-772-0925	preferredsources.com CURNSAMCOURT asH.Hed.com
CURTIS McDONALD	930 BARON RD WAXHAW, NC 28173	704-923-2293	tamara.mcdonald 05@gmail.com
Tamara McDonald	930 Baron Rd	412-999-6707	
Andrew Staley	907 Toe Top Lane	704-441-1014	andrewihi@me.com
Joel Leigh Lamonia	935 WOODS Loop	704-256-9089	leighlamonia@yahoo.com
WALTON HOGAN	5009 Laurel Grove Ln	704 849 2383	W L Hogan
John Galich	5022 Oxfordshire	704 846 9126	
Gary Palmer	1008 Shyama La	704 201 5257	Gary.Palmer@PalmerCustom Builders.com
Bob Schlosser	Weddington	704-614-4484	Bob@RASBorHwyLLC.com
Orla Szprowski	Weddington	704-661-4808	ORLASZP@outlook.com
JACK PLYLER	1015 ESWATE LN	704-458-4062	jack.plyler@gmail.com
Linda Cashion	1142 Baron Rd.	704-256-5644	bob-cashion@char mai com

Exhibit C (Cont.)

Community Meeting Attendance Sheet

** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD

Date: May 2, 2024

Name	Address	Phone	Email
Jami Bartolucci	918 Osprey Ct	704 843 7627	jamibartolucci@aol.com
Adam Bartolucci	" " "	" " "	
Julie Staley	901 Tee Top Lane	704-287-7523	juliestaley@mac.com
Ned Rayson	840 Spring Oaks Dr	704 491 1632	nedrayson@gmail.com
Rick Bernier	146 LARKFIELD DR		RICKANDLU@Earthlink.net
L ANNE BERNIER	" " "		" " "
Patty Grau	4625 Stonybrook Ct	704-564-3850	pegelt@aol.com
KEELEPTAL TASE	634 BARON RD.	704.562.1028	KBRWNNTASF@GMAIL.COM
Mark Bivens	1000 Baron Road	704-604-1492	mbbivens@outlook.com
BILL DETER	401 HAVENCHASE DR	515-326-5584	deterbille@gmail.com
VERONICA GUEROLA	1203 GOLDFINCH LN	704-840-3274	r_hooper@yahoo.com vguerola@hotmail.com
Gary Frenette	6065 Oxfordwood	704 844 0323	cconcology@hotmail.com
HARRY CHILCAT	Fox Run	704-975-7000	
Susan Wedem	4344 Oxford Mill Rd		Susan.Wedem@gmail.com
Keith Long	Wedge Club Hill	412 580 2098	Long.Keith@gmail.com
Justin Patel	727 Ridgeline Dr	704-787-0425	jatinku@gmail.com
Jill Szklarski	624 Maple Valley CT	704-661-2644	JSZKL1@yahoo.com

Exhibit C (Cont.)

Community Meeting Attendance Sheet

** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD
Date: May 2, 2024

Name	Address	Phone	Email
Samantha Dunn	3616 Bountycf	704-301-4528	SNKrsam@gmail.com
Dan + Janet Maday	1012 Woods Loop	704-579-9384	janethmaday@aol.com
Dan + Kathy Queen	660 Brandy Ct	704-614-2852	Danqueen2001@gmail
Enrol Weber	4344 Grand Mill Rd	516-906-1385	
Mary + Kelly Stevens	5050 Dickside	704-846-7107	
Ed Hannon	643 Baron Rd	704-560-9233	Amydawn59@gmail.
Apeksh Dave	804 Pine Valley ct	704-756-0587	ehannoname.com
Jonel Szekinski	624 Maple Valley Ct	704-507-0969	apetsh.dave@gmail.com
Peter Balletta	630 BARON RD, 28173	704-576-9168	JSZKINSKI@CHARRON CAROLY CLUB. ORG
Cherry Carvey	5036 Oxfordshire	704-651-8933	262 RUNNR @GMAIL.COM
Phil McQuinn	808 Summer Harvest Dr.	860 338 9339	
Ellen McLaughlin	3021 Highway Pl.	312-498-2150	nidolfe sbcglobal.net
PAUL WELSH	513 PINE NEEDLE CT		
Rob Kneisher	1500 Barton Creek		

Exhibit C (Cont.)

Community Meeting Attendance Sheet

** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD
Date: May 2, 2024

Name	Address	Phone	Email
Julie Hunter	943 Woods Loop		juliehunter46@gmail.com
Tom Smith			
Tom Smith	1840 Tanglebent Ct	204 877 8826	tsmith@townofweddington.com
Ryan Smith	300 Pines Ferry Rd		RSmith@weddington.com
John KUNICH	1026 LAKE FOREST		johnckunich@aol.com
Jac Joubert	679 BRANDT CT		jacjoubert@gmail.com
Christopher New	110 CHIBSTONE CT	919-672-2539	christophernew@gmail.com
Greg Golder	7327 Sylvan Crossing Ct		golder.373@gmail.com
Kirsty Letzen	VINTAGE CR. 100	704-451-2532	
Pete Becker	weddington Rd		
Tracey Star	Longwood Pl		tlsgaj@msn.com
Burtin Podrebarac	1154 Baron Rd.		bpodre@msn.com
Kelly Ashley	2018 Weddington Lake Dr.		
Ryan WELLS	213 Sugar Plum Ct.		WELLS1198@carolina.rr.com
Mike Anton	230 Baron Rd		antonm@bellsouth.net

Exhibit C (Cont.)

Community Meeting Attendance Sheet

** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD
Date: May 2, 2024

Name	Address	Phone	Email
Mr & Mrs Mark Ascroft	718 Baron Rd	704-306-3656	mdausa@aol.com
Laura Linton	730 Baron Rd	678-428-0105	lantona@bell.net
Alan C	1012 Baron	704-744-4444	agm
Oran Podichm	700 Lash Rd	701-897-4841	-
Wesley Hens	1200 Baron Rd	239-206-3498	-
Philip Chukwueke	1205 Shippin Lane, Waxhaw	619-890-5938	philchukwueke@gmail.com
Duke Dembe	4011 Lake Prairie Dr.	704-907-4759	mdembe@gmail.com
FRANK Correll	2005 Weddington Lake Dr	914-804-9966	-
Stephanie Godbold	3117 Michelle Dr.	704-965-5073	godbold.family.mail@gmail.com
Vignesh C	5022 Dockside Ct	704-886-0614	vigneshc@gmail.com
Hattow	7025 High Meadows Dr.		


Exhibit C (Cont.)

Community Meeting Attendance Sheet


** This sign in sheet is to acknowledge your attendance at the community meeting and so that the City Council may know who attended the community meeting. Signing this attendance sheet does not indicate support or opposition to the proposed rezoning petition. **

Petitioner: Toll Brothers Deal Lake Weddington
St. Margaret's Episcopal Church, 8515 Rea Rd., Waxhaw
Rezoning petition Number: TBD
Date: May 2, 2024

Name	Address	Phone	Email
CHRIS FAULK	1162 W. HLOW OAKS DR	980.721.2353	CFAULK5@verizon.net
DARCEY LADNER		704.299.8698	
CRAIG/ANGELA FULTON	1309 VEECH CT MATT. 28104		CFFULTON@HOTMAIL.COM
AMANDA JARRELL	1325 LONGLEAF CT	704-774-0265	AMANDA@JARRELLHOMES
Michael McLoughlin	3031 Highbury Place	312-355-2150	mmc@delme.com
PAUL HIATT	# 2201 DEER MEADOWS	908.442.8875	hiattp@gmail.com
Brian Helms	1421 BRADLEY DR.	(704) 400-1435	
ANAND THIRUMANGI	3055 TWIN LAKES DR	704.933.2333	
DAVID B			



VICINITY MAP
NOT TO SCALE




- NOTES:**
- ALL DISTANCES ARE HORIZONTAL GROUND DISTANCES UNLESS OTHERWISE NOTED.
 - AREAS COMPUTED BY COORDINATE GEOMETRY METHOD UNLESS OTHERWISE NOTED.
 - AUTHORIZED REPRODUCTIONS OF THIS SURVEY ARE AFFIXED WITH AN ORIGINAL SEAL AND SIGNATURE. THOSE REPRODUCTIONS NOT BEARING AN ORIGINAL SEAL AND SIGNATURE ARE NOT THE PRODUCT OF THE UNDERSIGNED LAND SURVEYOR AND NO CONSIDERATION SHOULD BE GIVEN TO THE INFORMATION CONTAINED HEREIN.
 - THIS PROPERTY IS SUBJECT TO ALL EASEMENTS, BUFFERS AND RESTRICTIONS SHOWN HEREON AND ALL OTHERS OF RECORD.
 - SPECIAL FLOOD HAZARD AREAS (SFHAs) SUBJECT TO INUNDATION BY 1% ANNUAL CHANCE FLOOD. THE 1% ANNUAL CHANCE FLOOD (100-YEAR FLOOD), ALSO KNOWN AS THE BASE FLOOD, IS THE FLOOD THAT HAS A 1% CHANCE OF BEING EQUALED OR EXCEEDED IN ANY GIVEN YEAR. THERE ARE NO REGULATED FLOODWAYS ON PROPERTY AT TIME OF SURVEY.
-ZONE AE: BASE FLOOD ELEVATIONS DETERMINED
-ZONE X: AREA OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN
 - PORTIONS OF THIS PROPERTY ARE LOCATED IN A SPECIAL FLOOD HAZARD AREA (ZONE AE) DETERMINED BY FEMA. REFERENCE COMMUNITY PANEL NUMBERS: 3710 4475 00J AND 3710 4476 00J, DATED 10/16/2008.
 - EAGLE NEST LOCATION GPS COORDINATES PROVIDED BY WETLANDS & WATERS, DATED 02/27/2024.

LINE TABLE:

LINE	BEARING	DISTANCE
L1	N 32°28'22" W	69.72
L2	N 35°57'59" W	68.72
L3	N 33°54'50" W	60.92
L4	N 31°01'48" W	93.90
L5	N 28°14'09" W	44.40
L6	N 14°25'05" W	73.66
L7	N 88°02'34" E	30.82
L8	N 13°15'19" W	83.70
L9	N 11°04'17" W	84.10
L10	N 10°17'50" W	43.97

CURVE TABLE:

STATION	CHORD BEARING	CHORD DISTANCE	ARC DISTANCE	CHORD BEARING	CHORD DISTANCE	ARC DISTANCE
1+00	N 32°28'22" W	69.72	69.72	N 35°57'59" W	68.72	68.72
1+50	N 33°54'50" W	60.92	60.92	N 31°01'48" W	93.90	93.90
2+00	N 28°14'09" W	44.40	44.40	N 14°25'05" W	73.66	73.66
2+50	N 88°02'34" E	30.82	30.82	N 13°15'19" W	83.70	83.70
3+00	N 11°04'17" W	84.10	84.10	N 10°17'50" W	43.97	43.97



LEGEND:

- ETV - CABLE TV PEDESTAL
ET - ELECTRIC TRANSFORMER
PC - PLAT CABINET
PD - TELEPHONE PEDESTAL
RW - RIGHT OF WAY
SFHA - SPECIAL FLOOD HAZARD AREA
ZONE AE
TPD - TELEPHONE PEDESTAL
WM - WATER METER
WV - WATER VALVE
WOOD LAND AREA

TRACT NO.	PARCEL NO.	PARCEL AREA	AREA WITHIN R/W	TOTAL AREA	LEGAL REFERENCE
TRACT 1	06129109	±4,570,194.17 SQ. FT. OR ±104,917 ACRES	NONE	±4,570,194.17 SQ. FT. OR ±104,917 ACRES	DEED BOOK 5904, PAGE 719 (106.5 ACRES)
TRACT 2	06126001	±1,734,401.05 SQ. FT. OR ±39,816 ACRES	±48,562.23 SQ. FT. OR ±1.115 ACRES	±1,782,963.28 SQ. FT. OR ±40,931 ACRES	DEED BOOK 5904, PAGE 721 (40.91 ACRES)
TRACT 3	06126017C	±1,591,525.71 SQ. FT. OR ±36,536 ACRES	±54,256.72 SQ. FT. OR ±1.246 ACRES	±1,645,782.43 SQ. FT. OR ±37,782 ACRES	DEED BOOK 5224, PAGE 270; PLAT CABINET K, FILE 879 (37.79 ACRES)
TRACT 4	06126017	±56,277.64 SQ. FT. OR ±1.29 ACRES	±7,350.73 SQ. FT. OR ±0.169 ACRES	±63,628.37 SQ. FT. OR ±1.461 ACRES	DEED BOOK 4361, PAGE 619; PLAT CABINET K, FILE 879 (1.30 ACRES)
TRACT 5	06126017B	±125,028.99 SQ. FT. OR ±2.870 ACRES	±6,662.01 SQ. FT. OR ±0.153 ACRES	±131,691.00 SQ. FT. OR ±3.023 ACRES	DEED BOOK 5224, PAGE 272; PLAT CABINET K, FILE 878 (2.87 ACRES)
TOTAL AREA		±8,077,427.56 SQ. FT. OR ±185,432 ACRES	±116,833.69 SQ. FT. OR ±2.682 ACRES	±8,194,261.25 SQ. FT. OR ±188,114 ACRES	

TAG	TRUNK	TYPE	TAG	TRUNK	TYPE	TAG	TRUNK	TYPE
1	24	PIN	61	24	GUM	121	24	OAK
2	24	PIN	62	26	TREE	122	24	OAK
3	24	PIN	63	24	OAK	123	24	OAK
4	24	PIN	64	24	OAK	124	30	OAK
5	24	PIN	65	32	OAK	125	24	OAK
6	26	PIN	66	36	GUM	126	30	POP
7	26	PIN	67	24	OAK	127	26	OAK
8	24	PIN	68	26	OAK	128	30	OAK
9	24	HOL	69	36	POP	129	24	OAK
10	25	OAK	70	24	OAK	130	34	OAK
11	24	OAK	71	24	GUM	131	30	OAK
12	24	OAK	72	29	POP	132	30	OAK
13	26	OAK	73	24	GUM	133	30	OAK
14	24	OAK	74	24	MAP	134	26	PIN
15	26	OAK	75	24	MAP	135	26	PIN
16	36	GUM	76	26	OAK	136	26	PIN
17	25	OAK	77	48	ASH	137	26	GUM
18	36	OAK	78	24	MAP	138	28	GUM
19	30	OAK	79	40	OAK	139	40	OAK
20	24	OAK	80	35	OAK	140	32	OAK
21	24	OAK	81	35	OAK	141	49	OAK
22	36	GUM	82	24	OAK	142	27	OAK
23	36	OAK	83	30	MAP	143	30	OAK
24	24	OAK	84	24	OAK	144	36	OAK
25	26	OAK	85	24	GUM	145	29	OAK
26	25	GUM	86	24	GUM	146	36	OAK
27	36	OAK	87	24	POP	147	24	OAK
28	26	GUM	88	24	GUM	148	50	OAK
29	29	OAK	89	26	GUM	149	40	OAK
30	24	OAK	90	24	OAK	150	32	OAK
31	28	OAK	91	24	PIN	151	32	OAK
32	26	OAK	92	30	OAK	152	28	OAK
33	20	GUM	93	30	POP	153	28	OAK
34	32	OAK	94	24	POP	154	24	OAK
35	27	OAK	95	24	POP	155	24	OAK
36	32	OAK	96	24	OAK	156	40	POP
37	27	OAK	97	24	POP	157	34	OAK
38	38	OAK	98	32	OAK	158	24	MAP
39	24	OAK	99	30	OAK	159	25	OAK
40	25	OAK	100	36	OAK	160	24	OAK
41	32	OAK	101	34	OAK	161	25	OAK
42	24	GUM	102	26	OAK	162	25	OAK
43	28	POP	103	26	OAK	163	24	OAK
44	26	GUM	104	30	OAK	164	30	OAK
45	24	OAK	105	44	OAK	165	29	OAK
46	36	POP	106	24	MAP	166	30	OAK
47	36	GUM	107	24	OAK	167	35	OAK
48	26	OAK	108	24	GUM	168	24	POP
49	36	OAK	109	24	OAK	169	36	OAK
50	26	OAK	110	48	OAK	170	30	OAK
51	26	OAK	111	29	GUM	171	28	OAK
52	26	OAK	112	36	OAK	172	24	OAK
53	30	OAK	113	30	OAK	173	26	OAK
54	28	OAK	114	24	MAP	174	26	OAK
55	24	HIC	115	36	OAK	175	32	OAK
56	27	OAK	116	33	OAK	176	32	OAK
57	25	OAK	117	24	POP	177	30	OAK
58	27	OAK	118	25	OAK	178	28	OAK
59	25	OAK	119	32	MAP	179	28	OAK
60	25	OAK	120	26	OAK			



SURVEYOR CERTIFICATION:
I CERTIFY THAT THIS MAP WAS DRAWN UNDER MY SUPERVISION FROM AN ACTUAL SURVEY MADE UNDER MY SUPERVISION (PLAT DESCRIPTION RECORDED IN DEED BOOK 5904, PAGE 719-724); THAT THE BOUNDARIES NOT SURVEYED ARE INDICATED AS DRAWN FROM INFORMATION IN DEED BOOK 5904, PAGE 719-724; THAT THE RATIO OF PRECISION OR POSITIONAL ACCURACY IS GREATER THAN 1:10,000; AND THAT THIS MAP MEETS THE REQUIREMENTS OF THE STANDARDS OF PRACTICE FOR LAND SURVEYING IN NORTH CAROLINA (21 NCAC 56.1600)."

JOHN W. STEVENS, PLS. L-4545
DATE 03/24/2025

HERITAGE TREE SURVEY
EAGLE CROSSING - WEDDINGTON ROAD (HWY 84)
TOLL SOUTHEAST LP COMPANY, INC.
9130 KINGS PARADE BOULEVARD CHARLOTTE, NC 28273
SANDY RIDGE TOWNSHIP, TOWN OF WEDDINGTON, UNION COUNTY, NORTH CAROLINA

DATE: 03/24/2025
SCALE: 1" = 50'
DESIGN: N/A
DRAWN: JWS
JOB NO.: 2017
FILE NAME: TreeSurv
REF. NO.: S0003
SHEET NO.: 2 OF 6

ESE CONSULTANTS
ENGINEERING • PLANNING • SURVEYING • ENVIRONMENTAL
ESE of North Carolina, P.C.
9130 Kings Parade Boulevard • Charlotte, NC 28273
T: (980) 223-3873
jstevens@eseconsultants.com
License # C-2973

From: [Chris Huysman](#)
To: [Robert Price](#)
Subject: Fwd: [EXTERNAL] Eagle Take Application CS6520355
Date: Tuesday, October 29, 2024 12:57:30 PM

This message came from outside Toll Brothers

This message came from a sender outside Toll Brothers. Please be careful before clicking on or opening any links. If you are unsure about any of the contents, click the "Report Suspicious" button to report this email to Information Security and they will determine if the email is secure.

[Report Suspicious](#)

Give me a shout when you get a moment-

I need to either ignore this or respond.

Let me know your thoughts.

----- Forwarded message -----

From: Letowt, Mariah E <mariah_letowt@fws.gov>
Date: Fri, Oct 25, 2024 at 9:42 AM
Subject: Re: [EXTERNAL] Eagle Take Application CS6520355
To: Chris Huysman <chrishuysman@wetlands-waters.com>

Good morning Chris,

Can you please confirm that you authorize I withdraw the application CS6520355 due to the change in project plans?

Thank you!

Mariah Letowt
Migratory Bird and Eagle Permit Biologist

U.S. Fish and Wildlife Service
Migratory Bird Permit Office
Cookeville, TN 470-808-4731

From: Letowt, Mariah E <mariah_letowt@fws.gov>
Sent: Thursday, October 17, 2024 10:27 AM
To: Chris Huysman <chrishuysman@wetlands-waters.com>
Cc: Tompkins, Bryan <bryan_tompkins@fws.gov>; Kirkpatrick, Ulgonda <ulgonda_kirkpatrick@fws.gov>
Subject: Re: [EXTERNAL] Eagle Take Application CS6520355

Good morning Chris,

Thank you for clarifying on our phone call this morning that adjacent land owners possibly want a fence at 330ft from the nest.

Based on all the information provided, should all exterior work and activities be conducted outside of the 660ft buffer, disturbance is not expected to occur and a permit is no longer recommended. We recommend avoiding all work within 660ft, but, should you still decide to install a fence at 330ft, we recommend conducting that activity outside of the nesting season, or, should that work need to occur during the nesting season, obtain a [General Permit](#).

Feel free to reach out if you have any questions,

Mariah Letowt
Migratory Bird and Eagle Permit Biologist

U.S. Fish and Wildlife Service
Migratory Bird Permit Office
Cookeville, TN 470-808-4731

From: Chris Huysman <chrishuysman@wetlands-waters.com>

Sent: Monday, October 7, 2024 4:55 AM

To: Tompkins, Bryan <bryan_tompkins@fws.gov>; Letowt, Mariah E <mariah_letowt@fws.gov>

Subject: [EXTERNAL] Eagle Take Application CS6520355

This email has been received from outside of DOI - Use caution before clicking on links, opening attachments, or responding.

Mariah and Bryan-

Attached please find a site plan for the "Deal Lake" project.

After months of work Toll Brothers has revised the site plan to avoid all construction within the 660' radius but for a fence- the final details of it have not been determined yet.

Wondering if we can have a quick phone conversation to map out the best way forward.

Thanks so much.

As an aside- we checked the nest tree last week and it is still standing after the storm.

--

Chris Huysman
336.406.0906
170 Dew Drop Road
Sparta, NC 28675

chrishuysman@wetlands-waters.com
chris.huysman@gmail.com
wetlands-waters.com



The information contained in this email message is confidential and may be legally privileged and is intended only for the use of the individual or entity named above. If you are not an intended recipient or if you have received this message in error, you are hereby notified that any dissemination, distribution or copy of this email is strictly prohibited. If you have received this email in error, please immediately notify us by return email or telephone if the sender's phone number is listed above, then promptly and permanently delete this message. Thank you for your cooperation and consideration.

--

Chris Huysman
336.406.0906
170 Dew Drop Road
Sparta, NC 28675


chrishuysman@wetlands-waters.com
chris.huysman@gmail.com
wetlands-waters.com



The information contained in this email message is confidential and may be legally privileged and is intended only for the use of the individual or entity named above. If you are not an intended recipient or if you have received this message in error, you are hereby notified that any dissemination, distribution or copy of this email is strictly prohibited. If you have received this email in error, please immediately notify us by return email or telephone if the sender's phone number is listed above, then promptly and permanently delete this message. Thank you for your cooperation and consideration.



TRACT AREAS:					
TRACT NO.	PARCELS NO.	PARCEL AREA	AREA 01/28/97 ACRES	TOTAL AREA	LEGAL REFERENCE
TRACT 1	01/29/98	14,330.1861 SQ. FT. OR 150.911 ACRES	NONE	14,330.1861 SQ. FT. OR 150.911 ACRES	DEED BOOK 506 PAGE 191 (01/26/95 ACRES)
TRACT 2	01/29/98	41,744.8116 SQ. FT. OR 439.146 ACRES	48,562.592 SQ. FT. OR 415 ACRES	41,744.8116 SQ. FT. OR 439.146 ACRES	DEED BOOK 506 PAGE 191 (01/26/95 ACRES)
TRACT 3	01/29/98	14,330.1861 SQ. FT. OR 150.911 ACRES	14,330.1861 SQ. FT. OR 150.911 ACRES	14,330.1861 SQ. FT. OR 150.911 ACRES	DEED BOOK 506 PAGE 191 (01/26/95 ACRES)
TRACT 4	01/29/98	41,744.8116 SQ. FT. OR 439.146 ACRES	48,562.592 SQ. FT. OR 415 ACRES	41,744.8116 SQ. FT. OR 439.146 ACRES	DEED BOOK 506 PAGE 191 (01/26/95 ACRES)
TRACT 5	01/29/98	14,330.1861 SQ. FT. OR 150.911 ACRES	14,330.1861 SQ. FT. OR 150.911 ACRES	14,330.1861 SQ. FT. OR 150.911 ACRES	DEED BOOK 506 PAGE 191 (01/26/95 ACRES)




NOTES:

- [illegible]

LINE	BEARING	DISTANCE
1-1	S 40° 00' 00" W	28.50
1-2	S 38° 58' 00" W	29.42
1-3	S 38° 57' 00" W	58.71
1-4	S 34° 11' 00" W	55.30
1-5	S 31° 01' 00" W	55.30
1-6	S 28° 14' 00" W	55.40
1-7	S 14° 25' 00" W	74.60
1-8	N 20° 02' 00" E	74.60
1-9	N 14° 55' 00" E	74.60
1-10	S 11° 04' 00" W	58.10
1-11	S 10° 14' 00" W	74.60

LEGEND:
 CTV - CABLE TV PEDESTAL
 ET - ELECTRIC TRANSFORMER
 PC - PLAT CABINET
 PD - TELEPHONE PEDESTAL
 RW - RIGHT OF WAY
 SFHA - SPECIAL FLOOD HAZARD AREA
 ZONE AE
 TPO - TELEPHONE PEDESTAL
 WM - WATER METER
 WV - WATER VALVE
 WOODLAND AREA

CURVE	CHORD BEARING	CHORD LENGTH	RADIUS	ARC LENGTH	NET T/A ANGLE
C1	S 83°24'21" E	33.30	2355.22	15.30	87°19'28"
C2	N 83°24'21" W	33.30	2355.22	15.30	87°19'28"



SURVEYOR CERTIFICATION:
I CERTIFY THAT THIS MAP WAS DRAWN UNDER MY SUPERVISION FROM AN
ACTUAL SURVEY MADE UNDER MY SUPERVISION (PLAT DESCRIPTION
RECORDED IN DEED BOOK 5904, PAGE 719-724); THAT THE BOUNDARIES
NOT SURVEYED ARE INDICATED AS DRAWN FROM INFORMATION IN DEED BOOK 5904,
PAGE 719-724, THAT THE RATIO OF PRECISION OR POSITIONAL ACCURACY IS
GREATER THAN 1:10,000; AND THAT THIS MAP MEETS THE REQUIREMENTS OF
THE STANDARDS OF PRACTICE FOR LAND SURVEYING IN NORTH CAROLINA (21
N.C.A.C. 1503).

John E. Stevens
JOHN E. STEVENS
03/24/2025
DATE: _____

NORTH CAROLINA
POSTAL
SEAL
L-4848
U.S. POST SERVICE
JOHN E. STEVENS

EESE CONSULTANTS

TREE SURVEY
EAGLE CROSSING - WEDDINGTON ROAD (HWY 84)
TOLL SOUTHEAST LP COMPANY, INC.
AND MISS POORE CONSULTANTS, INC.
AND MISS POORE CONSULTANTS, INC.
WENDY ROSE TOWNSHIP, TOWN OF WEDDINGTON, UNION COUNTY, NORTH CAROLINA

DATE 03/24/2025	SCALE 1" = 50'
SOURCE N/A	DRAWING JRS
FILE NO 0917	FILE NUMBER TredSurv
S0003	
2 OF 6	

TOLL BROTHERS WEDDINGTON ROAD COMMUNITY

PUBLIC HEARING

April 14, 2025



DEVELOPMENT TEAM

Toll Brothers
AMERICA'S LUXURY HOME BUILDER™

ESE CONSULTANTS
ENGINEERING • PLANNING • SURVEYING • ENVIRONMENTAL

Kimley»Horn



 **McKIM & CREED**
ENGINEERS SURVEYORS PLANNERS

Moore & VanAllen

SITE LOCATION & HISTORY

AERIAL SITE CONTEXT



SITE / FAMILY HISTORY

- The Deal Family were prominent farmers and the largest landowners in Union County dating back to the 1800's. At the passing of Mr. J.A Deal, it was noted that he was "*a man of strict integrity, a good neighbor, and one possessing the confidence and respect of his community.*"
- J.A. Deal had 9 sons who farmed, ran a sawmill and cotton gin, and operated a general store in what is now considered downtown Weddington.
- Clifford M. Deal Sr. inherited the homeplace in the 1920's. With his older brother Claude the two brothers established a successful farming operation and 2 dairy operations until Claude's death in 1968 and Clifford Sr. death in 1973.
- Farming operations have been "rented" for agriculture and the government managed forestry program. The last government forestry evaluation in 2023 recommended a "Clearcut" of the forested areas, and replant in Loblolly Pine seedlings.
- Continued farming is not a sustainable option.


DEAL FAMILY COMMUNITIES

- Over the last 100 years, various Deal properties have been sold to develop multiple communities in Weddington and the broader county
- The Deal Family is preserving the Deal Homeplace and 15 acres

FAMILY MEMBER	ACREAGE	DESCRIPTION
Claude Deal	430	Highway 84, Twelve Mile Ck Rd. N. Which includes Weddington Heights, Deal Road and part ownership of the property that became the 3 Weddington Schools. Highway 84 acreage known to many as the "Woods" Development.
Clifford M Deal Sr.	435	The Deal Homeplace, Highway 84 farm, Twelve Mile Ck Rd N. Deal Road, ownership of the property that became 3 Weddington Schools, Wedgewood Development, Canesteo, Camden Forest.
Aubry J. Deal	261	Right side of Cox Rd. area now called Lake Forest Preserve
Fred F. Deal	125	Left side of Cox Rod, area now called Hunting Creek
Henry C. Deal	235	Corner of Hwy 84 & Twelve Mile Creek Rd. subdivision called Skycroft, Grace Baptist Church, Weddington Brook Subdivision
Doyle Deal	255	Twelve Mile Creek Rd. S. Part of Skycroft subdivision and land called Chatelain, and the gated community to the right, Devonridge
Garnett Deal	165	Hwy 84, WCWAA and Optimist Park Athletic Fields, Shannon Woods, future Cardinal Row and the right side of Lester Davis Rd.
Harry Deal	115	Hwy 84, ownership with Garnett of the WCWAA and OPAF, and the neighborhoods called Nigh Meadows and Highview Estates
Quincy Deal	143	Corner of Hwy 84 & Twelve Mile Creek Rd. North, a portion of Weddington Hills
	2164	


ZONING, LAND USE & PROPOSED PLAN

SITE LOCATION & EXISTING ZONING



- Site is zoned R-CD – Residential Conditional.
- Proposed zoning is R-CD CZ – Conservation Residential Development to allow the development of the site with 93 single family residential dwelling units.

WEDDINGTON COMPREHENSIVE PLAN



Weddington Comprehensive Plan recommendation: Conservation Residential

REZONING OUTREACH

- 12/2023 Charette/Site Walk/Submittal
- 1/30/24 Meeting with Aero Plantation and Weddington Hills
- 2/12/24 Call with Lake Forest HOA
- 3/6/24 Call with Aero Plantation to discuss updates to plan
- 5/2/24 Required Developer's Community Meeting
- 6/26/24 Discuss Updated Plan with Town of Weddington
- 7/16/24 2nd optional project update
- 8/7/24 Meeting with Chris Faulk and Travis Manning regarding updated plan
- 8/7/24 Meeting with Brannon Howie, Bill Deter, Tom Smith regarding updated plan
- 10/2/24 Meeting with Greg Gordos – regarding updated plan
- 12/2/24 Meeting with Greg Gordos, Mayor Jim Bell and Jeff Perryman
- 12/2/24 Meeting with Aero Plantation representatives
- 12/18/24 Passed Planning Board with a Vote of 5:1

PREVIOUS PLANS – Sketch Plan 12/11/23


Number of homes: 93

Lot Size: 15,000

Weddington Road Buffer: 50'

Septic: Community

Eagle Radius: No structures; septic fields in radius



PREVIOUS PLANS –Sketch Plan 10/8/2024

Number of homes: 82


Lot Size: 40,000

Weddington Road Buffer: 50' plus

Septic: On lot with some shared

Eagle Radius: Out of 330' radius; 8

rear yards and SCM in 660'



PROPOSED CONCEPTUAL SITE PLAN

Number of homes: 62

Weddington Road Buffer: 100'

Septic: On lot

Eagle Radius: No encroachment in full 660' radius

50' STRUCTURE SETBACK
AROUND PERIMETER OF SITE

CONSERVATION AREAS

FLOODPLAIN

COMMUNITY SEPTIC SYSTEM


AMENITIZED
OPEN SPACE

CONSERVATION AREAS

STORMWATER
MANAGEMENT

±15 AC TO BE
SUBDIVIDED TO SELLER

100' ROADSIDE
BUFFERS



SEPTIC and TREE EXHIBIT



SUMMARY OF CHANGES | BENEFITS OF CONDITIONAL ZONING

- Decrease in number of units from 93 to 62 (33% reduction)
- Increase setbacks and roadside buffers along Weddington Road to 100'; outside of proposed future right-of-way
- Increased Eagle Protection Encroachment Area from 330' to 660'
- Eliminated shared septic system; committed to deeded individual panel block system
- Relocated stormwater ponds away from existing lake
- Increased distance between new homes and existing lake
- Committed double high hazard silt fence during construction at the lake
- 78+/- acres of open space
- 50' structure setback around perimeter of site – actual distance much greater
- Commitment to no fishing/piers around lake

DEVELOPMENT PATTERN COMPARISON



TRADITIONAL FORM

- Larger lots
- Lots up to the property lines
- No buffer requirements around site periphery
- Less common/protected open space





CONDITIONAL ZONING

- Smaller lots provide protection for open space
- Larger buffers along property lines
- 100' buffer along Weddington Road
- Specific conditions


TRAFFIC IMPACT ANALYSIS

- TIA and Identified Mitigation approved by Town and NCDOT staff
- No mitigation required at off-site intersections
- Mitigation required only at site driveways
- Per coordination with Town Staff, additional analysis performed to reflect:
 - Additional developments underway/approved since original TIA submittal
 - Scenario if NCDOT project schedules delay

NOT TO
SCALE



NOT TO
SCALE



LEGEND

- Existing Lane
- X' Storage Length
- Traffic Signal
- Stop Control
- Not a Study Intersection
- Site Improvements
- IPS Internal Protected Stem

Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

Ongoing coordination with NCDOT will be needed as the development progresses to determine if turn lanes and medians are constructed by the development or if a fee-in-lieu will be needed.

TOLL OPTIONS & PRECEDENT IMAGES

TOLL BROTHERS APPROACH

DISTINCTIVE ARCHITECTURE

You can see it in the details and feel it in the craftsmanship from the moment you walk into a Toll Brothers home; this is where form meets function in exquisite fashion.

UNRIVALED CHOICE

With your selections from premium products, state-of-the-art appliances, and luxury fixtures and finishes, your Toll Brothers home becomes a showcase for your individual style and preferences

EXTRAORDINARY CUSTOMER SERVICE

We are here to deliver an experience beyond compare and to exceed expectations at every turn.

PRESTIGIOUS LOCATIONS


Toll Brothers builds communities in the heart of where you want to live


TOLL BROTHERS APPROACH

- Architectural commitments/ certainty on homes to be built
 - New 6000 + SF Homes
 - Minimum of 6 floor plans
 - Minimum of 18 of elevations
 - Minimum of 20 color schemes

225 house combinations

- Diversity of home type
- Home type pattern cannot repeat
- Custom designed entry monuments






- High end signature line plumbing fixtures
- Top of line built-in commercial grade appliances
- Marble, quartz, and/or quartzite countertops
- Attention to detail (hinges, hardware, pocket doors, trim work)
- Lifestyle upgrades – wine storage, outdoor kitchens, saunas



WEDDINGTON ROAD LANDSCAPE CONCEPT



TOLL BROTHERS ENTRY MONUMENTATION



PROPOSED RESIDENTIAL RENDERINGS



PROPOSED RESIDENTIAL RENDERINGS




PROPOSED RESIDENTIAL RENDERINGS



INTERIOR PRECEDENT IMAGES



AMENITIES & OUTDOOR LIVING



SUMMARY OF CHANGES | BENEFITS OF CONDITIONAL ZONING

- Decrease in number of units from 93 to 62 (33% reduction)
- Increase setbacks and roadside buffers along Weddington Road to 100'; outside of proposed future right-of-way
- Increased Eagle Protection Encroachment Area from 330' to 660'
- Eliminated shared septic system; committed to deeded individual panel block system
- Relocated stormwater ponds away from existing lake
- Increased distance between new homes and existing lake
- Committed double high hazard silt fence during construction at the lake
- 78+/- acres of open space
- 50' structure setback around perimeter of site – actual distance much greater
- Commitment to no fishing/piers around lake
- Demonstrated dedication to collaboration

COMPARISON TABLE

Weddington has worked to establish a standard that “raises the bar” through the conditional zoning process. The table below depicts the application of these site design goals and the consistency across our proposed community and two recently approved communities.

Category	Toll Brothers	Classica Homes	Keystone Custom Homes
Total Acreage	167.48	36.22	17.3
Total Lots	62	26	12
Average Lot Size	40,000 SF	21,541 SF	43,832 SF
Minimum Lot Width	100 ft	80 ft	100 ft +
Lot Configuration	Uniform	Uniform	Irregular
Wastewater System	Septic	Septic	Septic
Open Space % Provided	47% total site area	50.67% total site area	13% total site area
Sidewalks	Yes	Yes	TBD (Not shown on plan)
Buffering and Landscaping	100 ft roadside buffer w/berm and planting	100 ft roadside buffer w/berm and planting	50ft roadside buffer, w/planting (year round screening reduces requiring to 50ft)

THANK YOU



CZ 2025-03 TOLL BROTHERS
WEDDINGTON CROSSING
EXHIBIT B.
DEVELOPMENT STANDARDS
Page 1 of 7

Draft 04/07/25

- I. **Development Standards.** The development will be governed by these development standards, all submittals presented to the Weddington Town Council in support of this application, and the applicable provisions of the Town of Weddington Unified Development Ordinance (UDO) in place on the Filing Date. Toll Brothers shall be held to ordinance on or before the filing of R-CD zoning on 12/11/24.
- II. **Applicability of Other Regulations.** The Rezoning Plan shall comply with the current version of applicable non-Unified Development Ordinance regulations at the time of individual permit submission unless otherwise specified under state or federal law, including G.S. 160D-108: Permit Choice and Vested Rights. Examples of these codes may include, but are not limited to, building codes, fire codes, and/or codes or regulations administered by outside agencies. Toll Brothers shall be held to ordinance on or before the filing date of 12/11/24. **Rights.** This rezoning plan is a site-specific development plan, and approval thereof constitutes vested rights in the rezoning plan pursuant to the provisions of the ordinance. Due to the size, level of investment, economic and market conditions and other considerations, the site shall remain vested for a period of five (5) years from the time a site plan approval is granted as authorized in G.S. 160D-108.1. Notwithstanding any other provisions of these development standards, if, at some point, modifications are made to the Ordinance by the village board, Petitioner may voluntarily agree to apply such modifications to the rezoning plan in a manner consistent with the Ordinance as it changes from time to time, and without pursuing a rezoning. Such modifications to the ordinance shall in no way impact the Petitioner's vested rights.

III. Schematic Nature of Rezoning Plan. The Rezoning Plan shows the general location of all structures and exact locations of structures may be altered or modified during design, engineering, and construction phases of the development so long as the Ordinance standards are met, and such alterations or modifications are materially in keeping with the Rezoning Plan and in compliance with these Development Standards.

Toll Brothers shall be held to ordinance on or before the filing date 12/11/24.

IV. Access and Transportation. All roadway improvements and construction within the subdivision will be subject to the approved Transportation Impact Analysis and the standards and criteria of the Town of Weddington and/or NCDOT standards for road construction. Interior road design and construction shall include sloped curb, gutter, sidewalk and planting strip. All entrances to subdivision (3) will be limited to right in-right out only per the NCDOT requirements. Toll Brother agrees

V. Environmental Features.

1. Open Space Requirements

- a) The site shall comply with the Open Space/Conservation Areas depicted on site plans submitted to the Town as shown on Exhibit A to this Ordinance. In no event shall Open Space be less than 40% of the site. Toll is willing to provide a total of 30% open space
- b) Applicant shall retain an undisturbed Conservation Area with a perimeter of 660 feet from the identified active eagle's nest located upon the site and shall be identified as a perpetual conservation area on the recorded Final Plat and shall be maintained in perpetuity by the HOA. Toll Agrees
- c) Open Space depicted on the site plans and identified as "Conservation Areas" must remain undisturbed and shall be identified as a perpetual conservation area on the recorded Final Plat and shall be maintained in perpetuity by the HOA . Toll Agrees
- d) In accordance with UDO Section D 804.C, Applicant will submit a maintenance plan for Open Space and conservation areas prior to Final Plat approval. The maintenance plan will be included in the

Covenants, Conditions, and Restrictions to be filed with the Union County Register of Deeds. Toll Agrees

2. Tree Requirements

- a) ~~Applicant shall comply with Tree Requirements set forth in Section D-917A (Q) as adopted by the Town of Weddington's Town Council on February 10, 2025. The Tree Survey and Tree save and mitigation plan shall be approved by the Union County Arborist prior to issuance of a grading permit.~~ Toll agrees to provide a tree survey identifying the various species and caliper tree size for the entire site development. Toll further agrees to not mass clear and to only select clear all homesites and to not clear exceeding 50' from the rear of each principal structure exempting areas impacted by septic within this area. Toll also agrees to adhere to street tree requirements and to add 2 additional trees per homesite.
- b) Applicant shall submit a landscape plan that includes verification of compliance with tree save and mitigation requirements before construction document approval.
- c) ~~All tree mitigation in accordance to the UDO Section 917A.(Q) will be completed prior to issuance of final plat. Failure to comply will leave the Applicant subject to penalties listed in Section 917A.(Q)11.~~

3. Waterways

- a) All-natural waterways shall be contained to the Common Open Space.

Applicant shall retain a minimum of a 50-foot undisturbed buffer on all streams and waterways located upon the site. 50' on pond and stream downstream on pond, 30' - 20' maximum on all others.

4. Buffers

- a) Applicant shall submit a landscape plan that includes a 100-foot thoroughfare buffer with an earthen berm and plantings to provide year-round screening in the absence of existing woodlands along Weddington Road, per UDO Section D917A.O.b. to be approved by the Planning Administrator prior to approval of construction documents.
- b) Infrastructure may not encroach within 50' of the project boundary and shall be clearly shown within the limits of disturbance including

closest distance to property lines. Toll to further evaluate during engineering to determine any conflicts and septic to be subject to conditions similar to BMP's

VI. Erosion Control: Site shall be developed under Enhanced Erosion Control Requirements to include:

1. A preconstruction conference with Town Engineers shall occur prior to submission of Applicant's Erosion and Sedimentation Control Plan.
2. Double silt fencing will be included as Erosion and Sedimentation Control.
3. To ensure compliance with plans and functionality after construction, the site will be subject to enhanced oversight by Town Engineers. All sediment and erosion control devices shall be inspected every calendar week or after one-half ($\frac{1}{2}$) inch of rainfall once grading activities commence up to completion by a third-party company. A copy of the inspection records, and rainfall data must be retained at the construction site or a nearby location easily accessible during normal business hours, from the date of commencement of construction activities to the date that final stabilization is reached. If periodic inspection or other information indicates that a BMP has been inappropriately or incorrectly maintained, the permittee must address the necessary replacement or modification required to correct the BMP within 48 hours of identification.
4. Necessary action must be taken to minimize the tracking of mud unto paved roadways from construction areas and the generation of dust. The contractor shall daily remove mud/soil from pavement as may be required.
5. Minimize the discharge of pollutants from equipment and vehicle washing, wheel wash water, and other wash waters. Wash waters must be treated in a sediment basin or alternative control that provides equivalent or better treatment prior to discharge.
6. The following discharges from site are prohibited within the downstream ponds' drainage area basin during construction activities.
 - a) Wastewater from washout of concrete, unless managed by an appropriate control.
 - b) Wastewater from washout and cleanout of paint, from release oils, curing compounds and other construction materials.
 - c) Fuels, oils, and/or other pollutants used in vehicle and equipment operation and maintenance.
 - d) Soaps or solvents used in vehicle and equipment washing.
7. Pond Assessment: with requisite approval, this requirement will be based on the direct impact the construction site may have on the waterbodies.

Recorded results recorded results are to be submitted to the Planner and the Town Engineers prior to pre-construction meeting. Data shall be collected by a registered land surveyor or person with adequate experience, using methods generally accepted in the industry as being accurate and reliable and should accurately portray pre-construction conditions in the receiving waterbody of concern. Data will be collected five (5) times throughout the course of ongoing construction activities for comparison with preconstruction baseline data. If an analysis of the data indicates an unacceptable accumulation of sediment beyond natural sedimentation, the financially responsible party will be required to restore the waterbody to its predevelopment depth. Any sediment issues will be required to be restored to baseline before issuance of final plat.

- a) Accurate depth measurements, a bathymetric survey, coring or similar survey, taken throughout the pond.
 - b) Baseline Turbidity test for the ponds before any construction commences.
 - c) Five (5) Turbidity tests during the course of construction for baseline comparison will be run on the downstream lakes (Aero Plantation Lake #1, Aero Plantation Lake #2, and Weddington Hills Lake aka Lake Louise).
 1. At installation of sediment fencing to establish baseline.
 2. ~~After each rain event during which one quarter inch of rain falls.~~
 3. After grading is completed.
 4. At final plat.
 5. Prior to issuance of certificates of occupancy for final five lots.
 - d) Installation of junk trap (comparable to "Trash Trout") in stream feeding into Aero Plantation Lake #1. Or comparable erosion device(s) recommended by a professional erosion control/environmental consultant
8. Enforcement Actions
- a) Inspections and Compliance Monitoring: Officials may inspect sites to ensure compliance with turbidity and sediment control regulations.
 - b) Notices of Violations (NOVs) issued if a site exceeds permitted turbidity levels or fails to implement Best Management Practices (BMPs)

- c) Stop work orders for construction activities may be issued until violations are corrected.
- 9. Penalties for Non-Compliance
 - a) Fines: Monetary Penalties for exceeding turbidity limits or failing to install/maintain BMPs.
 - b) Civil Penalties: Daily fines may accrue until violation is resolved.
 - c) Legal Action: Persistent violations may lead to court action, including injunctions or lawsuits.
- 10. Limits of disturbance may not exceed the area identified in Exhibit A and identified on the grading plan and tree survey.
- 11. Applicant will construct a barrier/fence to block access to Aero Plantation Lakes from new development.
- 12. Toll shall not be held responsible for acts of sediment outside their property limits resulting from shared property and offender shall be held to similar sanctions and removal of sediment

VII. Stormwater Management. Applicant shall meet all requirements for storm water management as required by the Weddington Unified Development Ordinance and as required by town engineers.

- 1. The storm drainage will be conveyed via channels and a storm pipe system to the proposed BMPs. All swales, culverts, drainage system, BMPS and other stormwater infrastructure will be designed and constructed for the 100-year runoff.
- 2. Prior to the issuance of any permits, the applicant shall provide a Performance Bond for the construction of the stormwater improvements associated with the development proposal. The Performance Bond shall be equal to 125% of the cost of those improvements and shall not be released until at least two (2) years after the final Certificate of Occupancy has been issued for the development, or the date of final inspection approval on the stormwater improvements by the engineer of record, whichever occurs last.
- 3. Existing pond will be evaluated for present stormwater code compliance (100-year runoff) and brought up to current standards at the expense of the applicant if pond is found to be both substandard and to be utilized as part of the stormwater control measures/BMPs.

VIII. Septic Requirements: Union County Environmental Health or State of North Carolina approval of the proposed lots for septic tanks and wells before construction document submittal/approval. Neighborhood covenants shall include maintenance plans and requirements for off-lot septic fields to

ensure performance. The Homeowner's Association shall retain right to repair private septic fields. Toll Agrees

IX. Architectural Standards:

1. The building materials used on the principal buildings constructed on Site will be a combination of portions of the following: brick, stone, precast stone, precast concrete, synthetic stone, cementitious fiber board, cementitious fiber shake, stucco, decorative block and/or wood.
2. Vinyl or Aluminum shall not be used as a primary siding material however it may be used on windows, soffits, fascia, and/or similar roof overhang elements, handrails/railings, and/or other miscellaneous trim elements
3. The proposed roofing materials will be architectural shingles, slate, tile and/or metal. Toll Agrees

- X. Permitted Uses.** Permitted uses for this site include all uses permitted in the R-CD and R-40 districts. This site may be developed with up to sixty-two (62) single-family residential units. Toll Agrees